

# TERRANO S/R

## GENERAL CARD



### TECHNICAL PARAMETERS

<b>Rated power of the luminaire [W]*:</b>	9.00 - 53.00
<b>Luminous flux [lm]*:</b>	1050 - 6300
<b>Energy efficiency class:</b>	G
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	3000; 4000
<b>Diffuser type:</b>	matrix led
<b>Material of the body:</b>	powder coated steel
<b>Colour of the body:</b>	black; white
<b>Dimensions (H/W/T/S) [mm]:</b>	48/630/85; 48/1180/85;
<b>Ingress protection:</b>	IP20

### CHARACTERISTICS

Thanks to the use of the latest generation of LED modules, the new Terrano S/R linear luminaire is characterised by energy efficiency and outstanding technical performance. Equipped with a focusing lens, Terrano S/R luminaires are visually friendly and effectively reduce glare (UGR of 12-19). Mounted in a trunking system, they are available in two colour temperatures of 3000 K and 4000 K and two colour versions: white and black. The 630mm-long version allows 360° rotation around its axis and 45° rotation of the light system. The 1180mm version allows the light system to rotate 45°. DALI version available on request.

### APPLICATION

Mounting on a trunking system, increases the range of applications for this luminaire and allows for rearrangement by the user, even after installation. The luminaire has an adaptor equipped with mechanical clips which make it easy to plug in, unplug and move the luminaire, while ensuring that the luminaire is securely held in the rail. The luminaires, together with suitably selected rails and components, allow for ceiling or wall mounting. The Terrano S/R luminaire is ideal as a source of light in offices, shops, dressing rooms and passageways.

# TERRANO S/R

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### Terrano S/R 48/1180/85mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	3000	3000	black	48/1180/85	<a href="#">&gt;&gt; 577666</a>
28	3200	4000	black	48/1180/85	<a href="#">&gt;&gt; 577741</a>
28	3300	3000	white	48/1180/85	<a href="#">&gt;&gt; 577703</a>
28	3500	4000	white	48/1180/85	<a href="#">&gt;&gt; 577789</a>
35	3700	3000	black	48/1180/85	<a href="#">&gt;&gt; 577673</a>
35	3900	4000	black	48/1180/85	<a href="#">&gt;&gt; 577758</a>
35	4100	3000	white	48/1180/85	<a href="#">&gt;&gt; 577710</a>
35	4300	4000	white	48/1180/85	<a href="#">&gt;&gt; 577796</a>
40	4100	3000	black	48/1180/85	<a href="#">&gt;&gt; 577680</a>
40	4400	4000	black	48/1180/85	<a href="#">&gt;&gt; 577765</a>
40	4600	3000	white	48/1180/85	<a href="#">&gt;&gt; 577727</a>
40	4800	4000	white	48/1180/85	<a href="#">&gt;&gt; 577802</a>
53	5400	3000	black	48/1180/85	<a href="#">&gt;&gt; 577697</a>
53	5700	4000	black	48/1180/85	<a href="#">&gt;&gt; 577772</a>
53	5900	3000	white	48/1180/85	<a href="#">&gt;&gt; 577734</a>
53	6300	4000	white	48/1180/85	<a href="#">&gt;&gt; 577819</a>

### Terrano S/R 48/630/85mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
9	1050	3000	black	48/630/85	<a href="#">&gt;&gt; 577505</a>
9	1100	4000	black	48/630/85	<a href="#">&gt;&gt; 577581</a>
9	1150	3000	white	48/630/85	<a href="#">&gt;&gt; 577543</a>
9	1200	4000	white	48/630/85	<a href="#">&gt;&gt; 577628</a>
16	1750	3000	black	48/630/85	<a href="#">&gt;&gt; 577512</a>
16	1850	4000	black	48/630/85	<a href="#">&gt;&gt; 577598</a>
16	1950	3000	white	48/630/85	<a href="#">&gt;&gt; 577550</a>
16	2050	4000	white	48/630/85	<a href="#">&gt;&gt; 577635</a>
22	2300	3000	black	48/630/85	<a href="#">&gt;&gt; 577529</a>
22	2400	4000	black	48/630/85	<a href="#">&gt;&gt; 577604</a>
22	2500	3000	white	48/630/85	<a href="#">&gt;&gt; 577567</a>
22	2650	4000	white	48/630/85	<a href="#">&gt;&gt; 577642</a>
28	2700	3000	black	48/630/85	<a href="#">&gt;&gt; 577536</a>
28	2850	4000	black	48/630/85	<a href="#">&gt;&gt; 577611</a>
28	2950	3000	white	48/630/85	<a href="#">&gt;&gt; 577574</a>

# TERRANO S/R

## GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	3150	4000	white	48/630/85	<a href="#">&gt;&gt; 577659</a>

Card creation date: 14 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 73/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

