

TERRANO S/R

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	9.00 - 53.00
Luminous flux [lm]*:	1050 - 6300
Energy efficiency class:	G
Electrical protection class:	I
Colour temperature [K]:	3000; 4000
Diffuser type:	matrix led
Material of the body:	powder coated steel
Colour of the body:	black; white
Dimensions (H/W/T/S) [mm]:	48/630/85; 48/1180/85;
Ingress protection:	IP20
Colour rendering index:	>80
SDCM:	≤ 3
Diffuser material:	PC
Mounting version:	track

CHARACTERISTICS

Thanks to the use of the latest generation of LED modules, the new Terrano S/R linear luminaire is characterised by energy efficiency and outstanding technical performance. Equipped with a focusing lens, Terrano S/R luminaires are visually friendly and effectively reduce glare (UGR of 12-19). Mounted in a trunking system, they are available in two colour temperatures of 3000 K and 4000 K and two colour versions: white and black. The 630mm-long version allows 360° rotation around its axis and 45° rotation of the light system. The 1180mm version allows the light system to rotate 45°. DALI version available on request.

APPLICATION

Mounting on a trunking system, increases the range of applications for this luminaire and allows for rearrangement by the user, even after installation. The luminaire has an adaptor equipped with mechanical clips which make it easy to plug in, unplug and move the luminaire, while ensuring that the luminaire is securely held in the rail. The luminaires, together with suitably selected rails and components, allow for ceiling or wall mounting. The Terrano S/R luminaire is ideal as a source of light in offices, shops, dressing rooms and passageways.

TERRANO S/R

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Terrano S/R 48/1180/85mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	3000	3000	black	48/1180/85	>> 577666
28	3200	4000	black	48/1180/85	>> 577741
28	3300	3000	white	48/1180/85	>> 577703
28	3500	4000	white	48/1180/85	>> 577789
35	3700	3000	black	48/1180/85	>> 577673
35	3900	4000	black	48/1180/85	>> 577758
35	4100	3000	white	48/1180/85	>> 577710
35	4300	4000	white	48/1180/85	>> 577796
40	4100	3000	black	48/1180/85	>> 577680
40	4400	4000	black	48/1180/85	>> 577765
40	4600	3000	white	48/1180/85	>> 577727
40	4800	4000	white	48/1180/85	>> 577802
53	5400	3000	black	48/1180/85	>> 577697
53	5700	4000	black	48/1180/85	>> 577772
53	5900	3000	white	48/1180/85	>> 577734
53	6300	4000	white	48/1180/85	>> 577819

Terrano S/R 48/630/85mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
9	1050	3000	black	48/630/85	>> 577505
9	1100	4000	black	48/630/85	>> 577581
9	1150	3000	white	48/630/85	>> 577543
9	1200	4000	white	48/630/85	>> 577628
16	1750	3000	black	48/630/85	>> 577512
16	1850	4000	black	48/630/85	>> 577598
16	1950	3000	white	48/630/85	>> 577550
16	2050	4000	white	48/630/85	>> 577635
22	2300	3000	black	48/630/85	>> 577529
22	2400	4000	black	48/630/85	>> 577604
22	2500	3000	white	48/630/85	>> 577567
22	2650	4000	white	48/630/85	>> 577642
28	2700	3000	black	48/630/85	>> 577536
28	2850	4000	black	48/630/85	>> 577611
28	2950	3000	white	48/630/85	>> 577574

TERRANO S/R

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	3150	4000	white	48/630/85	>> 577659

Card creation date: 10 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 73/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

