GENERAL CARD





TECHNICAL PARAMETERS

Rated power of the luminaire [W]*: 100.00; 150.00; 200.00

Luminous flux [lm]*: 16000; 24000; 32000

Colour temperature [K]: 4000

Color rendering index (Ra) >: 80

Electrical protection class:

Impact resistance: IK07

Ingress protection: IP65

Material of the body: powder coated aluminium

Colour of the body: black

Diffuser material: glass

Mounting version: suspended

Dimensions (H/W/T/S) [mm]: 205/153; 235/161;

265/161;

Warranty [years]: 5

CHARACTERISTICS

HIGH-BAY lamp with LED technology. The body is made of die-cast aluminium, powder-coated black, with passive heat dissipation. LED modules with high luminous efficacy (160 lm/W) ensure that the required lighting levels are achieved while saving energy and reducing purchase costs. The diffuser is made of tempered glass, which does not alter the optics of the light source - it provides an overall distribution of 120 degrees. The lamp is terminated with electrical cables (which require an airtight connector if the connection is to be IP65 tight) and signal cables for 1-10V light intensity control. The design of the lamp is suitable for pendant mounting using the threaded, eyebolt hook supplied. The lamp should be suspended by means of a cord or chain dedicated to such solutions (not supplied).

APPLICATION

The lamp is designed for suspended mounting (using chains, cables, etc.) indoors, even in high humidity (IP65). It is ideal for use in factories and production halls as well as large-scale warehouses and logistics centres.



HULK LED EVO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser material	DIMM 1- 10V	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
100	4000	16000	glass	yes	black	205/153	>> 729607
150	4000	24000	glass	yes	black	235/161	>> 729614
200	4000	32000	glass	yes	black	265/161	<u>>> 729621</u>



HULK LED EVO

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
626104	IP68 quick connector 0.5-2.5mm2 Dia5-10mm 3P
626111	IP68 quick connector 0.5-2.5mm2 Dia8-12mm 5P



IP68 quick connector 0.5-2.5mm2 Dia5-10mm 3P (626104)

