CORAL LED EVO PLUS

GENERAL CARD

TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	9.00
Luminous flux [lm]*:	740 - 810
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	F; G
Material of the body:	PP
Ring material:	PP
Diffuser material:	PC
Diffuser type:	OPAL
Optics material:	PMMA
Mounting version:	recessed; surface
Dimensions (H/W/T/S) [mm]:	ø260/108;

CHARACTERISTICS

Ceiling lights for ceiling or wall mounting. Luminaire design allows surface and concealed installation.The unique design allows replacement of the LED GO! (light source) module without having to replace the entire luminaire. Integrated design for easy installation.Surface-mounted luminaire allows cable termination.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).
This ceiling fixture is also available in the following variants:
- with a radio motion sensor.

APPLICATION

Suspended mounting board allows quick installation. Removable mounting board available on request as a service kit. Surface wiring. Holes for connection with surface installation, through-wiring possible.

CORAL LED EVO PLUS

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

CORAL LED EVO PLUS surface

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Energy efficiency class	Index
9	3000	740	OPAL		F	>> 223655
9	4000	810	OPAL		F	>> 223679
9	3000	740	OPAL	yes	F	>> 223662
9	4000	810	OPAL	yes	F	>> 223686

CORAL LED EVO PLUS recessed

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Energy efficiency class	Index
9	3000	740	OPAL		F	>> 223716
9	4000	810	OPAL		F	>> 223730
9	3000	740	OPAL	yes	G	>> 223723
9	4000	810	OPAL	yes	F	>> 223747

CORAL LED EVO PLUS

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



CORAL LED

CORAL LED EVO PLUS

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
223778	CORAL LED EVO PLUS 830 - SERVICE KIT
223792	CORAL LED EVO PLUS 830 RCR - SERVICE KIT
223785	CORAL LED EVO PLUS 840 - SERVICE KIT
223808	CORAL LED EVO PLUS 840 RCR - SERVICE KIT

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 74/2018

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl