

FLEX LINE LED

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	80.00; 120.00; 160.00
Luminous flux of the luminaire 30min [lm]*:	6633; 9950; 13266
Colour temperature [K]:	4000
Electrical protection class:	II
Colour rendering index:	70
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	273/278/98; 320/313/120;
Ingress protection:	IP44
Plug type:	UNI-SCHUKO
Wire type:	H07RN-F 2x1.5mm ²
Cable length [m]:	1.50
Warranty [years]:	2

CHARACTERISTICS

The Flex Line LED light is a light line designed for quick and temporary illumination of a workstation or construction site. Available in 10m, 15m and 20m LED cable versions, it allows line connections of up to a maximum of 50m. The lamp's special shape and operating principle allows it to be freely mounted in a variety of working conditions (mounting on nails, screws, pipes, scaffolding, etc.) while directing the position of the light direction.

APPLICATION

An innovative light chain designed for fast and versatile lighting of workplaces. Its unique shape and clever design, allow for express installation even in very unusual places: construction sites, workshops, renovations, vehicle repair areas, service shops, etc.

FLEX LINE LED

GENERAL CARD

AVAILABLE VERSIONS

 Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Dimensions (H/W/T/S) [mm]	Index
80	6633	4000	273/278/98	>> 608728
120	9950	4000	273/278/98	>> 608735
160	13266	4000	320/313/120	>> 608742

Card creation date: 06 October 2023
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 453/2023