FLEX LINE LED

GENERAL CARD





TECHNICAL PARAMETERS

Rated power of the luminaire [W]*: 80.00; 120.00; 160.00

Luminous flux of the luminaire **30**min 6633; 9950; 13266 [lm]*:

Colour temperature [K]: 4000

Electrical protection class:

Color rendering index (Ra) >: 70

Colour of the body: grey

Dimensions (H/W/T/S) [mm]: 273/278/98; 320/313/120;

Ingress protection: IP44

Plug type: UNI-SCHUKO

Wire type: H07RN-F 2x1.5mm2

Cable length [m]: 1.50

Warranty [years]: 2

CHARACTERISTICS

The Flex Line LED light is a light line designed for quick and temporary illumination of a workstation or construction site. Available in 10m, 15m and 20m LED cable versions, it allows line connections of up to a maximum of 50m. The lamp's special shape and operating principle allows it to be freely mounted in a variety of working conditions (mounting on nails, screws, pipes, scaffolding, etc.) while directing the position of the light direction.

APPLICATION

An innovative light chain designed for fast and versatile lighting of workplaces. Its unique shape and clever design, allow for express installation even in very unusual places: construction sites, workshops, renovations, vehicle repair areas, service shops, etc.



FLEX LINE LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Dimensions (H/W/T/S) [mm]	Index
80	6633	4000	273/278/98	<u>>> 608728</u>
120	9950	4000	273/278/98	<u>>> 608735</u>
160	13266	4000	320/313/120	>> 608742

Card creation date: 06 October 2023



