## **TOWER LITE MULTIBATTERY**

GENERAL CARD





#### **TECHNICAL PARAMETERS**

| Ingress protection: | IP20 |
|---------------------|------|
|---------------------|------|

Impact resistance: IK07

Rated power of the luminaire [W]\*: 68.00

Colour temperature [K]: 4000

Luminous flux [lm]\*: 10285

Supply voltage [V]: 18

Electrical protection class:

Colour of the body: black; grey

**Diffuser material:** PC

**Diffuser type:** MAT

**Dimensions (H/W/T/S) [mm]:** 1130/263/169;

#### **CHARACTERISTICS**

A set of compact floodlights providing even and stable directional illumination. The lamp body made from co-polymer with rubber for high durability. The lamps are fitted with an anti-glare frosted PC diffuser with UV stabiliser, allowing up to 80% of the light emitted by the LEDs to pass through, despite the matt surface, providing a soft and diffuse light. The set is set on a 2-metre stand allowing easy positioning of the light and selection of the right angle for the work surface.

Kit equipped with an on/off switch with 4-stage light output adjustment. Lamp compatible with 18V batteries from manufacturers such as:

- directBosch (18V Professional),
- with a dedicated adapter: Makita, Milwaukee, DeWalt, Festool, Hikoki, Metabo (CAS), Hilt .

The unit has a battery discharge indication.

## **APPLICATION**

Thanks to its various functions, the lamp is the ideal solution for illuminating all workplaces. The high luminous flux and maximum degree of impact resistance are particularly important for illuminating construction sites or intervening services at various emergencies. The lamp's design allows it to be used in the harshest of weather conditions. The multi-position arm provides a wide range of mounting options so that the light beam can be precisely directed, leaving the worker's hands free. Its small size and light weight make it easy to use in workshops, car showrooms, for lighting workplaces in industrial halls or finishing work.



# **TOWER LITE MULTIBATTERY**

**GENERAL CARD** 

## **AVAILABLE VERSIONS**



Click index >>, to see details

| Rated power of the luminaire [W]* | Colour temperature<br>[K] | Luminous flux<br>[lm]* | Colour of the body | Battery | Tilt angle adjustment<br>[°] | Dimensions (H/W/T/S)<br>[mm] | Index                  |
|-----------------------------------|---------------------------|------------------------|--------------------|---------|------------------------------|------------------------------|------------------------|
| 68                                | 4000                      | 10285                  | black              | 18V     | yes                          | 1130/263/169                 | >> 250248              |
| 68                                | 4000                      | 10285                  | grey               | 18V     | yes                          | 1130/263/169                 | <u>&gt;&gt; 250255</u> |



## **TOWER LITE MULTIBATTERY**

GENERAL CARD

### **ACCESSORIES AVAILABLE**

| index  | Name  |
|--------|---|
| 608803 | Adapter for Magnum Battery BOSCH / MIL - DEW (NEW)  |
| 608810 | Adapter for Magnum Battery BOSCH / MAKITA (NEW)     |
| 608827 | Adapter for Magnum Battery BOSCH / FESTOOL (NEW)    |
| 608841 | Adapter for Magnum Battery BOSCH / METABO (NEW)     |
| 608858 | Adapter for Magnum Battery BOSCH / Hikoki 18V (NEW) |
| 608834 | Adapter for Magnum Battery BOSCH / Hilti 22V (NEW)  |
|        | ACCU BOSCH 18V 2Ah                                  |
|        | ACCU BOSCH 18V 5Ah                                  |
|        | ACCU CHARGER BOSCH EU 18V 2Ah/5Ah                   |
| 608681 | Adapter for Makita 18V batteries                    |
| 608650 | Adapter for Milwaukee/DeWalt 18V batteries          |




Adapter for Magnum Battery BOSCH / MIL - DEW (NEW) (608803)



Adapter for Magnum Battery BOSCH / MAKITA (NEW) (608810)



Adapter for Magnum Battery BOSCH / FESTOOL (NEW) (608827)



Adapter for Magnum Battery BOSCH / METABO (NEW) (608841)



Adapter for Magnum Battery BOSCH / Hikoki 18V (NEW) (608858)

Card creation date: 24 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

