MULTI LIGHT LED

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED
Ingress protection:	IP20
Supply voltage [V]:	3.6
Electrical protection class:	III
Color rendering index (Ra) >:	80
Charging time [h:min]:	4
Battery life [h:min]:	min 1.5- max 40
Battery:	2 pcs Li-Ion 2600mAh 3.6V 5A (9.36Wh) rechargeable batteries with C-type charging input - can be charged outside the lamp
Dimensions (H/W/T/S) [mm]:	420/300/250;

CHARACTERISTICS

The torch and work light set is the perfect solution for mechanics, craftsmen and DIY enthusiasts. It is a state-of-the-art work light system that allows various light tips to be mounted on a single base (with battery). A professional set of lamps for illumination during work. Particularly suitable for servicing cars, vans and trucks. The set consists of a base and various attachable tips with bayonet connector. The replaceable rechargeable battery can be charged separately (outside of the lamp) using a C-connector.
Flashlight-type tip - max. 273 Lm SLIM hand lamp nozzle - max. 385 Lm Flexible tip with light source - max. 199Lm Slim flexible tip with light source - max. 3 Lm
Battery life [h:min]
Flashlight-type nozzle - LOW level 139 Lm / 5h; POWER level 273 Lm / 2.5h SLIM hand lamp-type nozzle - LOW level 192 Lm / 4h; POWER level 385 Lm / 1.5h Flexible nozzle with light source - LOW level 99 Lm / 8h; POWER level 199 Lm / 5h Slim flexible nozzle with light source - LOW level 1.50 Lm / 80h ; POWER level 3.00 Lm / 40h

APPLICATION

Car services (car, van and truck repairs), detailing salons, car washes, mobile services, etc.

MULTI LIGHT LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Luminous flux of the luminaire [lm] - range	Charging time [h:min]	Battery life [h:min]	Battery capacity [mAh]	Dimensions (H/W/T/S) [mm]	Switch	Magnet	Index
3-385	4	min 1.5- max 40	2600	420/300/250	yes	yes	>> 608759

Card creation date: 13 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 472/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl