

# LINEA S LED IP40 LIGHT MODULE

GENERAL CARD



## TECHNICAL PARAMETERS

|   |                           |
|---|---------------------------|
| <b>Rated power of the luminaire [W]*:</b> | 14.00 - 146.00            |
| <b>Luminous flux [lm]*:</b>               | 1950 - 23100              |
| <b>Energy efficiency class:</b>           | A; B; C                   |
| <b>Electrical protection class:</b>       | I                         |
| <b>Colour temperature [K]:</b>            | 4000                      |
| <b>Colour rendering index:</b>            | >80                       |
| <b>Diffuser material:</b>                 | PC                        |
| <b>Material of the body:</b>              | Steel; coated sheet steel |
| <b>Colour of the body:</b>                | RAL9010; white            |
| <b>Ingress protection:</b>                | IP40                      |
| <b>Mounting version:</b>                  | surface, suspended        |
| <b>ENEC Certificate:</b>                  | 0331/ENEC/23              |
| <b>HACCP:</b>                             | 852/2004                  |

## CHARACTERISTICS

LINEA S LED is a surface-mounted and suspended light line system, representing a new generation of lamps dedicated to LED technology. The innovative connection system and loop-through cabling enables lamps to be quickly connected to form a light line and allows flexible replacement of light modules to suit current needs. The design used allows for easy assembly and power connection. The steel body, designed from the ground up, ensures the lamp's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficiency.

## APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities.

# LINEA S LED IP40 LIGHT MODULE

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### Linea S LED IP40 light module 14W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 14                                | 2050                | 35/67            | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855023</a> |
| 14                                | 2050                | 35/67            | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855269</a> |
| 14                                | 1950                | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850387</a> |
| 14                                | 1950                | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850622</a> |
| 14                                | 2100                | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975455</a> |
| 14                                | 2100                | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983580</a> |
| 14                                | 2000                | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848063</a> |
| 14                                | 2000                | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848308</a> |
| 14                                | 2000                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858222</a> |
| 14                                | 2000                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858468</a> |
| 14                                | 2050                | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857348</a> |
| 14                                | 2050                | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857584</a> |
| 14                                | 2100                | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975233</a> |
| 14                                | 2100                | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981975</a> |
| 14                                | 2050                | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852701</a> |
| 14                                | 2050                | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852947</a> |
| 14                                | 2100                | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975677</a> |
| 14                                | 2100                | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975899</a> |

### Linea S LED IP40 light module 18W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 18                                | 2650                | 35/67            | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855016</a> |
| 18                                | 2650                | 35/67            | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855252</a> |
| 18                                | 2550                | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850370</a> |
| 18                                | 2550                | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850615</a> |
| 18                                | 2700                | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975448</a> |
| 18                                | 2700                | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983573</a> |
| 18                                | 2600                | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848056</a> |
| 18                                | 2600                | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848292</a> |
| 18                                | 2600                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858215</a> |
| 18                                | 2600                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858451</a> |
| 18                                | 2650                | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857331</a> |
| 18                                | 2650                | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857577</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 18                                | 2700                | 80             | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975226</a> |
| 18                                | 2700                | 80             | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981968</a> |
| 18                                | 2650                | 30             | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852695</a> |
| 18                                | 2650                | 30             | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852930</a> |
| 18                                | 2700                | 105            | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975660</a> |
| 18                                | 2700                | 105            | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975882</a> |

## Linea S LED IP40 light module 19W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 19                                | 2850                | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855139</a> |
| 19                                | 2850                | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855351</a> |
| 19                                | 2750                | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850493</a> |
| 19                                | 2750                | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850714</a> |
| 19                                | 2900                | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975561</a> |
| 19                                | 2900                | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983672</a> |
| 19                                | 2750                | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848179</a> |
| 19                                | 2750                | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848391</a> |
| 19                                | 2750                | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858338</a> |
| 19                                | 2750                | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858550</a> |
| 19                                | 2850                | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857454</a> |
| 19                                | 2850                | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857676</a> |
| 19                                | 2900                | 80               | SW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975349</a> |
| 19                                | 2900                | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983696</a> |
| 19                                | 2850                | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852817</a> |
| 19                                | 2850                | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 853036</a> |
| 19                                | 2900                | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975783</a> |
| 19                                | 2900                | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975981</a> |

## Linea S LED IP40 light module 26W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]  | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|-----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 26                                | 4000                | 35/67           | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855009</a> |
| 26                                | 4000                | 35/67           | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855146</a> |
| 26                                | 4600                | butterfly       | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850363</a> |
| 26                                | 4600                | butterfly       | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850509</a> |
| 26                                | 4100                | 90              | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975431</a> |
| 26                                | 4100                | 90              | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981838</a> |
| 26                                | 3950                | asymmetric left | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848049</a> |
| 26                                | 3950                | asymmetric left | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848186</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 26                                | 3950                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858208</a> |
| 26                                | 3950                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858345</a> |
| 26                                | 4000                | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857324</a> |
| 26                                | 4000                | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857461</a> |
| 26                                | 4100                | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975219</a> |
| 26                                | 4100                | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981722</a> |
| 26                                | 4000                | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852688</a> |
| 26                                | 4000                | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852824</a> |
| 26                                | 4100                | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975653</a> |
| 26                                | 4100                | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975875</a> |

## Linea S LED IP40 light module 27W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 27                                | 4000                | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855122</a> |
| 27                                | 4000                | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855344</a> |
| 27                                | 3850                | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850486</a> |
| 27                                | 3850                | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850707</a> |
| 27                                | 4100                | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975554</a> |
| 27                                | 4100                | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983665</a> |
| 27                                | 3950                | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848162</a> |
| 27                                | 3950                | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848384</a> |
| 27                                | 3950                | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858321</a> |
| 27                                | 3950                | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858543</a> |
| 27                                | 4000                | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857447</a> |
| 27                                | 4000                | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857669</a> |
| 27                                | 4100                | 80               | SW                      |           | IP40               | 1764/67/50                | <a href="#">&gt;&gt; 975332</a> |
| 27                                | 4100                | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981760</a> |
| 27                                | 4000                | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852800</a> |
| 27                                | 4000                | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 853029</a> |
| 27                                | 4100                | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975776</a> |
| 27                                | 4100                | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981876</a> |

## Linea S LED IP40 light module 31W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 31                                | 4900                | 35/67          | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854996</a> |
| 31                                | 4900                | 35/67          | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855245</a> |
| 31                                | 4750                | butterfly      | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850356</a> |
| 31                                | 4750                | butterfly      | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850608</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 31                                | 5000                | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975424</a> |
| 31                                | 5000                | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983566</a> |
| 31                                | 4800                | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848032</a> |
| 31                                | 4800                | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848285</a> |
| 31                                | 4800                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858192</a> |
| 31                                | 4800                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858444</a> |
| 31                                | 4900                | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857317</a> |
| 31                                | 4900                | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857560</a> |
| 31                                | 5000                | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975202</a> |
| 31                                | 5000                | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981746</a> |
| 31                                | 4900                | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852671</a> |
| 31                                | 4900                | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852923</a> |
| 31                                | 5000                | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975646</a> |
| 31                                | 5000                | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975868</a> |

## Linea S LED IP40 light module 33W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 33                                | 5100                | 46x117         | corridor                |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980350</a> |
| 33                                | 5100                | 46x117         | corridor                | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980756</a> |
| 33                                | 5450                | 120            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980343</a> |
| 33                                | 5450                | 120            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980749</a> |
| 33                                | 5050                | 105            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980336</a> |
| 33                                | 5050                | 105            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980732</a> |

## Linea S LED IP40 light module 34W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 34                                | 5500                | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855115</a> |
| 34                                | 5500                | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855337</a> |
| 34                                | 5300                | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850479</a> |
| 34                                | 5300                | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850691</a> |
| 34                                | 5600                | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975547</a> |
| 34                                | 5600                | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983658</a> |
| 34                                | 5400                | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848155</a> |
| 34                                | 5400                | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848377</a> |
| 34                                | 5400                | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858314</a> |
| 34                                | 5400                | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858536</a> |
| 34                                | 5500                | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857430</a> |
| 34                                | 5500                | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857652</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 34                                | 5600                | 80             | SW                      |           | IP40               | 1764/67/50                | <a href="#">&gt;&gt; 975325</a> |
| 34                                | 5600                | 80             | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981777</a> |
| 34                                | 5500                | 30             | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852794</a> |
| 34                                | 5500                | 30             | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 853012</a> |
| 34                                | 5600                | 105            | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975769</a> |
| 34                                | 5600                | 105            | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975974</a> |

## Linea S LED IP40 light module 40W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 40                                | 6300                | 35/67            | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854989</a> |
| 40                                | 6300                | 35/67            | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855238</a> |
| 40                                | 6050                | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850349</a> |
| 40                                | 6050                | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850592</a> |
| 40                                | 6400                | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975417</a> |
| 40                                | 6400                | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983559</a> |
| 40                                | 6150                | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848025</a> |
| 40                                | 6150                | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848278</a> |
| 40                                | 6150                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858185</a> |
| 40                                | 6150                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858437</a> |
| 40                                | 6300                | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857300</a> |
| 40                                | 6300                | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857553</a> |
| 40                                | 6400                | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975196</a> |
| 40                                | 6400                | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981739</a> |
| 40                                | 6300                | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852664</a> |
| 40                                | 6300                | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852916</a> |
| 40                                | 6400                | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975639</a> |
| 40                                | 6400                | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975851</a> |

## Linea S LED IP40 light module 46W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 46                                | 7100                | 46x117         | corridor                |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980398</a> |
| 46                                | 7100                | 46x117         | corridor                | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980794</a> |
| 46                                | 7600                | 120            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980381</a> |
| 46                                | 7600                | 120            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980787</a> |
| 46                                | 7050                | 105            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980374</a> |
| 46                                | 7050                | 105            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980770</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

### Linea S LED IP40 light module 47W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 47                                | 7850                | 35/67            | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854972</a> |
| 47                                | 7850                | 35/67            | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855153</a> |
| 47                                | 8350                | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855108</a> |
| 47                                | 8350                | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855320</a> |
| 47                                | 7600                | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850332</a> |
| 47                                | 7600                | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850516</a> |
| 47                                | 8050                | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850462</a> |
| 47                                | 8050                | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850684</a> |
| 47                                | 8000                | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975400</a> |
| 47                                | 8500                | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975530</a> |
| 47                                | 8000                | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981845</a> |
| 47                                | 8500                | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983641</a> |
| 47                                | 7700                | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848018</a> |
| 47                                | 7700                | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848193</a> |
| 47                                | 8200                | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848148</a> |
| 47                                | 8200                | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848360</a> |
| 47                                | 7700                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858178</a> |
| 47                                | 7700                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858352</a> |
| 47                                | 8200                | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858307</a> |
| 47                                | 8200                | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858529</a> |
| 47                                | 7850                | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857294</a> |
| 47                                | 7850                | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857478</a> |
| 47                                | 8350                | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857423</a> |
| 47                                | 8350                | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857645</a> |
| 47                                | 8000                | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975189</a> |
| 47                                | 8500                | 80               | SW                      |           | IP40               | 1764/67/50                | <a href="#">&gt;&gt; 975318</a> |
| 47                                | 8000                | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981951</a> |
| 47                                | 8500                | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981791</a> |
| 47                                | 7850                | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852657</a> |
| 47                                | 7850                | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852831</a> |
| 47                                | 8350                | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852787</a> |
| 47                                | 8350                | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 853005</a> |
| 47                                | 8000                | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975622</a> |
| 47                                | 8500                | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975752</a> |
| 47                                | 8000                | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975844</a> |
| 47                                | 8500                | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981883</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

### Linea S LED IP40 light module 48W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 48                                | 7500                | 46x117         | corridor                |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980169</a> |
| 48                                | 7500                | 46x117         | corridor                | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980558</a> |
| 48                                | 8000                | 120            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980152</a> |
| 48                                | 8000                | 120            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980541</a> |
| 48                                | 7400                | 105            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980145</a> |
| 48                                | 7400                | 105            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980534</a> |

### Linea S LED IP40 light module 57W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 57                                | 9350                | 35/67            | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854965</a> |
| 57                                | 9350                | 35/67            | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855221</a> |
| 57                                | 9000                | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850325</a> |
| 57                                | 9000                | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850585</a> |
| 57                                | 9500                | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975394</a> |
| 57                                | 9500                | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983542</a> |
| 57                                | 9150                | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848001</a> |
| 57                                | 9150                | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848261</a> |
| 57                                | 9150                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858161</a> |
| 57                                | 9150                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858420</a> |
| 57                                | 9350                | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857287</a> |
| 57                                | 9350                | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857546</a> |
| 57                                | 9500                | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975172</a> |
| 57                                | 9500                | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981944</a> |
| 57                                | 9350                | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852640</a> |
| 57                                | 9350                | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852909</a> |
| 57                                | 9500                | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975615</a> |
| 57                                | 9500                | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975837</a> |

### Linea S LED IP40 light module 61W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 61                                | 10100               | 35/67          | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854958</a> |
| 61                                | 10100               | 35/67          | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855214</a> |
| 61                                | 9750                | butterfly      | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850318</a> |
| 61                                | 9750                | butterfly      | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850578</a> |
| 61                                | 10300               | 90             | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975387</a> |
| 61                                | 10300               | 90             | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983535</a> |



# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 61                                | 9900                | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 847998</a> |
| 61                                | 9900                | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848254</a> |
| 61                                | 9900                | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858154</a> |
| 61                                | 9900                | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858413</a> |
| 61                                | 10100               | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857270</a> |
| 61                                | 10100               | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857539</a> |
| 61                                | 10300               | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975165</a> |
| 61                                | 10300               | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981753</a> |
| 61                                | 10100               | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852633</a> |
| 61                                | 10100               | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852893</a> |
| 61                                | 10300               | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975608</a> |
| 61                                | 10300               | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975820</a> |

## Linea S LED IP40 light module 63W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 63                                | 9900                | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855092</a> |
| 63                                | 9900                | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855313</a> |
| 63                                | 9550                | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850455</a> |
| 63                                | 9550                | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850677</a> |
| 63                                | 10100               | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975523</a> |
| 63                                | 10100               | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983634</a> |
| 63                                | 9700                | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848131</a> |
| 63                                | 9700                | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848353</a> |
| 63                                | 9700                | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858291</a> |
| 63                                | 9700                | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858512</a> |
| 63                                | 9900                | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857416</a> |
| 63                                | 9900                | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857638</a> |
| 63                                | 10100               | 80               | SW                      |           | IP40               | 1764/67/50                | <a href="#">&gt;&gt; 975301</a> |
| 63                                | 10100               | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981784</a> |
| 63                                | 9900                | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852770</a> |
| 63                                | 9900                | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852992</a> |
| 63                                | 10100               | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975745</a> |
| 63                                | 10100               | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975967</a> |

## Linea S LED IP40 light module 65W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 65                                | 9600                | 46x117         | corridor                |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980206</a> |
| 65                                | 9600                | 46x117         | corridor                | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980596</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 65                                | 10200               | 120            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980190</a> |
| 65                                | 10200               | 120            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980589</a> |
| 65                                | 9500                | 105            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980183</a> |
| 65                                | 9500                | 105            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980572</a> |

## Linea S LED IP40 light module 67W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 67                                | 10400               | 46x117         | corridor                |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980510</a> |
| 67                                | 10400               | 46x117         | corridor                | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980831</a> |
| 67                                | 11100               | 120            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980503</a> |
| 67                                | 11100               | 120            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980824</a> |
| 67                                | 10300               | 105            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980497</a> |
| 67                                | 10300               | 105            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980817</a> |

## Linea S LED IP40 light module 70W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 70                                | 11900               | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855085</a> |
| 70                                | 11900               | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855160</a> |
| 70                                | 11450               | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850448</a> |
| 70                                | 11450               | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850523</a> |
| 70                                | 12100               | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975516</a> |
| 70                                | 12100               | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981852</a> |
| 70                                | 11650               | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848124</a> |
| 70                                | 11650               | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848209</a> |
| 70                                | 11650               | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858284</a> |
| 70                                | 11650               | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858369</a> |
| 70                                | 11900               | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857409</a> |
| 70                                | 11900               | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857485</a> |
| 70                                | 12100               | 80               | SW                      |           | IP40               | 1764/67/50                | <a href="#">&gt;&gt; 975295</a> |
| 70                                | 12100               | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981807</a> |
| 70                                | 11900               | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852763</a> |
| 70                                | 11900               | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852848</a> |
| 70                                | 12100               | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975738</a> |
| 70                                | 12100               | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975950</a> |

## Linea S LED IP40 light module 71W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 71                                | 11600               | 35/67          | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854941</a> |
| 71                                | 11600               | 35/67          | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855207</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 71                                | 11200               | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850301</a> |
| 71                                | 11200               | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850561</a> |
| 71                                | 11800               | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975370</a> |
| 71                                | 11800               | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983528</a> |
| 71                                | 11350               | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 847981</a> |
| 71                                | 11350               | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848247</a> |
| 71                                | 11350               | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858147</a> |
| 71                                | 11350               | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858406</a> |
| 71                                | 11600               | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857263</a> |
| 71                                | 11600               | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857522</a> |
| 71                                | 11800               | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975158</a> |
| 71                                | 11800               | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981937</a> |
| 71                                | 11600               | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852626</a> |
| 71                                | 11600               | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852886</a> |
| 71                                | 11800               | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975592</a> |
| 71                                | 11800               | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975813</a> |

### Linea S LED IP40 light module 73W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 73                                | 10800               | 46x117         | corridor                |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980435</a> |
| 73                                | 10800               | 46x117         | corridor                | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980879</a> |
| 73                                | 11500               | 120            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980312</a> |
| 73                                | 11500               | 120            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980862</a> |
| 73                                | 10700               | 105            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980411</a> |
| 73                                | 10700               | 105            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980855</a> |

### Linea S LED IP40 light module 77W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 77                                | 11700               | 46x117         | corridor                |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980046</a> |
| 77                                | 11700               | 46x117         | corridor                | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980916</a> |
| 77                                | 12500               | 120            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980466</a> |
| 77                                | 12500               | 120            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980909</a> |
| 77                                | 11600               | 105            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980459</a> |
| 77                                | 11600               | 105            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980893</a> |

### Linea S LED IP40 light module 80W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 80                                | 13100               | 35/67          | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854934</a> |
| 80                                | 13100               | 35/67          | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855191</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 80                                | 12600               | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850295</a> |
| 80                                | 12600               | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850554</a> |
| 80                                | 13300               | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975363</a> |
| 80                                | 13300               | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983511</a> |
| 80                                | 12800               | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 847974</a> |
| 80                                | 12800               | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848230</a> |
| 80                                | 12800               | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858130</a> |
| 80                                | 12800               | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858390</a> |
| 80                                | 13100               | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857256</a> |
| 80                                | 13100               | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857515</a> |
| 80                                | 13300               | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975141</a> |
| 80                                | 13300               | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981920</a> |
| 80                                | 13100               | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852619</a> |
| 80                                | 13100               | 30               | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852879</a> |
| 80                                | 13300               | 105              | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975585</a> |
| 80                                | 13300               | 105              | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975806</a> |

## Linea S LED IP40 light module 82W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 82                                | 13650               | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855078</a> |
| 82                                | 13650               | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855177</a> |
| 82                                | 13200               | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850431</a> |
| 82                                | 13200               | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850530</a> |
| 82                                | 13900               | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975509</a> |
| 82                                | 13900               | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981869</a> |
| 82                                | 13400               | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848117</a> |
| 82                                | 13400               | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848216</a> |
| 82                                | 13400               | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858277</a> |
| 82                                | 13400               | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858376</a> |
| 82                                | 13650               | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857393</a> |
| 82                                | 13650               | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857492</a> |
| 82                                | 13900               | 80               | SW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975288</a> |
| 82                                | 13900               | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981814</a> |
| 82                                | 13650               | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852756</a> |
| 82                                | 13650               | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852855</a> |
| 82                                | 13900               | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975721</a> |
| 82                                | 13900               | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975943</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

### Linea S LED IP40 light module 88W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 88                                | 14550               | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855061</a> |
| 88                                | 14550               | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855306</a> |
| 88                                | 14050               | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850424</a> |
| 88                                | 14050               | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850660</a> |
| 88                                | 14800               | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975493</a> |
| 88                                | 14800               | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983627</a> |
| 88                                | 14250               | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848100</a> |
| 88                                | 14250               | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848346</a> |
| 88                                | 14250               | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858260</a> |
| 88                                | 14250               | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858505</a> |
| 88                                | 14550               | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857386</a> |
| 88                                | 14550               | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857621</a> |
| 88                                | 14800               | 80               | SW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975271</a> |
| 88                                | 14800               | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981821</a> |
| 88                                | 14550               | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852749</a> |
| 88                                | 14550               | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852985</a> |
| 88                                | 14800               | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975714</a> |
| 88                                | 14800               | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975936</a> |

### Linea S LED IP40 light module 91W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 91                                | 14650               | 35/67            | CN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 854927</a> |
| 91                                | 14650               | 35/67            | CN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 855184</a> |
| 91                                | 14150               | butterfly        | DAN                     |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850288</a> |
| 91                                | 14150               | butterfly        | DAN                     | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 850547</a> |
| 91                                | 14900               | 90               | MW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975356</a> |
| 91                                | 14900               | 90               | MW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 983504</a> |
| 91                                | 14350               | asymmetric left  | SA-L                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 847967</a> |
| 91                                | 14350               | asymmetric left  | SA-L                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 848223</a> |
| 91                                | 14350               | asymmetric right | SA-R                    |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858123</a> |
| 91                                | 14350               | asymmetric right | SA-R                    | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 858383</a> |
| 91                                | 14650               | 65               | SN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857249</a> |
| 91                                | 14650               | 65               | SN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 857508</a> |
| 91                                | 14900               | 80               | SW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975134</a> |
| 91                                | 14900               | 80               | SW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981913</a> |
| 91                                | 14650               | 30               | VN                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852602</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 91                                | 14650               | 30             | VN                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 852862</a> |
| 91                                | 14900               | 105            | VW                      |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975578</a> |
| 91                                | 14900               | 105            | VW                      | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 975790</a> |

## Linea S LED IP40 light module 92W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 92                                | 14000               | 46x117         | corridor                |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981043</a> |
| 92                                | 14000               | 46x117         | corridor                | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981128</a> |
| 92                                | 14900               | 120            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981005</a> |
| 92                                | 14900               | 120            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981081</a> |
| 92                                | 13800               | 105            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 980053</a> |
| 92                                | 13800               | 105            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981104</a> |

## Linea S LED IP40 light module 94W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 94                                | 14500               | 46x117         | corridor                |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981050</a> |
| 94                                | 14500               | 46x117         | corridor                | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981135</a> |
| 94                                | 15500               | 120            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981012</a> |
| 94                                | 15500               | 120            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981098</a> |
| 94                                | 14400               | 105            | symmetric               |           | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981036</a> |
| 94                                | 14400               | 105            | symmetric               | yes       | IP40               | 1176/53/26                | <a href="#">&gt;&gt; 981111</a> |

## Linea S LED IP40 light module 96W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 96                                | 14000               | 46x117         | corridor                |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980244</a> |
| 96                                | 14000               | 46x117         | corridor                | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980633</a> |
| 96                                | 15000               | 120            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980237</a> |
| 96                                | 15000               | 120            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980626</a> |
| 96                                | 13900               | 105            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980220</a> |
| 96                                | 13900               | 105            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980619</a> |

## Linea S LED IP40 light module 107W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 107                               | 17400               | 35/67          | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855054</a> |
| 107                               | 17400               | 35/67          | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855290</a> |
| 107                               | 16800               | butterfly      | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850417</a> |
| 107                               | 16800               | butterfly      | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850653</a> |
| 107                               | 17700               | 90             | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975486</a> |
| 107                               | 17700               | 90             | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983610</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 107                               | 17050               | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848094</a> |
| 107                               | 17050               | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848339</a> |
| 107                               | 17050               | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858253</a> |
| 107                               | 17050               | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858499</a> |
| 107                               | 17400               | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857379</a> |
| 107                               | 17400               | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857614</a> |
| 107                               | 17700               | 80               | SW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975264</a> |
| 107                               | 17700               | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983689</a> |
| 107                               | 17400               | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852732</a> |
| 107                               | 17400               | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852978</a> |
| 107                               | 17700               | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975707</a> |
| 107                               | 17700               | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975929</a> |

## Linea S LED IP40 light module 109W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 109                               | 16400               | 46x117         | corridor                |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980282</a> |
| 109                               | 16400               | 46x117         | corridor                | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980671</a> |
| 109                               | 17500               | 120            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980275</a> |
| 109                               | 17500               | 120            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980664</a> |
| 109                               | 16200               | 105            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980268</a> |
| 109                               | 16200               | 105            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980657</a> |

## Linea S LED IP40 light module 122W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 122                               | 19700               | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855047</a> |
| 122                               | 19700               | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855283</a> |
| 122                               | 19000               | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850400</a> |
| 122                               | 19000               | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850646</a> |
| 122                               | 20000               | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975479</a> |
| 122                               | 20000               | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983603</a> |
| 122                               | 19300               | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848087</a> |
| 122                               | 19300               | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848322</a> |
| 122                               | 19300               | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858246</a> |
| 122                               | 19300               | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858482</a> |
| 122                               | 19700               | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857362</a> |
| 122                               | 19700               | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857607</a> |
| 122                               | 20000               | 80               | SW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975257</a> |
| 122                               | 20000               | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981999</a> |

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 122                               | 19700               | 30             | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852725</a> |
| 122                               | 19700               | 30             | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852961</a> |
| 122                               | 20000               | 105            | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975691</a> |
| 122                               | 20000               | 105            | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975912</a> |

## Linea S LED IP40 light module 139W

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°]   | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|------------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 139                               | 22150               | 35/67            | CN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855030</a> |
| 139                               | 22150               | 35/67            | CN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 855276</a> |
| 139                               | 21350               | butterfly        | DAN                     |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850394</a> |
| 139                               | 21350               | butterfly        | DAN                     | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 850639</a> |
| 139                               | 22500               | 90               | MW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975462</a> |
| 139                               | 22500               | 90               | MW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 983597</a> |
| 139                               | 21700               | asymmetric left  | SA-L                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848070</a> |
| 139                               | 21700               | asymmetric left  | SA-L                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 848315</a> |
| 139                               | 21700               | asymmetric right | SA-R                    |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858239</a> |
| 139                               | 21700               | asymmetric right | SA-R                    | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 858475</a> |
| 139                               | 22150               | 65               | SN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857355</a> |
| 139                               | 22150               | 65               | SN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 857591</a> |
| 139                               | 22500               | 80               | SW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975240</a> |
| 139                               | 22500               | 80               | SW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 981982</a> |
| 139                               | 22150               | 30               | VN                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852718</a> |
| 139                               | 22150               | 30               | VN                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 852954</a> |
| 139                               | 22500               | 105              | VW                      |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975684</a> |
| 139                               | 22500               | 105              | VW                      | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 975905</a> |

## Linea S LED IP40 light module 146W


| Rated power of the luminaire [W]* | Luminous flux [lm]* | Beam angle [°] | Light distribution type | DIMM DALI | Ingress protection | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|---------------------|----------------|-------------------------|-----------|--------------------|---------------------------|---------------------------------|
| 146                               | 21600               | 46x117         | corridor                |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980473</a> |
| 146                               | 21600               | 46x117         | corridor                | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980718</a> |
| 146                               | 23100               | 120            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980428</a> |
| 146                               | 23100               | 120            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980701</a> |
| 146                               | 21400               | 105            | symmetric               |           | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980305</a> |
| 146                               | 21400               | 105            | symmetric               | yes       | IP40               | 1764/53/26                | <a href="#">&gt;&gt; 980695</a> |




# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD


### LUMINOUS INTENSITY DISTRIB. CURVE




105D




120D




46X117D




CN




DAN




MW




SA-L




SA-R




SN



SW



VN



VW

# LINEA S LED IP40 LIGHT MODULE

GENERAL CARD

## ACCESSORIES AVAILABLE

| index                  | Name   |
|------------------------|--|
| 981173                 | LINEA S LED hang 1.5m  |
| 980077                 | LINEA S LED hang 3m  |
| 981425                 | LINEA S LED chain pendant  |
| 981418                 | LINEA S LED pendant sm 1.5   |
| 980961                 | LINEA S LED pendant sm 3m  |
| 980954                 | Linea S LED surface mount bracket  |
| 980930                 | LINEA S LED PVC bezel 1176mm   |
| <a href="#">981258</a> | LINEA S LED 588mm universal module 4P                                      |
| 981159                 | LINEA S LED - PVC grille 1764mm  |
| 981401                 | LINEA S LED IP40 connection bezel  |
| 980985                 | LINEA S LED metal grille 588mm   |
| 980947                 | LINEA S LED metal grille 1176mm  |
| 980039                 | LINEA S LED masking 1764mm   |
| 980992                 | LINEA S LED - PVC grille 588mm   |
| 980060                 | LINEA S LED – end cap IP40 push-in   |
| 981166                 | LINEA S LED – end cap IP40 for screws                                      |
| 980084                 | LINEA S LED power set 5P   |
| <a href="#">981906</a> | LINEA S LED 588mm module IoT BT HTR PIR DIMM 12(15)m                       |
| 980978                 | Linea S LED power set 7P   |
| <a href="#">981715</a> | LINEA S LED 1176mm module IoT BT HTR PIR DIMM 8(12)m                       |
| 981388                 | LINEA S LED power set 11P  |
| <a href="#">981234</a> | LINEA S LED 588mm AW DOT CSC 2W 1h NM AT                                   |
| <a href="#">981227</a> | LINEA S LED 588mm AW DOT CS 2W 1h NM AT                                    |
| <a href="#">981241</a> | LINEA S LED 588mm AW DOT CSO 2W 1h NM AT                                   |
| <a href="#">981265</a> | LINEA S LED 588mm - 1xEXPO ADJUST 2050lm zoom 22-55st. WHITE 840 20W       |
| <a href="#">981272</a> | LINEA S LED 588mm - 1xEXPO ADJUST 2050lm DALI zoom 22-55st. WHITE 840 20W  |
| <a href="#">981289</a> | LINEA S LED 1176mm - 2xEXPO ADJUST 2050lm zoom 22-55st. WHITE 840 20W      |
| <a href="#">981296</a> | LINEA S LED 1176mm - 2xEXPO ADJUST 2050lm DALI zoom 22-55st. WHITE 840 20W |



LINEA S LED hang 1.5m (981173)



LINEA S LED chain pendant (981425)



Linea S LED surface mount bracket (980954)



LINEA S LED PVC bezel 1176mm (980930)

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD



LINEA S LED - PVC grille  
1764mm (981159)



LINEA S LED metal grille  
588mm (980985)



LINEA S LED metal grille  
1176mm (980947)



LINEA S LED masking  
1764mm (980039)




LINEA S LED - PVC grille  
588mm (980992)



LINEA S LED - end cap IP40 push-in  
(980060)




LINEA S LED power set 5P (980084)




Linea S LED power set 7P (980978)




LINEA S LED power set 11P (981388)




LINEA S LED 588mm AW DOT CSC  
2W 1h NM AT (981234)




LINEA S LED 588mm AW DOT CS 2W  
1h NM AT (981227)



LINEA S LED 588mm AW DOT CSO  
2W 1h NM AT (981241)



LINEA S LED 588mm - 1xEXPO  
ADJUST 2050lm zoom 22-55st. WHITE  
840 20W (981265)



LINEA S LED 588mm - 1xEXPO  
ADJUST 2050lm DALI zoom 22-  
55st. WHITE 840 20W (981272)



LINEA S LED 1176mm - 2xEXPO  
ADJUST 2050lm zoom 22-55st. WHITE  
840 20W (981289)



LINEA S LED 1176mm - 2xEXPO  
ADJUST 2050lm DALI zoom 22-55st.  
WHITE 840 20W (981296)

# LINEA S LED IP40 LIGHT MODULE

## GENERAL CARD

The Linea S LED has been equipped with new light distributions:

**SW** - standard wide lens (conventional angle 80D) with a wide range of applications in commercial facilities, industrial halls, and even - due to the low glare index  $UGR < 19$  - in office parts of the facility. It provides high lighting efficiency and helps meet the most stringent requirements of the EN 12464-1 standard in terms of the glare index, illuminance and high uniformity on the surface of aisles and shelves. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-8m.

**MW** - medium wide lens (90D conventional angle) with a wide range of applications in commercial facilities, industrial halls, and even - due to the low glare index  $UGR < 19$  - in office parts of the facility. It provides high lighting efficiency and helps meet the most stringent requirements of the EN 12464-1 standard in terms of glare index, illuminance and high uniformity on the surface of aisles and shelves. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-6m.

**VW** - very wide lens (105D conventional angle) with wide application in open spaces and low warehouses. It provides high luminous efficacy and helps meet the most stringent requirements of EN 12464-1 in terms of glare index ( $UGR < 22$ ,  $UGR < 25$ ), illuminance and high uniformity when the system is installed in low spaces. Particularly recommended for rooms where luminaires are mounted at a height of 2.5-5m.

**SN** - standard narrow lens (standard narrow, conventional angle 65D) for general lighting in open areas in industrial and warehouse halls, workshops, and even - due to the low glare index  $UGR < 19$  - in office parts of the facility. Particularly recommended for rooms where lighting fixtures are mounted at a height of 8-12m.

**VN** - very narrow lens (very narrow, conventional angle 30D) for illuminating open spaces in facilities where the luminaire mounting height exceeds 13m. Particularly recommended for premises where luminaires are mounted at heights of 13-20m.

**CN** - corridor narrow lens (corridor narrow, conventional angle 35/67D) for communication lighting in industrial halls and shelf aisles in high storage warehouses. Particularly suitable for rooms where luminaires are mounted at a height of 7-12m.

**DAN** - butterfly lens, double asymmetric narrow, for shelf lighting in retail facilities where it is essential to direct light onto the goods on display. Particularly recommended for premises where luminaires are mounted at heights of 3-4.5m.


**SA-L** - Single asymmetric lens (single asymmetric, left - supply side view) for single-sided illumination of shelf areas in retail spaces, signs, advertising surfaces on building walls, illumination of work surfaces in conditions where it is not possible to position luminaires directly above them. Particularly suitable for rooms where luminaires are mounted at heights of 3-4.5m.

**SA-R** - single asymmetric lens, right - view from the supply side, for single-sided illumination of shelf areas in retail spaces, signs, advertising surfaces on the walls of a building, illumination of working areas in conditions where it is not possible to position luminaires directly above them. Particularly suitable for spaces where luminaires are mounted at heights of 3-4.5m.

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 09/2023; 172/2023; 465/2023

