


# TERRANO P

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]*:</b>	9.00 - 53.00
<b>Luminous flux [lm]*:</b>	1050 - 6300
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Material of the body:</b>	powder coated steel
<b>Colour of the body:</b>	black; white
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	matrix led
<b>Mounting version:</b>	recessed
<b>Dimensions (H/W/T/S) [mm]:</b>	566/40/34; 1117/40/34;

## CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses allows extremely effective glare reduction (UGR of 12-19). Terrano luminaires are characterised by excellent performance and a number of conveniences. These include, above all, express installation in plasterboard and modular ceilings. The Terrano P lamp - a plastic louver in a slim steel housing - is available in two colour temperatures of 3000 K and 4000 K and in two colour versions: white and black.

## APPLICATION

Terrano P is suitable for installation in plasterboard and modular ceilings and is ideal as general lighting, but it can also be used to spotlight selected elements of a space. Terrano P can be used both as an eye-catching feature in modern settings where lighting plays a key role and to complement subtle, minimalist spaces.

# TERRANO P

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
9	1050	3000	black		566/40/34	<a href="#">&gt;&gt; 946462</a>
9	1100	4000	black		566/40/34	<a href="#">&gt;&gt; 946370</a>
9	1150	3000	white		566/40/34	<a href="#">&gt;&gt; 946288</a>
9	1200	4000	white		566/40/34	<a href="#">&gt;&gt; 946141</a>
16	1750	3000	black		566/40/34	<a href="#">&gt;&gt; 946479</a>
16	1850	4000	black		566/40/34	<a href="#">&gt;&gt; 946387</a>
16	1950	3000	white		566/40/34	<a href="#">&gt;&gt; 946295</a>
16	2050	4000	white		566/40/34	<a href="#">&gt;&gt; 946158</a>
22	2300	3000	black		566/40/34	<a href="#">&gt;&gt; 946240</a>
22	2300	3000	black	yes	566/40/34	<a href="#">&gt;&gt; 946486</a>
22	2400	4000	black		566/40/34	<a href="#">&gt;&gt; 946004</a>
22	2400	4000	black	yes	566/40/34	<a href="#">&gt;&gt; 946394</a>
22	2500	3000	white		566/40/34	<a href="#">&gt;&gt; 946264</a>
22	2500	3000	white	yes	566/40/34	<a href="#">&gt;&gt; 946301</a>
22	2650	4000	white		566/40/34	<a href="#">&gt;&gt; 946042</a>
22	2650	4000	white	yes	566/40/34	<a href="#">&gt;&gt; 946165</a>
28	2850	4000	black	yes	566/40/34	<a href="#">&gt;&gt; 577949</a>
28	2850	3000	black	yes	566/40/34	<a href="#">&gt;&gt; 577963</a>
28	2850	4000	black		566/40/34	<a href="#">&gt;&gt; 946400</a>
28	2850	3000	black		566/40/34	<a href="#">&gt;&gt; 946493</a>
28	2950	3000	white	yes	566/40/34	<a href="#">&gt;&gt; 577925</a>
28	2950	3000	white		566/40/34	<a href="#">&gt;&gt; 946318</a>
28	3150	4000	white	yes	566/40/34	<a href="#">&gt;&gt; 577901</a>
28	3150	4000	white		566/40/34	<a href="#">&gt;&gt; 946172</a>
22	2300	3000	black		1117/40/34	<a href="#">&gt;&gt; 946257</a>
22	2400	4000	black		1117/40/34	<a href="#">&gt;&gt; 946011</a>
22	2500	3000	white		1117/40/34	<a href="#">&gt;&gt; 946271</a>
22	2650	4000	white		1117/40/34	<a href="#">&gt;&gt; 946059</a>
28	2700	3000	black	yes	1117/40/34	<a href="#">&gt;&gt; 577970</a>
28	2700	3000	black		1117/40/34	<a href="#">&gt;&gt; 946530</a>
28	2850	4000	black	yes	1117/40/34	<a href="#">&gt;&gt; 577956</a>
28	2850	4000	black		1117/40/34	<a href="#">&gt;&gt; 946448</a>
28	2950	3000	white	yes	1117/40/34	<a href="#">&gt;&gt; 577932</a>
28	2950	3000	white		1117/40/34	<a href="#">&gt;&gt; 946356</a>
28	3150	4000	white	yes	1117/40/34	<a href="#">&gt;&gt; 577918</a>

# TERRANO P

## GENERAL CARD

28	3150	4000	white		1117/40/34	<a href="#">&gt;&gt; 946219</a>
35	3700	3000	black		1117/40/34	<a href="#">&gt;&gt; 946509</a>
35	3900	4000	black		1117/40/34	<a href="#">&gt;&gt; 946417</a>
35	4100	3000	white		1117/40/34	<a href="#">&gt;&gt; 946325</a>
35	4300	4000	white		1117/40/34	<a href="#">&gt;&gt; 946189</a>
40	4100	3000	black		1117/40/34	<a href="#">&gt;&gt; 946516</a>
40	4400	4000	black		1117/40/34	<a href="#">&gt;&gt; 946424</a>
40	4600	3000	white		1117/40/34	<a href="#">&gt;&gt; 946332</a>
40	4800	4000	white		1117/40/34	<a href="#">&gt;&gt; 946196</a>
44	4600	3000	white	yes	1117/40/34	<a href="#">&gt;&gt; 946363</a>
44	4600	4000	black	yes	1117/40/34	<a href="#">&gt;&gt; 946547</a>
44	4800	4000	black	yes	1117/40/34	<a href="#">&gt;&gt; 946455</a>
44	5000	4000	white	yes	1117/40/34	<a href="#">&gt;&gt; 946226</a>
53	5400	3000	black		1117/40/34	<a href="#">&gt;&gt; 946523</a>
53	5700	4000	black		1117/40/34	<a href="#">&gt;&gt; 946431</a>
53	5900	3000	white		1117/40/34	<a href="#">&gt;&gt; 946349</a>
53	6300	4000	white		1117/40/34	<a href="#">&gt;&gt; 946202</a>

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 01/2024