

# RQ 160 LED PLUS P AW

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44/20
<b>Rated power of the luminaire [W]*:</b>	19.00; 22.00
<b>Luminous flux [lm]*:</b>	1700 - 2900
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	D; E; F
<b>Material of the body:</b>	ABS
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	MAT; OPAL; PRM
<b>Mounting version:</b>	recessed
<b>Dimensions (H/W/T/S) [mm]:</b>	162/70;
<b>CNBOP certificate:</b>	5152/2023

## CHARACTERISTICS

RQ 160 LED PLUS P AW is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

# RQ 160 LED PLUS P AW

GENERAL CARD

## AVAILABLE VERSIONS




Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Emergency luminous flux [lm]*	Diffuser type	Emergency lighting [h]	Index
19	3000	1700	180	MAT	3	<a href="#">&gt;&gt; 571510</a>
19	4000	1800	180	MAT	3	<a href="#">&gt;&gt; 571336</a>
19	3000	1900	180	OPAL	3	<a href="#">&gt;&gt; 571633</a>
19	4000	2050	180	OPAL	3	<a href="#">&gt;&gt; 571459</a>
19	3000	2100	180	PRM	3	<a href="#">&gt;&gt; 571572</a>
19	4000	2200	180	PRM	3	<a href="#">&gt;&gt; 571398</a>
22	3000	2300	180	MAT	3	<a href="#">&gt;&gt; 571541</a>
22	4000	2450	180	MAT	3	<a href="#">&gt;&gt; 571367</a>
22	3000	2600	180	OPAL	3	<a href="#">&gt;&gt; 571664</a>
22	4000	2750	180	OPAL	3	<a href="#">&gt;&gt; 571480</a>
22	3000	2750	180	PRM	3	<a href="#">&gt;&gt; 571602</a>
22	4000	2900	180	PRM	3	<a href="#">&gt;&gt; 571428</a>


# RQ 160 LED PLUS P AW

GENERAL CARD


## LUMINOUS INTENSITY DISTRIB. CURVE



RQ MAT



RQ Opal



RQ PRM

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 322/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl