

# TERRANO R

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]*:</b>	23.00 - 43.00
<b>Luminous flux [lm]*:</b>	3000 - 6300
<b>Colour temperature [K]:</b>	3000; 4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	D; E
<b>Material of the body:</b>	powder coated steel
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	matrix led
<b>Dimensions (H/W/T/S) [mm]:</b>	1180/46/55;
<b>Mounting version:</b>	to T-profile ceilings suspended

## CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses allows extremely effective glare reduction (UGR of 12-19). Terrano luminaires are characterised by excellent performance and a number of conveniences. Above all, it is the express installation on the supporting structure of the modular ceiling. The mounting location of the same lamp can be changed just as quickly. Changing the location will not leave any traces of mounting holes. For convenience and aesthetics, the lamp is fitted with an extremely thin power cable, which fits between the structure and the ceiling tile. An additional feature of the luminaire is the swivelling light system of up to 45°.

## APPLICATION

Terrano is a luminaire which can be fitted directly into modular ceiling profiles and is ideal for general lighting, but can also be used to spotlight selected elements of a space. Terrano can be used both as an effective element of modern arrangements where lighting plays a key role and as a complement to subtle, minimalist spaces.

# TERRANO R

GENERAL CARD

## AVAILABLE VERSIONS




Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
23	3000	3000	60	black	1180/46/55	<a href="#">&gt;&gt; 937644</a>
23	4000	3200	60	black	1180/46/55	<a href="#">&gt;&gt; 937729</a>
23	3000	3300	60	white	1180/46/55	<a href="#">&gt;&gt; 937682</a>
23	4000	3500	60	white	1180/46/55	<a href="#">&gt;&gt; 937767</a>
29	3000	3700	60	black	1180/46/55	<a href="#">&gt;&gt; 937651</a>
29	4000	3900	60	black	1180/46/55	<a href="#">&gt;&gt; 937736</a>
29	3000	4100	60	white	1180/46/55	<a href="#">&gt;&gt; 937699</a>
29	4000	4300	60	white	1180/46/55	<a href="#">&gt;&gt; 937774</a>
34	3000	4100	60	black	1180/46/55	<a href="#">&gt;&gt; 937668</a>
34	4000	4400	60	black	1180/46/55	<a href="#">&gt;&gt; 937743</a>
34	3000	4600	60	white	1180/46/55	<a href="#">&gt;&gt; 937705</a>
34	4000	4800	60	white	1180/46/55	<a href="#">&gt;&gt; 937781</a>
43	3000	5400	60	black	1180/46/55	<a href="#">&gt;&gt; 937675</a>
43	4000	5700	60	black	1180/46/55	<a href="#">&gt;&gt; 937750</a>
43	3000	5900	60	white	1180/46/55	<a href="#">&gt;&gt; 937712</a>
43	4000	6000	70	white	1180/46/55	<a href="#">&gt;&gt; 420832</a>
43	4000	6300	60	white	1180/46/55	<a href="#">&gt;&gt; 937798</a>

# TERRANO R

## GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



60D

Card creation date: 25 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 64/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl