

TERRANO R

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Rated power of the luminaire [W]*:	28.00 - 53.00
Luminous flux [lm]*:	3000 - 6300
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	D; E
Material of the body:	powder coated steel
Diffuser material:	PC
Diffuser type:	matrix led
Dimensions (H/W/T/S) [mm]:	1180/46/55;
Mounting version:	to T-profile ceilings suspended

CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses allows extremely effective glare reduction (UGR of 12-19). Terrano luminaires are characterised by excellent performance and a number of conveniences. Above all, it is the express installation on the supporting structure of the modular ceiling. The mounting location of the same lamp can be changed just as quickly. Changing the location will not leave any traces of mounting holes. For convenience and aesthetics, the lamp is fitted with an extremely thin power cable, which fits between the structure and the ceiling tile. An additional feature of the luminaire is the swivelling light system of up to 45°.

APPLICATION

Terrano is a luminaire which can be fitted directly into modular ceiling profiles and is ideal for general lighting, but can also be used to spotlight selected elements of a space. Terrano can be used both as an effective element of modern arrangements where lighting plays a key role and as a complement to subtle, minimalist spaces.

TERRANO R

GENERAL CARD

AVAILABLE VERSIONS




Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	3000	3000	black	1180/46/55	>> 937644
28	4000	3200	black	1180/46/55	>> 937729
28	3000	3300	white	1180/46/55	>> 937682
28	4000	3500	white	1180/46/55	>> 937767
35	3000	3700	black	1180/46/55	>> 937651
35	4000	3900	black	1180/46/55	>> 937736
35	3000	4100	white	1180/46/55	>> 937699
35	4000	4300	white	1180/46/55	>> 937774
40	3000	4100	black	1180/46/55	>> 937668
40	4000	4400	black	1180/46/55	>> 937743
40	3000	4600	white	1180/46/55	>> 937705
40	4000	4800	white	1180/46/55	>> 937781
53	3000	5400	black	1180/46/55	>> 937675
53	4000	5700	black	1180/46/55	>> 937750
53	3000	5900	white	1180/46/55	>> 937712
53	4000	6300	white	1180/46/55	>> 937798

TERRANO R

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



60D

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 21/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl