

LINEA S LED SINGLE IP54

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------------|---------------------------------------------------|
| Ingress protection: | IP54 |
| Impact resistance: | IK03 |
| Rated power of the luminaire [W]*: | 22.00 - 142.00 |
| Luminous flux [lm]*: | 3200 - 23400 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | B; C |
| Material of the body: | coated steel |
| Colour of the body: | RAL9010 |
| Diffuser material: | PC |
| Diffuser type: | matrix led |
| Mounting version: | surface, suspended |
| Dimensions (H/W/T/S) [mm]: | 588/60/50; 1181/60/50; 1495/60/50; 1769/60/50; |
| HACCP: | 852/2004 |
| ENEC Certificate: | 0331/ENEC/23 |

CHARACTERISTICS

LINEA S LED SINGLE is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. The high IP54 sealing rating allows the lamps to be installed in environments with increased humidity and dust. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

Attention!

The suspension should be selected separately, as an accessory, depending on the intended installation method.

Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.

Surface mounting does not require the selection of mounting accessories.

APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.

LINEA S LED SINGLE IP54

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Linea S LED Single IP54 1

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 22 | 3200 | IP54 | 105 | symmetric | yes | | 588/60/50 | >> 587375 |
| 22 | 3200 | IP54 | 105 | symmetric | | | 588/60/50 | >> 587337 |
| 22 | 3550 | IP54 | 120 | symmetric | yes | | 588/60/50 | >> 587047 |
| 22 | 3550 | IP54 | 120 | symmetric | | | 588/60/50 | >> 587009 |
| 22 | 3500 | IP54 | 90 | MW | yes | | 588/60/50 | >> 587214 |
| 22 | 3500 | IP54 | 90 | MW | | | 588/60/50 | >> 587177 |
| 22 | 3500 | IP54 | 80 | SW | yes | | 588/60/50 | >> 587139 |
| 22 | 3500 | IP54 | 80 | SW | | | 588/60/50 | >> 587092 |
| 22 | 3500 | IP54 | 105 | VW | yes | | 588/60/50 | >> 587290 |
| 22 | 3500 | IP54 | 105 | VW | | | 588/60/50 | >> 587252 |
| 22 | 3300 | IP54 | butterfly | DAN | | | 588/60/50 | >> 849206 |
| 22 | 3300 | IP54 | butterfly | DAN | yes | | 588/60/50 | >> 849244 |
| 22 | 3350 | IP54 | asymmetric | SA | | | 588/60/50 | >> 846809 |
| 22 | 3350 | IP54 | asymmetric | SA | yes | | 588/60/50 | >> 846847 |
| 22 | 3400 | IP54 | 35/67 | CN | | | 588/60/50 | >> 853845 |
| 22 | 3400 | IP54 | 35/67 | CN | yes | | 588/60/50 | >> 853883 |
| 22 | 3400 | IP54 | 65 | SN | | | 588/60/50 | >> 856167 |
| 22 | 3400 | IP54 | 65 | SN | yes | | 588/60/50 | >> 856204 |
| 22 | 3400 | IP54 | 30 | VN | | | 588/60/50 | >> 851520 |
| 22 | 3400 | IP54 | 30 | VN | yes | | 588/60/50 | >> 851568 |
| 27 | 3900 | IP54 | 105 | symmetric | yes | | 588/60/50 | >> 587382 |
| 27 | 3900 | IP54 | 105 | symmetric | | | 588/60/50 | >> 587344 |
| 27 | 4300 | IP54 | 120 | symmetric | yes | | 588/60/50 | >> 587054 |
| 27 | 4300 | IP54 | 120 | symmetric | | | 588/60/50 | >> 587016 |
| 27 | 4250 | IP54 | 90 | MW | yes | | 588/60/50 | >> 587221 |
| 27 | 4250 | IP54 | 90 | MW | | | 588/60/50 | >> 587184 |
| 27 | 4250 | IP54 | 80 | SW | yes | | 588/60/50 | >> 587146 |
| 27 | 4250 | IP54 | 80 | SW | | | 588/60/50 | >> 587108 |
| 27 | 4250 | IP54 | 105 | VW | yes | | 588/60/50 | >> 587306 |
| 27 | 4250 | IP54 | 105 | VW | | | 588/60/50 | >> 587269 |
| 27 | 4000 | IP54 | butterfly | DAN | | | 588/60/50 | >> 849213 |
| 27 | 4000 | IP54 | butterfly | DAN | yes | | 588/60/50 | >> 849251 |
| 27 | 4100 | IP54 | asymmetric | SA | | | 588/60/50 | >> 846816 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 27 | 4100 | IP54 | asymmetric | SA | yes | | 588/60/50 | >> 846854 |
| 27 | 4150 | IP54 | 35/67 | CN | | | 588/60/50 | >> 853852 |
| 27 | 4150 | IP54 | 35/67 | CN | yes | | 588/60/50 | >> 853890 |
| 27 | 4150 | IP54 | 65 | SN | | | 588/60/50 | >> 856174 |
| 27 | 4150 | IP54 | 65 | SN | yes | | 588/60/50 | >> 856211 |
| 27 | 4150 | IP54 | 30 | VN | | | 588/60/50 | >> 851537 |
| 27 | 4150 | IP54 | 30 | VN | yes | | 588/60/50 | >> 851575 |
| 32 | 4750 | IP54 | 105 | symmetric | yes | | 588/60/50 | >> 587399 |
| 32 | 4750 | IP54 | 105 | symmetric | | | 588/60/50 | >> 587351 |
| 32 | 5200 | IP54 | 120 | symmetric | yes | | 588/60/50 | >> 587061 |
| 32 | 5200 | IP54 | 120 | symmetric | | | 588/60/50 | >> 587023 |
| 32 | 5150 | IP54 | 90 | MW | yes | | 588/60/50 | >> 587238 |
| 32 | 5150 | IP54 | 90 | MW | | | 588/60/50 | >> 587191 |
| 32 | 5150 | IP54 | 80 | SW | yes | | 588/60/50 | >> 587153 |
| 32 | 5150 | IP54 | 80 | SW | | | 588/60/50 | >> 587115 |
| 32 | 5150 | IP54 | 105 | VW | yes | | 588/60/50 | >> 587313 |
| 32 | 5150 | IP54 | 105 | VW | | | 588/60/50 | >> 587276 |
| 32 | 4850 | IP54 | butterfly | DAN | | | 588/60/50 | >> 849220 |
| 32 | 4850 | IP54 | butterfly | DAN | yes | | 588/60/50 | >> 849268 |
| 32 | 4950 | IP54 | asymmetric | SA | | | 588/60/50 | >> 846823 |
| 32 | 4950 | IP54 | asymmetric | SA | yes | | 588/60/50 | >> 846861 |
| 32 | 5050 | IP54 | 35/67 | CN | | | 588/60/50 | >> 853869 |
| 32 | 5050 | IP54 | 35/67 | CN | yes | | 588/60/50 | >> 853906 |
| 32 | 5050 | IP54 | 65 | SN | | | 588/60/50 | >> 856181 |
| 32 | 5050 | IP54 | 65 | SN | yes | | 588/60/50 | >> 856228 |
| 32 | 5050 | IP54 | 30 | VN | | | 588/60/50 | >> 851544 |
| 32 | 5050 | IP54 | 30 | VN | yes | | 588/60/50 | >> 851582 |
| 36 | 5300 | IP54 | 105 | symmetric | yes | | 588/60/50 | >> 587405 |
| 36 | 5300 | IP54 | 105 | symmetric | | | 588/60/50 | >> 587368 |
| 36 | 5800 | IP54 | 120 | symmetric | yes | | 588/60/50 | >> 587078 |
| 36 | 5800 | IP54 | 120 | symmetric | | | 588/60/50 | >> 587030 |
| 36 | 5750 | IP54 | 90 | MW | yes | | 588/60/50 | >> 587245 |
| 36 | 5750 | IP54 | 90 | MW | | | 588/60/50 | >> 587207 |
| 36 | 5750 | IP54 | 80 | SW | yes | | 588/60/50 | >> 587160 |
| 36 | 5750 | IP54 | 80 | SW | | | 588/60/50 | >> 587122 |
| 36 | 5750 | IP54 | 105 | VW | yes | | 588/60/50 | >> 587320 |
| 36 | 5750 | IP54 | 105 | VW | | | 588/60/50 | >> 587283 |
| 36 | 5450 | IP54 | butterfly | DAN | | | 588/60/50 | >> 849237 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 36 | 5450 | IP54 | butterfly | DAN | yes | | 588/60/50 | >> 849275 |
| 36 | 5500 | IP54 | asymmetric | SA | | | 588/60/50 | >> 846830 |
| 36 | 5500 | IP54 | asymmetric | SA | yes | | 588/60/50 | >> 846878 |
| 36 | 5650 | IP54 | 35/67 | CN | | | 588/60/50 | >> 853876 |
| 36 | 5650 | IP54 | 35/67 | CN | yes | | 588/60/50 | >> 853913 |
| 36 | 5650 | IP54 | 65 | SN | | | 588/60/50 | >> 856198 |
| 36 | 5650 | IP54 | 65 | SN | yes | | 588/60/50 | >> 856235 |
| 36 | 5650 | IP54 | 30 | VN | | | 588/60/50 | >> 851551 |
| 36 | 5650 | IP54 | 30 | VN | yes | | 588/60/50 | >> 851599 |

Linea S LED Single IP54 2

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 35 | 5350 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 585906 |
| 35 | 5350 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 586903 |
| 35 | 5350 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 585807 |
| 35 | 5350 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 586804 |
| 35 | 5850 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 585104 |
| 35 | 5850 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 586101 |
| 35 | 5850 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 585005 |
| 35 | 5850 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 586002 |
| 35 | 5800 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 585500 |
| 35 | 5800 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 586507 |
| 35 | 5800 | IP54 | 90 | MW | | | 1181/60/50 | >> 585401 |
| 35 | 5800 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 586408 |
| 35 | 5800 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 585302 |
| 35 | 5800 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 586309 |
| 35 | 5800 | IP54 | 80 | SW | | | 1181/60/50 | >> 585203 |
| 35 | 5800 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 586200 |
| 35 | 5800 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 585708 |
| 35 | 5800 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 586705 |
| 35 | 5800 | IP54 | 105 | VW | | | 1181/60/50 | >> 585609 |
| 35 | 5800 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 586606 |
| 35 | 5500 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848841 |
| 35 | 5500 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848933 |
| 35 | 5500 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 849022 |
| 35 | 5500 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 849114 |
| 35 | 5550 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846441 |
| 35 | 5550 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846533 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 35 | 5550 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846625 |
| 35 | 5550 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846717 |
| 35 | 5700 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853487 |
| 35 | 5700 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853579 |
| 35 | 5700 | IP54 | 65 | SN | | | 1181/60/50 | >> 855801 |
| 35 | 5700 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855894 |
| 35 | 5700 | IP54 | 30 | VN | | | 1181/60/50 | >> 851162 |
| 35 | 5700 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 851254 |
| 35 | 5700 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853661 |
| 35 | 5700 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853753 |
| 35 | 5700 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 855986 |
| 35 | 5700 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 856075 |
| 35 | 5700 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 851346 |
| 35 | 5700 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 851438 |
| 41 | 6400 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 007590 |
| 41 | 6400 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 007606 |
| 41 | 6400 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 007576 |
| 41 | 6400 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 007583 |
| 41 | 7000 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 007156 |
| 41 | 7000 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 007163 |
| 41 | 7000 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 007132 |
| 41 | 7000 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 007149 |
| 41 | 6900 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 003196 |
| 41 | 6900 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 003202 |
| 41 | 6900 | IP54 | 90 | MW | | | 1181/60/50 | >> 003172 |
| 41 | 6900 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 003189 |
| 41 | 6900 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 005534 |
| 41 | 6900 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 005541 |
| 41 | 6900 | IP54 | 80 | SW | | | 1181/60/50 | >> 005510 |
| 41 | 6900 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 005527 |
| 41 | 6900 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 003639 |
| 41 | 6900 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 003646 |
| 41 | 6900 | IP54 | 105 | VW | | | 1181/60/50 | >> 003615 |
| 41 | 6900 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 003622 |
| 41 | 6550 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848520 |
| 41 | 6550 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848544 |
| 41 | 6550 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 848537 |
| 41 | 6550 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 848551 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 41 | 6650 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846120 |
| 41 | 6650 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846144 |
| 41 | 6650 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846137 |
| 41 | 6650 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846151 |
| 41 | 6750 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853166 |
| 41 | 6750 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853180 |
| 41 | 6750 | IP54 | 65 | SN | | | 1181/60/50 | >> 855481 |
| 41 | 6750 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855504 |
| 41 | 6750 | IP54 | 30 | VN | | | 1181/60/50 | >> 850844 |
| 41 | 6750 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 850868 |
| 41 | 6750 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853173 |
| 41 | 6750 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853197 |
| 41 | 6750 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 855498 |
| 41 | 6750 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 855511 |
| 41 | 6750 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 850851 |
| 41 | 6750 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 850875 |
| 49 | 7550 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 585920 |
| 49 | 7550 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 586927 |
| 49 | 7550 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 585814 |
| 49 | 7550 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 586811 |
| 49 | 8250 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 585128 |
| 49 | 8250 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 586125 |
| 49 | 8250 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 585012 |
| 49 | 8250 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 586019 |
| 49 | 8200 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 585524 |
| 49 | 8200 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 586521 |
| 49 | 8200 | IP54 | 90 | MW | | | 1181/60/50 | >> 585418 |
| 49 | 8200 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 586415 |
| 49 | 8200 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 585326 |
| 49 | 8200 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 586323 |
| 49 | 8200 | IP54 | 80 | SW | | | 1181/60/50 | >> 585210 |
| 49 | 8200 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 586217 |
| 49 | 8200 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 585722 |
| 49 | 8200 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 586729 |
| 49 | 8200 | IP54 | 105 | VW | | | 1181/60/50 | >> 585616 |
| 49 | 8200 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 586613 |
| 49 | 7750 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848858 |
| 49 | 7750 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848940 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 49 | 7750 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 849039 |
| 49 | 7750 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 849121 |
| 49 | 7900 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846458 |
| 49 | 7900 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846540 |
| 49 | 7900 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846632 |
| 49 | 7900 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846724 |
| 49 | 8050 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853494 |
| 49 | 8050 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853586 |
| 49 | 8050 | IP54 | 65 | SN | | | 1181/60/50 | >> 855818 |
| 49 | 8050 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855900 |
| 49 | 8050 | IP54 | 30 | VN | | | 1181/60/50 | >> 851179 |
| 49 | 8050 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 851261 |
| 49 | 8050 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853678 |
| 49 | 8050 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853760 |
| 49 | 8050 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 855993 |
| 49 | 8050 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 856082 |
| 49 | 8050 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 851353 |
| 49 | 8050 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 851445 |
| 55 | 8400 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 007637 |
| 55 | 8400 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 007644 |
| 55 | 8400 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 007613 |
| 55 | 8400 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 007620 |
| 55 | 9300 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 007194 |
| 55 | 9300 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 007200 |
| 55 | 9300 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 007170 |
| 55 | 9300 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 007187 |
| 55 | 9200 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 003233 |
| 55 | 9200 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 003240 |
| 55 | 9200 | IP54 | 90 | MW | | | 1181/60/50 | >> 003219 |
| 55 | 9200 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 003226 |
| 55 | 9200 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 005572 |
| 55 | 9200 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 005589 |
| 55 | 9200 | IP54 | 80 | SW | | | 1181/60/50 | >> 005558 |
| 55 | 9200 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 005565 |
| 55 | 9200 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 003677 |
| 55 | 9200 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 003684 |
| 55 | 9200 | IP54 | 105 | VW | | | 1181/60/50 | >> 003653 |
| 55 | 9200 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 003660 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 55 | 8700 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848568 |
| 55 | 8700 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848582 |
| 55 | 8700 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 848575 |
| 55 | 8700 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 848599 |
| 55 | 8850 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846168 |
| 55 | 8850 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846182 |
| 55 | 8850 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846175 |
| 55 | 8850 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846199 |
| 55 | 9050 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853203 |
| 55 | 9050 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853227 |
| 55 | 9050 | IP54 | 65 | SN | | | 1181/60/50 | >> 855528 |
| 55 | 9050 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855542 |
| 55 | 9050 | IP54 | 30 | VN | | | 1181/60/50 | >> 850882 |
| 55 | 9050 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 850905 |
| 55 | 9050 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853210 |
| 55 | 9050 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853234 |
| 55 | 9050 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 855535 |
| 55 | 9050 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 855559 |
| 55 | 9050 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 850899 |
| 55 | 9050 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 850912 |
| 62 | 9500 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 007477 |
| 62 | 9500 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 007484 |
| 62 | 9500 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 007453 |
| 62 | 9500 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 007460 |
| 62 | 10400 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 007033 |
| 62 | 10400 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 007040 |
| 62 | 10400 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 007019 |
| 62 | 10400 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 007026 |
| 62 | 10300 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 003073 |
| 62 | 10300 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 003080 |
| 62 | 10300 | IP54 | 90 | MW | | | 1181/60/50 | >> 003059 |
| 62 | 10300 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 003066 |
| 62 | 10300 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 983290 |
| 62 | 10300 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 983306 |
| 62 | 10300 | IP54 | 80 | SW | | | 1181/60/50 | >> 983276 |
| 62 | 10300 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 983283 |
| 62 | 10300 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 003516 |
| 62 | 10300 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 003523 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 62 | 10300 | IP54 | 105 | VW | | | 1181/60/50 | >> 003493 |
| 62 | 10300 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 003509 |
| 62 | 10100 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853043 |
| 62 | 10100 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853067 |
| 62 | 10100 | IP54 | 65 | SN | | | 1181/60/50 | >> 855368 |
| 62 | 10100 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855382 |
| 62 | 10100 | IP54 | 30 | VN | | | 1181/60/50 | >> 850721 |
| 62 | 10100 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 850745 |
| 62 | 10100 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853050 |
| 62 | 10100 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853074 |
| 62 | 10100 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 855375 |
| 62 | 10100 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 855399 |
| 62 | 10100 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 850738 |
| 62 | 10100 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 850752 |
| 62 | 9750 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848407 |
| 62 | 9750 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848421 |
| 62 | 9750 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 848414 |
| 62 | 9750 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 848438 |
| 62 | 9900 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846007 |
| 62 | 9900 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846021 |
| 62 | 9900 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846014 |
| 62 | 9900 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846038 |
| 74 | 11100 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 007675 |
| 74 | 11100 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 007682 |
| 74 | 11100 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 007651 |
| 74 | 11100 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 007668 |
| 74 | 12200 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 007231 |
| 74 | 12200 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 007248 |
| 74 | 12200 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 007217 |
| 74 | 12200 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 007224 |
| 74 | 12100 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 003271 |
| 74 | 12100 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 003288 |
| 74 | 12100 | IP54 | 90 | MW | | | 1181/60/50 | >> 003257 |
| 74 | 12100 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 003264 |
| 74 | 12100 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 005619 |
| 74 | 12100 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 005626 |
| 74 | 12100 | IP54 | 80 | SW | | | 1181/60/50 | >> 005596 |
| 74 | 12100 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 005602 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 74 | 12100 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 003714 |
| 74 | 12100 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 003721 |
| 74 | 12100 | IP54 | 105 | VW | | | 1181/60/50 | >> 003691 |
| 74 | 12100 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 003707 |
| 74 | 11450 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848605 |
| 74 | 11450 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848629 |
| 74 | 11450 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 848612 |
| 74 | 11450 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 848636 |
| 74 | 11650 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846205 |
| 74 | 11650 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846229 |
| 74 | 11650 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846212 |
| 74 | 11650 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846236 |
| 74 | 11900 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853241 |
| 74 | 11900 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853265 |
| 74 | 11900 | IP54 | 65 | SN | | | 1181/60/50 | >> 855566 |
| 74 | 11900 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855580 |
| 74 | 11900 | IP54 | 30 | VN | | | 1181/60/50 | >> 850929 |
| 74 | 11900 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 850943 |
| 74 | 11900 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853258 |
| 74 | 11900 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853272 |
| 74 | 11900 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 855573 |
| 74 | 11900 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 855597 |
| 74 | 11900 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 850936 |
| 74 | 11900 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 850950 |
| 88 | 13000 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 007712 |
| 88 | 13000 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 007729 |
| 88 | 13000 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 007699 |
| 88 | 13000 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 007705 |
| 88 | 14300 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 007279 |
| 88 | 14300 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 007286 |
| 88 | 14300 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 007255 |
| 88 | 14300 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 007262 |
| 88 | 14100 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 003318 |
| 88 | 14100 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 003325 |
| 88 | 14100 | IP54 | 90 | MW | | | 1181/60/50 | >> 003295 |
| 88 | 14100 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 003301 |
| 88 | 14100 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 005657 |
| 88 | 14100 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 005664 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 88 | 14100 | IP54 | 80 | SW | | | 1181/60/50 | >> 005633 |
| 88 | 14100 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 005640 |
| 88 | 14100 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 003752 |
| 88 | 14100 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 003769 |
| 88 | 14100 | IP54 | 105 | VW | | | 1181/60/50 | >> 003738 |
| 88 | 14100 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 003745 |
| 88 | 13350 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848643 |
| 88 | 13350 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848667 |
| 88 | 13350 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 848650 |
| 88 | 13350 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 848674 |
| 88 | 13600 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846243 |
| 88 | 13600 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846267 |
| 88 | 13600 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846250 |
| 88 | 13600 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846274 |
| 88 | 13850 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853289 |
| 88 | 13850 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853302 |
| 88 | 13850 | IP54 | 65 | SN | | | 1181/60/50 | >> 855603 |
| 88 | 13850 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855627 |
| 88 | 13850 | IP54 | 30 | VN | | | 1181/60/50 | >> 850967 |
| 88 | 13850 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 850981 |
| 88 | 13850 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853296 |
| 88 | 13850 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853319 |
| 88 | 13850 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 855610 |
| 88 | 13850 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 855634 |
| 88 | 13850 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 850974 |
| 88 | 13850 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 850998 |
| 92 | 13700 | IP54 | 105 | symmetric | yes | | 1181/60/50 | >> 585937 |
| 92 | 13700 | IP54 | 105 | symmetric | yes | LS2 | 1181/60/50 | >> 586934 |
| 92 | 13700 | IP54 | 105 | symmetric | | | 1181/60/50 | >> 585821 |
| 92 | 13700 | IP54 | 105 | symmetric | | LS2 | 1181/60/50 | >> 586828 |
| 92 | 15100 | IP54 | 120 | symmetric | yes | | 1181/60/50 | >> 585135 |
| 92 | 15100 | IP54 | 120 | symmetric | yes | LS2 | 1181/60/50 | >> 586132 |
| 92 | 15100 | IP54 | 120 | symmetric | | | 1181/60/50 | >> 585029 |
| 92 | 15100 | IP54 | 120 | symmetric | | LS2 | 1181/60/50 | >> 586026 |
| 92 | 14900 | IP54 | 90 | MW | yes | | 1181/60/50 | >> 585531 |
| 92 | 14900 | IP54 | 90 | MW | yes | LS2 | 1181/60/50 | >> 586538 |
| 92 | 14900 | IP54 | 90 | MW | | | 1181/60/50 | >> 585425 |
| 92 | 14900 | IP54 | 90 | MW | | LS2 | 1181/60/50 | >> 586422 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 92 | 14900 | IP54 | 80 | SW | yes | | 1181/60/50 | >> 585333 |
| 92 | 14900 | IP54 | 80 | SW | yes | LS2 | 1181/60/50 | >> 586330 |
| 92 | 14900 | IP54 | 80 | SW | | | 1181/60/50 | >> 585227 |
| 92 | 14900 | IP54 | 80 | SW | | LS2 | 1181/60/50 | >> 586224 |
| 92 | 14900 | IP54 | 105 | VW | yes | | 1181/60/50 | >> 585739 |
| 92 | 14900 | IP54 | 105 | VW | yes | LS2 | 1181/60/50 | >> 586736 |
| 92 | 14900 | IP54 | 105 | VW | | | 1181/60/50 | >> 585623 |
| 92 | 14900 | IP54 | 105 | VW | | LS2 | 1181/60/50 | >> 586620 |
| 92 | 14150 | IP54 | butterfly | DAN | | | 1181/60/50 | >> 848865 |
| 92 | 14150 | IP54 | butterfly | DAN | yes | | 1181/60/50 | >> 848957 |
| 92 | 14150 | IP54 | butterfly | DAN | | LS2 | 1181/60/50 | >> 849046 |
| 92 | 14150 | IP54 | butterfly | DAN | yes | LS2 | 1181/60/50 | >> 849138 |
| 92 | 14350 | IP54 | asymmetric | SA | | | 1181/60/50 | >> 846465 |
| 92 | 14350 | IP54 | asymmetric | SA | yes | | 1181/60/50 | >> 846557 |
| 92 | 14350 | IP54 | asymmetric | SA | | LS2 | 1181/60/50 | >> 846649 |
| 92 | 14350 | IP54 | asymmetric | SA | yes | LS2 | 1181/60/50 | >> 846731 |
| 92 | 14650 | IP54 | 35/67 | CN | | | 1181/60/50 | >> 853500 |
| 92 | 14650 | IP54 | 35/67 | CN | yes | | 1181/60/50 | >> 853593 |
| 92 | 14650 | IP54 | 65 | SN | | | 1181/60/50 | >> 855825 |
| 92 | 14650 | IP54 | 65 | SN | yes | | 1181/60/50 | >> 855917 |
| 92 | 14650 | IP54 | 30 | VN | | | 1181/60/50 | >> 851186 |
| 92 | 14650 | IP54 | 30 | VN | yes | | 1181/60/50 | >> 851278 |
| 92 | 14650 | IP54 | 35/67 | CN | | LS2 | 1181/60/50 | >> 853685 |
| 92 | 14650 | IP54 | 35/67 | CN | yes | LS2 | 1181/60/50 | >> 853777 |
| 92 | 14650 | IP54 | 65 | SN | | LS2 | 1181/60/50 | >> 856006 |
| 92 | 14650 | IP54 | 65 | SN | yes | LS2 | 1181/60/50 | >> 856099 |
| 92 | 14650 | IP54 | 30 | VN | | LS2 | 1181/60/50 | >> 851360 |
| 92 | 14650 | IP54 | 30 | VN | yes | LS2 | 1181/60/50 | >> 851452 |

Linea S LED Single IP54 3

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 35 | 5350 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 585944 |
| 35 | 5350 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 586941 |
| 35 | 5350 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 585838 |
| 35 | 5350 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 586835 |
| 35 | 5850 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 585142 |
| 35 | 5850 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 586149 |
| 35 | 5850 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 585036 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 35 | 5850 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 586033 |
| 35 | 5800 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 585548 |
| 35 | 5800 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 586545 |
| 35 | 5800 | IP54 | 90 | MW | | | 1495/60/50 | >> 585432 |
| 35 | 5800 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 586439 |
| 35 | 5800 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 585340 |
| 35 | 5800 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 586347 |
| 35 | 5800 | IP54 | 80 | SW | | | 1495/60/50 | >> 585234 |
| 35 | 5800 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 586231 |
| 35 | 5800 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 585746 |
| 35 | 5800 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 586743 |
| 35 | 5800 | IP54 | 105 | VW | | | 1495/60/50 | >> 585630 |
| 35 | 5800 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 586637 |
| 35 | 5500 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848872 |
| 35 | 5500 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848964 |
| 35 | 5500 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 849053 |
| 35 | 5500 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 849145 |
| 35 | 5550 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846472 |
| 35 | 5550 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846564 |
| 35 | 5550 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846656 |
| 35 | 5550 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846748 |
| 35 | 5700 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853517 |
| 35 | 5700 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853609 |
| 35 | 5700 | IP54 | 65 | SN | | | 1495/60/50 | >> 855832 |
| 35 | 5700 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855924 |
| 35 | 5700 | IP54 | 30 | VN | | | 1495/60/50 | >> 851193 |
| 35 | 5700 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 851285 |
| 35 | 5700 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853692 |
| 35 | 5700 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853784 |
| 35 | 5700 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 856013 |
| 35 | 5700 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 856105 |
| 35 | 5700 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 851377 |
| 35 | 5700 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 851469 |
| 41 | 6400 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 007750 |
| 41 | 6400 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 007767 |
| 41 | 6400 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 007736 |
| 41 | 6400 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 007743 |
| 41 | 7000 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 007316 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 41 | 7000 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 007323 |
| 41 | 7000 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 007293 |
| 41 | 7000 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 007309 |
| 41 | 6900 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 003356 |
| 41 | 6900 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 003363 |
| 41 | 6900 | IP54 | 90 | MW | | | 1495/60/50 | >> 003332 |
| 41 | 6900 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 003349 |
| 41 | 6900 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 005695 |
| 41 | 6900 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 005701 |
| 41 | 6900 | IP54 | 80 | SW | | | 1495/60/50 | >> 005671 |
| 41 | 6900 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 005688 |
| 41 | 6900 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 003790 |
| 41 | 6900 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 003806 |
| 41 | 6900 | IP54 | 105 | VW | | | 1495/60/50 | >> 003776 |
| 41 | 6900 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 003783 |
| 41 | 6550 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848681 |
| 41 | 6550 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848704 |
| 41 | 6550 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 848698 |
| 41 | 6550 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 848711 |
| 41 | 6650 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846281 |
| 41 | 6650 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846304 |
| 41 | 6650 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846298 |
| 41 | 6650 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846311 |
| 41 | 6750 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853326 |
| 41 | 6750 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853340 |
| 41 | 6750 | IP54 | 65 | SN | | | 1495/60/50 | >> 855641 |
| 41 | 6750 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855665 |
| 41 | 6750 | IP54 | 30 | VN | | | 1495/60/50 | >> 851001 |
| 41 | 6750 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 851025 |
| 41 | 6750 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853333 |
| 41 | 6750 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853357 |
| 41 | 6750 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 855658 |
| 41 | 6750 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 855672 |
| 41 | 6750 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 851018 |
| 41 | 6750 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 851032 |
| 49 | 7550 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 585951 |
| 49 | 7550 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 586958 |
| 49 | 7550 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 585845 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 49 | 7550 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 586842 |
| 49 | 8250 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 585159 |
| 49 | 8250 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 586156 |
| 49 | 8250 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 585043 |
| 49 | 8250 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 586040 |
| 49 | 8200 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 585555 |
| 49 | 8200 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 586552 |
| 49 | 8200 | IP54 | 90 | MW | | | 1495/60/50 | >> 585449 |
| 49 | 8200 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 586446 |
| 49 | 8200 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 585357 |
| 49 | 8200 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 586354 |
| 49 | 8200 | IP54 | 80 | SW | | | 1495/60/50 | >> 585241 |
| 49 | 8200 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 586248 |
| 49 | 8200 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 585753 |
| 49 | 8200 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 586750 |
| 49 | 8200 | IP54 | 105 | VW | | | 1495/60/50 | >> 585647 |
| 49 | 8200 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 586644 |
| 49 | 7750 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848889 |
| 49 | 7750 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848971 |
| 49 | 7750 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 849060 |
| 49 | 7750 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 849152 |
| 49 | 7900 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846489 |
| 49 | 7900 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846571 |
| 49 | 7900 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846663 |
| 49 | 7900 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846755 |
| 49 | 8050 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853524 |
| 49 | 8050 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853616 |
| 49 | 8050 | IP54 | 65 | SN | | | 1495/60/50 | >> 855849 |
| 49 | 8050 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855931 |
| 49 | 8050 | IP54 | 30 | VN | | | 1495/60/50 | >> 851209 |
| 49 | 8050 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 851292 |
| 49 | 8050 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853708 |
| 49 | 8050 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853791 |
| 49 | 8050 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 856020 |
| 49 | 8050 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 856112 |
| 49 | 8050 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 851384 |
| 49 | 8050 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 851476 |
| 55 | 8400 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 007798 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 55 | 8400 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 007804 |
| 55 | 8400 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 007774 |
| 55 | 8400 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 007781 |
| 55 | 9300 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 007354 |
| 55 | 9300 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 007361 |
| 55 | 9300 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 007330 |
| 55 | 9300 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 007347 |
| 55 | 9200 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 003394 |
| 55 | 9200 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 003400 |
| 55 | 9200 | IP54 | 90 | MW | | | 1495/60/50 | >> 003370 |
| 55 | 9200 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 003387 |
| 55 | 9200 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 005732 |
| 55 | 9200 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 005749 |
| 55 | 9200 | IP54 | 80 | SW | | | 1495/60/50 | >> 005718 |
| 55 | 9200 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 005725 |
| 55 | 9200 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 003837 |
| 55 | 9200 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 003844 |
| 55 | 9200 | IP54 | 105 | VW | | | 1495/60/50 | >> 003813 |
| 55 | 9200 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 003820 |
| 55 | 8700 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848728 |
| 55 | 8700 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848742 |
| 55 | 8700 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 848735 |
| 55 | 8700 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 848759 |
| 55 | 8850 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846328 |
| 55 | 8850 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846342 |
| 55 | 8850 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846335 |
| 55 | 8850 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846359 |
| 55 | 9050 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853364 |
| 55 | 9050 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853388 |
| 55 | 9050 | IP54 | 65 | SN | | | 1495/60/50 | >> 855689 |
| 55 | 9050 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855702 |
| 55 | 9050 | IP54 | 30 | VN | | | 1495/60/50 | >> 851049 |
| 55 | 9050 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 851063 |
| 55 | 9050 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853371 |
| 55 | 9050 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853395 |
| 55 | 9050 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 855696 |
| 55 | 9050 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 855719 |
| 55 | 9050 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 851056 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 55 | 9050 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 851070 |
| 62 | 9500 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 007514 |
| 62 | 9500 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 007521 |
| 62 | 9500 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 007491 |
| 62 | 9500 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 007507 |
| 62 | 10400 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 007071 |
| 62 | 10400 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 007088 |
| 62 | 10400 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 007057 |
| 62 | 10400 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 007064 |
| 62 | 10300 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 003110 |
| 62 | 10300 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 003127 |
| 62 | 10300 | IP54 | 90 | MW | | | 1495/60/50 | >> 003097 |
| 62 | 10300 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 003103 |
| 62 | 10300 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 983337 |
| 62 | 10300 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 983344 |
| 62 | 10300 | IP54 | 80 | SW | | | 1495/60/50 | >> 983313 |
| 62 | 10300 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 983320 |
| 62 | 10300 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 003554 |
| 62 | 10300 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 003561 |
| 62 | 10300 | IP54 | 105 | VW | | | 1495/60/50 | >> 003530 |
| 62 | 10300 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 003547 |
| 62 | 10100 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853081 |
| 62 | 10100 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853104 |
| 62 | 10100 | IP54 | 65 | SN | | | 1495/60/50 | >> 855405 |
| 62 | 10100 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855429 |
| 62 | 10100 | IP54 | 30 | VN | | | 1495/60/50 | >> 850769 |
| 62 | 10100 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 850783 |
| 62 | 10100 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853098 |
| 62 | 10100 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853111 |
| 62 | 10100 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 855412 |
| 62 | 10100 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 855436 |
| 62 | 10100 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 850776 |
| 62 | 10100 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 850790 |
| 62 | 9750 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848445 |
| 62 | 9750 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848469 |
| 62 | 9750 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 848452 |
| 62 | 9750 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 848476 |
| 62 | 9900 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846045 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 62 | 9900 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846069 |
| 62 | 9900 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846052 |
| 62 | 9900 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846076 |
| 74 | 11100 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 007835 |
| 74 | 11100 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 007842 |
| 74 | 11100 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 007811 |
| 74 | 11100 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 007828 |
| 74 | 12200 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 007392 |
| 74 | 12200 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 007408 |
| 74 | 12200 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 007378 |
| 74 | 12200 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 007385 |
| 74 | 12100 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 003431 |
| 74 | 12100 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 003448 |
| 74 | 12100 | IP54 | 90 | MW | | | 1495/60/50 | >> 003417 |
| 74 | 12100 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 003424 |
| 74 | 12100 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 005770 |
| 74 | 12100 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 005787 |
| 74 | 12100 | IP54 | 80 | SW | | | 1495/60/50 | >> 005756 |
| 74 | 12100 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 005763 |
| 74 | 12100 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 003875 |
| 74 | 12100 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 003882 |
| 74 | 12100 | IP54 | 105 | VW | | | 1495/60/50 | >> 003851 |
| 74 | 12100 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 003868 |
| 74 | 11450 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848766 |
| 74 | 11450 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848780 |
| 74 | 11450 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 848773 |
| 74 | 11450 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 848797 |
| 74 | 11650 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846366 |
| 74 | 11650 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846380 |
| 74 | 11650 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846373 |
| 74 | 11650 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846397 |
| 74 | 11900 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853401 |
| 74 | 11900 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853425 |
| 74 | 11900 | IP54 | 65 | SN | | | 1495/60/50 | >> 855726 |
| 74 | 11900 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855740 |
| 74 | 11900 | IP54 | 30 | VN | | | 1495/60/50 | >> 851087 |
| 74 | 11900 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 851100 |
| 74 | 11900 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853418 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 74 | 11900 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853432 |
| 74 | 11900 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 855733 |
| 74 | 11900 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 855757 |
| 74 | 11900 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 851094 |
| 74 | 11900 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 851117 |
| 88 | 13000 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 007873 |
| 88 | 13000 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 007880 |
| 88 | 13000 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 007859 |
| 88 | 13000 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 007866 |
| 88 | 14300 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 007439 |
| 88 | 14300 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 007446 |
| 88 | 14300 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 007415 |
| 88 | 14300 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 007422 |
| 88 | 14100 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 003479 |
| 88 | 14100 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 003486 |
| 88 | 14100 | IP54 | 90 | MW | | | 1495/60/50 | >> 003455 |
| 88 | 14100 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 003462 |
| 88 | 14100 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 005817 |
| 88 | 14100 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 005824 |
| 88 | 14100 | IP54 | 80 | SW | | | 1495/60/50 | >> 005794 |
| 88 | 14100 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 005800 |
| 88 | 14100 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 003981 |
| 88 | 14100 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 003998 |
| 88 | 14100 | IP54 | 105 | VW | | | 1495/60/50 | >> 003967 |
| 88 | 14100 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 003974 |
| 88 | 13350 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848803 |
| 88 | 13350 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848827 |
| 88 | 13350 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 848810 |
| 88 | 13350 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 848834 |
| 88 | 13600 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846403 |
| 88 | 13600 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846427 |
| 88 | 13600 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846410 |
| 88 | 13600 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846434 |
| 88 | 13850 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853449 |
| 88 | 13850 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853463 |
| 88 | 13850 | IP54 | 65 | SN | | | 1495/60/50 | >> 855764 |
| 88 | 13850 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855788 |
| 88 | 13850 | IP54 | 30 | VN | | | 1495/60/50 | >> 851124 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 88 | 13850 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 851148 |
| 88 | 13850 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853456 |
| 88 | 13850 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853470 |
| 88 | 13850 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 855771 |
| 88 | 13850 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 855795 |
| 88 | 13850 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 851131 |
| 88 | 13850 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 851155 |
| 92 | 13700 | IP54 | 105 | symmetric | yes | | 1495/60/50 | >> 585968 |
| 92 | 13700 | IP54 | 105 | symmetric | yes | LS2 | 1495/60/50 | >> 586965 |
| 92 | 13700 | IP54 | 105 | symmetric | | | 1495/60/50 | >> 585852 |
| 92 | 13700 | IP54 | 105 | symmetric | | LS2 | 1495/60/50 | >> 586859 |
| 92 | 15100 | IP54 | 120 | symmetric | yes | | 1495/60/50 | >> 585166 |
| 92 | 15100 | IP54 | 120 | symmetric | yes | LS2 | 1495/60/50 | >> 586163 |
| 92 | 15100 | IP54 | 120 | symmetric | | | 1495/60/50 | >> 585050 |
| 92 | 15100 | IP54 | 120 | symmetric | | LS2 | 1495/60/50 | >> 586057 |
| 92 | 14900 | IP54 | 90 | MW | yes | | 1495/60/50 | >> 585562 |
| 92 | 14900 | IP54 | 90 | MW | yes | LS2 | 1495/60/50 | >> 586569 |
| 92 | 14900 | IP54 | 90 | MW | | | 1495/60/50 | >> 585456 |
| 92 | 14900 | IP54 | 90 | MW | | LS2 | 1495/60/50 | >> 586453 |
| 92 | 14900 | IP54 | 80 | SW | yes | | 1495/60/50 | >> 585364 |
| 92 | 14900 | IP54 | 80 | SW | yes | LS2 | 1495/60/50 | >> 586361 |
| 92 | 14900 | IP54 | 80 | SW | | | 1495/60/50 | >> 585258 |
| 92 | 14900 | IP54 | 80 | SW | | LS2 | 1495/60/50 | >> 586255 |
| 92 | 14900 | IP54 | 105 | VW | yes | | 1495/60/50 | >> 585760 |
| 92 | 14900 | IP54 | 105 | VW | yes | LS2 | 1495/60/50 | >> 586767 |
| 92 | 14900 | IP54 | 105 | VW | | | 1495/60/50 | >> 585654 |
| 92 | 14900 | IP54 | 105 | VW | | LS2 | 1495/60/50 | >> 586651 |
| 92 | 14150 | IP54 | butterfly | DAN | | | 1495/60/50 | >> 848896 |
| 92 | 14150 | IP54 | butterfly | DAN | yes | | 1495/60/50 | >> 848988 |
| 92 | 14150 | IP54 | butterfly | DAN | | LS2 | 1495/60/50 | >> 849077 |
| 92 | 14150 | IP54 | butterfly | DAN | yes | LS2 | 1495/60/50 | >> 849169 |
| 92 | 14350 | IP54 | asymmetric | SA | | | 1495/60/50 | >> 846496 |
| 92 | 14350 | IP54 | asymmetric | SA | yes | | 1495/60/50 | >> 846588 |
| 92 | 14350 | IP54 | asymmetric | SA | | LS2 | 1495/60/50 | >> 846670 |
| 92 | 14350 | IP54 | asymmetric | SA | yes | LS2 | 1495/60/50 | >> 846762 |
| 92 | 14650 | IP54 | 35/67 | CN | | | 1495/60/50 | >> 853531 |
| 92 | 14650 | IP54 | 35/67 | CN | yes | | 1495/60/50 | >> 853623 |
| 92 | 14650 | IP54 | 65 | SN | | | 1495/60/50 | >> 855856 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 92 | 14650 | IP54 | 65 | SN | yes | | 1495/60/50 | >> 855948 |
| 92 | 14650 | IP54 | 30 | VN | | | 1495/60/50 | >> 851216 |
| 92 | 14650 | IP54 | 30 | VN | yes | | 1495/60/50 | >> 851308 |
| 92 | 14650 | IP54 | 35/67 | CN | | LS2 | 1495/60/50 | >> 853715 |
| 92 | 14650 | IP54 | 35/67 | CN | yes | LS2 | 1495/60/50 | >> 853807 |
| 92 | 14650 | IP54 | 65 | SN | | LS2 | 1495/60/50 | >> 856037 |
| 92 | 14650 | IP54 | 65 | SN | yes | LS2 | 1495/60/50 | >> 856129 |
| 92 | 14650 | IP54 | 30 | VN | | LS2 | 1495/60/50 | >> 851391 |
| 92 | 14650 | IP54 | 30 | VN | yes | LS2 | 1495/60/50 | >> 851483 |

Linea S LED Single IP54 4

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 53 | 8250 | IP54 | 105 | symmetric | yes | | 1769/60/50 | >> 585975 |
| 53 | 8250 | IP54 | 105 | symmetric | yes | LS2 | 1769/60/50 | >> 586972 |
| 53 | 8250 | IP54 | 105 | symmetric | | | 1769/60/50 | >> 585869 |
| 53 | 8250 | IP54 | 105 | symmetric | | LS2 | 1769/60/50 | >> 586866 |
| 53 | 9100 | IP54 | 120 | symmetric | yes | | 1769/60/50 | >> 585173 |
| 53 | 9100 | IP54 | 120 | symmetric | yes | LS2 | 1769/60/50 | >> 586170 |
| 53 | 9100 | IP54 | 120 | symmetric | | | 1769/60/50 | >> 585067 |
| 53 | 9100 | IP54 | 120 | symmetric | | LS2 | 1769/60/50 | >> 586064 |
| 53 | 9000 | IP54 | 90 | MW | yes | | 1769/60/50 | >> 585579 |
| 53 | 9000 | IP54 | 90 | MW | yes | LS2 | 1769/60/50 | >> 586576 |
| 53 | 9000 | IP54 | 90 | MW | | | 1769/60/50 | >> 585463 |
| 53 | 9000 | IP54 | 90 | MW | | LS2 | 1769/60/50 | >> 586460 |
| 53 | 9000 | IP54 | 80 | SW | yes | | 1769/60/50 | >> 585371 |
| 53 | 9000 | IP54 | 80 | SW | yes | LS2 | 1769/60/50 | >> 586378 |
| 53 | 9000 | IP54 | 80 | SW | | | 1769/60/50 | >> 585265 |
| 53 | 9000 | IP54 | 80 | SW | | LS2 | 1769/60/50 | >> 586262 |
| 53 | 9000 | IP54 | 105 | VW | yes | | 1769/60/50 | >> 585777 |
| 53 | 9000 | IP54 | 105 | VW | yes | LS2 | 1769/60/50 | >> 586774 |
| 53 | 9000 | IP54 | 105 | VW | | | 1769/60/50 | >> 585661 |
| 53 | 9000 | IP54 | 105 | VW | | LS2 | 1769/60/50 | >> 586668 |
| 53 | 8550 | IP54 | butterfly | DAN | | | 1769/60/50 | >> 848902 |
| 53 | 8550 | IP54 | butterfly | DAN | yes | | 1769/60/50 | >> 848995 |
| 53 | 8550 | IP54 | butterfly | DAN | | LS2 | 1769/60/50 | >> 849084 |
| 53 | 8550 | IP54 | butterfly | DAN | yes | LS2 | 1769/60/50 | >> 849176 |
| 53 | 8650 | IP54 | asymmetric | SA | | | 1769/60/50 | >> 846502 |
| 53 | 8650 | IP54 | asymmetric | SA | yes | | 1769/60/50 | >> 846595 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 53 | 8650 | IP54 | asymmetric | SA | | LS2 | 1769/60/50 | >> 846687 |
| 53 | 8650 | IP54 | asymmetric | SA | yes | LS2 | 1769/60/50 | >> 846779 |
| 53 | 8850 | IP54 | 35/67 | CN | | | 1769/60/50 | >> 853548 |
| 53 | 8850 | IP54 | 35/67 | CN | yes | | 1769/60/50 | >> 853630 |
| 53 | 8850 | IP54 | 65 | SN | | | 1769/60/50 | >> 855863 |
| 53 | 8850 | IP54 | 65 | SN | yes | | 1769/60/50 | >> 855955 |
| 53 | 8850 | IP54 | 30 | VN | | | 1769/60/50 | >> 851223 |
| 53 | 8850 | IP54 | 30 | VN | yes | | 1769/60/50 | >> 851315 |
| 53 | 8850 | IP54 | 35/67 | CN | | LS2 | 1769/60/50 | >> 853722 |
| 53 | 8850 | IP54 | 35/67 | CN | yes | LS2 | 1769/60/50 | >> 853814 |
| 53 | 8850 | IP54 | 65 | SN | | LS2 | 1769/60/50 | >> 856044 |
| 53 | 8850 | IP54 | 65 | SN | yes | LS2 | 1769/60/50 | >> 856136 |
| 53 | 8850 | IP54 | 30 | VN | | LS2 | 1769/60/50 | >> 851407 |
| 53 | 8850 | IP54 | 30 | VN | yes | LS2 | 1769/60/50 | >> 851490 |
| 77 | 12000 | IP54 | 105 | symmetric | yes | | 1769/60/50 | >> 585982 |
| 77 | 12000 | IP54 | 105 | symmetric | yes | LS2 | 1769/60/50 | >> 586989 |
| 77 | 12000 | IP54 | 105 | symmetric | | | 1769/60/50 | >> 585876 |
| 77 | 12000 | IP54 | 105 | symmetric | | LS2 | 1769/60/50 | >> 586873 |
| 77 | 13200 | IP54 | 120 | symmetric | yes | | 1769/60/50 | >> 585180 |
| 77 | 13200 | IP54 | 120 | symmetric | yes | LS2 | 1769/60/50 | >> 586187 |
| 77 | 13200 | IP54 | 120 | symmetric | | | 1769/60/50 | >> 585074 |
| 77 | 13200 | IP54 | 120 | symmetric | | LS2 | 1769/60/50 | >> 586071 |
| 77 | 13000 | IP54 | 90 | MW | yes | | 1769/60/50 | >> 585586 |
| 77 | 13000 | IP54 | 90 | MW | yes | LS2 | 1769/60/50 | >> 586583 |
| 77 | 13000 | IP54 | 90 | MW | | | 1769/60/50 | >> 585470 |
| 77 | 13000 | IP54 | 90 | MW | | LS2 | 1769/60/50 | >> 586477 |
| 77 | 13000 | IP54 | 80 | SW | yes | | 1769/60/50 | >> 585388 |
| 77 | 13000 | IP54 | 80 | SW | yes | LS2 | 1769/60/50 | >> 586385 |
| 77 | 13000 | IP54 | 80 | SW | | | 1769/60/50 | >> 585272 |
| 77 | 13000 | IP54 | 80 | SW | | LS2 | 1769/60/50 | >> 586279 |
| 77 | 13000 | IP54 | 105 | VW | yes | | 1769/60/50 | >> 585784 |
| 77 | 13000 | IP54 | 105 | VW | yes | LS2 | 1769/60/50 | >> 586781 |
| 77 | 13000 | IP54 | 105 | VW | | | 1769/60/50 | >> 585678 |
| 77 | 13000 | IP54 | 105 | VW | | LS2 | 1769/60/50 | >> 586675 |
| 77 | 12350 | IP54 | butterfly | DAN | | | 1769/60/50 | >> 848919 |
| 77 | 12350 | IP54 | butterfly | DAN | yes | | 1769/60/50 | >> 849008 |
| 77 | 12350 | IP54 | butterfly | DAN | | LS2 | 1769/60/50 | >> 849091 |
| 77 | 12350 | IP54 | butterfly | DAN | yes | LS2 | 1769/60/50 | >> 849183 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 77 | 12500 | IP54 | asymmetric | SA | | | 1769/60/50 | >> 846519 |
| 77 | 12500 | IP54 | asymmetric | SA | yes | | 1769/60/50 | >> 846601 |
| 77 | 12500 | IP54 | asymmetric | SA | | LS2 | 1769/60/50 | >> 846694 |
| 77 | 12500 | IP54 | asymmetric | SA | yes | LS2 | 1769/60/50 | >> 846786 |
| 77 | 12800 | IP54 | 35/67 | CN | | | 1769/60/50 | >> 853555 |
| 77 | 12800 | IP54 | 35/67 | CN | yes | | 1769/60/50 | >> 853647 |
| 77 | 12800 | IP54 | 65 | SN | | | 1769/60/50 | >> 855870 |
| 77 | 12800 | IP54 | 65 | SN | yes | | 1769/60/50 | >> 855962 |
| 77 | 12800 | IP54 | 30 | VN | | | 1769/60/50 | >> 851230 |
| 77 | 12800 | IP54 | 30 | VN | yes | | 1769/60/50 | >> 851322 |
| 77 | 12800 | IP54 | 35/67 | CN | | LS2 | 1769/60/50 | >> 853739 |
| 77 | 12800 | IP54 | 35/67 | CN | yes | LS2 | 1769/60/50 | >> 853821 |
| 77 | 12800 | IP54 | 65 | SN | | LS2 | 1769/60/50 | >> 856051 |
| 77 | 12800 | IP54 | 65 | SN | yes | LS2 | 1769/60/50 | >> 856143 |
| 77 | 12800 | IP54 | 30 | VN | | LS2 | 1769/60/50 | >> 851414 |
| 77 | 12800 | IP54 | 30 | VN | yes | LS2 | 1769/60/50 | >> 851506 |
| 102 | 15600 | IP54 | 105 | symmetric | yes | | 1769/60/50 | >> 585999 |
| 102 | 15600 | IP54 | 105 | symmetric | yes | LS2 | 1769/60/50 | >> 586996 |
| 102 | 15600 | IP54 | 105 | symmetric | | | 1769/60/50 | >> 585883 |
| 102 | 15600 | IP54 | 105 | symmetric | | LS2 | 1769/60/50 | >> 586880 |
| 102 | 17100 | IP54 | 120 | symmetric | yes | | 1769/60/50 | >> 585197 |
| 102 | 17100 | IP54 | 120 | symmetric | yes | LS2 | 1769/60/50 | >> 586194 |
| 102 | 17100 | IP54 | 120 | symmetric | | | 1769/60/50 | >> 585081 |
| 102 | 17100 | IP54 | 120 | symmetric | | LS2 | 1769/60/50 | >> 586088 |
| 102 | 16900 | IP54 | 90 | MW | yes | | 1769/60/50 | >> 585593 |
| 102 | 16900 | IP54 | 90 | MW | yes | LS2 | 1769/60/50 | >> 586590 |
| 102 | 16900 | IP54 | 90 | MW | | | 1769/60/50 | >> 585487 |
| 102 | 16900 | IP54 | 90 | MW | | LS2 | 1769/60/50 | >> 586484 |
| 102 | 16900 | IP54 | 80 | SW | yes | | 1769/60/50 | >> 585395 |
| 102 | 16900 | IP54 | 80 | SW | yes | LS2 | 1769/60/50 | >> 586392 |
| 102 | 16900 | IP54 | 80 | SW | | | 1769/60/50 | >> 585289 |
| 102 | 16900 | IP54 | 80 | SW | | LS2 | 1769/60/50 | >> 586286 |
| 102 | 16900 | IP54 | 105 | VW | yes | | 1769/60/50 | >> 585791 |
| 102 | 16900 | IP54 | 105 | VW | yes | LS2 | 1769/60/50 | >> 586798 |
| 102 | 16900 | IP54 | 105 | VW | | | 1769/60/50 | >> 585685 |
| 102 | 16900 | IP54 | 105 | VW | | LS2 | 1769/60/50 | >> 586682 |
| 102 | 16050 | IP54 | butterfly | DAN | | | 1769/60/50 | >> 848926 |
| 102 | 16050 | IP54 | butterfly | DAN | yes | | 1769/60/50 | >> 849015 |

LINEA S LED SINGLE IP54

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 102 | 16050 | IP54 | butterfly | DAN | | LS2 | 1769/60/50 | >> 849107 |
| 102 | 16050 | IP54 | butterfly | DAN | yes | LS2 | 1769/60/50 | >> 849190 |
| 102 | 16300 | IP54 | asymmetric | SA | | | 1769/60/50 | >> 846526 |
| 102 | 16300 | IP54 | asymmetric | SA | yes | | 1769/60/50 | >> 846618 |
| 102 | 16300 | IP54 | asymmetric | SA | | LS2 | 1769/60/50 | >> 846700 |
| 102 | 16300 | IP54 | asymmetric | SA | yes | LS2 | 1769/60/50 | >> 846793 |
| 102 | 16600 | IP54 | 35/67 | CN | | | 1769/60/50 | >> 853562 |
| 102 | 16600 | IP54 | 35/67 | CN | yes | | 1769/60/50 | >> 853654 |
| 102 | 16600 | IP54 | 65 | SN | | | 1769/60/50 | >> 855887 |
| 102 | 16600 | IP54 | 65 | SN | yes | | 1769/60/50 | >> 855979 |
| 102 | 16600 | IP54 | 30 | VN | | | 1769/60/50 | >> 851247 |
| 102 | 16600 | IP54 | 30 | VN | yes | | 1769/60/50 | >> 851339 |
| 102 | 16600 | IP54 | 35/67 | CN | | LS2 | 1769/60/50 | >> 853746 |
| 102 | 16600 | IP54 | 35/67 | CN | yes | LS2 | 1769/60/50 | >> 853838 |
| 102 | 16600 | IP54 | 65 | SN | | LS2 | 1769/60/50 | >> 856068 |
| 102 | 16600 | IP54 | 65 | SN | yes | LS2 | 1769/60/50 | >> 856150 |
| 102 | 16600 | IP54 | 30 | VN | | LS2 | 1769/60/50 | >> 851421 |
| 102 | 16600 | IP54 | 30 | VN | yes | LS2 | 1769/60/50 | >> 851513 |
| 142 | 21300 | IP54 | 105 | symmetric | yes | | 1769/60/50 | >> 007552 |
| 142 | 21300 | IP54 | 105 | symmetric | yes | LS2 | 1769/60/50 | >> 007569 |
| 142 | 21300 | IP54 | 105 | symmetric | | | 1769/60/50 | >> 007538 |
| 142 | 21300 | IP54 | 105 | symmetric | | LS2 | 1769/60/50 | >> 007545 |
| 142 | 23400 | IP54 | 120 | symmetric | yes | | 1769/60/50 | >> 007118 |
| 142 | 23400 | IP54 | 120 | symmetric | yes | LS2 | 1769/60/50 | >> 007125 |
| 142 | 23400 | IP54 | 120 | symmetric | | | 1769/60/50 | >> 007095 |
| 142 | 23400 | IP54 | 120 | symmetric | | LS2 | 1769/60/50 | >> 007101 |
| 142 | 23100 | IP54 | 90 | MW | yes | | 1769/60/50 | >> 003158 |
| 142 | 23100 | IP54 | 90 | MW | yes | LS2 | 1769/60/50 | >> 003165 |
| 142 | 23100 | IP54 | 90 | MW | | | 1769/60/50 | >> 003134 |
| 142 | 23100 | IP54 | 90 | MW | | LS2 | 1769/60/50 | >> 003141 |
| 142 | 23100 | IP54 | 80 | SW | yes | | 1769/60/50 | >> 983375 |
| 142 | 23100 | IP54 | 80 | SW | yes | LS2 | 1769/60/50 | >> 983382 |
| 142 | 23100 | IP54 | 80 | SW | | | 1769/60/50 | >> 983351 |
| 142 | 23100 | IP54 | 80 | SW | | LS2 | 1769/60/50 | >> 983368 |
| 142 | 23100 | IP54 | 105 | VW | yes | | 1769/60/50 | >> 003592 |
| 142 | 23100 | IP54 | 105 | VW | yes | LS2 | 1769/60/50 | >> 003608 |
| 142 | 23100 | IP54 | 105 | VW | | | 1769/60/50 | >> 003578 |
| 142 | 23100 | IP54 | 105 | VW | | LS2 | 1769/60/50 | >> 003585 |

LINEA S LED SINGLE IP54


GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Ingress protection | Beam angle [°] | Light distribution type | DIMM DALI | Through wiring | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|--------------------|----------------|-------------------------|-----------|----------------|---------------------------|---------------------------------|
| 142 | 21900 | IP54 | butterfly | DAN | | | 1769/60/50 | >> 848483 |
| 142 | 21900 | IP54 | butterfly | DAN | yes | | 1769/60/50 | >> 848506 |
| 142 | 21900 | IP54 | butterfly | DAN | | LS2 | 1769/60/50 | >> 848490 |
| 142 | 21900 | IP54 | butterfly | DAN | yes | LS2 | 1769/60/50 | >> 848513 |
| 142 | 22250 | IP54 | asymmetric | SA | | | 1769/60/50 | >> 846083 |
| 142 | 22250 | IP54 | asymmetric | SA | yes | | 1769/60/50 | >> 846106 |
| 142 | 22250 | IP54 | asymmetric | SA | | LS2 | 1769/60/50 | >> 846090 |
| 142 | 22250 | IP54 | asymmetric | SA | yes | LS2 | 1769/60/50 | >> 846113 |
| 142 | 22750 | IP54 | 35/67 | CN | | | 1769/60/50 | >> 853128 |
| 142 | 22750 | IP54 | 35/67 | CN | yes | | 1769/60/50 | >> 853142 |
| 142 | 22750 | IP54 | 65 | SN | | | 1769/60/50 | >> 855443 |
| 142 | 22750 | IP54 | 65 | SN | yes | | 1769/60/50 | >> 855467 |
| 142 | 22750 | IP54 | 30 | VN | | | 1769/60/50 | >> 850806 |
| 142 | 22750 | IP54 | 30 | VN | yes | | 1769/60/50 | >> 850820 |
| 142 | 22750 | IP54 | 35/67 | CN | | LS2 | 1769/60/50 | >> 853135 |
| 142 | 22750 | IP54 | 35/67 | CN | yes | LS2 | 1769/60/50 | >> 853159 |
| 142 | 22750 | IP54 | 65 | SN | | LS2 | 1769/60/50 | >> 855450 |
| 142 | 22750 | IP54 | 65 | SN | yes | LS2 | 1769/60/50 | >> 855474 |
| 142 | 22750 | IP54 | 30 | VN | | LS2 | 1769/60/50 | >> 850813 |
| 142 | 22750 | IP54 | 30 | VN | yes | LS2 | 1769/60/50 | >> 850837 |


LINEA S LED SINGLE IP54

GENERAL CARD


LUMINOUS INTENSITY DISTRIB. CURVE




105D




120D




CN




DAN




MW




SN



SW



VN



VW

LINEA S LED SINGLE IP54

GENERAL CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|----------------------------|
| 981173 | LINEA S LED hang 1.5m |
| 980077 | LINEA S LED hang 3m |
| 981425 | LINEA S LED chain pendant |
| 981418 | LINEA S LED pendant sm 1.5 |
| 980961 | LINEA S LED pendant sm 3m |



LINEA S LED hang 1.5m (981173)



LINEA S LED chain pendant (981425)

LINEA S LED SINGLE IP54

GENERAL CARD

Linea S LED Single is equipped with new light distributions:

SW - standard wide lens (conventional angle 80D) with a wide range of applications in commercial facilities, industrial halls, and even - due to the low glare index $UGR < 19$ - in office parts of the facility. It provides high lighting efficiency and helps meet the most stringent requirements of the EN 12464-1 standard in terms of the glare index, illuminance and high uniformity on the surface of aisles and shelves. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-8m.

MW - medium wide lens (90D conventional angle) with a wide range of applications in commercial facilities, industrial halls. It provides high lighting efficiency and helps meet the most stringent requirements of the EN 12464-1 standard in terms of glare index, illuminance and high uniformity on the surface of aisles and shelves. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-6m.

VW - a very wide lens (105D conventional angle) with wide application in open spaces and low warehouses. It provides high luminous efficacy and helps meet the most stringent requirements of EN 12464-1 in terms of glare index ($UGR < 22$, $UGR < 25$), illuminance and high uniformity when the system is installed in low spaces. Particularly recommended for rooms where luminaires are mounted at a height of 2.5-5m.

SN - standard narrow lens (standard narrow, conventional angle 65D) for general lighting in open areas in industrial and warehouse halls, workshops, and even - due to the low glare index $UGR < 19$ - in office parts of the facility. Particularly recommended for rooms where lighting fixtures are mounted at a height of 8-12m.

VN - very narrow lens (very narrow, conventional angle 30D) for illumination of open spaces in facilities where the luminaire mounting height exceeds 13m. Particularly recommended for premises where luminaires are mounted at a height of 13-20m.

CN - corridor narrow lens (corridor narrow, conventional angle 35/67D) for communication lighting in industrial halls and racking aisles in high storage warehouses. Particularly suitable for rooms where luminaires are mounted at a height of 7-12m.

DAN - butterfly lens, double asymmetric narrow, for shelf lighting in retail facilities where it is essential to direct light onto the goods on display. Particularly recommended for premises where luminaires are mounted at a height of 3-4.5m.

SA - single asymmetric lens for single-sided illumination of shelf areas in retail spaces, signs, advertising surfaces on building walls, illumination of work surfaces in conditions where it is not possible to position luminaires directly above them. Particularly suitable for spaces where luminaires are mounted at heights of 3-4.5m.

UGR < 19

The Unified Glare Rating is an indicator that characterises glare. The lower the Unified Glare Rating (UGR), the lower the glare.

Card creation date: 29 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 32/2024

