LINEA S LED SINGLE IP54

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK03
Rated power of the luminaire [W]*:	23.00 - 142.00
Luminous flux [lm]*:	3600 - 25800
Colour temperature [K]:	4000
Energy efficiency class:	A; B; C; G
Material of the body:	coated steel
Colour of the body:	RAL9010
Diffuser material:	PC
Diffuser type:	matrix led
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	588/60/50; 1181/60/50; 1495/60/50; 1769/60/50;
HACCP:	852/2004
ENEC Certificate:	0331/ENEC/23
Optics:	2 rows

CHARACTERISTICS

LINEA S LED SINGLE is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. The high IP54 sealing rating allows the lamps to be installed in environments with increased humidity and dust. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

Attention!
The suspension should be selected separately, as an accessory, depending on the intended installation method.
Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.
Surface mounting does not require the selection of mounting accessories.

APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.

LINEA S LED SINGLE IP54

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Linea S LED Single IP54

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	5727	IP54		MW MAT			LS2	1181/60/50	>> 154652
35	5727	IP54		MW MAT		yes	LS2	1181/60/50	>> 154744
35	5727	IP54		SW MAT			LS2	1181/60/50	>> 158186
35	5727	IP54		SW MAT		yes	LS2	1181/60/50	>> 158292
35	5650	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 158186/2
35	5650	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 158292/2
35	5650	IP54		VW MAT			LS2	1181/60/50	>> 165184
35	5650	IP54		VW MAT		yes	LS2	1181/60/50	>> 165276
35	5650	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 165184/2
35	5650	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 165276/2
35	5750	IP54		SA MAT			LS2	1181/60/50	>> 198076
35	5750	IP54		SA MAT		yes	LS2	1181/60/50	>> 198168
35	5750	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 198076/2
35	5750	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 198168/2
35	5750	IP54		SN MAT			LS2	1181/60/50	>> 186240
35	5750	IP54		SN MAT		yes	LS2	1181/60/50	>> 186332
35	5850	IP54		DAN MAT			LS2	1181/60/50	>> 203428
35	5850	IP54		DAN MAT		yes	LS2	1181/60/50	>> 203886
35	5850	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 203428/2
35	5850	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 203886/2
35	6208	IP54		MW MAT				1181/60/50	>> 154478
35	6208	IP54		MW MAT		yes		1181/60/50	>> 154560
35	6208	IP54		SW MAT				1181/60/50	>> 157974
35	6208	IP54		SW MAT		yes		1181/60/50	>> 158094
35	6150	IP54		SW MAT	2 rows			1181/60/50	>> 157974/2
35	6150	IP54		SW MAT	2 rows	yes		1181/60/50	>> 158094/2
35	6150	IP54		VW MAT				1181/60/50	>> 163999
35	6150	IP54		VW MAT		yes		1181/60/50	>> 165092

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	6150	IP54		VW MAT	2 rows			1181/60/50	>> 163999/2
35	6150	IP54		VW MAT	2 rows	yes		1181/60/50	>> 165092/2
35	6200	IP54		SA MAT				1181/60/50	>> 197888
35	6200	IP54		SA MAT		yes		1181/60/50	>> 197970
35	6200	IP54		SA MAT	2 rows			1181/60/50	>> 197888/2
35	6200	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197970/2
35	6200	IP54		SN MAT				1181/60/50	>> 186059
35	6200	IP54		SN MAT		yes		1181/60/50	>> 186158
35	6350	IP54		DAN MAT				1181/60/50	>> 203237
35	6350	IP54		DAN MAT		yes		1181/60/50	>> 203336
35	6350	IP54		DAN MAT	2 rows			1181/60/50	>> 203237/2
35	6350	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 203336/2
41	7652	IP54		MW MAT				1181/60/50	>> 154133
41	7652	IP54		MW MAT		yes		1181/60/50	>> 154157
41	7652	IP54		SW MAT				1181/60/50	>> 157639
41	7652	IP54		SW MAT		yes		1181/60/50	>> 157653
41	7600	IP54		SW MAT	2 rows			1181/60/50	>> 157639/2
41	7600	IP54		SW MAT	2 rows	yes		1181/60/50	>> 157653/2
41	7600	IP54		VW MAT				1181/60/50	>> 163654
41	7600	IP54		VW MAT		yes		1181/60/50	>> 163678
41	7600	IP54		VW MAT	2 rows			1181/60/50	>> 163654/2
41	7600	IP54		VW MAT	2 rows	yes		1181/60/50	>> 163678/2
41	7652	IP54		MW MAT			LS2	1181/60/50	>> 154140
41	7652	IP54		MW MAT		yes	LS2	1181/60/50	>> 154164
41	7652	IP54		SW MAT			LS2	1181/60/50	>> 157646
41	7652	IP54		SW MAT		yes	LS2	1181/60/50	>> 157660
41	7600	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 157646/2
41	7600	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 157660/2
41	7600	IP54		VW MAT			LS2	1181/60/50	>> 163661
41	7600	IP54		VW MAT		yes	LS2	1181/60/50	>> 163685
41	7600	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 163661/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
41	7600	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 163685/2
41	7650	IP54		SA MAT				1181/60/50	>> 197543
41	7650	IP54		SA MAT		yes		1181/60/50	>> 197567
41	7650	IP54		SA MAT	2 rows			1181/60/50	>> 197543/2
41	7650	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197567/2
41	7650	IP54		SN MAT				1181/60/50	>> 184550
41	7650	IP54		SN MAT		yes		1181/60/50	>> 184574
41	7650	IP54		SA MAT			LS2	1181/60/50	>> 197550
41	7650	IP54		SA MAT		yes	LS2	1181/60/50	>> 197574
41	7650	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 197550/2
41	7650	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 197574/2
41	7650	IP54		SN MAT			LS2	1181/60/50	>> 184567
41	7650	IP54		SN MAT		yes	LS2	1181/60/50	>> 184581
41	7850	IP54		DAN MAT				1181/60/50	>> 202872
41	7850	IP54		DAN MAT		yes		1181/60/50	>> 202896
41	7850	IP54		DAN MAT	2 rows			1181/60/50	>> 202872/2
41	7850	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 202896/2
41	7850	IP54		DAN MAT			LS2	1181/60/50	>> 202889
41	7850	IP54		DAN MAT		yes	LS2	1181/60/50	>> 202919
41	7850	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 202889/2
41	7850	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 202919/2
48	8952	IP54		MW MAT				1181/60/50	>> 154485
48	8952	IP54		MW MAT		yes		1181/60/50	>> 154577
48	8952	IP54		SW MAT				1181/60/50	>> 157981
48	8952	IP54		SW MAT		yes		1181/60/50	>> 158100
48	8850	IP54		SW MAT	2 rows			1181/60/50	>> 157981/2
48	8850	IP54		SW MAT	2 rows	yes		1181/60/50	>> 158100/2
48	8850	IP54		VW MAT				1181/60/50	>> 165016
48	8850	IP54		VW MAT		yes		1181/60/50	>> 165108
48	8850	IP54		VW MAT	2 rows			1181/60/50	>> 165016/2
48	8850	IP54		VW MAT	2 rows	yes		1181/60/50	>> 165108/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
48	8952	IP54		MW MAT			LS2	1181/60/50	>> 154669
48	8952	IP54		MW MAT		yes	LS2	1181/60/50	>> 154751
48	8952	IP54		SW MAT			LS2	1181/60/50	>> 158193
48	8952	IP54		SW MAT		yes	LS2	1181/60/50	>> 158308
48	8850	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 158193/2
48	8850	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 158308/2
48	8850	IP54		VW MAT			LS2	1181/60/50	>> 165191
48	8850	IP54		VW MAT		yes	LS2	1181/60/50	>> 165283
48	8850	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 165191/2
48	8850	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 165283/2
48	8950	IP54		SA MAT				1181/60/50	>> 197895
48	8950	IP54		SA MAT		yes		1181/60/50	>> 197987
48	8950	IP54		SA MAT	2 rows			1181/60/50	>> 197895/2
48	8950	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197987/2
48	8950	IP54		SN MAT				1181/60/50	>> 186066
48	8950	IP54		SN MAT		yes		1181/60/50	>> 186165
48	8950	IP54		SA MAT			LS2	1181/60/50	>> 198083
48	8950	IP54		SA MAT		yes	LS2	1181/60/50	>> 198175
48	8950	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 198083/2
48	8950	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 198175/2
48	8950	IP54		SN MAT			LS2	1181/60/50	>> 186257
48	8950	IP54		SN MAT		yes	LS2	1181/60/50	>> 186349
48	9150	IP54		DAN MAT				1181/60/50	>> 203244
48	9150	IP54		DAN MAT		yes		1181/60/50	>> 203343
48	9150	IP54		DAN MAT	2 rows			1181/60/50	>> 203244/2
48	9150	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 203343/2
48	9150	IP54		DAN MAT			LS2	1181/60/50	>> 203435
48	9150	IP54		DAN MAT		yes	LS2	1181/60/50	>> 203893
48	9150	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 203435/2
48	9150	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 203893/2
58	0	IP54		MW MAT				1181/60/50	>> 159022
58	10684	IP54		MW MAT		yes		1181/60/50	>> 154195

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
58		IP54		MW MAT	2 rows			1181/60/50	>> 159022/2
58	10684	IP54		SW MAT				1181/60/50	>> 157677
58	10684	IP54		SW MAT		yes		1181/60/50	>> 157691
58	10600	IP54		SW MAT	2 rows			1181/60/50	>> 157677/2
58	10600	IP54		SW MAT	2 rows	yes		1181/60/50	>> 157691/2
58	10600	IP54		VW MAT				1181/60/50	>> 163692
58	10600	IP54		VW MAT		yes		1181/60/50	>> 163715
58	10600	IP54		VW MAT	2 rows			1181/60/50	>> 163692/2
58	10600	IP54		VW MAT	2 rows	yes		1181/60/50	>> 163715/2
58	10684	IP54		MW MAT			LS2	1181/60/50	>> 154188
58	10684	IP54		MW MAT		yes	LS2	1181/60/50	>> 154201
58	10684	IP54		SW MAT			LS2	1181/60/50	>> 157684
58	10684	IP54		SW MAT		yes	LS2	1181/60/50	>> 157707
58	10600	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 157684/2
58	10600	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 157707/2
58	10600	IP54		VW MAT			LS2	1181/60/50	>> 163708
58	10600	IP54		VW MAT		yes	LS2	1181/60/50	>> 163722
58	10600	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 163708/2
58	10600	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 163722/2
58	10700	IP54		SA MAT				1181/60/50	>> 197581
58	10700	IP54		SA MAT		yes		1181/60/50	>> 197604
58	10700	IP54		SA MAT	2 rows			1181/60/50	>> 197581/2
58	10700	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197604/2
58	10700	IP54		SN MAT				1181/60/50	>> 184598
58	10700	IP54		SN MAT		yes		1181/60/50	>> 184611
58	10700	IP54		SA MAT			LS2	1181/60/50	>> 197598
58	10700	IP54		SA MAT		yes	LS2	1181/60/50	>> 197611
58	10700	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 197598/2
58	10700	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 197611/2
58	10700	IP54		SN MAT			LS2	1181/60/50	>> 184604
58	10700	IP54		SN MAT		yes	LS2	1181/60/50	>> 184628

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
58	10950	IP54		DAN MAT				1181/60/50	>> 202926
58	10950	IP54		DAN MAT		yes		1181/60/50	>> 202940
58	10950	IP54		DAN MAT	2 rows			1181/60/50	>> 202926/2
58	10950	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 202940/2
58	10950	IP54		DAN MAT			LS2	1181/60/50	>> 202933
58	10950	IP54		DAN MAT		yes	LS2	1181/60/50	>> 202957
58	10950	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 202933/2
58	10950	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 202957/2
63	11550	IP54		MW MAT				1181/60/50	>> 154010
63	11550	IP54		MW MAT		yes		1181/60/50	>> 154034
63	11550	IP54		SW MAT				1181/60/50	>> 157516
63	11550	IP54		SW MAT		yes		1181/60/50	>> 157530
63	11450	IP54		SW MAT	2 rows			1181/60/50	>> 157516/2
63	11450	IP54		SW MAT	2 rows	yes		1181/60/50	>> 157530/2
63	11450	IP54		VW MAT				1181/60/50	>> 163531
63	11450	IP54		VW MAT		yes		1181/60/50	>> 163555
63	11450	IP54		VW MAT	2 rows			1181/60/50	>> 163531/2
63	11450	IP54		VW MAT	2 rows	yes		1181/60/50	>> 163555/2
63	11550	IP54		MW MAT			LS2	1181/60/50	>> 154027
63	11550	IP54		MW MAT		yes	LS2	1181/60/50	>> 154041
63	11550	IP54		SW MAT			LS2	1181/60/50	>> 157523
63	11550	IP54		SW MAT		yes	LS2	1181/60/50	>> 157547
63	11450	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 157523/2
63	11450	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 157547/2
63	11450	IP54		VW MAT			LS2	1181/60/50	>> 163548
63	11450	IP54		VW MAT		yes	LS2	1181/60/50	>> 163562
63	11450	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 163548/2
63	11450	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 163562/2
63	11550	IP54		SA MAT				1181/60/50	>> 197420
63	11550	IP54		SA MAT		yes		1181/60/50	>> 197444
63	11550	IP54		SA MAT	2 rows			1181/60/50	>> 197420/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
63	11550	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197444/2
63	11550	IP54		SN MAT				1181/60/50	>> 184437
63	11550	IP54		SN MAT		yes		1181/60/50	>> 184451
63	11550	IP54		SA MAT			LS2	1181/60/50	>> 197437
63	11550	IP54		SA MAT		yes	LS2	1181/60/50	>> 197451
63	11550	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 197437/2
63	11550	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 197451/2
63	11550	IP54		SN MAT			LS2	1181/60/50	>> 184444
63	11550	IP54		SN MAT		yes	LS2	1181/60/50	>> 184468
63	11800	IP54		DAN MAT				1181/60/50	>> 202742
63	11800	IP54		DAN MAT		yes		1181/60/50	>> 202766
63	11800	IP54		DAN MAT	2 rows			1181/60/50	>> 202742/2
63	11800	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 202766/2
63	11800	IP54		DAN MAT			LS2	1181/60/50	>> 202759
63	11800	IP54		DAN MAT		yes	LS2	1181/60/50	>> 202773
63	11800	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 202759/2
63	11800	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 202773/2
73	13187	IP54		MW MAT				1181/60/50	>> 154218
73	13187	IP54		MW MAT		yes		1181/60/50	>> 154232
73	13187	IP54		SW MAT				1181/60/50	>> 157714
73	13187	IP54		SW MAT		yes		1181/60/50	>> 157738
73	13050	IP54		SW MAT	2 rows			1181/60/50	>> 157714/2
73	13050	IP54		SW MAT	2 rows	yes		1181/60/50	>> 157738/2
73	13050	IP54		VW MAT				1181/60/50	>> 163739
73	13050	IP54		VW MAT		yes		1181/60/50	>> 163753
73	13050	IP54		VW MAT	2 rows			1181/60/50	>> 163739/2
73	13050	IP54		VW MAT	2 rows	yes		1181/60/50	>> 163753/2
73	13187	IP54		MW MAT			LS2	1181/60/50	>> 154225
73	13187	IP54		MW MAT		yes	LS2	1181/60/50	>> 154249
73	13187	IP54		SW MAT			LS2	1181/60/50	>> 157721
73	13187	IP54		SW MAT		yes	LS2	1181/60/50	>> 157745
73	13050	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 157721/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
73	13050	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 157745/2
73	13050	IP54		VW MAT			LS2	1181/60/50	>> 163746
73	13050	IP54		VW MAT		yes	LS2	1181/60/50	>> 163760
73	13050	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 163746/2
73	13050	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 163760/2
73	13200	IP54		SA MAT				1181/60/50	>> 197628
73	13200	IP54		SA MAT		yes		1181/60/50	>> 197642
73	13200	IP54		SA MAT	2 rows			1181/60/50	>> 197628/2
73	13200	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197642/2
73	13200	IP54		SN MAT				1181/60/50	>> 184635
73	13200	IP54		SN MAT		yes		1181/60/50	>> 184659
73	13200	IP54		SA MAT			LS2	1181/60/50	>> 197635
73	13200	IP54		SA MAT		yes	LS2	1181/60/50	>> 197659
73	13200	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 197635/2
73	13200	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 197659/2
73	13200	IP54		SN MAT			LS2	1181/60/50	>> 184642
73	13200	IP54		SN MAT		yes	LS2	1181/60/50	>> 184666
73	13500	IP54		DAN MAT				1181/60/50	>> 202964
73	13500	IP54		DAN MAT		yes		1181/60/50	>> 202988
73	13500	IP54		DAN MAT	2 rows			1181/60/50	>> 202964/2
73	13500	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 202988/2
73	13500	IP54		DAN MAT			LS2	1181/60/50	>> 202971
73	13500	IP54		DAN MAT		yes	LS2	1181/60/50	>> 202995
73	13500	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 202971/2
73	13500	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 202995/2
88	15497	IP54		MW MAT				1181/60/50	>> 154256
88	15497	IP54		MW MAT		yes		1181/60/50	>> 154270
88	15497	IP54		SW MAT				1181/60/50	>> 157752
88	15497	IP54		SW MAT		yes		1181/60/50	>> 157776
88	15350	IP54		SW MAT	2 rows			1181/60/50	>> 157752/2
88	15350	IP54		SW MAT	2 rows	yes		1181/60/50	>> 157776/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	15350	IP54		VW MAT				1181/60/50	>> 163777
88	15350	IP54		VW MAT		yes		1181/60/50	>> 163791
88	15350	IP54		VW MAT	2 rows			1181/60/50	>> 163777/2
88	15350	IP54		VW MAT	2 rows	yes		1181/60/50	>> 163791/2
88	15497	IP54		MW MAT			LS2	1181/60/50	>> 154263
88	15497	IP54		MW MAT		yes	LS2	1181/60/50	>> 154287
88	15497	IP54		SW MAT			LS2	1181/60/50	>> 157769
88	15497	IP54		SW MAT		yes	LS2	1181/60/50	>> 157783
88	15350	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 157769/2
88	15350	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 157783/2
88	15350	IP54		VW MAT			LS2	1181/60/50	>> 163784
88	15350	IP54		VW MAT		yes	LS2	1181/60/50	>> 163807
88	15350	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 163784/2
88	15350	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 163807/2
88	15500	IP54		SA MAT				1181/60/50	>> 197666
88	15500	IP54		SA MAT		yes		1181/60/50	>> 197680
88	15500	IP54		SA MAT	2 rows			1181/60/50	>> 197666/2
88	15500	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197680/2
88	15500	IP54		SN MAT				1181/60/50	>> 184673
88	15500	IP54		SN MAT		yes		1181/60/50	>> 184697
88	15500	IP54		SA MAT			LS2	1181/60/50	>> 197673
88	15500	IP54		SA MAT		yes	LS2	1181/60/50	>> 197697
88	15500	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 197673/2
88	15500	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 197697/2
88	15500	IP54		SN MAT			LS2	1181/60/50	>> 184680
88	15500	IP54		SN MAT		yes	LS2	1181/60/50	>> 184703
88	15850	IP54		DAN MAT				1181/60/50	>> 203008
88	15850	IP54		DAN MAT		yes		1181/60/50	>> 203022
88	15850	IP54		DAN MAT	2 rows			1181/60/50	>> 203008/2
88	15850	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 203022/2
88	15850	IP54		DAN MAT			LS2	1181/60/50	>> 203015
88	15850	IP54		DAN MAT		yes	LS2	1181/60/50	>> 203039

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	15850	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 203015/2
88	15850	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 203039/2
92	16171	IP54		MW MAT				1181/60/50	>> 154492
92	16171	IP54		MW MAT		yes		1181/60/50	>> 154584
92	16171	IP54		SW MAT				1181/60/50	>> 157998
92	16171	IP54		SW MAT		yes		1181/60/50	>> 158117
92	16000	IP54		SW MAT	2 rows			1181/60/50	>> 157998/2
92	16000	IP54		SW MAT	2 rows	yes		1181/60/50	>> 158117/2
92	16000	IP54		VW MAT				1181/60/50	>> 165023
92	16000	IP54		VW MAT		yes		1181/60/50	>> 165115
92	16000	IP54		VW MAT	2 rows			1181/60/50	>> 165023/2
92	16000	IP54		VW MAT	2 rows	yes		1181/60/50	>> 165115/2
92	16171	IP54		MW MAT			LS2	1181/60/50	>> 154676
92	16171	IP54		MW MAT		yes	LS2	1181/60/50	>> 154768
92	16171	IP54		SW MAT			LS2	1181/60/50	>> 158223
92	16171	IP54		SW MAT		yes	LS2	1181/60/50	>> 158315
92	16000	IP54		SW MAT	2 rows		LS2	1181/60/50	>> 158223/2
92	16000	IP54		SW MAT	2 rows	yes	LS2	1181/60/50	>> 158315/2
92	16000	IP54		VW MAT			LS2	1181/60/50	>> 165207
92	16000	IP54		VW MAT		yes	LS2	1181/60/50	>> 165351
92	16000	IP54		VW MAT	2 rows		LS2	1181/60/50	>> 165207/2
92	16000	IP54		VW MAT	2 rows	yes	LS2	1181/60/50	>> 165351/2
92	16200	IP54		SA MAT				1181/60/50	>> 197901
92	16200	IP54		SA MAT		yes		1181/60/50	>> 197994
92	16200	IP54		SA MAT	2 rows			1181/60/50	>> 197901/2
92	16200	IP54		SA MAT	2 rows	yes		1181/60/50	>> 197994/2
92	16200	IP54		SN MAT				1181/60/50	>> 186073
92	16200	IP54		SN MAT		yes		1181/60/50	>> 186172
92	16200	IP54		SA MAT			LS2	1181/60/50	>> 198090
92	16200	IP54		SA MAT		yes	LS2	1181/60/50	>> 198182
92	16200	IP54		SA MAT	2 rows		LS2	1181/60/50	>> 198090/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
92	16200	IP54		SA MAT	2 rows	yes	LS2	1181/60/50	>> 198182/2
92	16200	IP54		SN MAT			LS2	1181/60/50	>> 186264
92	16200	IP54		SN MAT		yes	LS2	1181/60/50	>> 186356
92	16550	IP54		DAN MAT				1181/60/50	>> 203251
92	16550	IP54		DAN MAT		yes		1181/60/50	>> 203350
92	16550	IP54		DAN MAT	2 rows			1181/60/50	>> 203251/2
92	16550	IP54		DAN MAT	2 rows	yes		1181/60/50	>> 203350/2
92	16550	IP54		DAN MAT			LS2	1181/60/50	>> 203442
92	16550	IP54		DAN MAT		yes	LS2	1181/60/50	>> 203909
92	16550	IP54		DAN MAT	2 rows		LS2	1181/60/50	>> 203442/2
92	16550	IP54		DAN MAT	2 rows	yes	LS2	1181/60/50	>> 203909/2
35	5727	IP54		MW MAT			LS2	1495/60/50	>> 154683
35	5727	IP54		MW MAT		yes	LS2	1495/60/50	>> 154775
35	0	IP54		SW MAT			LS2	1495/60/50	>> 159039
35	5727	IP54		SW MAT		yes	LS2	1495/60/50	>> 158322
35		IP54		SW MAT	2 rows		LS2	1495/60/50	>> 159039/2
35	5650	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 158322/2
35	5650	IP54		VW MAT			LS2	1495/60/50	>> 165214
35	5650	IP54		VW MAT		yes	LS2	1495/60/50	>> 165368
35	5650	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 165214/2
35	5650	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 165368/2
35	5750	IP54		SA MAT			LS2	1495/60/50	>> 198106
35	5750	IP54		SA MAT		yes	LS2	1495/60/50	>> 198199
35	5750	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 198106/2
35	5750	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 198199/2
35	5750	IP54		SN MAT			LS2	1495/60/50	>> 186271
35	5750	IP54		SN MAT		yes	LS2	1495/60/50	>> 186363
35	5850	IP54		DAN MAT			LS2	1495/60/50	>> 203459
35	5850	IP54		DAN MAT		yes	LS2	1495/60/50	>> 203916
35	5850	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 203459/2
35	5850	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 203916/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	6208	IP54		MW MAT				1495/60/50	>> 154508
35	6208	IP54		MW MAT		yes		1495/60/50	>> 154591
35	6208	IP54		SW MAT				1495/60/50	>> 158032
35	6208	IP54		SW MAT		yes		1495/60/50	>> 158124
35	6150	IP54		SW MAT	2 rows			1495/60/50	>> 158032/2
35	6150	IP54		SW MAT	2 rows	yes		1495/60/50	>> 158124/2
35	6150	IP54		VW MAT				1495/60/50	>> 165030
35	6150	IP54		VW MAT		yes		1495/60/50	>> 165122
35	6150	IP54		VW MAT	2 rows			1495/60/50	>> 165030/2
35	6150	IP54		VW MAT	2 rows	yes		1495/60/50	>> 165122/2
35	6200	IP54		SA MAT				1495/60/50	>> 197918
35	6200	IP54		SA MAT		yes		1495/60/50	>> 198014
35	6200	IP54		SA MAT	2 rows			1495/60/50	>> 197918/2
35	6200	IP54		SA MAT	2 rows	yes		1495/60/50	>> 198014/2
35	6200	IP54		SN MAT				1495/60/50	>> 186080
35	6200	IP54		SN MAT		yes		1495/60/50	>> 186189
35	6350	IP54		DAN MAT				1495/60/50	>> 203268
35	6350	IP54		DAN MAT		yes		1495/60/50	>> 203367
35	6350	IP54		DAN MAT	2 rows			1495/60/50	>> 203268/2
35	6350	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 203367/2
41	7652	IP54		MW MAT				1495/60/50	>> 154294
41	7652	IP54		MW MAT		yes		1495/60/50	>> 154317
41	7652	IP54		SW MAT				1495/60/50	>> 157790
41	7652	IP54		SW MAT		yes		1495/60/50	>> 157813
41	7600	IP54		SW MAT	2 rows			1495/60/50	>> 157790/2
41	7600	IP54		SW MAT	2 rows	yes		1495/60/50	>> 157813/2
41	7600	IP54		VW MAT				1495/60/50	>> 163814
41	7600	IP54		VW MAT		yes		1495/60/50	>> 163838
41	7600	IP54		VW MAT	2 rows			1495/60/50	>> 163814/2
41	7600	IP54		VW MAT	2 rows	yes		1495/60/50	>> 163838/2
41	7652	IP54		MW MAT			LS2	1495/60/50	>> 154300
41	7652	IP54		MW MAT		yes	LS2	1495/60/50	>> 154324

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
41	7652	IP54		SW MAT			LS2	1495/60/50	>> 157806
41	7652	IP54		SW MAT		yes	LS2	1495/60/50	>> 157820
41	7600	IP54		SW MAT	2 rows		LS2	1495/60/50	>> 157806/2
41	7600	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 157820/2
41	7600	IP54		VW MAT			LS2	1495/60/50	>> 163821
41	7600	IP54		VW MAT		yes	LS2	1495/60/50	>> 163845
41	7600	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 163821/2
41	7600	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 163845/2
41	7650	IP54		SA MAT				1495/60/50	>> 197703
41	7650	IP54		SA MAT		yes		1495/60/50	>> 197727
41	7650	IP54		SA MAT	2 rows			1495/60/50	>> 197703/2
41	7650	IP54		SA MAT	2 rows	yes		1495/60/50	>> 197727/2
41	7650	IP54		SN MAT				1495/60/50	>> 184710
41	7650	IP54		SN MAT		yes		1495/60/50	>> 184734
41	7650	IP54		SA MAT			LS2	1495/60/50	>> 197710
41	7650	IP54		SA MAT		yes	LS2	1495/60/50	>> 197734
41	7650	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 197710/2
41	7650	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 197734/2
41	7650	IP54		SN MAT			LS2	1495/60/50	>> 184727
41	7650	IP54		SN MAT		yes	LS2	1495/60/50	>> 184741
41	7850	IP54		DAN MAT				1495/60/50	>> 203046
41	7850	IP54		DAN MAT		yes		1495/60/50	>> 203060
41	7850	IP54		DAN MAT	2 rows			1495/60/50	>> 203046/2
41	7850	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 203060/2
41	7850	IP54		DAN MAT			LS2	1495/60/50	>> 203053
41	7850	IP54		DAN MAT		yes	LS2	1495/60/50	>> 203077
41	7850	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 203053/2
41	7850	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 203077/2
48	8952	IP54		MW MAT				1495/60/50	>> 154515
48	8952	IP54		MW MAT		yes		1495/60/50	>> 154607
48	8952	IP54		SW MAT				1495/60/50	>> 158049
48	8952	IP54		SW MAT		yes		1495/60/50	>> 158131

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
48	8850	IP54		SW MAT	2 rows			1495/60/50	>> 158049/2
48	8850	IP54		SW MAT	2 rows	yes		1495/60/50	>> 158131/2
48	8850	IP54		VW MAT				1495/60/50	>> 165047
48	8850	IP54		VW MAT		yes		1495/60/50	>> 165139
48	8850	IP54		VW MAT	2 rows			1495/60/50	>> 165047/2
48	8850	IP54		VW MAT	2 rows	yes		1495/60/50	>> 165139/2
48	8952	IP54		MW MAT			LS2	1495/60/50	>> 154690
48	8952	IP54		MW MAT		yes	LS2	1495/60/50	>> 154782
48	8952	IP54		SW MAT			LS2	1495/60/50	>> 158247
48	8952	IP54		SW MAT		yes	LS2	1495/60/50	>> 158339
48	8850	IP54		SW MAT	2 rows		LS2	1495/60/50	>> 158247/2
48	8850	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 158339/2
48	8850	IP54		VW MAT			LS2	1495/60/50	>> 165221
48	8850	IP54		VW MAT		yes	LS2	1495/60/50	>> 165375
48	8850	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 165221/2
48	8850	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 165375/2
48	8950	IP54		SA MAT				1495/60/50	>> 197925
48	8950	IP54		SA MAT		yes		1495/60/50	>> 198021
48	8950	IP54		SA MAT	2 rows			1495/60/50	>> 197925/2
48	8950	IP54		SA MAT	2 rows	yes		1495/60/50	>> 198021/2
48	8950	IP54		SN MAT				1495/60/50	>> 186097
48	8950	IP54		SN MAT		yes		1495/60/50	>> 186196
48	8950	IP54		SA MAT			LS2	1495/60/50	>> 198113
48	8950	IP54		SA MAT		yes	LS2	1495/60/50	>> 198205
48	8950	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 198113/2
48	8950	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 198205/2
48	8950	IP54		SN MAT			LS2	1495/60/50	>> 186288
48	8950	IP54		SN MAT		yes	LS2	1495/60/50	>> 186370
48	9150	IP54		DAN MAT				1495/60/50	>> 203275
48	9150	IP54		DAN MAT		yes		1495/60/50	>> 203374
48	9150	IP54		DAN MAT	2 rows			1495/60/50	>> 203275/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
48	9150	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 203374/2
48	9150	IP54		DAN MAT			LS2	1495/60/50	>> 203466
48	9150	IP54		DAN MAT		yes	LS2	1495/60/50	>> 203923
48	9150	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 203466/2
48	9150	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 203923/2
58	10684	IP54		MW MAT				1495/60/50	>> 154331
58	10684	IP54		MW MAT		yes		1495/60/50	>> 154355
58	10684	IP54		SW MAT				1495/60/50	>> 157837
58	10684	IP54		SW MAT		yes		1495/60/50	>> 157851
58	10600	IP54		SW MAT	2 rows			1495/60/50	>> 157837/2
58	10600	IP54		SW MAT	2 rows	yes		1495/60/50	>> 157851/2
58	10600	IP54		VW MAT				1495/60/50	>> 163852
58	10600	IP54		VW MAT		yes		1495/60/50	>> 163876
58	10600	IP54		VW MAT	2 rows			1495/60/50	>> 163852/2
58	10600	IP54		VW MAT	2 rows	yes		1495/60/50	>> 163876/2
58	10684	IP54		MW MAT			LS2	1495/60/50	>> 154348
58	10684	IP54		MW MAT		yes	LS2	1495/60/50	>> 154362
58	10684	IP54		SW MAT			LS2	1495/60/50	>> 157844
58	10684	IP54		SW MAT		yes	LS2	1495/60/50	>> 157868
58	10600	IP54		SW MAT	2 rows		LS2	1495/60/50	>> 157844/2
58	10600	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 157868/2
58	10600	IP54		VW MAT			LS2	1495/60/50	>> 163869
58	10600	IP54		VW MAT		yes	LS2	1495/60/50	>> 163883
58	10600	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 163869/2
58	10600	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 163883/2
58	10700	IP54		SA MAT				1495/60/50	>> 197741
58	10700	IP54		SA MAT		yes		1495/60/50	>> 197765
58	10700	IP54		SA MAT	2 rows			1495/60/50	>> 197741/2
58	10700	IP54		SA MAT	2 rows	yes		1495/60/50	>> 197765/2
58	10700	IP54		SN MAT				1495/60/50	>> 184888
58	10700	IP54		SN MAT		yes		1495/60/50	>> 184901

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
58	10700	IP54		SA MAT			LS2	1495/60/50	>> 197758
58	10700	IP54		SA MAT		yes	LS2	1495/60/50	>> 197772
58	10700	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 197758/2
58	10700	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 197772/2
58	10700	IP54		SN MAT			LS2	1495/60/50	>> 184895
58	10700	IP54		SN MAT		yes	LS2	1495/60/50	>> 184918
58	10950	IP54		DAN MAT				1495/60/50	>> 203084
58	10950	IP54		DAN MAT		yes		1495/60/50	>> 203107
58	10950	IP54		DAN MAT	2 rows			1495/60/50	>> 203084/2
58	10950	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 203107/2
58	10950	IP54		DAN MAT			LS2	1495/60/50	>> 203091
58	10950	IP54		DAN MAT		yes	LS2	1495/60/50	>> 203114
58	10950	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 203091/2
58	10950	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 203114/2
63	11550	IP54		MW MAT				1495/60/50	>> 154058
63	11550	IP54		MW MAT		yes		1495/60/50	>> 154072
63	11550	IP54		SW MAT				1495/60/50	>> 157554
63	11550	IP54		SW MAT		yes		1495/60/50	>> 157578
63	11450	IP54		SW MAT	2 rows			1495/60/50	>> 157554/2
63	11450	IP54		SW MAT	2 rows	yes		1495/60/50	>> 157578/2
63	11450	IP54		VW MAT				1495/60/50	>> 163579
63	11450	IP54		VW MAT		yes		1495/60/50	>> 163593
63	11450	IP54		VW MAT	2 rows			1495/60/50	>> 163579/2
63	11450	IP54		VW MAT	2 rows	yes		1495/60/50	>> 163593/2
63	11550	IP54		MW MAT			LS2	1495/60/50	>> 154065
63	11550	IP54		MW MAT		yes	LS2	1495/60/50	>> 154089
63	11550	IP54		SW MAT			LS2	1495/60/50	>> 157561
63	11550	IP54		SW MAT		yes	LS2	1495/60/50	>> 157585
63	11450	IP54		SW MAT	2 rows		LS2	1495/60/50	>> 157561/2
63	11450	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 157585/2
63	11450	IP54		VW MAT			LS2	1495/60/50	>> 163586
63	11450	IP54		VW MAT		yes	LS2	1495/60/50	>> 163609

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
63	11450	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 163586/2
63	11450	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 163609/2
63	11550	IP54		SA MAT				1495/60/50	>> 197468
63	11550	IP54		SA MAT		yes		1495/60/50	>> 197482
63	11550	IP54		SA MAT	2 rows			1495/60/50	>> 197468/2
63	11550	IP54		SA MAT	2 rows	yes		1495/60/50	>> 197482/2
63	11550	IP54		SN MAT				1495/60/50	>> 184475
63	11550	IP54		SN MAT		yes		1495/60/50	>> 184499
63	11550	IP54		SA MAT			LS2	1495/60/50	>> 197475
63	11550	IP54		SA MAT		yes	LS2	1495/60/50	>> 197499
63	11550	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 197475/2
63	11550	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 197499/2
63	11550	IP54		SN MAT			LS2	1495/60/50	>> 184482
63	11550	IP54		SN MAT		yes	LS2	1495/60/50	>> 184505
63	11800	IP54		DAN MAT				1495/60/50	>> 202780
63	11800	IP54		DAN MAT		yes		1495/60/50	>> 202810
63	11800	IP54		DAN MAT	2 rows			1495/60/50	>> 202780/2
63	11800	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 202810/2
63	11800	IP54		DAN MAT			LS2	1495/60/50	>> 202797
63	11800	IP54		DAN MAT		yes	LS2	1495/60/50	>> 202827
63	11800	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 202797/2
63	11800	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 202827/2
73	13187	IP54		MW MAT				1495/60/50	>> 154379
73	13187	IP54		MW MAT		yes		1495/60/50	>> 154393
73	13187	IP54		SW MAT				1495/60/50	>> 157875
73	13187	IP54		SW MAT		yes		1495/60/50	>> 157899
73	13050	IP54		SW MAT	2 rows			1495/60/50	>> 157875/2
73	13050	IP54		SW MAT	2 rows	yes		1495/60/50	>> 157899/2
73	13050	IP54		VW MAT				1495/60/50	>> 163890
73	13050	IP54		VW MAT		yes		1495/60/50	>> 163913
73	13050	IP54		VW MAT	2 rows			1495/60/50	>> 163890/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
73	13050	IP54		VW MAT	2 rows	yes		1495/60/50	>> 163913/2
73	13187	IP54		MW MAT			LS2	1495/60/50	>> 154386
73	13187	IP54		MW MAT		yes	LS2	1495/60/50	>> 154409
73	13187	IP54		SW MAT			LS2	1495/60/50	>> 157882
73	13187	IP54		SW MAT		yes	LS2	1495/60/50	>> 157905
73	13050	IP54		SW MAT	2 rows		LS2	1495/60/50	>> 157882/2
73	13050	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 157905/2
73	13050	IP54		VW MAT			LS2	1495/60/50	>> 163906
73	13050	IP54		VW MAT		yes	LS2	1495/60/50	>> 163920
73	13050	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 163906/2
73	13050	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 163920/2
73	13200	IP54		SA MAT				1495/60/50	>> 197789
73	13200	IP54		SA MAT		yes		1495/60/50	>> 197802
73	13200	IP54		SA MAT	2 rows			1495/60/50	>> 197789/2
73	13200	IP54		SA MAT	2 rows	yes		1495/60/50	>> 197802/2
73	13200	IP54		SN MAT				1495/60/50	>> 184925
73	13200	IP54		SN MAT		yes		1495/60/50	>> 184949
73	13200	IP54		SA MAT			LS2	1495/60/50	>> 197796
73	13200	IP54		SA MAT		yes	LS2	1495/60/50	>> 197819
73	13200	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 197796/2
73	13200	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 197819/2
73	13200	IP54		SN MAT			LS2	1495/60/50	>> 184932
73	13200	IP54		SN MAT		yes	LS2	1495/60/50	>> 184956
73	13500	IP54		DAN MAT				1495/60/50	>> 203121
73	13500	IP54		DAN MAT		yes		1495/60/50	>> 203145
73	13500	IP54		DAN MAT	2 rows			1495/60/50	>> 203121/2
73	13500	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 203145/2
73	13500	IP54		DAN MAT			LS2	1495/60/50	>> 203138
73	13500	IP54		DAN MAT		yes	LS2	1495/60/50	>> 203169
73	13500	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 203138/2
73	13500	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 203169/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	15497	IP54		MW MAT				1495/60/50	>> 154416
88	15497	IP54		MW MAT		yes		1495/60/50	>> 154430
88	15497	IP54		SW MAT				1495/60/50	>> 157912
88	15497	IP54		SW MAT		yes		1495/60/50	>> 157936
88	15350	IP54		SW MAT	2 rows			1495/60/50	>> 157912/2
88	15350	IP54		SW MAT	2 rows	yes		1495/60/50	>> 157936/2
88	15350	IP54		VW MAT				1495/60/50	>> 163937
88	15350	IP54		VW MAT		yes		1495/60/50	>> 163951
88	15350	IP54		VW MAT	2 rows			1495/60/50	>> 163937/2
88	15350	IP54		VW MAT	2 rows	yes		1495/60/50	>> 163951/2
88	15497	IP54		MW MAT			LS2	1495/60/50	>> 154423
88	15497	IP54		MW MAT		yes	LS2	1495/60/50	>> 154447
88	15497	IP54		SW MAT			LS2	1495/60/50	>> 157929
88	15497	IP54		SW MAT		yes	LS2	1495/60/50	>> 157943
88	15350	IP54		SW MAT	2 rows		LS2	1495/60/50	>> 157929/2
88	15350	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 157943/2
88	15350	IP54		VW MAT			LS2	1495/60/50	>> 163944
88	15350	IP54		VW MAT		yes	LS2	1495/60/50	>> 163968
88	15350	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 163944/2
88	15350	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 163968/2
88	15500	IP54		SA MAT				1495/60/50	>> 197826
88	15500	IP54		SA MAT		yes		1495/60/50	>> 197840
88	15500	IP54		SA MAT	2 rows			1495/60/50	>> 197826/2
88	15500	IP54		SA MAT	2 rows	yes		1495/60/50	>> 197840/2
88	15500	IP54		SN MAT				1495/60/50	>> 184963
88	15500	IP54		SN MAT		yes		1495/60/50	>> 184987
88	15500	IP54		SA MAT			LS2	1495/60/50	>> 197833
88	15500	IP54		SA MAT		yes	LS2	1495/60/50	>> 197857
88	15500	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 197833/2
88	15500	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 197857/2
88	15500	IP54		SN MAT			LS2	1495/60/50	>> 184970
88	15500	IP54		SN MAT		yes	LS2	1495/60/50	>> 184994

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	15850	IP54		DAN MAT				1495/60/50	>> 203176
88	15850	IP54		DAN MAT		yes		1495/60/50	>> 203190
88	15850	IP54		DAN MAT	2 rows			1495/60/50	>> 203176/2
88	15850	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 203190/2
88	15850	IP54		DAN MAT			LS2	1495/60/50	>> 203183
88	15850	IP54		DAN MAT		yes	LS2	1495/60/50	>> 203206
88	15850	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 203183/2
88	15850	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 203206/2
92	16171	IP54		MW MAT				1495/60/50	>> 154522
92	16171	IP54		MW MAT		yes		1495/60/50	>> 154614
92	16171	IP54		SW MAT				1495/60/50	>> 158056
92	16171	IP54		SW MAT		yes		1495/60/50	>> 158148
92	16000	IP54		SW MAT	2 rows			1495/60/50	>> 158056/2
92	16000	IP54		SW MAT	2 rows	yes		1495/60/50	>> 158148/2
92	16000	IP54		VW MAT				1495/60/50	>> 165054
92	16000	IP54		VW MAT		yes		1495/60/50	>> 165146
92	16000	IP54		VW MAT	2 rows			1495/60/50	>> 165054/2
92	16000	IP54		VW MAT	2 rows	yes		1495/60/50	>> 165146/2
92	16171	IP54		MW MAT			LS2	1495/60/50	>> 154706
92	16171	IP54		MW MAT		yes	LS2	1495/60/50	>> 154799
92	16171	IP54		SW MAT			LS2	1495/60/50	>> 158254
92	16171	IP54		SW MAT		yes	LS2	1495/60/50	>> 158346
92	16000	IP54		SW MAT	2 rows		LS2	1495/60/50	>> 158254/2
92	16000	IP54		SW MAT	2 rows	yes	LS2	1495/60/50	>> 158346/2
92	16000	IP54		VW MAT			LS2	1495/60/50	>> 165238
92	16000	IP54		VW MAT		yes	LS2	1495/60/50	>> 165382
92	16000	IP54		VW MAT	2 rows		LS2	1495/60/50	>> 165238/2
92	16000	IP54		VW MAT	2 rows	yes	LS2	1495/60/50	>> 165382/2
92	16200	IP54		SA MAT				1495/60/50	>> 197932
92	16200	IP54		SA MAT		yes		1495/60/50	>> 198038
92	16200	IP54		SA MAT	2 rows			1495/60/50	>> 197932/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
92	16200	IP54		SA MAT	2 rows	yes		1495/60/50	>> 198038/2
92	16200	IP54		SN MAT				1495/60/50	>> 186110
92	16200	IP54		SN MAT		yes		1495/60/50	>> 186202
92	16200	IP54		SA MAT			LS2	1495/60/50	>> 198120
92	16200	IP54		SA MAT		yes	LS2	1495/60/50	>> 198212
92	16200	IP54		SA MAT	2 rows		LS2	1495/60/50	>> 198120/2
92	16200	IP54		SA MAT	2 rows	yes	LS2	1495/60/50	>> 198212/2
92	16200	IP54		SN MAT			LS2	1495/60/50	>> 186295
92	16200	IP54		SN MAT		yes	LS2	1495/60/50	>> 186387
92	16550	IP54		DAN MAT				1495/60/50	>> 203282
92	16550	IP54		DAN MAT		yes		1495/60/50	>> 203381
92	16550	IP54		DAN MAT	2 rows			1495/60/50	>> 203282/2
92	16550	IP54		DAN MAT	2 rows	yes		1495/60/50	>> 203381/2
92	16550	IP54		DAN MAT			LS2	1495/60/50	>> 203473
92	16550	IP54		DAN MAT		yes	LS2	1495/60/50	>> 203930
92	16550	IP54		DAN MAT	2 rows		LS2	1495/60/50	>> 203473/2
92	16550	IP54		DAN MAT	2 rows	yes	LS2	1495/60/50	>> 203930/2
53	10107	IP54		MW MAT				1769/60/50	>> 154539
53	10107	IP54		MW MAT		yes		1769/60/50	>> 154621
53	10107	IP54		SW MAT				1769/60/50	>> 158063
53	10107	IP54		SW MAT		yes		1769/60/50	>> 158155
53	10000	IP54		SW MAT	2 rows			1769/60/50	>> 158063/2
53	10000	IP54		SW MAT	2 rows	yes		1769/60/50	>> 158155/2
53	10000	IP54		VW MAT				1769/60/50	>> 165061
53	10000	IP54		VW MAT		yes		1769/60/50	>> 165153
53	10000	IP54		VW MAT	2 rows			1769/60/50	>> 165061/2
53	10000	IP54		VW MAT	2 rows	yes		1769/60/50	>> 165153/2
53	10107	IP54		MW MAT			LS2	1769/60/50	>> 154713
53	10107	IP54		MW MAT		yes	LS2	1769/60/50	>> 154805
53	10107	IP54		SW MAT			LS2	1769/60/50	>> 158261
53	10107	IP54		SW MAT		yes	LS2	1769/60/50	>> 158353
53	10000	IP54		SW MAT	2 rows		LS2	1769/60/50	>> 158261/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
53	10000	IP54		SW MAT	2 rows	yes	LS2	1769/60/50	>> 158353/2
53	10000	IP54		VW MAT			LS2	1769/60/50	>> 165245
53	10000	IP54		VW MAT		yes	LS2	1769/60/50	>> 165399
53	10000	IP54		VW MAT	2 rows		LS2	1769/60/50	>> 165245/2
53	10000	IP54		VW MAT	2 rows	yes	LS2	1769/60/50	>> 165399/2
53	10100	IP54		SA MAT				1769/60/50	>> 197949
53	10100	IP54		SA MAT		yes		1769/60/50	>> 198045
53	10100	IP54		SA MAT	2 rows			1769/60/50	>> 197949/2
53	10100	IP54		SA MAT	2 rows	yes		1769/60/50	>> 198045/2
53	10100	IP54		SN MAT				1769/60/50	>> 186127
53	10100	IP54		SN MAT		yes		1769/60/50	>> 186219
53	10100	IP54		SA MAT			LS2	1769/60/50	>> 198137
53	10100	IP54		SA MAT		yes	LS2	1769/60/50	>> 198229
53	10100	IP54		SA MAT	2 rows		LS2	1769/60/50	>> 198137/2
53	10100	IP54		SA MAT	2 rows	yes	LS2	1769/60/50	>> 198229/2
53	10100	IP54		SN MAT			LS2	1769/60/50	>> 186301
53	10100	IP54		SN MAT		yes	LS2	1769/60/50	>> 186394
53	10350	IP54		DAN MAT				1769/60/50	>> 203299
53	10350	IP54		DAN MAT		yes		1769/60/50	>> 203398
53	10350	IP54		DAN MAT	2 rows			1769/60/50	>> 203299/2
53	10350	IP54		DAN MAT	2 rows	yes		1769/60/50	>> 203398/2
53	10350	IP54		DAN MAT			LS2	1769/60/50	>> 203480
53	10350	IP54		DAN MAT		yes	LS2	1769/60/50	>> 203947
53	10350	IP54		DAN MAT	2 rows		LS2	1769/60/50	>> 203480/2
53	10350	IP54		DAN MAT	2 rows	yes	LS2	1769/60/50	>> 203947/2
70	13379	IP54		MW MAT				1769/60/50	>> 154546
70	13379	IP54		MW MAT		yes		1769/60/50	>> 154638
70	13379	IP54		SW MAT				1769/60/50	>> 158070
70	13379	IP54		SW MAT		yes		1769/60/50	>> 158162
70	13250	IP54		SW MAT	2 rows			1769/60/50	>> 158070/2
70	13250	IP54		SW MAT	2 rows	yes		1769/60/50	>> 158162/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
70	13250	IP54		VW MAT				1769/60/50	>> 165078
70	13250	IP54		VW MAT		yes		1769/60/50	>> 165160
70	13250	IP54		VW MAT	2 rows			1769/60/50	>> 165078/2
70	13250	IP54		VW MAT	2 rows	yes		1769/60/50	>> 165160/2
70	13379	IP54		MW MAT			LS2	1769/60/50	>> 154720
70	13379	IP54		MW MAT		yes	LS2	1769/60/50	>> 154812
70	13379	IP54		SW MAT			LS2	1769/60/50	>> 158278
70	13379	IP54		SW MAT		yes	LS2	1769/60/50	>> 158360
70	13250	IP54		SW MAT	2 rows		LS2	1769/60/50	>> 158278/2
70	13250	IP54		SW MAT	2 rows	yes	LS2	1769/60/50	>> 158360/2
70	13250	IP54		VW MAT			LS2	1769/60/50	>> 165252
70	13250	IP54		VW MAT		yes	LS2	1769/60/50	>> 165405
70	13250	IP54		VW MAT	2 rows		LS2	1769/60/50	>> 165252/2
70	13250	IP54		VW MAT	2 rows	yes	LS2	1769/60/50	>> 165405/2
70	13400	IP54		SA MAT				1769/60/50	>> 197956
70	13400	IP54		SA MAT		yes		1769/60/50	>> 198052
70	13400	IP54		SA MAT	2 rows			1769/60/50	>> 197956/2
70	13400	IP54		SA MAT	2 rows	yes		1769/60/50	>> 198052/2
70	13400	IP54		SN MAT				1769/60/50	>> 186134
70	13400	IP54		SN MAT		yes		1769/60/50	>> 186226
70	13400	IP54		SA MAT			LS2	1769/60/50	>> 198144
70	13400	IP54		SA MAT		yes	LS2	1769/60/50	>> 198236
70	13400	IP54		SA MAT	2 rows		LS2	1769/60/50	>> 198144/2
70	13400	IP54		SA MAT	2 rows	yes	LS2	1769/60/50	>> 198236/2
70	13400	IP54		SN MAT			LS2	1769/60/50	>> 186318
70	13400	IP54		SN MAT		yes	LS2	1769/60/50	>> 186424
70	13700	IP54		DAN MAT				1769/60/50	>> 203312
70	13700	IP54		DAN MAT		yes		1769/60/50	>> 203404
70	13700	IP54		DAN MAT	2 rows			1769/60/50	>> 203312/2
70	13700	IP54		DAN MAT	2 rows	yes		1769/60/50	>> 203404/2
70	13700	IP54		DAN MAT			LS2	1769/60/50	>> 203497
70	13700	IP54		DAN MAT		yes	LS2	1769/60/50	>> 203954

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
70	13700	IP54		DAN MAT	2 rows		LS2	1769/60/50	>> 203497/2
70	13700	IP54		DAN MAT	2 rows	yes	LS2	1769/60/50	>> 203954/2
100	18192	IP54		MW MAT				1769/60/50	>> 154553
100	18192	IP54		MW MAT		yes		1769/60/50	>> 154645
100	18192	IP54		SW MAT				1769/60/50	>> 158087
100	18192	IP54		SW MAT		yes		1769/60/50	>> 158179
100	18000	IP54		SW MAT	2 rows			1769/60/50	>> 158087/2
100	18000	IP54		SW MAT	2 rows	yes		1769/60/50	>> 158179/2
100	18000	IP54		VW MAT				1769/60/50	>> 165085
100	18000	IP54		VW MAT		yes		1769/60/50	>> 165177
100	18000	IP54		VW MAT	2 rows			1769/60/50	>> 165085/2
100	18000	IP54		VW MAT	2 rows	yes		1769/60/50	>> 165177/2
100	18192	IP54		MW MAT			LS2	1769/60/50	>> 154737
100	18192	IP54		MW MAT		yes	LS2	1769/60/50	>> 154829
100	18192	IP54		SW MAT			LS2	1769/60/50	>> 158285
100	18192	IP54		SW MAT		yes	LS2	1769/60/50	>> 158377
100	18000	IP54		SW MAT	2 rows		LS2	1769/60/50	>> 158285/2
100	18000	IP54		SW MAT	2 rows	yes	LS2	1769/60/50	>> 158377/2
100	18000	IP54		VW MAT			LS2	1769/60/50	>> 165269
100	18000	IP54		VW MAT		yes	LS2	1769/60/50	>> 165412
100	18000	IP54		VW MAT	2 rows		LS2	1769/60/50	>> 165269/2
100	18000	IP54		VW MAT	2 rows	yes	LS2	1769/60/50	>> 165412/2
100	18200	IP54		SA MAT				1769/60/50	>> 197963
100	18200	IP54		SA MAT		yes		1769/60/50	>> 198069
100	18200	IP54		SA MAT	2 rows			1769/60/50	>> 197963/2
100	18200	IP54		SA MAT	2 rows	yes		1769/60/50	>> 198069/2
100	18200	IP54		SN MAT				1769/60/50	>> 186141
100	18200	IP54		SN MAT		yes		1769/60/50	>> 186233
100	18200	IP54		SA MAT			LS2	1769/60/50	>> 198151
100	18200	IP54		SA MAT		yes	LS2	1769/60/50	>> 198243
100	18200	IP54		SA MAT	2 rows		LS2	1769/60/50	>> 198151/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
100	18200	IP54		SA MAT	2 rows	yes	LS2	1769/60/50	>> 198243/2
100	18200	IP54		SN MAT			LS2	1769/60/50	>> 186325
100	18200	IP54		SN MAT		yes	LS2	1769/60/50	>> 186431
100	18600	IP54		DAN MAT				1769/60/50	>> 203329
100	18600	IP54		DAN MAT		yes		1769/60/50	>> 203411
100	18600	IP54		DAN MAT	2 rows			1769/60/50	>> 203329/2
100	18600	IP54		DAN MAT	2 rows	yes		1769/60/50	>> 203411/2
100	18600	IP54		DAN MAT			LS2	1769/60/50	>> 203879
100	18600	IP54		DAN MAT		yes	LS2	1769/60/50	>> 203961
100	18600	IP54		DAN MAT	2 rows		LS2	1769/60/50	>> 203879/2
100	18600	IP54		DAN MAT	2 rows	yes	LS2	1769/60/50	>> 203961/2
142	24593	IP54		MW MAT				1769/60/50	>> 154096
142	24593	IP54		MW MAT		yes		1769/60/50	>> 154119
142	24593	IP54		SW MAT				1769/60/50	>> 157592
142	24593	IP54		SW MAT		yes		1769/60/50	>> 157615
142	24350	IP54		SW MAT	2 rows			1769/60/50	>> 157592/2
142	24350	IP54		SW MAT	2 rows	yes		1769/60/50	>> 157615/2
142	24350	IP54		VW MAT				1769/60/50	>> 163616
142	24350	IP54		VW MAT		yes		1769/60/50	>> 163630
142	24350	IP54		VW MAT	2 rows			1769/60/50	>> 163616/2
142	24350	IP54		VW MAT	2 rows	yes		1769/60/50	>> 163630/2
142	24593	IP54		MW MAT			LS2	1769/60/50	>> 154102
142	24593	IP54		MW MAT		yes	LS2	1769/60/50	>> 154126
142	24593	IP54		SW MAT			LS2	1769/60/50	>> 157608
142	24593	IP54		SW MAT		yes	LS2	1769/60/50	>> 157622
142	24350	IP54		SW MAT	2 rows		LS2	1769/60/50	>> 157608/2
142	24350	IP54		SW MAT	2 rows	yes	LS2	1769/60/50	>> 157622/2
142	24350	IP54		VW MAT			LS2	1769/60/50	>> 163623
142	24350	IP54		VW MAT		yes	LS2	1769/60/50	>> 163647
142	24350	IP54		VW MAT	2 rows		LS2	1769/60/50	>> 163623/2
142	24350	IP54		VW MAT	2 rows	yes	LS2	1769/60/50	>> 163647/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
142	24600	IP54		SA MAT				1769/60/50	>> 197505
142	24600	IP54		SA MAT		yes		1769/60/50	>> 197529
142	24600	IP54		SA MAT	2 rows			1769/60/50	>> 197505/2
142	24600	IP54		SA MAT	2 rows	yes		1769/60/50	>> 197529/2
142	24600	IP54		SN MAT				1769/60/50	>> 184512
142	24600	IP54		SN MAT		yes		1769/60/50	>> 184536
142	24600	IP54		SA MAT			LS2	1769/60/50	>> 197512
142	24600	IP54		SA MAT		yes	LS2	1769/60/50	>> 197536
142	24600	IP54		SA MAT	2 rows		LS2	1769/60/50	>> 197512/2
142	24600	IP54		SA MAT	2 rows	yes	LS2	1769/60/50	>> 197536/2
142	24600	IP54		SN MAT			LS2	1769/60/50	>> 184529
142	24600	IP54		SN MAT		yes	LS2	1769/60/50	>> 184543
142	25150	IP54		DAN MAT				1769/60/50	>> 202834
142	25150	IP54		DAN MAT		yes		1769/60/50	>> 202858
142	25150	IP54		DAN MAT	2 rows			1769/60/50	>> 202834/2
142	25150	IP54		DAN MAT	2 rows	yes		1769/60/50	>> 202858/2
142	25150	IP54		DAN MAT			LS2	1769/60/50	>> 202841
142	25150	IP54		DAN MAT		yes	LS2	1769/60/50	>> 202865
142	25150	IP54		DAN MAT	2 rows		LS2	1769/60/50	>> 202841/2
142	25150	IP54		DAN MAT	2 rows	yes	LS2	1769/60/50	>> 202865/2
23	3754	IP54		MW MAT				588/60/50	>> 154836
23	3754	IP54		MW MAT		yes		588/60/50	>> 154874
23	3754	IP54		SW MAT				588/60/50	>> 158384
23	3754	IP54		SW MAT		yes		588/60/50	>> 158421
23	3700	IP54		SW MAT	2 rows			588/60/50	>> 158384/2
23	3700	IP54		SW MAT	2 rows	yes		588/60/50	>> 158421/2
23	3700	IP54		VW MAT				588/60/50	>> 165429
23	3700	IP54		VW MAT		yes		588/60/50	>> 165467
23	3700	IP54		VW MAT	2 rows			588/60/50	>> 165429/2
23	3700	IP54		VW MAT	2 rows	yes		588/60/50	>> 165467/2
23	3750	IP54		SA MAT				588/60/50	>> 198250
23	3750	IP54		SA MAT		yes		588/60/50	>> 198298

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
23	3750	IP54		SA MAT	2 rows			588/60/50	>> 198250/2
23	3750	IP54		SA MAT	2 rows	yes		588/60/50	>> 198298/2
23	3750	IP54		SN MAT				588/60/50	>> 186448
23	3750	IP54		SN MAT		yes		588/60/50	>> 186486
23	3850	IP54		DAN MAT				588/60/50	>> 203978
23	3850	IP54		DAN MAT		yes		588/60/50	>> 204074
23	3850	IP54		DAN MAT	2 rows			588/60/50	>> 203978/2
23	3850	IP54		DAN MAT	2 rows	yes		588/60/50	>> 204074/2
28	4668	IP54		MW MAT				588/60/50	>> 154843
28	4668	IP54		MW MAT		yes		588/60/50	>> 154881
28	4668	IP54		SW MAT				588/60/50	>> 158391
28	4668	IP54		SW MAT		yes		588/60/50	>> 158438
28	4600	IP54		SW MAT	2 rows			588/60/50	>> 158391/2
28	4600	IP54		SW MAT	2 rows	yes		588/60/50	>> 158438/2
28	4600	IP54		VW MAT				588/60/50	>> 165436
28	4600	IP54		VW MAT		yes		588/60/50	>> 165474
28	4600	IP54		VW MAT	2 rows			588/60/50	>> 165436/2
28	4600	IP54		VW MAT	2 rows	yes		588/60/50	>> 165474/2
28	4650	IP54		SA MAT				588/60/50	>> 198267
28	4650	IP54		SA MAT		yes		588/60/50	>> 198304
28	4650	IP54		SA MAT	2 rows			588/60/50	>> 198267/2
28	4650	IP54		SA MAT	2 rows	yes		588/60/50	>> 198304/2
28	4650	IP54		SN MAT				588/60/50	>> 186455
28	4650	IP54		SN MAT		yes		588/60/50	>> 186493
28	4800	IP54		DAN MAT				588/60/50	>> 203985
28	4800	IP54		DAN MAT		yes		588/60/50	>> 204081
28	4800	IP54		DAN MAT	2 rows			588/60/50	>> 203985/2
28	4800	IP54		DAN MAT	2 rows	yes		588/60/50	>> 204081/2
34	5679	IP54		MW MAT				588/60/50	>> 154850
34	5679	IP54		MW MAT		yes		588/60/50	>> 154898
34	5679	IP54		SW MAT				588/60/50	>> 158407
34	5679	IP54		SW MAT		yes		588/60/50	>> 158445

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
34	5600	IP54		SW MAT	2 rows			588/60/50	>> 158407/2
34	5600	IP54		SW MAT	2 rows	yes		588/60/50	>> 158445/2
34	5600	IP54		VW MAT				588/60/50	>> 165443
34	5600	IP54		VW MAT		yes		588/60/50	>> 165481
34	5600	IP54		VW MAT	2 rows			588/60/50	>> 165443/2
34	5600	IP54		VW MAT	2 rows	yes		588/60/50	>> 165481/2
34	5700	IP54		SA MAT				588/60/50	>> 198274
34	5700	IP54		SA MAT		yes		588/60/50	>> 198311
34	5700	IP54		SA MAT	2 rows			588/60/50	>> 198274/2
34	5700	IP54		SA MAT	2 rows	yes		588/60/50	>> 198311/2
34	5700	IP54		SN MAT				588/60/50	>> 186462
34	5700	IP54		SN MAT		yes		588/60/50	>> 186639
34	5800	IP54		DAN MAT				588/60/50	>> 203992
34	5800	IP54		DAN MAT		yes		588/60/50	>> 204098
34	5800	IP54		DAN MAT	2 rows			588/60/50	>> 203992/2
34	5800	IP54		DAN MAT	2 rows	yes		588/60/50	>> 204098/2
40	6497	IP54		MW MAT				588/60/50	>> 154867
40	6497	IP54		MW MAT		yes		588/60/50	>> 154904
40	6497	IP54		SW MAT				588/60/50	>> 158414
40	6497	IP54		SW MAT		yes		588/60/50	>> 158452
40	6450	IP54		SW MAT	2 rows			588/60/50	>> 158414/2
40	6450	IP54		SW MAT	2 rows	yes		588/60/50	>> 158452/2
40	6450	IP54		VW MAT				588/60/50	>> 165450
40	6450	IP54		VW MAT		yes		588/60/50	>> 165498
40	6450	IP54		VW MAT	2 rows			588/60/50	>> 165450/2
40	6450	IP54		VW MAT	2 rows	yes		588/60/50	>> 165498/2
40	6500	IP54		SA MAT				588/60/50	>> 198281
40	6500	IP54		SA MAT		yes		588/60/50	>> 198328
40	6500	IP54		SA MAT	2 rows			588/60/50	>> 198281/2
40	6500	IP54		SA MAT	2 rows	yes		588/60/50	>> 198328/2
40	6500	IP54		SN MAT				588/60/50	>> 186479

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
40	6500	IP54		SN MAT		yes		588/60/50	>> 186646
40	0	IP54		DAN MAT				588/60/50	>> 205132
40	6650	IP54		DAN MAT		yes		588/60/50	>> 204104
40		IP54		DAN MAT	2 rows			588/60/50	>> 205132/2
40	6650	IP54		DAN MAT	2 rows	yes		588/60/50	>> 204104/2

Linea S LED Single IP54 1

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
23	3750	IP54	butterfly	DAN	2 rows			588/60/50	>> 849206/2
23	3750	IP54	butterfly	DAN	2 rows	yes		588/60/50	>> 849244/2
23	3750	IP54	asymmetric	SA	2 rows			588/60/50	>> 846809/2
23	3750	IP54	asymmetric	SA	2 rows	yes		588/60/50	>> 846847/2
23	3900	IP54	90	MW	2 rows			588/60/50	>> 587177/2
23	3900	IP54	90	MW	2 rows	yes		588/60/50	>> 587214/2
23	3900	IP54	80	SW	2 rows			588/60/50	>> 587092/2
23	3900	IP54	80	SW	2 rows	yes		588/60/50	>> 587139/2
23	3900	IP54	105	VW	2 rows			588/60/50	>> 587252/2
23	3900	IP54	105	VW	2 rows	yes		588/60/50	>> 587290/2
23	3600	IP54	105	symmetric		yes		588/60/50	>> 587375
23	3600	IP54	105	symmetric				588/60/50	>> 587337
23	3950	IP54	120	symmetric		yes		588/60/50	>> 587047
23	3950	IP54	120	symmetric				588/60/50	>> 587009
23	3900	IP54	90	MW		yes		588/60/50	>> 587214
23	3900	IP54	90	MW				588/60/50	>> 587177
23	3900	IP54	80	SW		yes		588/60/50	>> 587139
23	3900	IP54	80	SW				588/60/50	>> 587092
23	3900	IP54	105	VW		yes		588/60/50	>> 587290
23	3900	IP54	105	VW				588/60/50	>> 587252
23	3750	IP54	butterfly	DAN				588/60/50	>> 849206
23	3750	IP54	butterfly	DAN		yes		588/60/50	>> 849244
23	3750	IP54	asymmetric	SA				588/60/50	>> 846809
23	3750	IP54	asymmetric	SA		yes		588/60/50	>> 846847

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
23	3900	IP54	35/67	CN				588/60/50	>> 853845
23	3900	IP54	35/67	CN		yes		588/60/50	>> 853883
23	3900	IP54	65	SN				588/60/50	>> 856167
23	3900	IP54	65	SN		yes		588/60/50	>> 856204
23	3900	IP54	30	VN				588/60/50	>> 851520
23	3900	IP54	30	VN		yes		588/60/50	>> 851568
23	3850	IP54	25x80	CW				588/60/50	>> 279461
23	3850	IP54	25x80	CW		yes		588/60/50	>> 279027
28	4500	IP54	105	symmetric		yes		588/60/50	>> 587382
28	4500	IP54	105	symmetric				588/60/50	>> 587344
28	4900	IP54	120	symmetric		yes		588/60/50	>> 587054
28	4900	IP54	120	symmetric				588/60/50	>> 587016
28	4850	IP54	90	MW		yes		588/60/50	>> 587221
28	4850	IP54	90	MW				588/60/50	>> 587184
28	4850	IP54	80	SW		yes		588/60/50	>> 587146
28	4850	IP54	80	SW				588/60/50	>> 587108
28	4850	IP54	105	VW		yes		588/60/50	>> 587306
28	4850	IP54	105	VW				588/60/50	>> 587269
28	4650	IP54	butterfly	DAN				588/60/50	>> 849213
28	4650	IP54	butterfly	DAN		yes		588/60/50	>> 849251
28	4700	IP54	asymmetric	SA				588/60/50	>> 846816
28	4700	IP54	asymmetric	SA		yes		588/60/50	>> 846854
28	4850	IP54	35/67	CN				588/60/50	>> 853852
28	4850	IP54	35/67	CN		yes		588/60/50	>> 853890
28	4850	IP54	65	SN				588/60/50	>> 856174
28	4850	IP54	65	SN		yes		588/60/50	>> 856211
28	4850	IP54	30	VN				588/60/50	>> 851537
28	4850	IP54	30	VN		yes		588/60/50	>> 851575
28	4750	IP54	25x80	CW				588/60/50	>> 279478
28	4750	IP54	25x80	CW		yes		588/60/50	>> 279034
28	4650	IP54	butterfly	DAN	2 rows			588/60/50	>> 849213/2
28	4650	IP54	butterfly	DAN	2 rows	yes		588/60/50	>> 849251/2
28	4700	IP54	asymmetric	SA	2 rows			588/60/50	>> 846816/2
28	4700	IP54	asymmetric	SA	2 rows	yes		588/60/50	>> 846854/2
28	4850	IP54	90	MW	2 rows			588/60/50	>> 587184/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
28	4850	IP54	90	MW	2 rows	yes		588/60/50	>> 587221/2
28	4850	IP54	80	SW	2 rows			588/60/50	>> 587108/2
28	4850	IP54	80	SW	2 rows	yes		588/60/50	>> 587146/2
28	4850	IP54	105	VW	2 rows			588/60/50	>> 587269/2
28	4850	IP54	105	VW	2 rows	yes		588/60/50	>> 587306/2
34	5650	IP54	butterfly	DAN	2 rows			588/60/50	>> 849220/2
34	5650	IP54	butterfly	DAN	2 rows	yes		588/60/50	>> 849268/2
34	5650	IP54	asymmetric	SA	2 rows			588/60/50	>> 846823/2
34	5650	IP54	asymmetric	SA	2 rows	yes		588/60/50	>> 846861/2
34	5900	IP54	90	MW	2 rows			588/60/50	>> 587191/2
34	5900	IP54	90	MW	2 rows	yes		588/60/50	>> 587238/2
34	5900	IP54	80	SW	2 rows			588/60/50	>> 587115/2
34	5900	IP54	80	SW	2 rows	yes		588/60/50	>> 587153/2
34	5900	IP54	105	VW	2 rows			588/60/50	>> 587276/2
34	5900	IP54	105	VW	2 rows	yes		588/60/50	>> 587313/2
34	5550	IP54	105	symmetric		yes		588/60/50	>> 587399
34	5550	IP54	105	symmetric				588/60/50	>> 587351
34	5950	IP54	120	symmetric		yes		588/60/50	>> 587061
34	5950	IP54	120	symmetric				588/60/50	>> 587023
34	5900	IP54	90	MW		yes		588/60/50	>> 587238
34	5900	IP54	90	MW				588/60/50	>> 587191
34	5900	IP54	80	SW		yes		588/60/50	>> 587153
34	5900	IP54	80	SW				588/60/50	>> 587115
34	5900	IP54	105	VW		yes		588/60/50	>> 587313
34	5900	IP54	105	VW				588/60/50	>> 587276
34	5650	IP54	butterfly	DAN				588/60/50	>> 849220
34	5650	IP54	butterfly	DAN		yes		588/60/50	>> 849268
34	5650	IP54	asymmetric	SA				588/60/50	>> 846823
34	5650	IP54	asymmetric	SA		yes		588/60/50	>> 846861
34	5850	IP54	35/67	CN				588/60/50	>> 853869

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
34	5850	IP54	35/67	CN		yes		588/60/50	>> 853906
34	5850	IP54	65	SN				588/60/50	>> 856181
34	5850	IP54	65	SN		yes		588/60/50	>> 856228
34	5850	IP54	30	VN				588/60/50	>> 851544
34	5850	IP54	30	VN		yes		588/60/50	>> 851582
34	5800	IP54	25x80	CW				588/60/50	>> 279485
34	5800	IP54	25x80	CW		yes		588/60/50	>> 279041
40	6250	IP54	105	symmetric		yes		588/60/50	>> 587405
40	6250	IP54	105	symmetric				588/60/50	>> 587368
40	7000	IP54	120	symmetric		yes		588/60/50	>> 587078
40	7000	IP54	120	symmetric				588/60/50	>> 587030
40	6750	IP54	90	MW		yes		588/60/50	>> 587245
40	6750	IP54	90	MW				588/60/50	>> 587207
40	6750	IP54	80	SW		yes		588/60/50	>> 587160
40	6750	IP54	80	SW				588/60/50	>> 587122
40	6750	IP54	105	VW		yes		588/60/50	>> 587320
40	6750	IP54	105	VW				588/60/50	>> 587283
40	6450	IP54	butterfly	DAN				588/60/50	>> 849237
40	6450	IP54	butterfly	DAN		yes		588/60/50	>> 849275
40	6500	IP54	asymmetric	SA				588/60/50	>> 846830
40	6500	IP54	asymmetric	SA		yes		588/60/50	>> 846878
40	6700	IP54	35/67	CN				588/60/50	>> 853876
40	6700	IP54	35/67	CN		yes		588/60/50	>> 853913
40	6700	IP54	65	SN				588/60/50	>> 856198
40	6700	IP54	65	SN		yes		588/60/50	>> 856235
40	6700	IP54	30	VN				588/60/50	>> 851551
40	6700	IP54	30	VN		yes		588/60/50	>> 851599
40	6600	IP54	25x80	CW		yes		588/60/50	>> 279096
40	6450	IP54	butterfly	DAN	2 rows			588/60/50	>> 849237/2
40	6450	IP54	butterfly	DAN	2 rows	yes		588/60/50	>> 849275/2
40	6500	IP54	asymmetric	SA	2 rows			588/60/50	>> 846830/2
40	6500	IP54	asymmetric	SA	2 rows	yes		588/60/50	>> 846878/2
40	6750	IP54	90	MW	2 rows			588/60/50	>> 587207/2
40	6750	IP54	90	MW	2 rows	yes		588/60/50	>> 587245/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
40	6750	IP54	80	SW	2 rows			588/60/50	>> 587122/2
40	6750	IP54	80	SW	2 rows	yes		588/60/50	>> 587160/2
40	6750	IP54	105	VW	2 rows			588/60/50	>> 587283/2
40	6750	IP54	105	VW	2 rows	yes		588/60/50	>> 587320/2

Linea S LED Single IP54 2

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	5950	IP54	105	symmetric		yes		1181/60/50	>> 585906
35	5950	IP54	105	symmetric		yes	LS2	1181/60/50	>> 586903
35	5950	IP54	105	symmetric				1181/60/50	>> 585807
35	5950	IP54	105	symmetric			LS2	1181/60/50	>> 586804
35	6500	IP54	120	symmetric		yes		1181/60/50	>> 585104
35	6500	IP54	120	symmetric		yes	LS2	1181/60/50	>> 586101
35	6500	IP54	120	symmetric				1181/60/50	>> 585005
35	6500	IP54	120	symmetric			LS2	1181/60/50	>> 586002
35	6450	IP54	90	MW		yes		1181/60/50	>> 585500
35	5950	IP54	90	MW		yes	LS2	1181/60/50	>> 586507
35	6450	IP54	90	MW				1181/60/50	>> 585401
35	5950	IP54	90	MW			LS2	1181/60/50	>> 586408
35	6450	IP54	80	SW		yes		1181/60/50	>> 585302
35	5950	IP54	80	SW		yes	LS2	1181/60/50	>> 586309
35	6450	IP54	80	SW				1181/60/50	>> 585203
35	5950	IP54	80	SW			LS2	1181/60/50	>> 586200
35	6450	IP54	105	VW		yes		1181/60/50	>> 585708
35	5950	IP54	105	VW		yes	LS2	1181/60/50	>> 586705
35	6450	IP54	105	VW				1181/60/50	>> 585609
35	5950	IP54	105	VW			LS2	1181/60/50	>> 586606
35	6150	IP54	butterfly	DAN				1181/60/50	>> 848841
35	6150	IP54	butterfly	DAN		yes		1181/60/50	>> 848933
35	6150	IP54	butterfly	DAN			LS2	1181/60/50	>> 849022
35	6150	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 849114
35	6200	IP54	asymmetric	SA				1181/60/50	>> 846441
35	6200	IP54	asymmetric	SA		yes		1181/60/50	>> 846533
35	6200	IP54	asymmetric	SA			LS2	1181/60/50	>> 846625
35	6200	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846717
35	6400	IP54	35/67	CN				1181/60/50	>> 853487

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	6400	IP54	35/67	CN		yes		1181/60/50	>> 853579
35	6400	IP54	65	SN				1181/60/50	>> 855801
35	6400	IP54	65	SN		yes		1181/60/50	>> 855894
35	6400	IP54	30	VN				1181/60/50	>> 851162
35	6400	IP54	30	VN		yes		1181/60/50	>> 851254
35	6400	IP54	35/67	CN			LS2	1181/60/50	>> 853661
35	6400	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853753
35	6400	IP54	65	SN			LS2	1181/60/50	>> 855986
35	6400	IP54	65	SN		yes	LS2	1181/60/50	>> 856075
35	6400	IP54	30	VN			LS2	1181/60/50	>> 851346
35	6400	IP54	30	VN		yes	LS2	1181/60/50	>> 851438
35	6350	IP54	25x80	CW				1181/60/50	>> 279492
35	6350	IP54	25x80	CW		yes		1181/60/50	>> 279058
35	5850	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279072
35	5950	IP54	90	MW	2 rows		LS2	1181/60/50	>> 586408/2
35	5950	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 586507/2
35	5950	IP54	80	SW	2 rows		LS2	1181/60/50	>> 586200/2
35	5950	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 586309/2
35	5950	IP54	105	VW	2 rows		LS2	1181/60/50	>> 586606/2
35	5950	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 586705/2
35	6150	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848841/2
35	6150	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848933/2
35	6150	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 849022/2
35	6150	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 849114/2
35	6200	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846441/2
35	6200	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846533/2
35	6200	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846625/2
35	6200	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846717/2
35	6450	IP54	90	MW	2 rows			1181/60/50	>> 585401/2
35	6450	IP54	90	MW	2 rows	yes		1181/60/50	>> 585500/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	6450	IP54	80	SW	2 rows			1181/60/50	>> 585203/2
35	6450	IP54	80	SW	2 rows	yes		1181/60/50	>> 585302/2
35	6450	IP54	105	VW	2 rows			1181/60/50	>> 585609/2
35	6450	IP54	105	VW	2 rows	yes		1181/60/50	>> 585708/2
41	7350	IP54	105	symmetric		yes		1181/60/50	>> 007590
41	7350	IP54	105	symmetric		yes	LS2	1181/60/50	>> 007606
41	7350	IP54	105	symmetric				1181/60/50	>> 007576
41	7350	IP54	105	symmetric			LS2	1181/60/50	>> 007583
41	8050	IP54	120	symmetric		yes		1181/60/50	>> 007156
41	8050	IP54	120	symmetric		yes	LS2	1181/60/50	>> 007163
41	8050	IP54	120	symmetric				1181/60/50	>> 007132
41	8050	IP54	120	symmetric			LS2	1181/60/50	>> 007149
41	7950	IP54	90	MW		yes		1181/60/50	>> 003196
41	7950	IP54	90	MW		yes	LS2	1181/60/50	>> 003202
41	7950	IP54	90	MW				1181/60/50	>> 003172
41	7950	IP54	90	MW			LS2	1181/60/50	>> 003189
41	7950	IP54	80	SW		yes		1181/60/50	>> 005534
41	7950	IP54	80	SW		yes	LS2	1181/60/50	>> 005541
41	7950	IP54	80	SW				1181/60/50	>> 005510
41	7950	IP54	80	SW			LS2	1181/60/50	>> 005527
41	7950	IP54	105	VW		yes		1181/60/50	>> 003639
41	7950	IP54	105	VW		yes	LS2	1181/60/50	>> 003646
41	7950	IP54	105	VW				1181/60/50	>> 003615
41	7950	IP54	105	VW			LS2	1181/60/50	>> 003622
41	7600	IP54	butterfly	DAN				1181/60/50	>> 848520
41	7600	IP54	butterfly	DAN		yes		1181/60/50	>> 848544
41	7600	IP54	butterfly	DAN			LS2	1181/60/50	>> 848537
41	7600	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 848551
41	7650	IP54	asymmetric	SA				1181/60/50	>> 846120
41	7650	IP54	asymmetric	SA		yes		1181/60/50	>> 846144
41	7650	IP54	asymmetric	SA			LS2	1181/60/50	>> 846137
41	7650	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846151
41	7900	IP54	35/67	CN				1181/60/50	>> 853166
41	7900	IP54	35/67	CN		yes		1181/60/50	>> 853180
41	7900	IP54	65	SN				1181/60/50	>> 855481
41	7900	IP54	65	SN		yes		1181/60/50	>> 855504

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
41	7900	IP54	30	VN				1181/60/50	>> 850844
41	7900	IP54	30	VN		yes		1181/60/50	>> 850868
41	7900	IP54	35/67	CN			LS2	1181/60/50	>> 853173
41	7900	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853197
41	7900	IP54	65	SN			LS2	1181/60/50	>> 855498
41	7900	IP54	65	SN		yes	LS2	1181/60/50	>> 855511
41	7900	IP54	30	VN			LS2	1181/60/50	>> 850851
41	7900	IP54	30	VN		yes	LS2	1181/60/50	>> 850875
41	7800	IP54	25x80	CW		yes		1181/60/50	>> 279102
41	7800	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279126
41	7600	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848520/2
41	7600	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848544/2
41	7600	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 848537/2
41	7600	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 848551/2
41	7650	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846120/2
41	7650	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846144/2
41	7650	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846137/2
41	7650	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846151/2
41	7950	IP54	90	MW	2 rows			1181/60/50	>> 003172/2
41	7950	IP54	90	MW	2 rows	yes		1181/60/50	>> 003196/2
41	7950	IP54	80	SW	2 rows			1181/60/50	>> 005510/2
41	7950	IP54	80	SW	2 rows	yes		1181/60/50	>> 005534/2
41	7950	IP54	105	VW	2 rows			1181/60/50	>> 003615/2
41	7950	IP54	105	VW	2 rows	yes		1181/60/50	>> 003639/2
41	7950	IP54	90	MW	2 rows		LS2	1181/60/50	>> 003189/2
41	7950	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 003202/2
41	7950	IP54	80	SW	2 rows		LS2	1181/60/50	>> 005527/2
41	7950	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 005541/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
41	7950	IP54	105	VW	2 rows		LS2	1181/60/50	>> 003622/2
41	7950	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 003646/2
48	8600	IP54	105	symmetric		yes		1181/60/50	>> 585920
48	8600	IP54	105	symmetric		yes	LS2	1181/60/50	>> 586927
48	8600	IP54	105	symmetric				1181/60/50	>> 585814
48	8600	IP54	105	symmetric			LS2	1181/60/50	>> 586811
48	9400	IP54	120	symmetric		yes		1181/60/50	>> 585128
48	9400	IP54	120	symmetric		yes	LS2	1181/60/50	>> 586125
48	9400	IP54	120	symmetric				1181/60/50	>> 585012
48	9400	IP54	120	symmetric			LS2	1181/60/50	>> 586019
48	9300	IP54	90	MW		yes		1181/60/50	>> 585524
48	9300	IP54	90	MW		yes	LS2	1181/60/50	>> 586521
48	9300	IP54	90	MW				1181/60/50	>> 585418
48	9300	IP54	90	MW			LS2	1181/60/50	>> 586415
48	9300	IP54	80	SW		yes		1181/60/50	>> 585326
48	9300	IP54	80	SW		yes	LS2	1181/60/50	>> 586323
48	9300	IP54	80	SW				1181/60/50	>> 585210
48	9300	IP54	80	SW			LS2	1181/60/50	>> 586217
48	9300	IP54	105	VW		yes		1181/60/50	>> 585722
48	9300	IP54	105	VW		yes	LS2	1181/60/50	>> 586729
48	9300	IP54	105	VW				1181/60/50	>> 585616
48	9300	IP54	105	VW			LS2	1181/60/50	>> 586613
48	8900	IP54	butterfly	DAN				1181/60/50	>> 848858
48	8900	IP54	butterfly	DAN		yes		1181/60/50	>> 848940
48	8900	IP54	butterfly	DAN			LS2	1181/60/50	>> 849039
48	8900	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 849121
48	9000	IP54	asymmetric	SA				1181/60/50	>> 846458
48	9000	IP54	asymmetric	SA		yes		1181/60/50	>> 846540
48	9000	IP54	asymmetric	SA			LS2	1181/60/50	>> 846632
48	9000	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846724
48	9300	IP54	35/67	CN				1181/60/50	>> 853494
48	9300	IP54	35/67	CN		yes		1181/60/50	>> 853586
48	9300	IP54	65	SN				1181/60/50	>> 855818
48	9300	IP54	65	SN		yes		1181/60/50	>> 855900
48	9300	IP54	30	VN				1181/60/50	>> 851179
48	9300	IP54	30	VN		yes		1181/60/50	>> 851261
48	9300	IP54	35/67	CN			LS2	1181/60/50	>> 853678

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
48	9300	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853760
48	9300	IP54	65	SN			LS2	1181/60/50	>> 855993
48	9300	IP54	65	SN		yes	LS2	1181/60/50	>> 856082
48	9300	IP54	30	VN			LS2	1181/60/50	>> 851353
48	9300	IP54	30	VN		yes	LS2	1181/60/50	>> 851445
48	9100	IP54	25x80	CW		yes		1181/60/50	>> 279140
48	9100	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279164
48	8900	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848858/2
48	8900	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848940/2
48	8900	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 849039/2
48	8900	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 849121/2
48	9000	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846458/2
48	9000	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846540/2
48	9000	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846632/2
48	9000	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846724/2
48	9300	IP54	90	MW	2 rows			1181/60/50	>> 585418/2
48	9300	IP54	90	MW	2 rows	yes		1181/60/50	>> 585524/2
48	9300	IP54	80	SW	2 rows			1181/60/50	>> 585210/2
48	9300	IP54	80	SW	2 rows	yes		1181/60/50	>> 585326/2
48	9300	IP54	105	VW	2 rows			1181/60/50	>> 585616/2
48	9300	IP54	105	VW	2 rows	yes		1181/60/50	>> 585722/2
48	9300	IP54	90	MW	2 rows		LS2	1181/60/50	>> 586415/2
48	9300	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 586521/2
48	9300	IP54	80	SW	2 rows		LS2	1181/60/50	>> 586217/2
48	9300	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 586323/2
48	9300	IP54	105	VW	2 rows		LS2	1181/60/50	>> 586613/2
48	9300	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 586729/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
58	10300	IP54	105	symmetric		yes		1181/60/50	>> 007637
58	10300	IP54	105	symmetric		yes	LS2	1181/60/50	>> 007644
58	10300	IP54	105	symmetric				1181/60/50	>> 007613
58	10300	IP54	105	symmetric			LS2	1181/60/50	>> 007620
58	11200	IP54	120	symmetric		yes		1181/60/50	>> 007194
58	11200	IP54	120	symmetric		yes	LS2	1181/60/50	>> 007200
58	11200	IP54	120	symmetric				1181/60/50	>> 007170
58	11200	IP54	120	symmetric			LS2	1181/60/50	>> 007187
58	11100	IP54	90	MW		yes		1181/60/50	>> 003233
58	11100	IP54	90	MW		yes	LS2	1181/60/50	>> 003240
58	11100	IP54	90	MW				1181/60/50	>> 003219
58	11100	IP54	90	MW			LS2	1181/60/50	>> 003226
58	11100	IP54	80	SW		yes		1181/60/50	>> 005572
58	11100	IP54	80	SW		yes	LS2	1181/60/50	>> 005589
58	11100	IP54	80	SW				1181/60/50	>> 005558
58	11100	IP54	80	SW			LS2	1181/60/50	>> 005565
58	11100	IP54	105	VW		yes		1181/60/50	>> 003677
58	11100	IP54	105	VW		yes	LS2	1181/60/50	>> 003684
58	11100	IP54	105	VW				1181/60/50	>> 003653
58	11100	IP54	105	VW			LS2	1181/60/50	>> 003660
58	10600	IP54	butterfly	DAN				1181/60/50	>> 848568
58	10600	IP54	butterfly	DAN		yes		1181/60/50	>> 848582
58	10600	IP54	butterfly	DAN			LS2	1181/60/50	>> 848575
58	10600	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 848599
58	10700	IP54	asymmetric	SA				1181/60/50	>> 846168
58	10700	IP54	asymmetric	SA		yes		1181/60/50	>> 846182
58	10700	IP54	asymmetric	SA			LS2	1181/60/50	>> 846175
58	10700	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846199
58	11100	IP54	35/67	CN				1181/60/50	>> 853203
58	11100	IP54	35/67	CN		yes		1181/60/50	>> 853227
58	11100	IP54	65	SN				1181/60/50	>> 855528
58	11100	IP54	65	SN		yes		1181/60/50	>> 855542
58	11100	IP54	30	VN				1181/60/50	>> 850882
58	11100	IP54	30	VN		yes		1181/60/50	>> 850905
58	11100	IP54	35/67	CN			LS2	1181/60/50	>> 853210
58	11100	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853234
58	11100	IP54	65	SN			LS2	1181/60/50	>> 855535
58	11100	IP54	65	SN		yes	LS2	1181/60/50	>> 855559

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
58	11100	IP54	30	VN			LS2	1181/60/50	>> 850899
58	11100	IP54	30	VN		yes	LS2	1181/60/50	>> 850912
58	10900	IP54	25x80	CW		yes		1181/60/50	>> 279201
58	10900	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279225
58	10600	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848568/2
58	10600	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848582/2
58	10600	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 848575/2
58	10600	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 848599/2
58	10700	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846168/2
58	10700	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846182/2
58	10700	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846175/2
58	10700	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846199/2
58	11100	IP54	90	MW	2 rows			1181/60/50	>> 003219/2
58	11100	IP54	90	MW	2 rows	yes		1181/60/50	>> 003233/2
58	11100	IP54	80	SW	2 rows			1181/60/50	>> 005558/2
58	11100	IP54	80	SW	2 rows	yes		1181/60/50	>> 005572/2
58	11100	IP54	105	VW	2 rows			1181/60/50	>> 003653/2
58	11100	IP54	105	VW	2 rows	yes		1181/60/50	>> 003677/2
58	11100	IP54	90	MW	2 rows		LS2	1181/60/50	>> 003226/2
58	11100	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 003240/2
58	11100	IP54	80	SW	2 rows		LS2	1181/60/50	>> 005565/2
58	11100	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 005589/2
58	11100	IP54	105	VW	2 rows		LS2	1181/60/50	>> 003660/2
58	11100	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 003684/2
63	11100	IP54	105	symmetric		yes		1181/60/50	>> 007477
63	11100	IP54	105	symmetric		yes	LS2	1181/60/50	>> 007484
63	11100	IP54	105	symmetric				1181/60/50	>> 007453

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
63	11100	IP54	105	symmetric			LS2	1181/60/50	>> 007460
63	12100	IP54	120	symmetric		yes		1181/60/50	>> 007033
63	12100	IP54	120	symmetric		yes	LS2	1181/60/50	>> 007040
63	12100	IP54	120	symmetric				1181/60/50	>> 007019
63	12100	IP54	120	symmetric			LS2	1181/60/50	>> 007026
63	12000	IP54	90	MW		yes		1181/60/50	>> 003073
63	12000	IP54	90	MW		yes	LS2	1181/60/50	>> 003080
63	12000	IP54	90	MW				1181/60/50	>> 003059
63	12000	IP54	90	MW			LS2	1181/60/50	>> 003066
63	12000	IP54	80	SW		yes		1181/60/50	>> 983290
63	12000	IP54	80	SW		yes	LS2	1181/60/50	>> 983306
63	12000	IP54	80	SW				1181/60/50	>> 983276
63	12000	IP54	80	SW			LS2	1181/60/50	>> 983283
63	12000	IP54	105	VW		yes		1181/60/50	>> 003516
63	12000	IP54	105	VW		yes	LS2	1181/60/50	>> 003523
63	12000	IP54	105	VW				1181/60/50	>> 003493
63	12000	IP54	105	VW			LS2	1181/60/50	>> 003509
63	12000	IP54	35/67	CN				1181/60/50	>> 853043
63	12000	IP54	35/67	CN		yes		1181/60/50	>> 853067
63	12000	IP54	65	SN				1181/60/50	>> 855368
63	12000	IP54	65	SN		yes		1181/60/50	>> 855382
63	12000	IP54	30	VN				1181/60/50	>> 850721
63	12000	IP54	30	VN		yes		1181/60/50	>> 850745
63	12000	IP54	35/67	CN			LS2	1181/60/50	>> 853050
63	12000	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853074
63	12000	IP54	65	SN			LS2	1181/60/50	>> 855375
63	12000	IP54	65	SN		yes	LS2	1181/60/50	>> 855399
63	12000	IP54	30	VN			LS2	1181/60/50	>> 850738
63	12000	IP54	30	VN		yes	LS2	1181/60/50	>> 850752
63	11400	IP54	butterfly	DAN				1181/60/50	>> 848407
63	11400	IP54	butterfly	DAN		yes		1181/60/50	>> 848421
63	11400	IP54	butterfly	DAN			LS2	1181/60/50	>> 848414
63	11400	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 848438
63	11600	IP54	asymmetric	SA				1181/60/50	>> 846007
63	11600	IP54	asymmetric	SA		yes		1181/60/50	>> 846021
63	11600	IP54	asymmetric	SA			LS2	1181/60/50	>> 846014
63	11600	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846038
63	11750	IP54	25x80	CW		yes		1181/60/50	>> 279249

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
63	11750	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279263
63	11400	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848407/2
63	11400	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848421/2
63	11400	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 848414/2
63	11400	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 848438/2
63	11600	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846007/2
63	11600	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846021/2
63	11600	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846014/2
63	11600	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846038/2
63	12000	IP54	90	MW	2 rows			1181/60/50	>> 003059/2
63	12000	IP54	90	MW	2 rows	yes		1181/60/50	>> 003073/2
63	12000	IP54	80	SW	2 rows			1181/60/50	>> 983276/2
63	12000	IP54	80	SW	2 rows	yes		1181/60/50	>> 983290/2
63	12000	IP54	105	VW	2 rows			1181/60/50	>> 003493/2
63	12000	IP54	105	VW	2 rows	yes		1181/60/50	>> 003516/2
63	12000	IP54	90	MW	2 rows		LS2	1181/60/50	>> 003066/2
63	12000	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 003080/2
63	12000	IP54	80	SW	2 rows		LS2	1181/60/50	>> 983283/2
63	12000	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 983306/2
63	12000	IP54	105	VW	2 rows		LS2	1181/60/50	>> 003509/2
63	12000	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 003523/2
73	12700	IP54	105	symmetric		yes		1181/60/50	>> 007675
73	12700	IP54	105	symmetric		yes	LS2	1181/60/50	>> 007682
73	12700	IP54	105	symmetric				1181/60/50	>> 007651
73	12700	IP54	105	symmetric			LS2	1181/60/50	>> 007668
73	13800	IP54	120	symmetric		yes		1181/60/50	>> 007231
73	13800	IP54	120	symmetric		yes	LS2	1181/60/50	>> 007248

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
73	13800	IP54	120	symmetric				1181/60/50	>> 007217
73	13800	IP54	120	symmetric			LS2	1181/60/50	>> 007224
73	13700	IP54	90	MW		yes		1181/60/50	>> 003271
73	13700	IP54	90	MW		yes	LS2	1181/60/50	>> 003288
73	13700	IP54	90	MW				1181/60/50	>> 003257
73	13700	IP54	90	MW			LS2	1181/60/50	>> 003264
73	13700	IP54	80	SW		yes		1181/60/50	>> 005619
73	13700	IP54	80	SW		yes	LS2	1181/60/50	>> 005626
73	13700	IP54	80	SW				1181/60/50	>> 005596
73	13700	IP54	80	SW			LS2	1181/60/50	>> 005602
73	13700	IP54	105	VW		yes		1181/60/50	>> 003714
73	13700	IP54	105	VW		yes	LS2	1181/60/50	>> 003721
73	13700	IP54	105	VW				1181/60/50	>> 003691
73	13700	IP54	105	VW			LS2	1181/60/50	>> 003707
73	13000	IP54	butterfly	DAN				1181/60/50	>> 848605
73	13000	IP54	butterfly	DAN		yes		1181/60/50	>> 848629
73	13000	IP54	butterfly	DAN			LS2	1181/60/50	>> 848612
73	13000	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 848636
73	13200	IP54	asymmetric	SA				1181/60/50	>> 846205
73	13200	IP54	asymmetric	SA		yes		1181/60/50	>> 846229
73	13200	IP54	asymmetric	SA			LS2	1181/60/50	>> 846212
73	13200	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846236
73	13600	IP54	35/67	CN				1181/60/50	>> 853241
73	13600	IP54	35/67	CN		yes		1181/60/50	>> 853265
73	13600	IP54	65	SN				1181/60/50	>> 855566
73	13600	IP54	65	SN		yes		1181/60/50	>> 855580
73	13600	IP54	30	VN				1181/60/50	>> 850929
73	13600	IP54	30	VN		yes		1181/60/50	>> 850943
73	13600	IP54	35/67	CN			LS2	1181/60/50	>> 853258
73	13600	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853272
73	13600	IP54	65	SN			LS2	1181/60/50	>> 855573
73	13600	IP54	65	SN		yes	LS2	1181/60/50	>> 855597
73	13600	IP54	30	VN			LS2	1181/60/50	>> 850936
73	13600	IP54	30	VN		yes	LS2	1181/60/50	>> 850950
73	13450	IP54	25x80	CW		yes		1181/60/50	>> 279287
73	13450	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279300
73	13000	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848605/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
73	13000	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848629/2
73	13000	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 848612/2
73	13000	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 848636/2
73	13200	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846205/2
73	13200	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846229/2
73	13200	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846212/2
73	13200	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846236/2
73	13700	IP54	90	MW	2 rows			1181/60/50	>> 003257/2
73	13700	IP54	90	MW	2 rows	yes		1181/60/50	>> 003271/2
73	13700	IP54	80	SW	2 rows			1181/60/50	>> 005596/2
73	13700	IP54	80	SW	2 rows	yes		1181/60/50	>> 005619/2
73	13700	IP54	105	VW	2 rows			1181/60/50	>> 003691/2
73	13700	IP54	105	VW	2 rows	yes		1181/60/50	>> 003714/2
73	13700	IP54	90	MW	2 rows		LS2	1181/60/50	>> 003264/2
73	13700	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 003288/2
73	13700	IP54	80	SW	2 rows		LS2	1181/60/50	>> 005602/2
73	13700	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 005626/2
73	13700	IP54	105	VW	2 rows		LS2	1181/60/50	>> 003707/2
73	13700	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 003721/2
88	14850	IP54	105	symmetric		yes		1181/60/50	>> 007712
88	14850	IP54	105	symmetric		yes	LS2	1181/60/50	>> 007729
88	14850	IP54	105	symmetric				1181/60/50	>> 007699
88	14850	IP54	105	symmetric			LS2	1181/60/50	>> 007705
88	16300	IP54	120	symmetric		yes		1181/60/50	>> 007279
88	16300	IP54	120	symmetric		yes	LS2	1181/60/50	>> 007286
88	16300	IP54	120	symmetric				1181/60/50	>> 007255
88	16300	IP54	120	symmetric			LS2	1181/60/50	>> 007262
88	16100	IP54	90	MW		yes		1181/60/50	>> 003318

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	16100	IP54	90	MW		yes	LS2	1181/60/50	>> 003325
88	16100	IP54	90	MW				1181/60/50	>> 003295
88	16100	IP54	90	MW			LS2	1181/60/50	>> 003301
88	16100	IP54	80	SW		yes		1181/60/50	>> 005657
88	16100	IP54	80	SW		yes	LS2	1181/60/50	>> 005664
88	16100	IP54	80	SW				1181/60/50	>> 005633
88	16100	IP54	80	SW			LS2	1181/60/50	>> 005640
88	16100	IP54	105	VW		yes		1181/60/50	>> 003752
88	16100	IP54	105	VW		yes	LS2	1181/60/50	>> 003769
88	16100	IP54	105	VW				1181/60/50	>> 003738
88	16100	IP54	105	VW			LS2	1181/60/50	>> 003745
88	15450	IP54	butterfly	DAN				1181/60/50	>> 848643
88	15450	IP54	butterfly	DAN		yes		1181/60/50	>> 848667
88	15450	IP54	butterfly	DAN			LS2	1181/60/50	>> 848650
88	15450	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 848674
88	15500	IP54	asymmetric	SA				1181/60/50	>> 846243
88	15500	IP54	asymmetric	SA		yes		1181/60/50	>> 846267
88	15500	IP54	asymmetric	SA			LS2	1181/60/50	>> 846250
88	15500	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846274
88	16050	IP54	35/67	CN				1181/60/50	>> 853289
88	16050	IP54	35/67	CN		yes		1181/60/50	>> 853302
88	16050	IP54	65	SN				1181/60/50	>> 855603
88	16050	IP54	65	SN		yes		1181/60/50	>> 855627
88	16050	IP54	30	VN				1181/60/50	>> 850967
88	16050	IP54	30	VN		yes		1181/60/50	>> 850981
88	16050	IP54	35/67	CN			LS2	1181/60/50	>> 853296
88	16050	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853319
88	16050	IP54	65	SN			LS2	1181/60/50	>> 855610
88	16050	IP54	65	SN		yes	LS2	1181/60/50	>> 855634
88	16050	IP54	30	VN			LS2	1181/60/50	>> 850974
88	16050	IP54	30	VN		yes	LS2	1181/60/50	>> 850998
88	15800	IP54	25x80	CW		yes		1181/60/50	>> 279348
88	15800	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279362
88	15450	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848643/2
88	15450	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848667/2
88	15450	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 848650/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	15450	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 848674/2
88	15500	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846243/2
88	15500	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846267/2
88	15500	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846250/2
88	15500	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846274/2
88	16100	IP54	90	MW	2 rows			1181/60/50	>> 003295/2
88	16100	IP54	90	MW	2 rows	yes		1181/60/50	>> 003318/2
88	16100	IP54	80	SW	2 rows			1181/60/50	>> 005633/2
88	16100	IP54	80	SW	2 rows	yes		1181/60/50	>> 005657/2
88	16100	IP54	105	VW	2 rows			1181/60/50	>> 003738/2
88	16100	IP54	105	VW	2 rows	yes		1181/60/50	>> 003752/2
88	16100	IP54	90	MW	2 rows		LS2	1181/60/50	>> 003301/2
88	16100	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 003325/2
88	16100	IP54	80	SW	2 rows		LS2	1181/60/50	>> 005640/2
88	16100	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 005664/2
88	16100	IP54	105	VW	2 rows		LS2	1181/60/50	>> 003745/2
88	16100	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 003769/2
92	15600	IP54	105	symmetric		yes		1181/60/50	>> 585937
92	15600	IP54	105	symmetric		yes	LS2	1181/60/50	>> 586934
92	15600	IP54	105	symmetric				1181/60/50	>> 585821
92	15600	IP54	105	symmetric			LS2	1181/60/50	>> 586828
92	17000	IP54	120	symmetric		yes		1181/60/50	>> 585135
92	17000	IP54	120	symmetric		yes	LS2	1181/60/50	>> 586132
92	17000	IP54	120	symmetric				1181/60/50	>> 585029
92	17000	IP54	120	symmetric			LS2	1181/60/50	>> 586026
92	16800	IP54	90	MW		yes		1181/60/50	>> 585531
92	16800	IP54	90	MW		yes	LS2	1181/60/50	>> 586538
92	16800	IP54	90	MW				1181/60/50	>> 585425
92	16800	IP54	90	MW			LS2	1181/60/50	>> 586422

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
92	16800	IP54	80	SW		yes		1181/60/50	>> 585333
92	16800	IP54	80	SW		yes	LS2	1181/60/50	>> 586330
92	16800	IP54	80	SW				1181/60/50	>> 585227
92	16800	IP54	80	SW			LS2	1181/60/50	>> 586224
92	16800	IP54	105	VW		yes		1181/60/50	>> 585739
92	16800	IP54	105	VW		yes	LS2	1181/60/50	>> 586736
92	16800	IP54	105	VW				1181/60/50	>> 585623
92	16800	IP54	105	VW			LS2	1181/60/50	>> 586620
92	16000	IP54	butterfly	DAN				1181/60/50	>> 848865
92	16000	IP54	butterfly	DAN		yes		1181/60/50	>> 848957
92	16000	IP54	butterfly	DAN			LS2	1181/60/50	>> 849046
92	16000	IP54	butterfly	DAN		yes	LS2	1181/60/50	>> 849138
92	16200	IP54	asymmetric	SA				1181/60/50	>> 846465
92	16200	IP54	asymmetric	SA		yes		1181/60/50	>> 846557
92	16200	IP54	asymmetric	SA			LS2	1181/60/50	>> 846649
92	16200	IP54	asymmetric	SA		yes	LS2	1181/60/50	>> 846731
92	16700	IP54	35/67	CN				1181/60/50	>> 853500
92	16700	IP54	35/67	CN		yes		1181/60/50	>> 853593
92	16700	IP54	65	SN				1181/60/50	>> 855825
92	16700	IP54	65	SN		yes		1181/60/50	>> 855917
92	16700	IP54	30	VN				1181/60/50	>> 851186
92	16700	IP54	30	VN		yes		1181/60/50	>> 851278
92	16700	IP54	35/67	CN			LS2	1181/60/50	>> 853685
92	16700	IP54	35/67	CN		yes	LS2	1181/60/50	>> 853777
92	16700	IP54	65	SN			LS2	1181/60/50	>> 856006
92	16700	IP54	65	SN		yes	LS2	1181/60/50	>> 856099
92	16700	IP54	30	VN			LS2	1181/60/50	>> 851360
92	16700	IP54	30	VN		yes	LS2	1181/60/50	>> 851452
92	16500	IP54	25x80	CW		yes		1181/60/50	>> 279386
92	16500	IP54	25x80	CW		yes	LS2	1181/60/50	>> 279409
92	16000	IP54	butterfly	DAN	2 rows			1181/60/50	>> 848865/2
92	16000	IP54	butterfly	DAN	2 rows	yes		1181/60/50	>> 848957/2
92	16000	IP54	butterfly	DAN	2 rows		LS2	1181/60/50	>> 849046/2
92	16000	IP54	butterfly	DAN	2 rows	yes	LS2	1181/60/50	>> 849138/2
92	16200	IP54	asymmetric	SA	2 rows			1181/60/50	>> 846465/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
92	16200	IP54	asymmetric	SA	2 rows	yes		1181/60/50	>> 846557/2
92	16200	IP54	asymmetric	SA	2 rows		LS2	1181/60/50	>> 846649/2
92	16200	IP54	asymmetric	SA	2 rows	yes	LS2	1181/60/50	>> 846731/2
92	16800	IP54	90	MW	2 rows			1181/60/50	>> 585425/2
92	16800	IP54	90	MW	2 rows	yes		1181/60/50	>> 585531/2
92	16800	IP54	80	SW	2 rows			1181/60/50	>> 585227/2
92	16800	IP54	80	SW	2 rows	yes		1181/60/50	>> 585333/2
92	16800	IP54	105	VW	2 rows			1181/60/50	>> 585623/2
92	16800	IP54	105	VW	2 rows	yes		1181/60/50	>> 585739/2
92	16800	IP54	90	MW	2 rows		LS2	1181/60/50	>> 586422/2
92	16800	IP54	90	MW	2 rows	yes	LS2	1181/60/50	>> 586538/2
92	16800	IP54	80	SW	2 rows		LS2	1181/60/50	>> 586224/2
92	16800	IP54	80	SW	2 rows	yes	LS2	1181/60/50	>> 586330/2
92	16800	IP54	105	VW	2 rows		LS2	1181/60/50	>> 586620/2
92	16800	IP54	105	VW	2 rows	yes	LS2	1181/60/50	>> 586736/2

Linea S LED Single IP54 3

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	5950	IP54	105	symmetric		yes		1495/60/50	>> 585944
35	5950	IP54	105	symmetric		yes	LS2	1495/60/50	>> 586941
35	5950	IP54	105	symmetric				1495/60/50	>> 585838
35	5950	IP54	105	symmetric			LS2	1495/60/50	>> 586835
35	6500	IP54	120	symmetric		yes		1495/60/50	>> 585142
35	6500	IP54	120	symmetric		yes	LS2	1495/60/50	>> 586149
35	6500	IP54	120	symmetric				1495/60/50	>> 585036
35	6500	IP54	120	symmetric			LS2	1495/60/50	>> 586033
35	6450	IP54	90	MW		yes		1495/60/50	>> 585548
35	5950	IP54	90	MW		yes	LS2	1495/60/50	>> 586545
35	6450	IP54	90	MW				1495/60/50	>> 585432
35	5950	IP54	90	MW			LS2	1495/60/50	>> 586439

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	6450	IP54	80	SW		yes		1495/60/50	>> 585340
35	5950	IP54	80	SW		yes	LS2	1495/60/50	>> 586347
35	6450	IP54	80	SW				1495/60/50	>> 585234
35	5950	IP54	80	SW			LS2	1495/60/50	>> 586231
35	6450	IP54	105	VW		yes		1495/60/50	>> 585746
35	5950	IP54	105	VW		yes	LS2	1495/60/50	>> 586743
35	6450	IP54	105	VW				1495/60/50	>> 585630
35	5950	IP54	105	VW			LS2	1495/60/50	>> 586637
35	6150	IP54	butterfly	DAN				1495/60/50	>> 848872
35	6150	IP54	butterfly	DAN		yes		1495/60/50	>> 848964
35	6150	IP54	butterfly	DAN			LS2	1495/60/50	>> 849053
35	6150	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 849145
35	6200	IP54	asymmetric	SA				1495/60/50	>> 846472
35	6200	IP54	asymmetric	SA		yes		1495/60/50	>> 846564
35	6200	IP54	asymmetric	SA			LS2	1495/60/50	>> 846656
35	6200	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846748
35	6400	IP54	35/67	CN				1495/60/50	>> 853517
35	6400	IP54	35/67	CN		yes		1495/60/50	>> 853609
35	6400	IP54	65	SN				1495/60/50	>> 855832
35	6400	IP54	65	SN		yes		1495/60/50	>> 855924
35	6400	IP54	30	VN				1495/60/50	>> 851193
35	6400	IP54	30	VN		yes		1495/60/50	>> 851285
35	6400	IP54	35/67	CN			LS2	1495/60/50	>> 853692
35	6400	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853784
35	6400	IP54	65	SN			LS2	1495/60/50	>> 856013
35	6400	IP54	65	SN		yes	LS2	1495/60/50	>> 856105
35	6400	IP54	30	VN			LS2	1495/60/50	>> 851377
35	6400	IP54	30	VN		yes	LS2	1495/60/50	>> 851469
35	6350	IP54	25x80	CW				1495/60/50	>> 279508
35	6350	IP54	25x80	CW		yes		1495/60/50	>> 279065
35	5850	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279089
35	5950	IP54	90	MW	2 rows		LS2	1495/60/50	>> 586439/2
35	5950	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 586545/2
35	5950	IP54	80	SW	2 rows		LS2	1495/60/50	>> 586231/2
35	5950	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 586347/2
35	5950	IP54	105	VW	2 rows		LS2	1495/60/50	>> 586637/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	5950	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 586743/2
35	6150	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848872/2
35	6150	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848964/2
35	6150	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 849053/2
35	6150	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 849145/2
35	6200	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846472/2
35	6200	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846564/2
35	6200	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846656/2
35	6200	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846748/2
35	6450	IP54	90	MW	2 rows			1495/60/50	>> 585432/2
35	6450	IP54	90	MW	2 rows	yes		1495/60/50	>> 585548/2
35	6450	IP54	80	SW	2 rows			1495/60/50	>> 585234/2
35	6450	IP54	80	SW	2 rows	yes		1495/60/50	>> 585340/2
35	6450	IP54	105	VW	2 rows			1495/60/50	>> 585630/2
35	6450	IP54	105	VW	2 rows	yes		1495/60/50	>> 585746/2
41	7350	IP54	105	symmetric		yes		1495/60/50	>> 007750
41	7350	IP54	105	symmetric		yes	LS2	1495/60/50	>> 007767
41	7350	IP54	105	symmetric				1495/60/50	>> 007736
41	7350	IP54	105	symmetric			LS2	1495/60/50	>> 007743
41	8050	IP54	120	symmetric		yes		1495/60/50	>> 007316
41	8050	IP54	120	symmetric		yes	LS2	1495/60/50	>> 007323
41	8050	IP54	120	symmetric				1495/60/50	>> 007293
41	8050	IP54	120	symmetric			LS2	1495/60/50	>> 007309
41	7950	IP54	90	MW		yes		1495/60/50	>> 003356
41	7950	IP54	90	MW		yes	LS2	1495/60/50	>> 003363
41	7950	IP54	90	MW				1495/60/50	>> 003332
41	7950	IP54	90	MW			LS2	1495/60/50	>> 003349
41	7950	IP54	80	SW		yes		1495/60/50	>> 005695
41	7950	IP54	80	SW		yes	LS2	1495/60/50	>> 005701
41	7950	IP54	80	SW				1495/60/50	>> 005671

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
41	7950	IP54	80	SW			LS2	1495/60/50	>> 005688
41	7950	IP54	105	VW		yes		1495/60/50	>> 003790
41	7950	IP54	105	VW		yes	LS2	1495/60/50	>> 003806
41	7950	IP54	105	VW				1495/60/50	>> 003776
41	7950	IP54	105	VW			LS2	1495/60/50	>> 003783
41	7600	IP54	butterfly	DAN				1495/60/50	>> 848681
41	7600	IP54	butterfly	DAN		yes		1495/60/50	>> 848704
41	7600	IP54	butterfly	DAN			LS2	1495/60/50	>> 848698
41	7600	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 848711
41	7650	IP54	asymmetric	SA				1495/60/50	>> 846281
41	7650	IP54	asymmetric	SA		yes		1495/60/50	>> 846304
41	7650	IP54	asymmetric	SA			LS2	1495/60/50	>> 846298
41	7650	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846311
41	7900	IP54	35/67	CN				1495/60/50	>> 853326
41	7900	IP54	35/67	CN		yes		1495/60/50	>> 853340
41	7900	IP54	65	SN				1495/60/50	>> 855641
41	7900	IP54	65	SN		yes		1495/60/50	>> 855665
41	7900	IP54	30	VN				1495/60/50	>> 851001
41	7900	IP54	30	VN		yes		1495/60/50	>> 851025
41	7900	IP54	35/67	CN			LS2	1495/60/50	>> 853333
41	7900	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853357
41	7900	IP54	65	SN			LS2	1495/60/50	>> 855658
41	7900	IP54	65	SN		yes	LS2	1495/60/50	>> 855672
41	7900	IP54	30	VN			LS2	1495/60/50	>> 851018
41	7900	IP54	30	VN		yes	LS2	1495/60/50	>> 851032
41	7800	IP54	25x80	CW		yes		1495/60/50	>> 279119
41	7800	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279133
41	7600	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848681/2
41	7600	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848704/2
41	7600	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 848698/2
41	7600	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 848711/2
41	7650	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846281/2
41	7650	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846304/2
41	7650	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846298/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
41	7650	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846311/2
41	7950	IP54	90	MW	2 rows			1495/60/50	>> 003332/2
41	7950	IP54	90	MW	2 rows	yes		1495/60/50	>> 003356/2
41	7950	IP54	80	SW	2 rows			1495/60/50	>> 005671/2
41	7950	IP54	80	SW	2 rows	yes		1495/60/50	>> 005695/2
41	7950	IP54	105	VW	2 rows			1495/60/50	>> 003776/2
41	7950	IP54	105	VW	2 rows	yes		1495/60/50	>> 003790/2
41	7950	IP54	90	MW	2 rows		LS2	1495/60/50	>> 003349/2
41	7950	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 003363/2
41	7950	IP54	80	SW	2 rows		LS2	1495/60/50	>> 005688/2
41	7950	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 005701/2
41	7950	IP54	105	VW	2 rows		LS2	1495/60/50	>> 003783/2
41	7950	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 003806/2
48	8600	IP54	105	symmetric		yes		1495/60/50	>> 585951
48	8600	IP54	105	symmetric		yes	LS2	1495/60/50	>> 586958
48	8600	IP54	105	symmetric				1495/60/50	>> 585845
48	8600	IP54	105	symmetric			LS2	1495/60/50	>> 586842
48	9400	IP54	120	symmetric		yes		1495/60/50	>> 585159
48	9400	IP54	120	symmetric		yes	LS2	1495/60/50	>> 586156
48	9400	IP54	120	symmetric				1495/60/50	>> 585043
48	9400	IP54	120	symmetric			LS2	1495/60/50	>> 586040
48	9300	IP54	90	MW		yes		1495/60/50	>> 585555
48	9300	IP54	90	MW		yes	LS2	1495/60/50	>> 586552
48	9300	IP54	90	MW				1495/60/50	>> 585449
48	9300	IP54	90	MW			LS2	1495/60/50	>> 586446
48	9300	IP54	80	SW		yes		1495/60/50	>> 585357
48	9300	IP54	80	SW		yes	LS2	1495/60/50	>> 586354
48	9300	IP54	80	SW				1495/60/50	>> 585241
48	9300	IP54	80	SW			LS2	1495/60/50	>> 586248
48	9300	IP54	105	VW		yes		1495/60/50	>> 585753
48	9300	IP54	105	VW		yes	LS2	1495/60/50	>> 586750

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
48	9300	IP54	105	VW				1495/60/50	>> 585647
48	9300	IP54	105	VW			LS2	1495/60/50	>> 586644
48	8900	IP54	butterfly	DAN				1495/60/50	>> 848889
48	8900	IP54	butterfly	DAN		yes		1495/60/50	>> 848971
48	8900	IP54	butterfly	DAN			LS2	1495/60/50	>> 849060
48	8900	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 849152
48	9000	IP54	asymmetric	SA				1495/60/50	>> 846489
48	9000	IP54	asymmetric	SA		yes		1495/60/50	>> 846571
48	9000	IP54	asymmetric	SA			LS2	1495/60/50	>> 846663
48	9000	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846755
48	9300	IP54	35/67	CN				1495/60/50	>> 853524
48	9300	IP54	35/67	CN		yes		1495/60/50	>> 853616
48	9300	IP54	65	SN				1495/60/50	>> 855849
48	9300	IP54	65	SN		yes		1495/60/50	>> 855931
48	9300	IP54	30	VN				1495/60/50	>> 851209
48	9300	IP54	30	VN		yes		1495/60/50	>> 851292
48	9300	IP54	35/67	CN			LS2	1495/60/50	>> 853708
48	9300	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853791
48	9300	IP54	65	SN			LS2	1495/60/50	>> 856020
48	9300	IP54	65	SN		yes	LS2	1495/60/50	>> 856112
48	9300	IP54	30	VN			LS2	1495/60/50	>> 851384
48	9300	IP54	30	VN		yes	LS2	1495/60/50	>> 851476
48	9100	IP54	25x80	CW		yes		1495/60/50	>> 279157
48	9100	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279171
48	8900	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848889/2
48	8900	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848971/2
48	8900	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 849060/2
48	8900	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 849152/2
48	9000	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846489/2
48	9000	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846571/2
48	9000	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846663/2
48	9000	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846755/2
48	9300	IP54	90	MW	2 rows			1495/60/50	>> 585449/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
48	9300	IP54	90	MW	2 rows	yes		1495/60/50	>> 585555/2
48	9300	IP54	80	SW	2 rows			1495/60/50	>> 585241/2
48	9300	IP54	80	SW	2 rows	yes		1495/60/50	>> 585357/2
48	9300	IP54	105	VW	2 rows			1495/60/50	>> 585647/2
48	9300	IP54	105	VW	2 rows	yes		1495/60/50	>> 585753/2
48	9300	IP54	90	MW	2 rows		LS2	1495/60/50	>> 586446/2
48	9300	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 586552/2
48	9300	IP54	80	SW	2 rows		LS2	1495/60/50	>> 586248/2
48	9300	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 586354/2
48	9300	IP54	105	VW	2 rows		LS2	1495/60/50	>> 586644/2
48	9300	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 586750/2
58	10300	IP54	105	symmetric		yes		1495/60/50	>> 007798
58	10300	IP54	105	symmetric		yes	LS2	1495/60/50	>> 007804
58	10300	IP54	105	symmetric				1495/60/50	>> 007774
58	10300	IP54	105	symmetric			LS2	1495/60/50	>> 007781
58	11200	IP54	120	symmetric		yes		1495/60/50	>> 007354
58	11200	IP54	120	symmetric		yes	LS2	1495/60/50	>> 007361
58	11200	IP54	120	symmetric				1495/60/50	>> 007330
58	11200	IP54	120	symmetric			LS2	1495/60/50	>> 007347
58	11100	IP54	90	MW		yes		1495/60/50	>> 003394
58	11100	IP54	90	MW		yes	LS2	1495/60/50	>> 003400
58	11100	IP54	90	MW				1495/60/50	>> 003370
58	11100	IP54	90	MW			LS2	1495/60/50	>> 003387
58	11100	IP54	80	SW		yes		1495/60/50	>> 005732
58	11100	IP54	80	SW		yes	LS2	1495/60/50	>> 005749
58	11100	IP54	80	SW				1495/60/50	>> 005718
58	11100	IP54	80	SW			LS2	1495/60/50	>> 005725
58	11100	IP54	105	VW		yes		1495/60/50	>> 003837
58	11100	IP54	105	VW		yes	LS2	1495/60/50	>> 003844
58	11100	IP54	105	VW				1495/60/50	>> 003813
58	11100	IP54	105	VW			LS2	1495/60/50	>> 003820
58	10600	IP54	butterfly	DAN				1495/60/50	>> 848728

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
58	10600	IP54	butterfly	DAN		yes		1495/60/50	>> 848742
58	10600	IP54	butterfly	DAN			LS2	1495/60/50	>> 848735
58	10600	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 848759
58	10700	IP54	asymmetric	SA				1495/60/50	>> 846328
58	10700	IP54	asymmetric	SA		yes		1495/60/50	>> 846342
58	10700	IP54	asymmetric	SA			LS2	1495/60/50	>> 846335
58	10700	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846359
58	11100	IP54	35/67	CN				1495/60/50	>> 853364
58	11100	IP54	35/67	CN		yes		1495/60/50	>> 853388
58	11100	IP54	65	SN				1495/60/50	>> 855689
58	11100	IP54	65	SN		yes		1495/60/50	>> 855702
58	11100	IP54	30	VN				1495/60/50	>> 851049
58	11100	IP54	30	VN		yes		1495/60/50	>> 851063
58	11100	IP54	35/67	CN			LS2	1495/60/50	>> 853371
58	11100	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853395
58	11100	IP54	65	SN			LS2	1495/60/50	>> 855696
58	11100	IP54	65	SN		yes	LS2	1495/60/50	>> 855719
58	11100	IP54	30	VN			LS2	1495/60/50	>> 851056
58	11100	IP54	30	VN		yes	LS2	1495/60/50	>> 851070
58	10900	IP54	25x80	CW		yes		1495/60/50	>> 279218
58	10900	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279232
58	10600	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848728/2
58	10600	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848742/2
58	10600	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 848735/2
58	10600	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 848759/2
58	10700	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846328/2
58	10700	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846342/2
58	10700	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846335/2
58	10700	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846359/2
58	11100	IP54	90	MW	2 rows			1495/60/50	>> 003370/2
58	11100	IP54	90	MW	2 rows	yes		1495/60/50	>> 003394/2
58	11100	IP54	80	SW	2 rows			1495/60/50	>> 005718/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
58	11100	IP54	80	SW	2 rows	yes		1495/60/50	>> 005732/2
58	11100	IP54	105	VW	2 rows			1495/60/50	>> 003813/2
58	11100	IP54	105	VW	2 rows	yes		1495/60/50	>> 003837/2
58	11100	IP54	90	MW	2 rows		LS2	1495/60/50	>> 003387/2
58	11100	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 003400/2
58	11100	IP54	80	SW	2 rows		LS2	1495/60/50	>> 005725/2
58	11100	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 005749/2
58	11100	IP54	105	VW	2 rows		LS2	1495/60/50	>> 003820/2
58	11100	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 003844/2
63	11100	IP54	105	symmetric		yes		1495/60/50	>> 007514
63	11100	IP54	105	symmetric		yes	LS2	1495/60/50	>> 007521
63	11100	IP54	105	symmetric				1495/60/50	>> 007491
63	11100	IP54	105	symmetric			LS2	1495/60/50	>> 007507
63	12100	IP54	120	symmetric		yes		1495/60/50	>> 007071
63	12100	IP54	120	symmetric		yes	LS2	1495/60/50	>> 007088
63	12100	IP54	120	symmetric				1495/60/50	>> 007057
63	12100	IP54	120	symmetric			LS2	1495/60/50	>> 007064
63	12000	IP54	90	MW		yes		1495/60/50	>> 003110
63	12000	IP54	90	MW		yes	LS2	1495/60/50	>> 003127
63	12000	IP54	90	MW				1495/60/50	>> 003097
63	12000	IP54	90	MW			LS2	1495/60/50	>> 003103
63	12000	IP54	80	SW		yes		1495/60/50	>> 983337
63	12000	IP54	80	SW		yes	LS2	1495/60/50	>> 983344
63	12000	IP54	80	SW				1495/60/50	>> 983313
63	12000	IP54	80	SW			LS2	1495/60/50	>> 983320
63	12000	IP54	105	VW		yes		1495/60/50	>> 003554
63	12000	IP54	105	VW		yes	LS2	1495/60/50	>> 003561
63	12000	IP54	105	VW				1495/60/50	>> 003530
63	12000	IP54	105	VW			LS2	1495/60/50	>> 003547
63	12000	IP54	35/67	CN				1495/60/50	>> 853081
63	12000	IP54	35/67	CN		yes		1495/60/50	>> 853104
63	12000	IP54	65	SN				1495/60/50	>> 855405
63	12000	IP54	65	SN		yes		1495/60/50	>> 855429

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
63	12000	IP54	30	VN				1495/60/50	>> 850769
63	12000	IP54	30	VN		yes		1495/60/50	>> 850783
63	12000	IP54	35/67	CN			LS2	1495/60/50	>> 853098
63	12000	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853111
63	12000	IP54	65	SN			LS2	1495/60/50	>> 855412
63	12000	IP54	65	SN		yes	LS2	1495/60/50	>> 855436
63	12000	IP54	30	VN			LS2	1495/60/50	>> 850776
63	12000	IP54	30	VN		yes	LS2	1495/60/50	>> 850790
63	11400	IP54	butterfly	DAN				1495/60/50	>> 848445
63	11400	IP54	butterfly	DAN		yes		1495/60/50	>> 848469
63	11400	IP54	butterfly	DAN			LS2	1495/60/50	>> 848452
63	11400	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 848476
63	11600	IP54	asymmetric	SA				1495/60/50	>> 846045
63	11600	IP54	asymmetric	SA		yes		1495/60/50	>> 846069
63	11600	IP54	asymmetric	SA			LS2	1495/60/50	>> 846052
63	11600	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846076
63	11750	IP54	25x80	CW		yes		1495/60/50	>> 279256
63	11750	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279270
63	11400	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848445/2
63	11400	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848469/2
63	11400	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 848452/2
63	11400	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 848476/2
63	11600	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846045/2
63	11600	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846069/2
63	11600	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846052/2
63	11600	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846076/2
63	12000	IP54	90	MW	2 rows			1495/60/50	>> 003097/2
63	12000	IP54	90	MW	2 rows	yes		1495/60/50	>> 003110/2
63	12000	IP54	80	SW	2 rows			1495/60/50	>> 983313/2
63	12000	IP54	80	SW	2 rows	yes		1495/60/50	>> 983337/2
63	12000	IP54	105	VW	2 rows			1495/60/50	>> 003530/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
63	12000	IP54	105	VW	2 rows	yes		1495/60/50	>> 003554/2
63	12000	IP54	90	MW	2 rows		LS2	1495/60/50	>> 003103/2
63	12000	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 003127/2
63	12000	IP54	80	SW	2 rows		LS2	1495/60/50	>> 983320/2
63	12000	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 983344/2
63	12000	IP54	105	VW	2 rows		LS2	1495/60/50	>> 003547/2
63	12000	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 003561/2
73	12700	IP54	105	symmetric		yes		1495/60/50	>> 007835
73	12700	IP54	105	symmetric		yes	LS2	1495/60/50	>> 007842
73	12700	IP54	105	symmetric				1495/60/50	>> 007811
73	12700	IP54	105	symmetric			LS2	1495/60/50	>> 007828
73	13800	IP54	120	symmetric		yes		1495/60/50	>> 007392
73	13800	IP54	120	symmetric		yes	LS2	1495/60/50	>> 007408
73	13800	IP54	120	symmetric				1495/60/50	>> 007378
73	13800	IP54	120	symmetric			LS2	1495/60/50	>> 007385
73	13700	IP54	90	MW		yes		1495/60/50	>> 003431
73	13700	IP54	90	MW		yes	LS2	1495/60/50	>> 003448
73	13700	IP54	90	MW				1495/60/50	>> 003417
73	13700	IP54	90	MW			LS2	1495/60/50	>> 003424
73	13700	IP54	80	SW		yes		1495/60/50	>> 005770
73	13700	IP54	80	SW		yes	LS2	1495/60/50	>> 005787
73	13700	IP54	80	SW				1495/60/50	>> 005756
73	13700	IP54	80	SW			LS2	1495/60/50	>> 005763
73	13700	IP54	105	VW		yes		1495/60/50	>> 003875
73	13700	IP54	105	VW		yes	LS2	1495/60/50	>> 003882
73	13700	IP54	105	VW				1495/60/50	>> 003851
73	13700	IP54	105	VW			LS2	1495/60/50	>> 003868
73	13000	IP54	butterfly	DAN				1495/60/50	>> 848766
73	13000	IP54	butterfly	DAN		yes		1495/60/50	>> 848780
73	13000	IP54	butterfly	DAN			LS2	1495/60/50	>> 848773
73	13000	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 848797
73	13200	IP54	asymmetric	SA				1495/60/50	>> 846366
73	13200	IP54	asymmetric	SA		yes		1495/60/50	>> 846380
73	13200	IP54	asymmetric	SA			LS2	1495/60/50	>> 846373

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
73	13200	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846397
73	13600	IP54	35/67	CN				1495/60/50	>> 853401
73	13600	IP54	35/67	CN		yes		1495/60/50	>> 853425
73	13600	IP54	65	SN				1495/60/50	>> 855726
73	13600	IP54	65	SN		yes		1495/60/50	>> 855740
73	13600	IP54	30	VN				1495/60/50	>> 851087
73	13600	IP54	30	VN		yes		1495/60/50	>> 851100
73	13600	IP54	35/67	CN			LS2	1495/60/50	>> 853418
73	13600	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853432
73	13600	IP54	65	SN			LS2	1495/60/50	>> 855733
73	13600	IP54	65	SN		yes	LS2	1495/60/50	>> 855757
73	13600	IP54	30	VN			LS2	1495/60/50	>> 851094
73	13600	IP54	30	VN		yes	LS2	1495/60/50	>> 851117
73	13450	IP54	25x80	CW		yes		1495/60/50	>> 279294
73	13450	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279317
73	13000	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848766/2
73	13000	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848780/2
73	13000	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 848773/2
73	13000	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 848797/2
73	13200	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846366/2
73	13200	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846380/2
73	13200	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846373/2
73	13200	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846397/2
73	13700	IP54	90	MW	2 rows			1495/60/50	>> 003417/2
73	13700	IP54	90	MW	2 rows	yes		1495/60/50	>> 003431/2
73	13700	IP54	80	SW	2 rows			1495/60/50	>> 005756/2
73	13700	IP54	80	SW	2 rows	yes		1495/60/50	>> 005770/2
73	13700	IP54	105	VW	2 rows			1495/60/50	>> 003851/2
73	13700	IP54	105	VW	2 rows	yes		1495/60/50	>> 003875/2
73	13700	IP54	90	MW	2 rows		LS2	1495/60/50	>> 003424/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
73	13700	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 003448/2
73	13700	IP54	80	SW	2 rows		LS2	1495/60/50	>> 005763/2
73	13700	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 005787/2
73	13700	IP54	105	VW	2 rows		LS2	1495/60/50	>> 003868/2
73	13700	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 003882/2
88	14850	IP54	105	symmetric		yes		1495/60/50	>> 007873
88	14850	IP54	105	symmetric		yes	LS2	1495/60/50	>> 007880
88	14850	IP54	105	symmetric				1495/60/50	>> 007859
88	14850	IP54	105	symmetric			LS2	1495/60/50	>> 007866
88	16300	IP54	120	symmetric		yes		1495/60/50	>> 007439
88	16300	IP54	120	symmetric		yes	LS2	1495/60/50	>> 007446
88	16300	IP54	120	symmetric				1495/60/50	>> 007415
88	16300	IP54	120	symmetric			LS2	1495/60/50	>> 007422
88	16100	IP54	90	MW		yes		1495/60/50	>> 003479
88	16100	IP54	90	MW		yes	LS2	1495/60/50	>> 003486
88	16100	IP54	90	MW				1495/60/50	>> 003455
88	16100	IP54	90	MW			LS2	1495/60/50	>> 003462
88	16100	IP54	80	SW		yes		1495/60/50	>> 005817
88	16100	IP54	80	SW		yes	LS2	1495/60/50	>> 005824
88	16100	IP54	80	SW				1495/60/50	>> 005794
88	16100	IP54	80	SW			LS2	1495/60/50	>> 005800
88	16100	IP54	105	VW		yes		1495/60/50	>> 003981
88	16100	IP54	105	VW		yes	LS2	1495/60/50	>> 003998
88	16100	IP54	105	VW				1495/60/50	>> 003967
88	16100	IP54	105	VW			LS2	1495/60/50	>> 003974
88	15450	IP54	butterfly	DAN				1495/60/50	>> 848803
88	15450	IP54	butterfly	DAN		yes		1495/60/50	>> 848827
88	15450	IP54	butterfly	DAN			LS2	1495/60/50	>> 848810
88	15450	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 848834
88	15500	IP54	asymmetric	SA				1495/60/50	>> 846403
88	15500	IP54	asymmetric	SA		yes		1495/60/50	>> 846427
88	15500	IP54	asymmetric	SA			LS2	1495/60/50	>> 846410
88	15500	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846434
88	16050	IP54	35/67	CN				1495/60/50	>> 853449
88	16050	IP54	35/67	CN		yes		1495/60/50	>> 853463
88	16050	IP54	65	SN				1495/60/50	>> 855764

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	16050	IP54	65	SN		yes		1495/60/50	>> 855788
88	16050	IP54	30	VN				1495/60/50	>> 851124
88	16050	IP54	30	VN		yes		1495/60/50	>> 851148
88	16050	IP54	35/67	CN			LS2	1495/60/50	>> 853456
88	16050	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853470
88	16050	IP54	65	SN			LS2	1495/60/50	>> 855771
88	16050	IP54	65	SN		yes	LS2	1495/60/50	>> 855795
88	16050	IP54	30	VN			LS2	1495/60/50	>> 851131
88	16050	IP54	30	VN		yes	LS2	1495/60/50	>> 851155
88	15800	IP54	25x80	CW		yes		1495/60/50	>> 279355
88	15800	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279379
88	15450	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848803/2
88	15450	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848827/2
88	15450	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 848810/2
88	15450	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 848834/2
88	15500	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846403/2
88	15500	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846427/2
88	15500	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846410/2
88	15500	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846434/2
88	16100	IP54	90	MW	2 rows			1495/60/50	>> 003455/2
88	16100	IP54	90	MW	2 rows	yes		1495/60/50	>> 003479/2
88	16100	IP54	80	SW	2 rows			1495/60/50	>> 005794/2
88	16100	IP54	80	SW	2 rows	yes		1495/60/50	>> 005817/2
88	16100	IP54	105	VW	2 rows			1495/60/50	>> 003967/2
88	16100	IP54	105	VW	2 rows	yes		1495/60/50	>> 003981/2
88	16100	IP54	90	MW	2 rows		LS2	1495/60/50	>> 003462/2
88	16100	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 003486/2
88	16100	IP54	80	SW	2 rows		LS2	1495/60/50	>> 005800/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
88	16100	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 005824/2
88	16100	IP54	105	VW	2 rows		LS2	1495/60/50	>> 003974/2
88	16100	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 003998/2
92	15600	IP54	105	symmetric		yes		1495/60/50	>> 585968
92	15600	IP54	105	symmetric		yes	LS2	1495/60/50	>> 586965
92	15600	IP54	105	symmetric				1495/60/50	>> 585852
92	15600	IP54	105	symmetric			LS2	1495/60/50	>> 586859
92	17000	IP54	120	symmetric		yes		1495/60/50	>> 585166
92	17000	IP54	120	symmetric		yes	LS2	1495/60/50	>> 586163
92	17000	IP54	120	symmetric				1495/60/50	>> 585050
92	17000	IP54	120	symmetric			LS2	1495/60/50	>> 586057
92	16800	IP54	90	MW		yes		1495/60/50	>> 585562
92	16800	IP54	90	MW		yes	LS2	1495/60/50	>> 586569
92	16800	IP54	90	MW				1495/60/50	>> 585456
92	16800	IP54	90	MW			LS2	1495/60/50	>> 586453
92	16800	IP54	80	SW		yes		1495/60/50	>> 585364
92	16800	IP54	80	SW		yes	LS2	1495/60/50	>> 586361
92	16800	IP54	80	SW				1495/60/50	>> 585258
92	16800	IP54	80	SW			LS2	1495/60/50	>> 586255
92	16800	IP54	105	VW		yes		1495/60/50	>> 585760
92	16800	IP54	105	VW		yes	LS2	1495/60/50	>> 586767
92	16800	IP54	105	VW				1495/60/50	>> 585654
92	16800	IP54	105	VW			LS2	1495/60/50	>> 586651
92	16000	IP54	butterfly	DAN				1495/60/50	>> 848896
92	16000	IP54	butterfly	DAN		yes		1495/60/50	>> 848988
92	16000	IP54	butterfly	DAN			LS2	1495/60/50	>> 849077
92	16000	IP54	butterfly	DAN		yes	LS2	1495/60/50	>> 849169
92	16200	IP54	asymmetric	SA				1495/60/50	>> 846496
92	16200	IP54	asymmetric	SA		yes		1495/60/50	>> 846588
92	16200	IP54	asymmetric	SA			LS2	1495/60/50	>> 846670
92	16200	IP54	asymmetric	SA		yes	LS2	1495/60/50	>> 846762
92	16700	IP54	35/67	CN				1495/60/50	>> 853531
92	16700	IP54	35/67	CN		yes		1495/60/50	>> 853623
92	16700	IP54	65	SN				1495/60/50	>> 855856
92	16700	IP54	65	SN		yes		1495/60/50	>> 855948
92	16700	IP54	30	VN				1495/60/50	>> 851216
92	16700	IP54	30	VN		yes		1495/60/50	>> 851308

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
92	16700	IP54	35/67	CN			LS2	1495/60/50	>> 853715
92	16700	IP54	35/67	CN		yes	LS2	1495/60/50	>> 853807
92	16700	IP54	65	SN			LS2	1495/60/50	>> 856037
92	16700	IP54	65	SN		yes	LS2	1495/60/50	>> 856129
92	16700	IP54	30	VN			LS2	1495/60/50	>> 851391
92	16700	IP54	30	VN		yes	LS2	1495/60/50	>> 851483
92	16500	IP54	25x80	CW		yes		1495/60/50	>> 279393
92	16500	IP54	25x80	CW		yes	LS2	1495/60/50	>> 279416
92	16000	IP54	butterfly	DAN	2 rows			1495/60/50	>> 848896/2
92	16000	IP54	butterfly	DAN	2 rows	yes		1495/60/50	>> 848988/2
92	16000	IP54	butterfly	DAN	2 rows		LS2	1495/60/50	>> 849077/2
92	16000	IP54	butterfly	DAN	2 rows	yes	LS2	1495/60/50	>> 849169/2
92	16200	IP54	asymmetric	SA	2 rows			1495/60/50	>> 846496/2
92	16200	IP54	asymmetric	SA	2 rows	yes		1495/60/50	>> 846588/2
92	16200	IP54	asymmetric	SA	2 rows		LS2	1495/60/50	>> 846670/2
92	16200	IP54	asymmetric	SA	2 rows	yes	LS2	1495/60/50	>> 846762/2
92	16800	IP54	90	MW	2 rows			1495/60/50	>> 585456/2
92	16800	IP54	90	MW	2 rows	yes		1495/60/50	>> 585562/2
92	16800	IP54	80	SW	2 rows			1495/60/50	>> 585258/2
92	16800	IP54	80	SW	2 rows	yes		1495/60/50	>> 585364/2
92	16800	IP54	105	VW	2 rows			1495/60/50	>> 585654/2
92	16800	IP54	105	VW	2 rows	yes		1495/60/50	>> 585760/2
92	16800	IP54	90	MW	2 rows		LS2	1495/60/50	>> 586453/2
92	16800	IP54	90	MW	2 rows	yes	LS2	1495/60/50	>> 586569/2
92	16800	IP54	80	SW	2 rows		LS2	1495/60/50	>> 586255/2
92	16800	IP54	80	SW	2 rows	yes	LS2	1495/60/50	>> 586361/2
92	16800	IP54	105	VW	2 rows		LS2	1495/60/50	>> 586651/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
92	16800	IP54	105	VW	2 rows	yes	LS2	1495/60/50	>> 586767/2

Linea S LED Single IP54 4

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
53	9700	IP54	105	symmetric		yes		1769/60/50	>> 585975
53	9700	IP54	105	symmetric		yes	LS2	1769/60/50	>> 586972
53	9700	IP54	105	symmetric				1769/60/50	>> 585869
53	9700	IP54	105	symmetric			LS2	1769/60/50	>> 586866
53	10600	IP54	120	symmetric		yes		1769/60/50	>> 585173
53	10600	IP54	120	symmetric		yes	LS2	1769/60/50	>> 586170
53	10600	IP54	120	symmetric				1769/60/50	>> 585067
53	10600	IP54	120	symmetric			LS2	1769/60/50	>> 586064
53	10500	IP54	90	MW		yes		1769/60/50	>> 585579
53	10500	IP54	90	MW		yes	LS2	1769/60/50	>> 586576
53	10500	IP54	90	MW				1769/60/50	>> 585463
53	10500	IP54	90	MW			LS2	1769/60/50	>> 586460
53	10500	IP54	80	SW		yes		1769/60/50	>> 585371
53	10500	IP54	80	SW		yes	LS2	1769/60/50	>> 586378
53	10500	IP54	80	SW				1769/60/50	>> 585265
53	10500	IP54	80	SW			LS2	1769/60/50	>> 586262
53	10500	IP54	105	VW		yes		1769/60/50	>> 585777
53	10500	IP54	105	VW		yes	LS2	1769/60/50	>> 586774
53	10500	IP54	105	VW				1769/60/50	>> 585661
53	10500	IP54	105	VW			LS2	1769/60/50	>> 586668
53	10050	IP54	butterfly	DAN				1769/60/50	>> 848902
53	10050	IP54	butterfly	DAN		yes		1769/60/50	>> 848995
53	10050	IP54	butterfly	DAN			LS2	1769/60/50	>> 849084
53	10050	IP54	butterfly	DAN		yes	LS2	1769/60/50	>> 849176
53	10100	IP54	asymmetric	SA				1769/60/50	>> 846502
53	10100	IP54	asymmetric	SA		yes		1769/60/50	>> 846595
53	10100	IP54	asymmetric	SA			LS2	1769/60/50	>> 846687
53	10100	IP54	asymmetric	SA		yes	LS2	1769/60/50	>> 846779
53	10450	IP54	35/67	CN				1769/60/50	>> 853548
53	10450	IP54	35/67	CN		yes		1769/60/50	>> 853630
53	10450	IP54	65	SN				1769/60/50	>> 855863
53	10450	IP54	65	SN		yes		1769/60/50	>> 855955
53	10450	IP54	30	VN				1769/60/50	>> 851223
53	10450	IP54	30	VN		yes		1769/60/50	>> 851315

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
53	10450	IP54	35/67	CN			LS2	1769/60/50	>> 853722
53	10450	IP54	35/67	CN		yes	LS2	1769/60/50	>> 853814
53	10450	IP54	65	SN			LS2	1769/60/50	>> 856044
53	10450	IP54	65	SN		yes	LS2	1769/60/50	>> 856136
53	10450	IP54	30	VN			LS2	1769/60/50	>> 851407
53	10450	IP54	30	VN		yes	LS2	1769/60/50	>> 851490
53	10300	IP54	25x80	CW		yes		1769/60/50	>> 279188
53	10300	IP54	25x80	CW		yes	LS2	1769/60/50	>> 279195
53	10050	IP54	butterfly	DAN	2 rows			1769/60/50	>> 848902/2
53	10050	IP54	butterfly	DAN	2 rows	yes		1769/60/50	>> 848995/2
53	10050	IP54	butterfly	DAN	2 rows		LS2	1769/60/50	>> 849084/2
53	10050	IP54	butterfly	DAN	2 rows	yes	LS2	1769/60/50	>> 849176/2
53	10100	IP54	asymmetric	SA	2 rows			1769/60/50	>> 846502/2
53	10100	IP54	asymmetric	SA	2 rows	yes		1769/60/50	>> 846595/2
53	10100	IP54	asymmetric	SA	2 rows		LS2	1769/60/50	>> 846687/2
53	10100	IP54	asymmetric	SA	2 rows	yes	LS2	1769/60/50	>> 846779/2
53	10500	IP54	90	MW	2 rows			1769/60/50	>> 585463/2
53	10500	IP54	90	MW	2 rows	yes		1769/60/50	>> 585579/2
53	10500	IP54	80	SW	2 rows			1769/60/50	>> 585265/2
53	10500	IP54	80	SW	2 rows	yes		1769/60/50	>> 585371/2
53	10500	IP54	105	VW	2 rows			1769/60/50	>> 585661/2
53	10500	IP54	105	VW	2 rows	yes		1769/60/50	>> 585777/2
53	10500	IP54	90	MW	2 rows		LS2	1769/60/50	>> 586460/2
53	10500	IP54	90	MW	2 rows	yes	LS2	1769/60/50	>> 586576/2
53	10500	IP54	80	SW	2 rows		LS2	1769/60/50	>> 586262/2
53	10500	IP54	80	SW	2 rows	yes	LS2	1769/60/50	>> 586378/2
53	10500	IP54	105	VW	2 rows		LS2	1769/60/50	>> 586668/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
53	10500	IP54	105	VW	2 rows	yes	LS2	1769/60/50	>> 586774/2
70	12900	IP54	105	symmetric		yes		1769/60/50	>> 585982
70	12900	IP54	105	symmetric		yes	LS2	1769/60/50	>> 586989
70	12900	IP54	105	symmetric				1769/60/50	>> 585876
70	12900	IP54	105	symmetric			LS2	1769/60/50	>> 586873
70	14000	IP54	120	symmetric		yes		1769/60/50	>> 585180
70	14000	IP54	120	symmetric		yes	LS2	1769/60/50	>> 586187
70	14000	IP54	120	symmetric				1769/60/50	>> 585074
70	14000	IP54	120	symmetric			LS2	1769/60/50	>> 586071
70	13900	IP54	90	MW		yes		1769/60/50	>> 585586
70	13900	IP54	90	MW		yes	LS2	1769/60/50	>> 586583
70	13900	IP54	90	MW				1769/60/50	>> 585470
70	13900	IP54	90	MW			LS2	1769/60/50	>> 586477
70	13900	IP54	80	SW		yes		1769/60/50	>> 585388
70	13900	IP54	80	SW		yes	LS2	1769/60/50	>> 586385
70	13900	IP54	80	SW				1769/60/50	>> 585272
70	13900	IP54	80	SW			LS2	1769/60/50	>> 586279
70	13900	IP54	105	VW		yes		1769/60/50	>> 585784
70	13900	IP54	105	VW		yes	LS2	1769/60/50	>> 586781
70	13900	IP54	105	VW				1769/60/50	>> 585678
70	13900	IP54	105	VW			LS2	1769/60/50	>> 586675
70	13200	IP54	butterfly	DAN				1769/60/50	>> 848919
70	13200	IP54	butterfly	DAN		yes		1769/60/50	>> 849008
70	13200	IP54	butterfly	DAN			LS2	1769/60/50	>> 849091
70	13200	IP54	butterfly	DAN		yes	LS2	1769/60/50	>> 849183
70	13400	IP54	asymmetric	SA				1769/60/50	>> 846519
70	13400	IP54	asymmetric	SA		yes		1769/60/50	>> 846601
70	13400	IP54	asymmetric	SA			LS2	1769/60/50	>> 846694
70	13400	IP54	asymmetric	SA		yes	LS2	1769/60/50	>> 846786
70	13800	IP54	35/67	CN				1769/60/50	>> 853555
70	13800	IP54	35/67	CN		yes		1769/60/50	>> 853647
70	13800	IP54	65	SN				1769/60/50	>> 855870
70	13800	IP54	65	SN		yes		1769/60/50	>> 855962
70	13800	IP54	30	VN				1769/60/50	>> 851230
70	13800	IP54	30	VN		yes		1769/60/50	>> 851322
70	13800	IP54	35/67	CN			LS2	1769/60/50	>> 853739
70	13800	IP54	35/67	CN		yes	LS2	1769/60/50	>> 853821
70	13800	IP54	65	SN			LS2	1769/60/50	>> 856051

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
70	13800	IP54	65	SN		yes	LS2	1769/60/50	>> 856143
70	13800	IP54	30	VN			LS2	1769/60/50	>> 851414
70	13800	IP54	30	VN		yes	LS2	1769/60/50	>> 851506
70	13650	IP54	25x80	CW		yes		1769/60/50	>> 279324
70	13650	IP54	25x80	CW		yes	LS2	1769/60/50	>> 279331
70	13200	IP54	butterfly	DAN	2 rows			1769/60/50	>> 848919/2
70	13200	IP54	butterfly	DAN	2 rows	yes		1769/60/50	>> 849008/2
70	13200	IP54	butterfly	DAN	2 rows		LS2	1769/60/50	>> 849091/2
70	13200	IP54	butterfly	DAN	2 rows	yes	LS2	1769/60/50	>> 849183/2
70	13400	IP54	asymmetric	SA	2 rows			1769/60/50	>> 846519/2
70	13400	IP54	asymmetric	SA	2 rows	yes		1769/60/50	>> 846601/2
70	13400	IP54	asymmetric	SA	2 rows		LS2	1769/60/50	>> 846694/2
70	13400	IP54	asymmetric	SA	2 rows	yes	LS2	1769/60/50	>> 846786/2
70	13900	IP54	90	MW	2 rows			1769/60/50	>> 585470/2
70	13900	IP54	90	MW	2 rows	yes		1769/60/50	>> 585586/2
70	13900	IP54	80	SW	2 rows			1769/60/50	>> 585272/2
70	13900	IP54	80	SW	2 rows	yes		1769/60/50	>> 585388/2
70	13900	IP54	105	VW	2 rows			1769/60/50	>> 585678/2
70	13900	IP54	105	VW	2 rows	yes		1769/60/50	>> 585784/2
70	13900	IP54	90	MW	2 rows		LS2	1769/60/50	>> 586477/2
70	13900	IP54	90	MW	2 rows	yes	LS2	1769/60/50	>> 586583/2
70	13900	IP54	80	SW	2 rows		LS2	1769/60/50	>> 586279/2
70	13900	IP54	80	SW	2 rows	yes	LS2	1769/60/50	>> 586385/2
70	13900	IP54	105	VW	2 rows		LS2	1769/60/50	>> 586675/2
70	13900	IP54	105	VW	2 rows	yes	LS2	1769/60/50	>> 586781/2
100	18000	IP54	butterfly	DAN	2 rows			1769/60/50	>> 848926/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
100	18000	IP54	butterfly	DAN	2 rows	yes		1769/60/50	>> 849015/2
100	18000	IP54	butterfly	DAN	2 rows		LS2	1769/60/50	>> 849107/2
100	18000	IP54	butterfly	DAN	2 rows	yes	LS2	1769/60/50	>> 849190/2
100	18200	IP54	asymmetric	SA	2 rows			1769/60/50	>> 846526/2
100	18200	IP54	asymmetric	SA	2 rows	yes		1769/60/50	>> 846618/2
100	18200	IP54	asymmetric	SA	2 rows		LS2	1769/60/50	>> 846700/2
100	18200	IP54	asymmetric	SA	2 rows	yes	LS2	1769/60/50	>> 846793/2
100	18900	IP54	90	MW	2 rows			1769/60/50	>> 585487/2
100	18900	IP54	90	MW	2 rows	yes		1769/60/50	>> 585593/2
100	18900	IP54	80	SW	2 rows			1769/60/50	>> 585289/2
100	18900	IP54	80	SW	2 rows	yes		1769/60/50	>> 585395/2
100	18900	IP54	105	VW	2 rows			1769/60/50	>> 585685/2
100	18900	IP54	105	VW	2 rows	yes		1769/60/50	>> 585791/2
100	18900	IP54	90	MW	2 rows		LS2	1769/60/50	>> 586484/2
100	18900	IP54	90	MW	2 rows	yes	LS2	1769/60/50	>> 586590/2
100	18900	IP54	80	SW	2 rows		LS2	1769/60/50	>> 586286/2
100	18900	IP54	80	SW	2 rows	yes	LS2	1769/60/50	>> 586392/2
100	18900	IP54	105	VW	2 rows		LS2	1769/60/50	>> 586682/2
100	18900	IP54	105	VW	2 rows	yes	LS2	1769/60/50	>> 586798/2
100	17500	IP54	105	symmetric		yes		1769/60/50	>> 585999
100	17500	IP54	105	symmetric		yes	LS2	1769/60/50	>> 586996
100	17500	IP54	105	symmetric				1769/60/50	>> 585883
100	17500	IP54	105	symmetric			LS2	1769/60/50	>> 586880
100	19100	IP54	120	symmetric		yes		1769/60/50	>> 585197
100	19100	IP54	120	symmetric		yes	LS2	1769/60/50	>> 586194
100	19100	IP54	120	symmetric				1769/60/50	>> 585081
100	19100	IP54	120	symmetric			LS2	1769/60/50	>> 586088
100	18900	IP54	90	MW		yes		1769/60/50	>> 585593

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
100	18900	IP54	90	MW		yes	LS2	1769/60/50	>> 586590
100	18900	IP54	90	MW				1769/60/50	>> 585487
100	18900	IP54	90	MW			LS2	1769/60/50	>> 586484
100	18900	IP54	80	SW		yes		1769/60/50	>> 585395
100	18900	IP54	80	SW		yes	LS2	1769/60/50	>> 586392
100	18900	IP54	80	SW				1769/60/50	>> 585289
100	18900	IP54	80	SW			LS2	1769/60/50	>> 586286
100	18900	IP54	105	VW		yes		1769/60/50	>> 585791
100	18900	IP54	105	VW		yes	LS2	1769/60/50	>> 586798
100	18900	IP54	105	VW				1769/60/50	>> 585685
100	18900	IP54	105	VW			LS2	1769/60/50	>> 586682
100	18000	IP54	butterfly	DAN				1769/60/50	>> 848926
100	18000	IP54	butterfly	DAN		yes		1769/60/50	>> 849015
100	18000	IP54	butterfly	DAN			LS2	1769/60/50	>> 849107
100	18000	IP54	butterfly	DAN		yes	LS2	1769/60/50	>> 849190
100	18200	IP54	asymmetric	SA				1769/60/50	>> 846526
100	18200	IP54	asymmetric	SA		yes		1769/60/50	>> 846618
100	18200	IP54	asymmetric	SA			LS2	1769/60/50	>> 846700
100	18200	IP54	asymmetric	SA		yes	LS2	1769/60/50	>> 846793
100	18800	IP54	35/67	CN				1769/60/50	>> 853562
100	18800	IP54	35/67	CN		yes		1769/60/50	>> 853654
100	18800	IP54	65	SN				1769/60/50	>> 855887
100	18800	IP54	65	SN		yes		1769/60/50	>> 855979
100	18800	IP54	30	VN				1769/60/50	>> 851247
100	18800	IP54	30	VN		yes		1769/60/50	>> 851339
100	18800	IP54	35/67	CN			LS2	1769/60/50	>> 853746
100	18800	IP54	35/67	CN		yes	LS2	1769/60/50	>> 853838
100	18800	IP54	65	SN			LS2	1769/60/50	>> 856068
100	18800	IP54	65	SN		yes	LS2	1769/60/50	>> 856150
100	18800	IP54	30	VN			LS2	1769/60/50	>> 851421
100	18800	IP54	30	VN		yes	LS2	1769/60/50	>> 851513
100	18550	IP54	25x80	CW		yes		1769/60/50	>> 279423
100	18550	IP54	25x80	CW		yes	LS2	1769/60/50	>> 279430
142	23550	IP54	105	symmetric		yes		1769/60/50	>> 007552
142	23550	IP54	105	symmetric		yes	LS2	1769/60/50	>> 007569
142	23550	IP54	105	symmetric				1769/60/50	>> 007538
142	23550	IP54	105	symmetric			LS2	1769/60/50	>> 007545
142	25800	IP54	120	symmetric		yes		1769/60/50	>> 007118

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
142	25800	IP54	120	symmetric		yes	LS2	1769/60/50	>> 007125
142	25800	IP54	120	symmetric				1769/60/50	>> 007095
142	25800	IP54	120	symmetric			LS2	1769/60/50	>> 007101
142	25550	IP54	90	MW		yes		1769/60/50	>> 003158
142	25550	IP54	90	MW		yes	LS2	1769/60/50	>> 003165
142	25550	IP54	90	MW				1769/60/50	>> 003134
142	25550	IP54	90	MW			LS2	1769/60/50	>> 003141
142	25550	IP54	80	SW		yes		1769/60/50	>> 983375
142	25550	IP54	80	SW		yes	LS2	1769/60/50	>> 983382
142	25550	IP54	80	SW				1769/60/50	>> 983351
142	25550	IP54	80	SW			LS2	1769/60/50	>> 983368
142	25550	IP54	105	VW		yes		1769/60/50	>> 003592
142	25550	IP54	105	VW		yes	LS2	1769/60/50	>> 003608
142	25550	IP54	105	VW				1769/60/50	>> 003578
142	25550	IP54	105	VW			LS2	1769/60/50	>> 003585
142	24450	IP54	butterfly	DAN				1769/60/50	>> 848483
142	24450	IP54	butterfly	DAN		yes		1769/60/50	>> 848506
142	24450	IP54	butterfly	DAN			LS2	1769/60/50	>> 848490
142	24450	IP54	butterfly	DAN		yes	LS2	1769/60/50	>> 848513
142	24600	IP54	asymmetric	SA				1769/60/50	>> 846083
142	24600	IP54	asymmetric	SA		yes		1769/60/50	>> 846106
142	24600	IP54	asymmetric	SA			LS2	1769/60/50	>> 846090
142	24600	IP54	asymmetric	SA		yes	LS2	1769/60/50	>> 846113
142	25400	IP54	35/67	CN				1769/60/50	>> 853128
142	25400	IP54	35/67	CN		yes		1769/60/50	>> 853142
142	25400	IP54	65	SN				1769/60/50	>> 855443
142	25400	IP54	65	SN		yes		1769/60/50	>> 855467
142	25400	IP54	30	VN				1769/60/50	>> 850806
142	25400	IP54	30	VN		yes		1769/60/50	>> 850820
142	25400	IP54	35/67	CN			LS2	1769/60/50	>> 853135
142	25400	IP54	35/67	CN		yes	LS2	1769/60/50	>> 853159
142	25400	IP54	65	SN			LS2	1769/60/50	>> 855450
142	25400	IP54	65	SN		yes	LS2	1769/60/50	>> 855474
142	25400	IP54	30	VN			LS2	1769/60/50	>> 850813
142	25400	IP54	30	VN		yes	LS2	1769/60/50	>> 850837
142	25050	IP54	25x80	CW		yes		1769/60/50	>> 279447
142	25050	IP54	25x80	CW		yes	LS2	1769/60/50	>> 279454
142	24450	IP54	butterfly	DAN	2 rows			1769/60/50	>> 848483/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
142	24450	IP54	butterfly	DAN	2 rows	yes		1769/60/50	>> 848506/2
142	24450	IP54	butterfly	DAN	2 rows		LS2	1769/60/50	>> 848490/2
142	24450	IP54	butterfly	DAN	2 rows	yes	LS2	1769/60/50	>> 848513/2
142	24600	IP54	asymmetric	SA	2 rows			1769/60/50	>> 846083/2
142	24600	IP54	asymmetric	SA	2 rows	yes		1769/60/50	>> 846106/2
142	24600	IP54	asymmetric	SA	2 rows		LS2	1769/60/50	>> 846090/2
142	24600	IP54	asymmetric	SA	2 rows	yes	LS2	1769/60/50	>> 846113/2
142	25550	IP54	90	MW	2 rows			1769/60/50	>> 003134/2
142	25550	IP54	90	MW	2 rows	yes		1769/60/50	>> 003158/2
142	25550	IP54	80	SW	2 rows			1769/60/50	>> 983351/2
142	25550	IP54	80	SW	2 rows	yes		1769/60/50	>> 983375/2
142	25550	IP54	105	VW	2 rows			1769/60/50	>> 003578/2
142	25550	IP54	105	VW	2 rows	yes		1769/60/50	>> 003592/2
142	25550	IP54	90	MW	2 rows		LS2	1769/60/50	>> 003141/2
142	25550	IP54	90	MW	2 rows	yes	LS2	1769/60/50	>> 003165/2
142	25550	IP54	80	SW	2 rows		LS2	1769/60/50	>> 983368/2
142	25550	IP54	80	SW	2 rows	yes	LS2	1769/60/50	>> 983382/2
142	25550	IP54	105	VW	2 rows		LS2	1769/60/50	>> 003585/2
142	25550	IP54	105	VW	2 rows	yes	LS2	1769/60/50	>> 003608/2

Linea S LED Single IP54 869/2025

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
35	5650	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154652/2
35	5650	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154744/2
35	6150	IP54		MW MAT	2 rows			1181/60/50	>> 154478/2
35	6150	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154560/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
41	7600	IP54		MW MAT	2 rows			1181/60/50	>> 154133/2
41	7600	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154157/2
41	7600	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154140/2
41	7600	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154164/2
48	8850	IP54		MW MAT	2 rows			1181/60/50	>> 154485/2
48	8850	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154577/2
48	8850	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154669/2
48	8850	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154751/2
58	10600	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154195/2
58	10600	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154188/2
58	10600	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154201/2
63	11550	IP54		MW MAT	2 rows			1181/60/50	>> 154010/2
63	11550	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154034/2
63	11550	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154027/2
63	11550	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154041/2
73	13050	IP54		MW MAT	2 rows			1181/60/50	>> 154218/2
73	13050	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154232/2
73	13050	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154225/2
73	13050	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154249/2
88	15350	IP54		MW MAT	2 rows			1181/60/50	>> 154256/2
88	15350	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154270/2
88	15350	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154263/2
88	15350	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154287/2
92	16000	IP54		MW MAT	2 rows			1181/60/50	>> 154492/2
92	16000	IP54		MW MAT	2 rows	yes		1181/60/50	>> 154584/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
92	16000	IP54		MW MAT	2 rows		LS2	1181/60/50	>> 154676/2
92	16000	IP54		MW MAT	2 rows	yes	LS2	1181/60/50	>> 154768/2
35	5650	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154683/2
35	5650	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154775/2
35	6150	IP54		MW MAT	2 rows			1495/60/50	>> 154508/2
35	6150	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154591/2
41	7600	IP54		MW MAT	2 rows			1495/60/50	>> 154294/2
41	7600	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154317/2
41	7600	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154300/2
41	7600	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154324/2
48	8850	IP54		MW MAT	2 rows			1495/60/50	>> 154515/2
48	8850	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154607/2
48	8850	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154690/2
48	8850	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154782/2
58	10600	IP54		MW MAT	2 rows			1495/60/50	>> 154331/2
58	10600	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154355/2
58	10600	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154348/2
58	10600	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154362/2
63	11550	IP54		MW MAT	2 rows			1495/60/50	>> 154058/2
63	11550	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154072/2
63	11550	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154065/2
63	11450	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154089/2
73	13050	IP54		MW MAT	2 rows			1495/60/50	>> 154379/2
73	13050	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154393/2
73	13050	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154386/2

LINEA S LED SINGLE IP54

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
73	13050	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154409/2
88	15350	IP54		MW MAT	2 rows			1495/60/50	>> 154416/2
88	15350	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154430/2
88	15350	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154423/2
88	15350	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154447/2
92	16000	IP54		MW MAT	2 rows			1495/60/50	>> 154522/2
92	16000	IP54		MW MAT	2 rows	yes		1495/60/50	>> 154614/2
92	16000	IP54		MW MAT	2 rows		LS2	1495/60/50	>> 154706/2
92	16000	IP54		MW MAT	2 rows	yes	LS2	1495/60/50	>> 154799/2
53	10000	IP54		MW MAT	2 rows			1769/60/50	>> 154539/2
53	10000	IP54		MW MAT	2 rows	yes		1769/60/50	>> 154621/2
53	10000	IP54		MW MAT	2 rows		LS2	1769/60/50	>> 154713/2
53	10000	IP54		MW MAT	2 rows	yes	LS2	1769/60/50	>> 154805/2
70	13250	IP54		MW MAT	2 rows			1769/60/50	>> 154546/2
70	13250	IP54		MW MAT	2 rows	yes		1769/60/50	>> 154638/2
70	13250	IP54		MW MAT	2 rows		LS2	1769/60/50	>> 154720/2
70	13250	IP54		MW MAT	2 rows	yes	LS2	1769/60/50	>> 154812/2
100	18000	IP54		MW MAT	2 rows			1769/60/50	>> 154553/2
100	18000	IP54		MW MAT	2 rows	yes		1769/60/50	>> 154645/2
100	18000	IP54		MW MAT	2 rows		LS2	1769/60/50	>> 154737/2
100	18000	IP54		MW MAT	2 rows	yes	LS2	1769/60/50	>> 154829/2
142	24350	IP54		MW MAT	2 rows			1769/60/50	>> 154096/2
142	24350	IP54		MW MAT	2 rows	yes		1769/60/50	>> 154119/2
142	24350	IP54		MW MAT	2 rows		LS2	1769/60/50	>> 154102/2
142	24350	IP54		MW MAT	2 rows	yes	LS2	1769/60/50	>> 154126/2

LINEA S LED SINGLE IP54


GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Ingress protection	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
23	3700	IP54		MW MAT	2 rows			588/60/50	>> 154836/2
23	3700	IP54		MW MAT	2 rows	yes		588/60/50	>> 154874/2
28	4600	IP54		MW MAT	2 rows			588/60/50	>> 154843/2
28	4600	IP54		MW MAT	2 rows	yes		588/60/50	>> 154881/2
34	5600	IP54		MW MAT	2 rows			588/60/50	>> 154850/2
34	5600	IP54		MW MAT	2 rows	yes		588/60/50	>> 154898/2
40	6450	IP54		MW MAT	2 rows			588/60/50	>> 154867/2
40	6450	IP54		MW MAT	2 rows	yes		588/60/50	>> 154904/2


LINEA S LED SINGLE IP54

GENERAL CARD


LUMINOUS INTENSITY DISTRIB. CURVE




105D




120D




CN




DAN




MW




SN



SW



VN



VW

LINEA S LED SINGLE IP54

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
981173	LINEA S LED hang 1.5m
	LINEA S LED hang 3m
981425	LINEA S LED chain pendant
981418	LINEA S LED pendant sm 1.5
980961	LINEA S LED pendant sm 3m



LINEA S LED hang 1.5m (981173)



LINEA S LED chain pendant (981425)

LINEA S LED SINGLE IP54

GENERAL CARD

Linea S LED Single is equipped with new light distributions:

SW - standard wide lens (conventional angle 80D) with a wide range of applications in commercial facilities, industrial halls, and even - due to the low glare index UGR<19 - in office parts of the facility. It provides high lighting efficiency and helps meet the most stringent requirements of the EN 12464-1 standard in terms of the glare index, illuminance and high uniformity on the surface of aisles and shelves. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-8m.
MW - medium wide lens (90D conventional angle) with a wide range of applications in commercial facilities, industrial halls. It provides high lighting efficiency and helps meet the most stringent requirements of the EN 12464-1 standard in terms of glare index, illuminance and high uniformity on the surface of aisles and shelves. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-6m.
VW - a very wide lens (105D conventional angle) with wide application in open spaces and low warehouses. It provides high luminous efficacy and helps meet the most stringent requirements of EN 12464-1 in terms of glare index (UGR<22, UGR<25), illuminance and high uniformity when the system is installed in low spaces. Particularly recommended for rooms where luminaires are mounted at a height of 2.5-5m.
SN - standard narrow lens (standard narrow, conventional angle 65D) for general lighting in open areas in industrial and warehouse halls, workshops, and even - due to the low glare index UGR<19 - in office parts of the facility. Particularly recommended for rooms where lighting fixtures are mounted at a height of 8-12m.
VN - very narrow lens (very narrow, conventional angle 30D) for illumination of open spaces in facilities where the luminaire mounting height exceeds 13m. Particularly recommended for premises where luminaires are mounted at a height of 13-20m.
CN - corridor narrow lens (corridor narrow, conventional angle 35/67D) for communication lighting in industrial halls and racking aisles in high storage warehouses. Particularly suitable for rooms where luminaires are mounted at a height of 7-12m.
DAN - butterfly lens, double asymmetric narrow, for shelf lighting in retail facilities where it is essential to direct light onto the goods on display. Particularly recommended for premises where luminaires are mounted at a height of 3-4.5m.
SA - single asymmetric lens for single-sided illumination of shelf areas in retail spaces, signs, advertising surfaces on building walls, illumination of work surfaces in conditions where it is not possible to position luminaires directly above them. Particularly suitable for spaces where luminaires are mounted at heights of 3-4.5m.

UGR < 19

The Unified Glare Rating is an indicator that characterises glare. The lower the Unified Glare Rating (UGR), the lower the glare.

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 139/2025; 32/2024

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

