

SKVER LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	19.00 - 50.00
Luminous flux [lm]*:	2250 - 6700
Colour temperature [K]:	3000; 4000
Colour rendering index:	80
Electrical protection class:	II
Optics:	RM7; no
Control:	Yes + 5-stage power reduction
Colour of the body:	black
Luminous efficacy [lm/W]:	115.00 - 138.00
Energy efficiency class:	C; D
Material of the body:	powder coated aluminium
Diffuser type:	transparent
Diffuser material:	PC
SDCM:	≤ 4
Socket type:	ZHAGA

CHARACTERISTICS

Skver LED is the new generation of LED park and urban luminaires. It utilizes directional multi-lens arrays made of PMMA, each lens having the same optics, ensuring consistent light characteristics over time. The luminaire's design ensures the tightness of the internal chamber. As standard, the luminaire offers tool-free access to the electrical equipment using two independent knobs, which, upon request and for protection against vandalism or unauthorized opening, can be permanently secured with screws. The upper part of the luminaire features a dedicated hinge. The luminaire allows for the replacement of the integrated internal power/lighting module (compliant with ZhagaBook 13 and ZhagaBook 15 standards) without the use of tools, enabling quick and convenient servicing, allowing for the exchange of one integrated component without dismantling the entire luminaire and making soldered or screwed connections. There is no need for servicing at the installation site. Simply replace the module with a spare (accessory), close the luminaire, and then carry out the servicing work at the service location: at the luminaire owner's facility or return it to the manufacturer's service. The body and bracket are made of pressure die-cast aluminum, powder-coated in black, characterized by a very high degree of IP66 tightness and IK10 mechanical impact resistance. Standard equipment: protection against accidental luminaire overheating NTC; fully programmable DALI driver; available constant light output maintenance functions over time CLO and autonomous, 5-step power reduction; connection terminals; tool-free access. Additional options: accessory canopies transforming the external appearance of the luminaire, Zhaga connector (ZhagaBook 18); compatibility with control systems, anti-vandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; knife switch disconnecting the integrated module voltage in case of chamber opening; made with a wire terminated with a quick connector; painting in any color from the RAL palette. Certificates: CE, RoHS, ENEC, ENEC+, Zhaga-D4i.

APPLICATION

External areas of places such as: town halls, libraries, city offices, healthcare facilities, schools, preschools, public gardens, streets, sidewalks, recreational areas: sports fields, playgrounds, bike paths, historical sites, old towns.

SKVER LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

SKVER LED A

Rated power of the luminaire [W]*	Luminous flux [lm]*	Luminous efficacy [lm/W]	Version	Energy efficiency class	Colour temperature [K]	Colour rendering index	Electrical protection class	Optics	DIMM DALI	Index
19	2250	118	A	D	3000	80	II	no		>> 435102
19	2350	124	A	D	4000	80	II	no		>> 435164
26	3000	115	A	D	4000	80	II	no		>> 435171
26	3100	119	A	D	3000	80	II	no		>> 435119
33	3900	118	A	D	3000	80	II	no		>> 435126
33	4100	124	A	D	4000	80	II	no		>> 435188
39	4550	117	A	D	3000	80	II	no		>> 435133
39	4800	123	A	D	4000	80	II	no		>> 435195
44	5250	119	A	D	3000	80	II	no		>> 435140
44	5550	126	A	D	4000	80	II	no		>> 435201
50	5900	118	A	D	3000	80	II	no		>> 435157
50	6200	124	A	D	4000	80	II	no		>> 435218

SKVER LED F

Rated power of the luminaire [W]*	Luminous flux [lm]*	Luminous efficacy [lm/W]	Version	Energy efficiency class	Colour temperature [K]	Colour rendering index	Electrical protection class	Optics	DIMM DALI	Index
19	2500	132	F	D	3000	80	II	RM7	yes	>> 435225
19	2600	137	F	C	4000	80	II	RM7	yes	>> 435287
26	3400	131	F	D	3000	80	II	RM7	yes	>> 435232
26	3600	138	F	C	4000	80	II	RM7	yes	>> 435294
33	4200	127	F	D	3000	80	II	RM7	yes	>> 435249
33	4450	135	F	D	4000	80	II	RM7	yes	>> 435300
39	5000	128	F	D	3000	80	II	RM7	yes	>> 435256
39	5250	135	F	D	4000	80	II	RM7	yes	>> 435317
44	5600	127	F	D	3000	80	II	RM7	yes	>> 435263
44	5900	134	F	D	4000	80	II	RM7	yes	>> 435324
50	6350	127	F	D	3000	80	II	RM7	yes	>> 435270
50	6700	134	F	D	4000	80	II	RM7	yes	>> 435331

SKVER LED L

Rated power of the luminaire [W]*	Luminous flux [lm]*	Luminous efficacy [lm/W]	Version	Energy efficiency class	Colour temperature [K]	Colour rendering index	Electrical protection class	Optics	DIMM DALI	Index
19	2500	132	L	D	3000	80	II	RM7	yes	>> 435348
19	2600	137	L	C	4000	80	II	RM7	yes	>> 435409
26	3400	131	L	D	3000	80	II	RM7	yes	>> 435355

SKVER LED

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Luminous efficacy [lm/W]	Version	Energy efficiency class	Colour temperature [K]	Colour rendering index	Electrical protection class	Optics	DIMM DALI	Index
26	3600	138	L	C	4000	80	II	RM7	yes	>> 435416
33	4200	127	L	D	3000	80	II	RM7	yes	>> 435362
33	4450	135	L	D	4000	80	II	RM7	yes	>> 435423
39	5000	128	L	D	3000	80	II	RM7	yes	>> 435379
39	5250	135	L	D	4000	80	II	RM7	yes	>> 435430
44	5600	127	L	D	3000	80	II	RM7	yes	>> 435386
44	5900	134	L	D	4000	80	II	RM7	yes	>> 435447
50	6350	127	L	D	3000	80	II		yes	>> 435393
50	6650	133	L	D	4000	80	II	RM7	yes	>> 435454

SKVER LED

GENERAL CARD

SKVER S L 7100lm 840 RM7 IP66 II kl. DALI ZG B 0 (50W)	
Model SKVER S SKVER M	Luminaire power [W] Value in [W] in steps of 1 W
Version A Non-accessible interior F Tool free accessible interior L Tool free accessible interior with knife disconnect	Accessories 0 Without aperture 1 With aperture no. 1 2 With aperture no. 2
Luminous flux [lm] Value in [lm] in steps of 25 lux	Body colour B Black G Grey W White
CRI/CCT 730, 740, 750, 757, 830, 840 , 850, 857	Socket BLANK = No socket ZG Zhaga (ZhagaBook 18)
Optics ASM, ASM2, AS N, ASW, ASW2, PL 1, PP1, PP1L, RM1 0, RM1 1, RM11+, RM12, RM 13, RM 14, RM1 5, RM1 6, RM16L, RM1 7, RM1 8, RM18+, RM 19, RM 3, RM3L, RM 4, RM4L, RM 5, RM 6, RM7 , RM7L, RM 8, RM8+, RM 9, RMW, RN1, RN2, RN 3, RP, RW2, RW2L, RW 3, RW 4, RW 5, RW 6, RW 7, RW8, RW9, RM1, RM2, RM2 0, RM20+, RM 21, RM22, RM2 3, RM 24, RM2 5, RM 26, RM 27, RM2 8, RM 29, RM30	Control 1DIM DALI
IP IP66	Protection class II kl.

The Skver LED luminaire is available in 6 types:

A version: pole mounting, basic version with omnidirectional light distribution.

F version: pole mounting, tool-free access to the internal chamber, available with omnidirectional light distribution and directed light distribution.

L version: pole mounting, tool-free access to the luminaire chamber, quick tool-free replacement of the integrated module, available with omnidirectional and directed light distribution.

R version: suspended mounting, tool-free access to the luminaire chamber, quick tool-free replacement of the integrated module, available with omnidirectional and directed light distribution.


W version: suspended installation on cables, tool-free access to the luminaire chamber, quick tool-free replacement of the integrated module, available with omnidirectional and directed light distribution.

Z version: assembly depending on the accessory used, tool-free access to the housing chamber, quick tool-free replacement of the integrated module.

Card creation date: 21 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 49/2024



Pole mounted luminaires

The Skver park and urban luminaires combine high light efficiency and unprecedented functionality with innovative, modular design.

This feature allows for easy and quick implementation of structural and visual changes in the luminaire.

Backshield

The luminaire can be equipped with a backshield, which prevents the light from spreading in unwanted directions.

Pole mounted luminaires

Skver Bespoke road luminaires provide a one-of-a-kind solution, showcasing our dedication to meeting the unique needs of our customers.

Bespoke version - Example 6

The Skver LED luminaire with a flower-shaped hood not only provides effective lighting, but also adds a touch of charm and aesthetics to urban streets, creating a pleasant atmosphere.

