

LINEA S LED ECO

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK03
Rated power of the luminaire [W]*:	7.00 - 143.00
Luminous flux [lm]*:	1000 - 25600
Colour temperature [K]:	4000
Energy efficiency class:	A; B; C
Material of the body:	coated steel
Colour of the body:	RAL9010
Diffuser material:	PC
Diffuser type:	matrix led
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	588/53/54; 1176/53/54; 1764/53/54; 2940/53/54; 3528/53/54
HACCP:	852/2004

CHARACTERISTICS

Linea S LED Eco is a surface-mounted and pendant light-line system, representing a new generation of luminaires dedicated to LED technology. The design used allows for easy installation and power connection. The steel body, designed from the ground up, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. The ECO version is dedicated to investments where the length of individual light lines supplied from a single cable (not including modules with bezels and not including current protection) does not exceed 40m. The light modules are permanently connected to the carrier modules using dedicated cubes. The optics used in the other luminaires of the LINEA S family are possible.

APPLICATION

A versatile led lamp for indoor use, particularly suitable for lighting large-scale commercial buildings, possibly on production and storage halls.

LINEA S LED ECO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Linea S LED Eco 1

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
7	4000	1000	105		588/53/54	>> 594069
7	4000	1000	105	yes	588/53/54	>> 594076
7	4000	1100	120		588/53/54	>> 594021
7	4000	1100	120	yes	588/53/54	>> 594038
25	4000	3850	105		588/53/54	>> 594045
25	4000	3850	105	yes	588/53/54	>> 594052
25	4000	4250	120		588/53/54	>> 594007
25	4000	4250	120	yes	588/53/54	>> 594014

Linea S LED Eco 2

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
13	4000	1900	105		1176/53/54	>> 594144
13	4000	1900	105	yes	1176/53/54	>> 594151
13	4000	2100	120		1176/53/54	>> 594106
13	4000	2100	120	yes	1176/53/54	>> 594113
50	4000	7450	105		1176/53/54	>> 594120
50	4000	7450	105	yes	1176/53/54	>> 594137
50	4000	8150	120		1176/53/54	>> 594083
50	4000	8150	120	yes	1176/53/54	>> 594090

Linea S LED Eco 3

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
21	4000	3350	105		1764/53/54	>> 594229
21	4000	3350	105	yes	1764/53/54	>> 594236
21	4000	3650	120		1764/53/54	>> 594182
21	4000	3650	120	yes	1764/53/54	>> 594199
75	4000	11950	105		1764/53/54	>> 594205
75	4000	11950	105	yes	1764/53/54	>> 594212
75	4000	13100	120		1764/53/54	>> 594168
75	4000	13100	120	yes	1764/53/54	>> 594175

Linea S LED Eco 4

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
31	4000	5200	105		2940/53/54	>> 594304
31	4000	5200	105	yes	2940/53/54	>> 594311

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
31	4000	5700	120		2940/53/54	>> 594267
31	4000	5700	120	yes	2940/53/54	>> 594274
111	4000	18250	105		2940/53/54	>> 594281
111	4000	18250	105	yes	2940/53/54	>> 594298
111	4000	20000	120		2940/53/54	>> 594243
111	4000	20000	120	yes	2940/53/54	>> 594250


Linea S LED Eco 5

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
37	4000	6200	105		3528/53/54	>> 594380
37	4000	6200	105	yes	3528/53/54	>> 594397
37	4000	6800	120		3528/53/54	>> 594342
37	4000	6800	120	yes	3528/53/54	>> 594359
143	4000	23350	105		3528/53/54	>> 594366
143	4000	23350	105	yes	3528/53/54	>> 594373
143	4000	25600	120		3528/53/54	>> 594328
143	4000	25600	120	yes	3528/53/54	>> 594335


LINEA S LED ECO

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



105D



120D

LINEA S LED ECO

GENERAL CARD

ACCESSORIES AVAILABLE


index	Name
981173	LINEA S LED hang 1.5m
594465	LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm DALI zoom 22-55st. White 840 20W
980077	LINEA S LED hang 3m
981425	LINEA S LED chain pendant
594472	LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm zoom 22-55st. White 840 20W
981418	LINEA S LED pendant sm 1.5
594458	LINEA S LED ECO 588mm 260lm AW DOT CS 2W 1h NM AT
980961	LINEA S LED pendant sm 3m
980954	Linea S LED surface mount bracket
594403	LINEA S LED ECO - metal cover 588mm
594410	LINEA S LED ECO - metal cover 1176mm
594427	LINEA S LED ECO - metal cover 1764mm
594434	LINEA S LED ECO - metal cover 2940mm
594441	LINEA S LED ECO - metal cover 3528mm
594496	LINEA S LED ECO - metal cover 588mm DALI
594502	LINEA S LED ECO - metal cover 1176mm DALI
594519	LINEA S LED ECO - metal cover 1764mm DALI
594526	LINEA S LED ECO - metal cover 2940mm DALI
594533	LINEA S LED ECO - metal cover 3528mm DALI
594489	LINEA S LED ECO - termination set

LINEA S LED ECO

GENERAL CARD




LINEA S LED hang 1.5m (981173)




LINEA S LED ECO 588mm - 1xEXPO
ADJUST 2050lm DALI zoom 22-55st.
White 840 20W (594465)



LINEA S LED chain pendant (981425)



LINEA S LED ECO 588mm - 1xEXPO
ADJUST 2050lm zoom 22-55st. White
840 20W (594472)



LINEA S LED ECO 588mm 260lm AW
DOT CS 2W 1h NM AT (594458)



Linea S LED surface mount
bracket (980954)

Card creation date: 07 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 62/2024