LINEA S LED ECO

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK03
Rated power of the luminaire [W]*:	7.00 - 143.00
Luminous flux [lm]*:	1000 - 25600
Colour temperature [K]:	4000
Energy efficiency class:	A; B; C
Material of the body:	coated steel
Colour of the body:	RAL9010
Diffuser material:	PC
Diffuser type:	matrix led
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	588/53/54; 1176/53/54; 1764/53/54; 2940/53/54; 3528/53/54
HACCP:	852/2004
ENEC Certificate:	0331/ENEC/23

CHARACTERISTICS

Linea S LED Eco is a surface-mounted and pendant light-line system, representing a new generation of luminaires dedicated to LED technology. The design used allows for easy installation and power connection. The steel body, designed from the ground up, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. The ECO version is dedicated to investments where the length of individual light lines supplied from a single cable (not including modules with bezels and not including current protection) does not exceed 40m. The light modules are permanently connected to the carrier modules using dedicated cubes. The optics used in the other luminaires of the LINEA S family are possible.

APPLICATION

A versatile led lamp for indoor use, particularly suitable for lighting large-scale commercial buildings, possibly on production and storage halls.

LINEA S LED ECO

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Linea S LED Eco

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
8	4000	1150	C			MW MAT R2	R2	588/53/54	>> 155529/2
8	4000	1150	C	yes		MW MAT R2	R2	588/53/54	>> 155680/2
8	4000	1150	C			SA-L MAT R2	R2	588/53/54	>> 255946/2
8	4000	1150	C	yes		SA-L MAT R2	R2	588/53/54	>> 256127/2
8	4000	1150	C			SA MAT R2	R2	588/53/54	>> 198946/2
8	4000	1150	C	yes		SA MAT R2	R2	588/53/54	>> 200113/2
8	4000	1150	C			SW MAT R2	R2	588/53/54	>> 160448/2
8	4000	1150	C	yes		SW MAT R2	R2	588/53/54	>> 160615/2
8	4000	1150	C			VW MAT R2	R2	588/53/54	>> 166273/2
8	4000	1150	C	yes		VW MAT R2	R2	588/53/54	>> 166464/2
8	4000	1200	C			DAN MAT R2	R2	588/53/54	>> 204746/2
8	4000	1200	C	yes		DAN MAT R2	R2	588/53/54	>> 204906/2
10	4000	1450	C			MW MAT R2	R2	588/53/54	>> 155536/2
10	4000	1450	C	yes		MW MAT R2	R2	588/53/54	>> 155697/2
10	4000	1450	C			SA-L MAT R2	R2	588/53/54	>> 255953/2
10	4000	1450	C	yes		SA-L MAT R2	R2	588/53/54	>> 256134/2
10	4000	1450	C			SA MAT R2	R2	588/53/54	>> 198953/2
10	4000	1450	C	yes		SA MAT R2	R2	588/53/54	>> 200120/2
10	4000	1450	C			SW MAT R2	R2	588/53/54	>> 160455/2
10	4000	1450	C	yes		SW MAT R2	R2	588/53/54	>> 160622/2
10	4000	1450	C			VW MAT R2	R2	588/53/54	>> 166280/2
10	4000	1450	C	yes		VW MAT R2	R2	588/53/54	>> 166471/2
10	4000	1500	C			DAN MAT R2	R2	588/53/54	>> 204753/2
10	4000	1500	C	yes		DAN MAT R2	R2	588/53/54	>> 204913/2
12	4000	1700	C			MW MAT R2	R2	588/53/54	>> 155543/2
12	4000	1700	C	yes		MW MAT R2	R2	588/53/54	>> 155703/2
12	4000	1700	C			SW MAT R2	R2	588/53/54	>> 160462/2
12	4000	1700	C	yes		SW MAT R2	R2	588/53/54	>> 160639/2
12	4000	1700	C			VW MAT R2	R2	588/53/54	>> 166297/2
12	4000	1700	C	yes		VW MAT R2	R2	588/53/54	>> 166488/2
12	4000	1750	C			DAN MAT R2	R2	588/53/54	>> 204760/2
12	4000	1750	C	yes		DAN MAT R2	R2	588/53/54	>> 204920/2
12	4000	1750	C			SA-L MAT R2	R2	588/53/54	>> 255960/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
12	4000	1750	C	yes		SA-L MAT R2	R2	588/53/54	>> 256141/2
12	4000	1750	C			SA MAT R2	R2	588/53/54	>> 198960/2
12	4000	1750	C	yes		SA MAT R2	R2	588/53/54	>> 200182/2
13	4000	1950	C			MW MAT R2	R2	588/53/54	>> 155550/2
13	4000	1950	C	yes		MW MAT R2	R2	588/53/54	>> 155710/2
13	4000	1950	C			SA-L MAT R2	R2	588/53/54	>> 255977/2
13	4000	1950	C	yes		SA-L MAT R2	R2	588/53/54	>> 256158/2
13	4000	1950	C			SA MAT R2	R2	588/53/54	>> 198977/2
13	4000	1950	C	yes		SA MAT R2	R2	588/53/54	>> 200199/2
13	4000	1950	C			SW MAT R2	R2	588/53/54	>> 160479/2
13	4000	1950	C	yes		SW MAT R2	R2	588/53/54	>> 160646/2
13	4000	1950	C			VW MAT R2	R2	588/53/54	>> 166334/2
13	4000	1950	C	yes		VW MAT R2	R2	588/53/54	>> 166495/2
13	4000	2000	C			DAN MAT R2	R2	588/53/54	>> 204777/2
13	4000	2000	C	yes		DAN MAT R2	R2	588/53/54	>> 204937/2
16	4000	2450	C			MW MAT R2	R2	588/53/54	>> 155512/2
16	4000	2450	C	yes		MW MAT R2	R2	588/53/54	>> 155673/2
16	4000	2450	C			SA-L MAT R2	R2	588/53/54	>> 255939/2
16	4000	2450	C	yes		SA-L MAT R2	R2	588/53/54	>> 256110/2
16	4000	2450	C			SA MAT R2	R2	588/53/54	>> 198939/2
16	4000	2450	C	yes		SA MAT R2	R2	588/53/54	>> 200106/2
16	4000	2450	C			SW MAT R2	R2	588/53/54	>> 160431/2
16	4000	2450	C	yes		SW MAT R2	R2	588/53/54	>> 160608/2
16	4000	2450	C			VW MAT R2	R2	588/53/54	>> 166266/2
16	4000	2450	C	yes		VW MAT R2	R2	588/53/54	>> 166457/2
16	4000	2500	C			DAN MAT R2	R2	588/53/54	>> 204739/2
16	4000	2500	C	yes		DAN MAT R2	R2	588/53/54	>> 204890/2
17	4000	2450	C			MW MAT R2	R2	1176/53/54	>> 155604/2
17	4000	2450	C	yes		MW MAT R2	R2	1176/53/54	>> 155765/2
17	4000	2450	C			SA-L MAT R2	R2	1176/53/54	>> 256028/2
17	4000	2450	C	yes		SA-L MAT R2	R2	1176/53/54	>> 256257/2
17	4000	2450	C			SA MAT R2	R2	1176/53/54	>> 200038/2
17	4000	2450	C	yes		SA MAT R2	R2	1176/53/54	>> 200243/2
17	4000	2450	C			SW MAT R2	R2	1176/53/54	>> 160530/2
17	4000	2450	C	yes		SW MAT R2	R2	1176/53/54	>> 160691/2
17	4000	2450	C			VW MAT R2	R2	1176/53/54	>> 166389/2
17	4000	2450	C	yes		VW MAT R2	R2	1176/53/54	>> 166549/2
17	4000	2500	C			DAN MAT R2	R2	1176/53/54	>> 204821/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
17	4000	2500	C	yes		DAN MAT R2	R2	1176/53/54	>> 204982/2
20	4000	3000	C			MW MAT R2	R2	588/53/54	>> 155505/2
20	4000	3000	C	yes		MW MAT R2	R2	588/53/54	>> 155666/2
20	4000	3000	C			SW MAT R2	R2	588/53/54	>> 160424/2
20	4000	3000	C	yes		SW MAT R2	R2	588/53/54	>> 160592/2
20	4000	3000	C			VW MAT R2	R2	588/53/54	>> 166259/2
20	4000	3000	C	yes		VW MAT R2	R2	588/53/54	>> 166440/2
20	4000	3050	C			SA-L MAT R2	R2	588/53/54	>> 255922/2
20	4000	3050	C	yes		SA-L MAT R2	R2	588/53/54	>> 256103/2
20	4000	3050	C			SA MAT R2	R2	588/53/54	>> 198922/2
20	4000	3050	C	yes		SA MAT R2	R2	588/53/54	>> 200090/2
20	4000	3100	C			DAN MAT R2	R2	588/53/54	>> 204722/2
20	4000	3100	C	yes		DAN MAT R2	R2	588/53/54	>> 204883/2
21	4000	3050	C			MW MAT R2	R2	1176/53/54	>> 155611/2
21	4000	3050	C	yes		MW MAT R2	R2	1176/53/54	>> 155772/2
21	4000	3050	C			SW MAT R2	R2	1176/53/54	>> 160547/2
21	4000	3050	C	yes		SW MAT R2	R2	1176/53/54	>> 160707/2
21	4000	3050	C			VW MAT R2	R2	1176/53/54	>> 166396/2
21	4000	3050	C	yes		VW MAT R2	R2	1176/53/54	>> 166556/2
21	4000	3100	C			SA-L MAT R2	R2	1176/53/54	>> 256035/2
21	4000	3100	C	yes		SA-L MAT R2	R2	1176/53/54	>> 256264/2
21	4000	3100	C			SA MAT R2	R2	1176/53/54	>> 200045/2
21	4000	3100	C	yes		SA MAT R2	R2	1176/53/54	>> 200250/2
21	4000	3150	C			DAN MAT R2	R2	1176/53/54	>> 204838/2
21	4000	3150	C	yes		DAN MAT R2	R2	1176/53/54	>> 204999/2
23	4000	3500	C			MW MAT R2	R2	588/53/54	>> 155499/2
23	4000	3500	C	yes		MW MAT R2	R2	588/53/54	>> 155659/2
23	4000	3500	C			SA-L MAT R2	R2	588/53/54	>> 255915/2
23	4000	3500	C	yes		SA-L MAT R2	R2	588/53/54	>> 256097/2
23	4000	3500	C			SA MAT R2	R2	588/53/54	>> 198915/2
23	4000	3500	C	yes		SA MAT R2	R2	588/53/54	>> 200083/2
23	4000	3500	C			SW MAT R2	R2	588/53/54	>> 160417/2
23	4000	3500	C	yes		SW MAT R2	R2	588/53/54	>> 160585/2
23	4000	3500	C			VW MAT R2	R2	588/53/54	>> 166242/2
23	4000	3500	C	yes		VW MAT R2	R2	588/53/54	>> 166433/2
23	4000	3600	C			DAN MAT R2	R2	588/53/54	>> 204715/2
23	4000	3600	C	yes		DAN MAT R2	R2	588/53/54	>> 204876/2
23	4000	3750	B			MW MAT R2	R2	1764/53/54	>> 155802/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
23	4000	3750	B	yes		MW MAT R2	R2	1764/53/54	>> 155840/2
23	4000	3750	B			SW MAT R2	R2	1764/53/54	>> 160738/2
23	4000	3750	B	yes		SW MAT R2	R2	1764/53/54	>> 160776/2
23	4000	3750	B			VW MAT R2	R2	1764/53/54	>> 166587/2
23	4000	3750	B	yes		VW MAT R2	R2	1764/53/54	>> 166624/2
23	4000	3800	B			SA-L MAT R2	R2	1764/53/54	>> 256295/2
23	4000	3800	B	yes		SA-L MAT R2	R2	1764/53/54	>> 256332/2
23	4000	3800	B			SA MAT R2	R2	1764/53/54	>> 200281/2
23	4000	3800	B	yes		SA MAT R2	R2	1764/53/54	>> 200328/2
23	4000	3900	B			DAN MAT R2	R2	1764/53/54	>> 207044/2
23	4000	3900	B	yes		DAN MAT R2	R2	1764/53/54	>> 207082/2
25	4000	3600	C			MW MAT R2	R2	1176/53/54	>> 155628/2
25	4000	3600	C	yes		MW MAT R2	R2	1176/53/54	>> 155789/2
25	4000	3600	C			SW MAT R2	R2	1176/53/54	>> 160554/2
25	4000	3600	C	yes		SW MAT R2	R2	1176/53/54	>> 160714/2
25	4000	3600	C			VW MAT R2	R2	1176/53/54	>> 166402/2
25	4000	3600	C	yes		VW MAT R2	R2	1176/53/54	>> 166563/2
25	4000	3650	C			SA-L MAT R2	R2	1176/53/54	>> 256042/2
25	4000	3650	C	yes		SA-L MAT R2	R2	1176/53/54	>> 256271/2
25	4000	3650	C			SA MAT R2	R2	1176/53/54	>> 200052/2
25	4000	3650	C	yes		SA MAT R2	R2	1176/53/54	>> 200267/2
25	4000	3750	C			DAN MAT R2	R2	1176/53/54	>> 204845/2
25	4000	3750	C	yes		DAN MAT R2	R2	1176/53/54	>> 207020/2
25	4000	4000	B			MW MAT R2	R2	588/53/54	>> 155482/2
25	4000	4000	B	yes		MW MAT R2	R2	588/53/54	>> 155642/2
25	4000	4000	B			SW MAT R2	R2	588/53/54	>> 160400/2
25	4000	4000	B	yes		SW MAT R2	R2	588/53/54	>> 160578/2
25	4000	4000	B			VW MAT R2	R2	588/53/54	>> 166235/2
25	4000	4000	B	yes		VW MAT R2	R2	588/53/54	>> 166426/2
25	4000	4050	B			SA-L MAT R2	R2	588/53/54	>> 255908/2
25	4000	4050	B	yes		SA-L MAT R2	R2	588/53/54	>> 256080/2
25	4000	4050	B			SA MAT R2	R2	588/53/54	>> 198908/2
25	4000	4050	B	yes		SA MAT R2	R2	588/53/54	>> 200076/2
25	4000	4150	B			DAN MAT R2	R2	588/53/54	>> 204708/2
25	4000	4150	B	yes		DAN MAT R2	R2	588/53/54	>> 204869/2
28	4000	4650	B			MW MAT R2	R2	1764/53/54	>> 155819/2
28	4000	4650	B	yes		MW MAT R2	R2	1764/53/54	>> 155857/2
28	4000	4650	B			SW MAT R2	R2	1764/53/54	>> 160745/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
28	4000	4650	B	yes		SW MAT R2	R2	1764/53/54	>> 160783/2
28	4000	4650	B			VW MAT R2	R2	1764/53/54	>> 166594/2
28	4000	4650	B	yes		VW MAT R2	R2	1764/53/54	>> 166631/2
28	4000	4700	B			SA-L MAT R2	R2	1764/53/54	>> 256301/2
28	4000	4700	B	yes		SA-L MAT R2	R2	1764/53/54	>> 256349/2
28	4000	4700	B			SA MAT R2	R2	1764/53/54	>> 200298/2
28	4000	4700	B	yes		SA MAT R2	R2	1764/53/54	>> 200335/2
28	4000	4850	B			DAN MAT R2	R2	1764/53/54	>> 207051/2
28	4000	4850	B	yes		DAN MAT R2	R2	1764/53/54	>> 207099/2
29	4000	4200	C			MW MAT R2	R2	1176/53/54	>> 155635/2
29	4000	4200	C	yes		MW MAT R2	R2	1176/53/54	>> 155796/2
29	4000	4200	C			SW MAT R2	R2	1176/53/54	>> 160561/2
29	4000	4200	C	yes		SW MAT R2	R2	1176/53/54	>> 160721/2
29	4000	4200	C			VW MAT R2	R2	1176/53/54	>> 166419/2
29	4000	4200	C	yes		VW MAT R2	R2	1176/53/54	>> 166570/2
29	4000	4250	C			SA-L MAT R2	R2	1176/53/54	>> 256073/2
29	4000	4250	C	yes		SA-L MAT R2	R2	1176/53/54	>> 256288/2
29	4000	4250	C			SA MAT R2	R2	1176/53/54	>> 200069/2
29	4000	4250	C	yes		SA MAT R2	R2	1176/53/54	>> 200274/2
29	4000	4350	C			DAN MAT R2	R2	1176/53/54	>> 204852/2
29	4000	4350	C	yes		DAN MAT R2	R2	1176/53/54	>> 207037/2
29	4000	4650	B			MW MAT R2	R2	1176/53/54	>> 155598/2
29	4000	4650	B	yes		MW MAT R2	R2	1176/53/54	>> 155758/2
29	4000	4650	B			SW MAT R2	R2	1176/53/54	>> 160523/2
29	4000	4650	B	yes		SW MAT R2	R2	1176/53/54	>> 160684/2
29	4000	4650	B			VW MAT R2	R2	1176/53/54	>> 166372/2
29	4000	4650	B	yes		VW MAT R2	R2	1176/53/54	>> 166532/2
29	4000	4700	B			SA-L MAT R2	R2	1176/53/54	>> 256011/2
29	4000	4700	B	yes		SA-L MAT R2	R2	1176/53/54	>> 256240/2
29	4000	4700	B			SA MAT R2	R2	1176/53/54	>> 200021/2
29	4000	4700	B	yes		SA MAT R2	R2	1176/53/54	>> 200236/2
29	4000	4850	B			DAN MAT R2	R2	1176/53/54	>> 204814/2
29	4000	4850	B	yes		DAN MAT R2	R2	1176/53/54	>> 204975/2
33	4000	5700	B			MW MAT R2	R2	2940/53/54	>> 155956/2
33	4000	5700	B	yes		MW MAT R2	R2	2940/53/54	>> 156045/2
33	4000	5700	B			SW MAT R2	R2	2940/53/54	>> 160882/2
33	4000	5700	B	yes		SW MAT R2	R2	2940/53/54	>> 160967/2
33	4000	5700	B			VW MAT R2	R2	2940/53/54	>> 166730/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
33	4000	5700	B	yes		VW MAT R2	R2	2940/53/54	>> 166815/2
33	4000	5800	B			SA-L MAT R2	R2	2940/53/54	>> 256448/2
33	4000	5800	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256530/2
33	4000	5800	B			SA MAT R2	R2	2940/53/54	>> 200434/2
33	4000	5800	B	yes		SA MAT R2	R2	2940/53/54	>> 200519/2
33	4000	5900	A			DAN MAT R2	R2	2940/53/54	>> 207198/2
33	4000	5900	A	yes		DAN MAT R2	R2	2940/53/54	>> 207273/2
34	4000	5600	B			MW MAT R2	R2	1764/53/54	>> 155826/2
34	4000	5600	B	yes		MW MAT R2	R2	1764/53/54	>> 155864/2
34	4000	5600	B			SW MAT R2	R2	1764/53/54	>> 160752/2
34	4000	5600	B	yes		SW MAT R2	R2	1764/53/54	>> 160790/2
34	4000	5600	B			VW MAT R2	R2	1764/53/54	>> 166600/2
34	4000	5600	B	yes		VW MAT R2	R2	1764/53/54	>> 166648/2
34	4000	5700	B			SA-L MAT R2	R2	1764/53/54	>> 256318/2
34	4000	5700	B	yes		SA-L MAT R2	R2	1764/53/54	>> 256356/2
34	4000	5700	B			SA MAT R2	R2	1764/53/54	>> 200304/2
34	4000	5700	B	yes		SA MAT R2	R2	1764/53/54	>> 200342/2
34	4000	5800	B			DAN MAT R2	R2	1764/53/54	>> 207068/2
34	4000	5800	B	yes		DAN MAT R2	R2	1764/53/54	>> 207105/2
36	4000	5850	B			MW MAT R2	R2	1176/53/54	>> 155581/2
36	4000	5850	B	yes		MW MAT R2	R2	1176/53/54	>> 155741/2
36	4000	5850	B			SW MAT R2	R2	1176/53/54	>> 160516/2
36	4000	5850	B	yes		SW MAT R2	R2	1176/53/54	>> 160677/2
36	4000	5850	B			VW MAT R2	R2	1176/53/54	>> 166365/2
36	4000	5850	B	yes		VW MAT R2	R2	1176/53/54	>> 166525/2
36	4000	5900	B			SA-L MAT R2	R2	1176/53/54	>> 256004/2
36	4000	5900	B	yes		SA-L MAT R2	R2	1176/53/54	>> 256233/2
36	4000	5900	B			SA MAT R2	R2	1176/53/54	>> 200014/2
36	4000	5900	B	yes		SA MAT R2	R2	1176/53/54	>> 200229/2
36	4000	6050	B			DAN MAT R2	R2	1176/53/54	>> 204807/2
36	4000	6050	B	yes		DAN MAT R2	R2	1176/53/54	>> 204968/2
39	4000	6550	B			MW MAT R2	R2	1764/53/54	>> 155833/2
39	4000	6550	B	yes		MW MAT R2	R2	1764/53/54	>> 155871/2
39	4000	6550	B			SW MAT R2	R2	1764/53/54	>> 160769/2
39	4000	6550	B	yes		SW MAT R2	R2	1764/53/54	>> 160806/2
39	4000	6550	B			VW MAT R2	R2	1764/53/54	>> 166617/2
39	4000	6550	B	yes		VW MAT R2	R2	1764/53/54	>> 166655/2
39	4000	6600	B			SA-L MAT R2	R2	1764/53/54	>> 256325/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
39	4000	6600	B	yes		SA-L MAT R2	R2	1764/53/54	>> 256363/2
39	4000	6600	B			SA MAT R2	R2	1764/53/54	>> 200311/2
39	4000	6600	B	yes		SA MAT R2	R2	1764/53/54	>> 200359/2
39	4000	6750	B			DAN MAT R2	R2	1764/53/54	>> 207075/2
39	4000	6750	B	yes		DAN MAT R2	R2	1764/53/54	>> 207112/2
40	4000	6900	B			MW MAT R2	R2	3528/53/54	>> 156137/2
40	4000	6900	B	yes		MW MAT R2	R2	3528/53/54	>> 156175/2
40	4000	6900	B			SW MAT R2	R2	3528/53/54	>> 161063/2
40	4000	6900	B	yes		SW MAT R2	R2	3528/53/54	>> 161131/2
40	4000	6900	B			VW MAT R2	R2	3528/53/54	>> 166907/2
40	4000	6900	B	yes		VW MAT R2	R2	3528/53/54	>> 166945/2
40	4000	7000	B			SA-L MAT R2	R2	3528/53/54	>> 258138/2
40	4000	7000	B	yes		SA-L MAT R2	R2	3528/53/54	>> 258176/2
40	4000	7000	B			SA-R MAT R2	R2	3528/53/54	>> 200601/2
40	4000	7000	B	yes		SA-R MAT R2	R2	3528/53/54	>> 200649/2
40	4000	7150	A			DAN MAT R2	R2	3528/53/54	>> 207365/2
40	4000	7150	A	yes		DAN MAT R2	R2	3528/53/54	>> 207402/2
41	4000	6600	B			MW MAT R2	R2	1176/53/54	>> 155574/2
41	4000	6600	B	yes		MW MAT R2	R2	1176/53/54	>> 155734/2
41	4000	6600	B			SW MAT R2	R2	1176/53/54	>> 160493/2
41	4000	6600	B	yes		SW MAT R2	R2	1176/53/54	>> 160660/2
41	4000	6600	B			VW MAT R2	R2	1176/53/54	>> 166358/2
41	4000	6600	B	yes		VW MAT R2	R2	1176/53/54	>> 166518/2
41	4000	6650	B			SA-L MAT R2	R2	1176/53/54	>> 255991/2
41	4000	6650	B	yes		SA-L MAT R2	R2	1176/53/54	>> 256226/2
41	4000	6650	B			SA MAT R2	R2	1176/53/54	>> 198991/2
41	4000	6650	B	yes		SA MAT R2	R2	1176/53/54	>> 200212/2
41	4000	6800	B			DAN MAT R2	R2	1176/53/54	>> 204791/2
41	4000	6800	B	yes		DAN MAT R2	R2	1176/53/54	>> 204951/2
42	4000	7100	B			MW MAT R2	R2	2940/53/54	>> 155963/2
42	4000	7100	B	yes		MW MAT R2	R2	2940/53/54	>> 156052/2
42	4000	7100	B			SW MAT R2	R2	2940/53/54	>> 160899/2
42	4000	7100	B	yes		SW MAT R2	R2	2940/53/54	>> 160974/2
42	4000	7100	B			VW MAT R2	R2	2940/53/54	>> 166747/2
42	4000	7100	B	yes		VW MAT R2	R2	2940/53/54	>> 166822/2
42	4000	7150	B			SA-L MAT R2	R2	2940/53/54	>> 256455/2
42	4000	7150	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256547/2
42	4000	7150	B			SA MAT R2	R2	2940/53/54	>> 200441/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
42	4000	7150	B	yes		SA MAT R2	R2	2940/53/54	>> 200526/2
42	4000	7350	B			DAN MAT R2	R2	2940/53/54	>> 207204/2
42	4000	7350	B	yes		DAN MAT R2	R2	2940/53/54	>> 207280/2
45	4000	7550	B			MW MAT R2	R2	1764/53/54	>> 155437/2
45	4000	7550	B	yes		MW MAT R2	R2	1764/53/54	>> 155901/2
45	4000	7550	B			SW MAT R2	R2	1764/53/54	>> 158995/2
45	4000	7550	B	yes		SW MAT R2	R2	1764/53/54	>> 160837/2
45	4000	7550	B			VW MAT R2	R2	1764/53/54	>> 166181/2
45	4000	7550	B	yes		VW MAT R2	R2	1764/53/54	>> 166686/2
45	4000	7600	B			SA-L MAT R2	R2	1764/53/54	>> 255854/2
45	4000	7600	B	yes		SA-L MAT R2	R2	1764/53/54	>> 256394/2
45	4000	7600	B			SA MAT R2	R2	1764/53/54	>> 198847/2
45	4000	7600	B	yes		SA MAT R2	R2	1764/53/54	>> 200380/2
45	4000	7800	B			DAN MAT R2	R2	1764/53/54	>> 204654/2
45	4000	7800	B	yes		DAN MAT R2	R2	1764/53/54	>> 207143/2
49	4000	7650	C			MW MAT R2	R2	1176/53/54	>> 155567/2
49	4000	7650	C	yes		MW MAT R2	R2	1176/53/54	>> 155727/2
49	4000	7650	C			SW MAT R2	R2	1176/53/54	>> 160486/2
49	4000	7650	C	yes		SW MAT R2	R2	1176/53/54	>> 160653/2
49	4000	7650	C			VW MAT R2	R2	1176/53/54	>> 166341/2
49	4000	7650	C	yes		VW MAT R2	R2	1176/53/54	>> 166501/2
49	4000	7750	B			SA-L MAT R2	R2	1176/53/54	>> 255984/2
49	4000	7750	B	yes		SA-L MAT R2	R2	1176/53/54	>> 256165/2
49	4000	7750	B			SA MAT R2	R2	1176/53/54	>> 198984/2
49	4000	7750	B	yes		SA MAT R2	R2	1176/53/54	>> 200205/2
49	4000	7950	B			DAN MAT R2	R2	1176/53/54	>> 204784/2
49	4000	7950	B	yes		DAN MAT R2	R2	1176/53/54	>> 204944/2
50	4000	8500	B			MW MAT R2	R2	2940/53/54	>> 155970/2
50	4000	8500	B	yes		MW MAT R2	R2	2940/53/54	>> 156069/2
50	4000	8500	B			SW MAT R2	R2	2940/53/54	>> 160905/2
50	4000	8500	B	yes		SW MAT R2	R2	2940/53/54	>> 160981/2
50	4000	8500	B			VW MAT R2	R2	2940/53/54	>> 166754/2
50	4000	8500	B	yes		VW MAT R2	R2	2940/53/54	>> 166839/2
50	4000	8550	B			SA-L MAT R2	R2	2940/53/54	>> 256462/2
50	4000	8550	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256554/2
50	4000	8550	B			SA MAT R2	R2	2940/53/54	>> 200458/2
50	4000	8550	B	yes		SA MAT R2	R2	2940/53/54	>> 200533/2
50	4000	8600	B			MW MAT R2	R2	3528/53/54	>> 156144/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
50	4000	8600	B	yes		MW MAT R2	R2	3528/53/54	>> 156182/2
50	4000	8600	B			SW MAT R2	R2	3528/53/54	>> 161070/2
50	4000	8600	B	yes		SW MAT R2	R2	3528/53/54	>> 161148/2
50	4000	8600	B			VW MAT R2	R2	3528/53/54	>> 166914/2
50	4000	8600	B	yes		VW MAT R2	R2	3528/53/54	>> 166952/2
50	4000	8650	B			SA-L MAT R2	R2	3528/53/54	>> 258145/2
50	4000	8650	B	yes		SA-L MAT R2	R2	3528/53/54	>> 258183/2
50	4000	8650	B			SA-R MAT R2	R2	3528/53/54	>> 200618/2
50	4000	8650	B	yes		SA-R MAT R2	R2	3528/53/54	>> 200656/2
50	4000	8750	B			DAN MAT R2	R2	2940/53/54	>> 207211/2
50	4000	8750	B	yes		DAN MAT R2	R2	2940/53/54	>> 207297/2
50	4000	8850	B			DAN MAT R2	R2	3528/53/54	>> 207372/2
50	4000	8850	B	yes		DAN MAT R2	R2	3528/53/54	>> 207419/2
58	4000	9750	B			MW MAT R2	R2	2940/53/54	>> 155987/2
58	4000	9750	B	yes		MW MAT R2	R2	2940/53/54	>> 156076/2
58	4000	9750	B			SW MAT R2	R2	2940/53/54	>> 160912/2
58	4000	9750	B	yes		SW MAT R2	R2	2940/53/54	>> 160998/2
58	4000	9750	B			VW MAT R2	R2	2940/53/54	>> 166761/2
58	4000	9750	B	yes		VW MAT R2	R2	2940/53/54	>> 166846/2
58	4000	9850	B			SA-L MAT R2	R2	2940/53/54	>> 256479/2
58	4000	9850	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256561/2
58	4000	9850	B			SA MAT R2	R2	2940/53/54	>> 200465/2
58	4000	9850	B	yes		SA MAT R2	R2	2940/53/54	>> 200540/2
58	4000	10100	B			DAN MAT R2	R2	2940/53/54	>> 207228/2
58	4000	10100	B	yes		DAN MAT R2	R2	2940/53/54	>> 207303/2
61	4000	10300	B			MW MAT R2	R2	3528/53/54	>> 156151/2
61	4000	10300	B	yes		MW MAT R2	R2	3528/53/54	>> 156199/2
61	4000	10300	B			SW MAT R2	R2	3528/53/54	>> 161087/2
61	4000	10300	B	yes		SW MAT R2	R2	3528/53/54	>> 161155/2
61	4000	10300	B			VW MAT R2	R2	3528/53/54	>> 166921/2
61	4000	10300	B	yes		VW MAT R2	R2	3528/53/54	>> 166969/2
61	4000	10400	B			SA-L MAT R2	R2	3528/53/54	>> 258152/2
61	4000	10400	B	yes		SA-L MAT R2	R2	3528/53/54	>> 258190/2
61	4000	10400	B			SA-R MAT R2	R2	3528/53/54	>> 200625/2
61	4000	10400	B	yes		SA-R MAT R2	R2	3528/53/54	>> 200663/2
61	4000	10650	B			DAN MAT R2	R2	3528/53/54	>> 207389/2
61	4000	10650	B	yes		DAN MAT R2	R2	3528/53/54	>> 207426/2
62	4000	10250	B			MW MAT R2	R2	1764/53/54	>> 155420/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
62	4000	10250	B	yes		MW MAT R2	R2	1764/53/54	>> 155895/2
62	4000	10250	B			SW MAT R2	R2	1764/53/54	>> 158988/2
62	4000	10250	B	yes		SW MAT R2	R2	1764/53/54	>> 160820/2
62	4000	10250	B			VW MAT R2	R2	1764/53/54	>> 166174/2
62	4000	10250	B	yes		VW MAT R2	R2	1764/53/54	>> 166679/2
62	4000	10350	B			SA-L MAT R2	R2	1764/53/54	>> 255847/2
62	4000	10350	B	yes		SA-L MAT R2	R2	1764/53/54	>> 256387/2
62	4000	10350	B			SA MAT R2	R2	1764/53/54	>> 198830/2
62	4000	10350	B	yes		SA MAT R2	R2	1764/53/54	>> 200373/2
62	4000	10600	B			DAN MAT R2	R2	1764/53/54	>> 204647/2
62	4000	10600	B	yes		DAN MAT R2	R2	1764/53/54	>> 207136/2
63	4000	10800	B			MW MAT R2	R2	2940/53/54	>> 155949/2
63	4000	10800	B	yes		MW MAT R2	R2	2940/53/54	>> 156038/2
63	4000	10800	B			SW MAT R2	R2	2940/53/54	>> 160875/2
63	4000	10800	B	yes		SW MAT R2	R2	2940/53/54	>> 160950/2
63	4000	10800	B			VW MAT R2	R2	2940/53/54	>> 166723/2
63	4000	10800	B	yes		VW MAT R2	R2	2940/53/54	>> 166808/2
63	4000	10950	B			SA-L MAT R2	R2	2940/53/54	>> 256431/2
63	4000	10950	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256516/2
63	4000	10950	B			SA MAT R2	R2	2940/53/54	>> 200427/2
63	4000	10950	B	yes		SA MAT R2	R2	2940/53/54	>> 200502/2
63	4000	11200	B			DAN MAT R2	R2	2940/53/54	>> 207181/2
63	4000	11200	B	yes		DAN MAT R2	R2	2940/53/54	>> 207266/2
71	4000	11900	B			MW MAT R2	R2	3528/53/54	>> 156168/2
71	4000	11900	B	yes		MW MAT R2	R2	3528/53/54	>> 156205/2
71	4000	11900	B			SW MAT R2	R2	3528/53/54	>> 161094/2
71	4000	11900	B	yes		SW MAT R2	R2	3528/53/54	>> 161162/2
71	4000	11900	B			VW MAT R2	R2	3528/53/54	>> 166938/2
71	4000	11900	B	yes		VW MAT R2	R2	3528/53/54	>> 166976/2
71	4000	12050	B			SA-L MAT R2	R2	3528/53/54	>> 258169/2
71	4000	12050	B	yes		SA-L MAT R2	R2	3528/53/54	>> 258237/2
71	4000	12050	B			SA-R MAT R2	R2	3528/53/54	>> 200632/2
71	4000	12050	B	yes		SA-R MAT R2	R2	3528/53/54	>> 200670/2
71	4000	12300	B			DAN MAT R2	R2	3528/53/54	>> 207396/2
71	4000	12300	B	yes		DAN MAT R2	R2	3528/53/54	>> 207433/2
75	4000	12300	B			MW MAT R2	R2	1764/53/54	>> 155413/2
75	4000	12300	B	yes		MW MAT R2	R2	1764/53/54	>> 155888/2
75	4000	12300	B			SW MAT R2	R2	1764/53/54	>> 158971/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
75	4000	12300	B	yes		SW MAT R2	R2	1764/53/54	>> 160813/2
75	4000	12300	B			VW MAT R2	R2	1764/53/54	>> 166167/2
75	4000	12300	B	yes		VW MAT R2	R2	1764/53/54	>> 166662/2
75	4000	12400	B			SA-L MAT R2	R2	1764/53/54	>> 255830/2
75	4000	12400	B	yes		SA-L MAT R2	R2	1764/53/54	>> 256370/2
75	4000	12400	B			SA MAT R2	R2	1764/53/54	>> 198823/2
75	4000	12400	B	yes		SA MAT R2	R2	1764/53/54	>> 200366/2
75	4000	12700	B			DAN MAT R2	R2	1764/53/54	>> 204630/2
75	4000	12700	B	yes		DAN MAT R2	R2	1764/53/54	>> 207129/2
79	4000	13500	B			MW MAT R2	R2	2940/53/54	>> 155932/2
79	4000	13500	B	yes		MW MAT R2	R2	2940/53/54	>> 156021/2
79	4000	13500	B			SW MAT R2	R2	2940/53/54	>> 160868/2
79	4000	13500	B	yes		SW MAT R2	R2	2940/53/54	>> 160943/2
79	4000	13500	B			VW MAT R2	R2	2940/53/54	>> 166716/2
79	4000	13500	B	yes		VW MAT R2	R2	2940/53/54	>> 166792/2
79	4000	13650	B			SA-L MAT R2	R2	2940/53/54	>> 256424/2
79	4000	13650	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256509/2
79	4000	13650	B			SA MAT R2	R2	2940/53/54	>> 200410/2
79	4000	13650	B	yes		SA MAT R2	R2	2940/53/54	>> 200496/2
79	4000	13950	B			DAN MAT R2	R2	2940/53/54	>> 207174/2
79	4000	13950	B	yes		DAN MAT R2	R2	2940/53/54	>> 207259/2
82	4000	13700	B			MW MAT R2	R2	3528/53/54	>> 155468/2
82	4000	13700	B	yes		MW MAT R2	R2	3528/53/54	>> 156120/2
82	4000	13700	B			SW MAT R2	R2	3528/53/54	>> 160387/2
82	4000	13700	B	yes		SW MAT R2	R2	3528/53/54	>> 161056/2
82	4000	13700	B			VW MAT R2	R2	3528/53/54	>> 166211/2
82	4000	13700	B	yes		VW MAT R2	R2	3528/53/54	>> 166891/2
82	4000	13800	B			SA-L MAT R2	R2	3528/53/54	>> 255885/2
82	4000	13800	B	yes		SA-L MAT R2	R2	3528/53/54	>> 256776/2
82	4000	13800	B			SA MAT R2	R2	3528/53/54	>> 198885/2
82	4000	13800	B	yes		SA-R MAT R2	R2	3528/53/54	>> 200595/2
82	4000	14150	B			DAN MAT R2	R2	3528/53/54	>> 204685/2
82	4000	14150	B	yes		DAN MAT R2	R2	3528/53/54	>> 207358/2
95	4000	16050	B			MW MAT R2	R2	2940/53/54	>> 155925/2
95	4000	16050	B	yes		MW MAT R2	R2	2940/53/54	>> 156014/2
95	4000	16050	B			SW MAT R2	R2	2940/53/54	>> 160851/2
95	4000	16050	B	yes		SW MAT R2	R2	2940/53/54	>> 160936/2
95	4000	16050	B			VW MAT R2	R2	2940/53/54	>> 166709/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
95	4000	16050	B	yes		VW MAT R2	R2	2940/53/54	>> 166785/2
95	4000	16250	B			SA-L MAT R2	R2	2940/53/54	>> 256417/2
95	4000	16250	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256493/2
95	4000	16250	B			SA MAT R2	R2	2940/53/54	>> 200403/2
95	4000	16250	B	yes		SA MAT R2	R2	2940/53/54	>> 200489/2
95	4000	16600	B			DAN MAT R2	R2	2940/53/54	>> 207167/2
95	4000	16600	B	yes		DAN MAT R2	R2	2940/53/54	>> 207242/2
103	4000	17150	B			MW MAT R2	R2	3528/53/54	>> 156083/2
103	4000	17150	B	yes		MW MAT R2	R2	3528/53/54	>> 156113/2
103	4000	17150	B			SW MAT R2	R2	3528/53/54	>> 161018/2
103	4000	17150	B	yes		SW MAT R2	R2	3528/53/54	>> 161049/2
103	4000	17150	B			VW MAT R2	R2	3528/53/54	>> 166853/2
103	4000	17150	B	yes		VW MAT R2	R2	3528/53/54	>> 166884/2
103	4000	17350	B			SA-L MAT R2	R2	3528/53/54	>> 256578/2
103	4000	17350	B	yes		SA-L MAT R2	R2	3528/53/54	>> 256769/2
103	4000	17350	B			SA MAT R2	R2	3528/53/54	>> 200557/2
103	4000	17350	B	yes		SA-R MAT R2	R2	3528/53/54	>> 200588/2
103	4000	17750	B			DAN MAT R2	R2	3528/53/54	>> 207310/2
103	4000	17750	B	yes		DAN MAT R2	R2	3528/53/54	>> 207341/2
111	4000	18800	B			MW MAT R2	R2	2940/53/54	>> 155918/2
111	4000	18800	B	yes		MW MAT R2	R2	2940/53/54	>> 155994/2
111	4000	18800	B			SW MAT R2	R2	2940/53/54	>> 160844/2
111	4000	18800	B	yes		SW MAT R2	R2	2940/53/54	>> 160929/2
111	4000	18800	B			VW MAT R2	R2	2940/53/54	>> 166693/2
111	4000	18800	B	yes		VW MAT R2	R2	2940/53/54	>> 166778/2
111	4000	19000	B			SA-L MAT R2	R2	2940/53/54	>> 256400/2
111	4000	19000	B	yes		SA-L MAT R2	R2	2940/53/54	>> 256486/2
111	4000	19000	B			SA MAT R2	R2	2940/53/54	>> 200397/2
111	4000	19000	B	yes		SA MAT R2	R2	2940/53/54	>> 200472/2
111	4000	19450	B			DAN MAT R2	R2	2940/53/54	>> 207150/2
111	4000	19450	B	yes		DAN MAT R2	R2	2940/53/54	>> 207235/2
123	4000	20550	B			MW MAT R2	R2	3528/53/54	>> 155451/2
123	4000	20550	B	yes		MW MAT R2	R2	3528/53/54	>> 156106/2
123	4000	20550	B			SW MAT R2	R2	3528/53/54	>> 160370/2
123	4000	20550	B	yes		SW MAT R2	R2	3528/53/54	>> 161032/2
123	4000	20550	B			VW MAT R2	R2	3528/53/54	>> 166204/2
123	4000	20550	B	yes		VW MAT R2	R2	3528/53/54	>> 166877/2
123	4000	20750	B			SA-L MAT R2	R2	3528/53/54	>> 255878/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
123	4000	20750	B	yes		SA-L MAT R2	R2	3528/53/54	>> 256592/2
123	4000	20750	B			SA MAT R2	R2	3528/53/54	>> 198878/2
123	4000	20750	B	yes		SA-R MAT R2	R2	3528/53/54	>> 200571/2
123	4000	21250	B			DAN MAT R2	R2	3528/53/54	>> 204678/2
123	4000	21250	B	yes		DAN MAT R2	R2	3528/53/54	>> 207334/2
143	4000	24000	B			MW MAT R2	R2	3528/53/54	>> 155444/2
143	4000	24000	B	yes		MW MAT R2	R2	3528/53/54	>> 156090/2
143	4000	24000	B			SW MAT R2	R2	3528/53/54	>> 159046/2
143	4000	24000	B	yes		SW MAT R2	R2	3528/53/54	>> 161025/2
143	4000	24000	B			VW MAT R2	R2	3528/53/54	>> 166198/2
143	4000	24000	B	yes		VW MAT R2	R2	3528/53/54	>> 166860/2
143	4000	24250	B			SA-L MAT R2	R2	3528/53/54	>> 255861/2
143	4000	24250	B	yes		SA-L MAT R2	R2	3528/53/54	>> 256585/2
143	4000	24250	B			SA MAT R2	R2	3528/53/54	>> 198854/2
143	4000	24250	B	yes		SA MAT R2	R2	3528/53/54	>> 200564/2
143	4000	24800	B			DAN MAT R2	R2	3528/53/54	>> 204661/2
143	4000	24800	B	yes		DAN MAT R2	R2	3528/53/54	>> 207327/2

Linea S LED Eco 1

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
7	4000	1000	C		105	symmetric		588/53/54	>> 594069
7	4000	1000	C	yes	105	symmetric		588/53/54	>> 594076
7	4000	1100	C		120	symmetric		588/53/54	>> 594021
7	4000	1100	C	yes	120	symmetric		588/53/54	>> 594038
8	4000	1150	C		butterfly	DAN		588/53/54	>> 666476
8	4000	1150	C	yes	butterfly	DAN		588/53/54	>> 667534
8	4000	1150	C		asymmetric left	SA-L		588/53/54	>> 686047
8	4000	1150	C	yes	asymmetric left	SA-L		588/53/54	>> 686207
8	4000	1150	C		asymmetric right	SA-R		588/53/54	>> 666513
8	4000	1150	C	yes	asymmetric right	SA-R		588/53/54	>> 667572
8	4000	1150	C		butterfly	DAN R2	R2	588/53/54	>> 666476/2
8	4000	1150	C	yes	butterfly	DAN R2	R2	588/53/54	>> 667534/2
8	4000	1150	C		asymmetric left	SA-L R2	R2	588/53/54	>> 686047/2
8	4000	1150	C	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686207/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
8	4000	1150	C		asymmetric right	SA-R R2	R2	588/53/54	>> 666513/2
8	4000	1150	C	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667572/2
8	4000	1200	C		35/67	CN		588/53/54	>> 666438
8	4000	1200	C	yes	35/67	CN		588/53/54	>> 667497
8	4000	1200	C		90	MW		588/53/54	>> 666353
8	4000	1200	C	yes	90	MW		588/53/54	>> 667411
8	4000	1200	C		105	VW		588/53/54	>> 666391
8	4000	1200	C	yes	105	VW		588/53/54	>> 667459
8	4000	1200	C		90	MW R2	R2	588/53/54	>> 666353/2
8	4000	1200	C	yes	90	MW R2	R2	588/53/54	>> 667411/2
8	4000	1200	C		105	VW R2	R2	588/53/54	>> 666391/2
8	4000	1200	C	yes	105	VW R2	R2	588/53/54	>> 667459/2
9	4000	1350	C		105	symmetric		588/53/54	>> 666322
9	4000	1350	C	yes	105	symmetric		588/53/54	>> 667381
9	4000	1450	B		120	symmetric		588/53/54	>> 666292
9	4000	1450	B	yes	120	symmetric		588/53/54	>> 667350
10	4000	1450	C		butterfly	DAN		588/53/54	>> 666483
10	4000	1450	C	yes	butterfly	DAN		588/53/54	>> 667541
10	4000	1450	C		asymmetric left	SA-L		588/53/54	>> 686054
10	4000	1450	C	yes	asymmetric left	SA-L		588/53/54	>> 686214
10	4000	1450	C		asymmetric right	SA-R		588/53/54	>> 666520
10	4000	1450	C	yes	asymmetric right	SA-R		588/53/54	>> 667589
10	4000	1450	C		butterfly	DAN R2	R2	588/53/54	>> 666483/2
10	4000	1450	C	yes	butterfly	DAN R2	R2	588/53/54	>> 667541/2
10	4000	1450	C		asymmetric left	SA-L R2	R2	588/53/54	>> 686054/2
10	4000	1450	C	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686214/2
10	4000	1450	C		asymmetric right	SA-R R2	R2	588/53/54	>> 666520/2
10	4000	1450	C	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667589/2
10	4000	1500	C		35/67	CN		588/53/54	>> 666445
10	4000	1500	C	yes	35/67	CN		588/53/54	>> 667503
10	4000	1500	C		90	MW		588/53/54	>> 666360
10	4000	1500	C	yes	90	MW		588/53/54	>> 667428
10	4000	1500	C		105	VW		588/53/54	>> 666407

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
10	4000	1500	C	yes	105	VW		588/53/54	>> 667466
10	4000	1500	C		90	MW R2	R2	588/53/54	>> 666360/2
10	4000	1500	C	yes	90	MW R2	R2	588/53/54	>> 667428/2
10	4000	1500	C		105	VW R2	R2	588/53/54	>> 666407/2
10	4000	1500	C	yes	105	VW R2	R2	588/53/54	>> 667466/2
11	4000	1600	C		105	symmetric		588/53/54	>> 666339
11	4000	1600	C	yes	105	symmetric		588/53/54	>> 667398
11	4000	1700	C		120	symmetric		588/53/54	>> 666308
11	4000	1700	C	yes	120	symmetric		588/53/54	>> 667367
12	4000	1700	C		butterfly	DAN		588/53/54	>> 666490
12	4000	1700	C	yes	butterfly	DAN		588/53/54	>> 667558
12	4000	1700	C		asymmetric left	SA-L		588/53/54	>> 686061
12	4000	1700	C	yes	asymmetric left	SA-L		588/53/54	>> 686221
12	4000	1700	C		asymmetric right	SA-R		588/53/54	>> 666537
12	4000	1700	C	yes	asymmetric right	SA-R		588/53/54	>> 667596
12	4000	1700	C		butterfly	DAN R2	R2	588/53/54	>> 666490/2
12	4000	1700	C	yes	butterfly	DAN R2	R2	588/53/54	>> 667558/2
12	4000	1700	C		asymmetric left	SA-L R2	R2	588/53/54	>> 686061/2
12	4000	1700	C	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686221/2
12	4000	1700	C		asymmetric right	SA-R R2	R2	588/53/54	>> 666537/2
12	4000	1700	C	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667596/2
12	4000	1800	C		105	symmetric		588/53/54	>> 666346
12	4000	1800	C	yes	105	symmetric		588/53/54	>> 667404
12	4000	1800	C		35/67	CN		588/53/54	>> 666452
12	4000	1800	C	yes	35/67	CN		588/53/54	>> 667510
12	4000	1800	C		90	MW		588/53/54	>> 666377
12	4000	1800	C	yes	90	MW		588/53/54	>> 667435
12	4000	1800	C		105	VW		588/53/54	>> 666414
12	4000	1800	C	yes	105	VW		588/53/54	>> 667473
12	4000	1800	C		90	MW R2	R2	588/53/54	>> 666377/2
12	4000	1800	C	yes	90	MW R2	R2	588/53/54	>> 667435/2
12	4000	1800	C		105	VW R2	R2	588/53/54	>> 666414/2
12	4000	1800	C	yes	105	VW R2	R2	588/53/54	>> 667473/2
12	4000	1950	B		120	symmetric		588/53/54	>> 666315

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
12	4000	1950	B	yes	120	symmetric		588/53/54	>> 667374
13	4000	1950	C		butterfly	DAN		588/53/54	>> 666506
13	4000	1950	C	yes	butterfly	DAN		588/53/54	>> 667565
13	4000	1950	C		asymmetric left	SA-L		588/53/54	>> 686078
13	4000	1950	C	yes	asymmetric left	SA-L		588/53/54	>> 686238
13	4000	1950	C		asymmetric right	SA-R		588/53/54	>> 666544
13	4000	1950	C	yes	asymmetric right	SA-R		588/53/54	>> 667602
13	4000	1950	C		butterfly	DAN R2	R2	588/53/54	>> 666506/2
13	4000	1950	C	yes	butterfly	DAN R2	R2	588/53/54	>> 667565/2
13	4000	1950	C		asymmetric left	SA-L R2	R2	588/53/54	>> 686078/2
13	4000	1950	C	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686238/2
13	4000	1950	C		asymmetric right	SA-R R2	R2	588/53/54	>> 666544/2
13	4000	1950	C	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667602/2
13	4000	2050	B		35/67	CN		588/53/54	>> 666469
13	4000	2050	B	yes	35/67	CN		588/53/54	>> 667527
13	4000	2050	B		90	MW		588/53/54	>> 666384
13	4000	2050	B	yes	90	MW		588/53/54	>> 667442
13	4000	2050	B		105	VW		588/53/54	>> 666421
13	4000	2050	B	yes	105	VW		588/53/54	>> 667480
13	4000	2050	B		90	MW R2	R2	588/53/54	>> 666384/2
13	4000	2050	B	yes	90	MW R2	R2	588/53/54	>> 667442/2
13	4000	2050	B		105	VW R2	R2	588/53/54	>> 666421/2
13	4000	2050	B	yes	105	VW R2	R2	588/53/54	>> 667480/2
16	4000	2400	C		105	symmetric		588/53/54	>> 666056
16	4000	2400	C	yes	105	symmetric		588/53/54	>> 667138
16	4000	2450	C		butterfly	DAN		588/53/54	>> 666247
16	4000	2450	C	yes	butterfly	DAN		588/53/54	>> 667305
16	4000	2450	C		asymmetric left	SA-L		588/53/54	>> 686030
16	4000	2450	C	yes	asymmetric left	SA-L		588/53/54	>> 686191
16	4000	2450	C		asymmetric right	SA-R		588/53/54	>> 666285
16	4000	2450	C	yes	asymmetric right	SA-R		588/53/54	>> 667343
16	4000	2450	C		butterfly	DAN R2	R2	588/53/54	>> 666247/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
16	4000	2450	C	yes	butterfly	DAN R2	R2	588/53/54	>> 667305/2
16	4000	2450	C		asymmetric left	SA-L R2	R2	588/53/54	>> 686030/2
16	4000	2450	C	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686191/2
16	4000	2450	C		asymmetric right	SA-R R2	R2	588/53/54	>> 666285/2
16	4000	2450	C	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667343/2
16	4000	2550	B		35/67	CN		588/53/54	>> 666193
16	4000	2550	B	yes	35/67	CN		588/53/54	>> 667268
16	4000	2550	B		90	MW		588/53/54	>> 666094
16	4000	2550	B	yes	90	MW		588/53/54	>> 667176
16	4000	2550	B		105	VW		588/53/54	>> 666155
16	4000	2550	B	yes	105	VW		588/53/54	>> 667213
16	4000	2550	B		90	MW R2	R2	588/53/54	>> 666094/2
16	4000	2550	B	yes	90	MW R2	R2	588/53/54	>> 667176/2
16	4000	2550	B		105	VW R2	R2	588/53/54	>> 666155/2
16	4000	2550	B	yes	105	VW R2	R2	588/53/54	>> 667213/2
16	4000	2600	B		120	symmetric		588/53/54	>> 666025
16	4000	2600	B	yes	120	symmetric		588/53/54	>> 667091
20	4000	2950	C		105	symmetric		588/53/54	>> 666049
20	4000	2950	C	yes	105	symmetric		588/53/54	>> 667114
20	4000	3050	C		butterfly	DAN		588/53/54	>> 666223
20	4000	3050	C	yes	butterfly	DAN		588/53/54	>> 667299
20	4000	3050	C		asymmetric left	SA-L		588/53/54	>> 686023
20	4000	3050	C	yes	asymmetric left	SA-L		588/53/54	>> 686184
20	4000	3050	C		asymmetric right	SA-R		588/53/54	>> 666278
20	4000	3050	C	yes	asymmetric right	SA-R		588/53/54	>> 667336
20	4000	3050	C		butterfly	DAN R2	R2	588/53/54	>> 666223/2
20	4000	3050	C	yes	butterfly	DAN R2	R2	588/53/54	>> 667299/2
20	4000	3050	C		asymmetric left	SA-L R2	R2	588/53/54	>> 686023/2
20	4000	3050	C	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686184/2
20	4000	3050	C		asymmetric right	SA-R R2	R2	588/53/54	>> 666278/2
20	4000	3050	C	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667336/2
20	4000	3150	B		35/67	CN		588/53/54	>> 666186

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
20	4000	3150	B	yes	35/67	CN		588/53/54	>> 667251
20	4000	3150	B		90	MW		588/53/54	>> 666087
20	4000	3150	B	yes	90	MW		588/53/54	>> 667169
20	4000	3150	B		105	VW		588/53/54	>> 666148
20	4000	3150	B	yes	105	VW		588/53/54	>> 667206
20	4000	3150	B		90	MW R2	R2	588/53/54	>> 666087/2
20	4000	3150	B	yes	90	MW R2	R2	588/53/54	>> 667169/2
20	4000	3150	B		105	VW R2	R2	588/53/54	>> 666148/2
20	4000	3150	B	yes	105	VW R2	R2	588/53/54	>> 667206/2
20	4000	3200	B		120	symmetric		588/53/54	>> 666018
20	4000	3200	B	yes	120	symmetric		588/53/54	>> 667084
23	4000	3400	C		105	symmetric		588/53/54	>> 666032
23	4000	3400	C	yes	105	symmetric		588/53/54	>> 667107
23	4000	3500	C		butterfly	DAN		588/53/54	>> 666216
23	4000	3500	C	yes	butterfly	DAN		588/53/54	>> 667282
23	4000	3500	C		asymmetric left	SA-L		588/53/54	>> 686016
23	4000	3500	C	yes	asymmetric left	SA-L		588/53/54	>> 686177
23	4000	3500	C		asymmetric right	SA-R		588/53/54	>> 666261
23	4000	3500	C	yes	asymmetric right	SA-R		588/53/54	>> 667329
23	4000	3500	C		butterfly	DAN R2	R2	588/53/54	>> 666216/2
23	4000	3500	C	yes	butterfly	DAN R2	R2	588/53/54	>> 667282/2
23	4000	3500	C		asymmetric left	SA-L R2	R2	588/53/54	>> 686016/2
23	4000	3500	C	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686177/2
23	4000	3500	C		asymmetric right	SA-R R2	R2	588/53/54	>> 666261/2
23	4000	3500	C	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667329/2
23	4000	3650	B		35/67	CN		588/53/54	>> 666179
23	4000	3650	B	yes	35/67	CN		588/53/54	>> 667244
23	4000	3650	B		90	MW		588/53/54	>> 666070
23	4000	3650	B	yes	90	MW		588/53/54	>> 667152
23	4000	3650	B		105	VW		588/53/54	>> 666117
23	4000	3650	B	yes	105	VW		588/53/54	>> 667190
23	4000	3650	B		90	MW R2	R2	588/53/54	>> 666070/2
23	4000	3650	B	yes	90	MW R2	R2	588/53/54	>> 667152/2
23	4000	3650	B		105	VW R2	R2	588/53/54	>> 666117/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
23	4000	3650	B	yes	105	VW R2	R2	588/53/54	>> 667190/2
23	4000	3700	B		120	symmetric		588/53/54	>> 666001
23	4000	3700	B	yes	120	symmetric		588/53/54	>> 667077
25	4000	3850	C		105	symmetric		588/53/54	>> 594045
25	4000	3850	C	yes	105	symmetric		588/53/54	>> 594052
25	4000	4050	B		butterfly	DAN		588/53/54	>> 666209
25	4000	4050	B	yes	butterfly	DAN		588/53/54	>> 667275
25	4000	4050	B		asymmetric left	SA-L		588/53/54	>> 686009
25	4000	4050	B	yes	asymmetric left	SA-L		588/53/54	>> 686160
25	4000	4050	B		asymmetric right	SA-R		588/53/54	>> 666254
25	4000	4050	B	yes	asymmetric right	SA-R		588/53/54	>> 667312
25	4000	4050	B		butterfly	DAN R2	R2	588/53/54	>> 666209/2
25	4000	4050	B	yes	butterfly	DAN R2	R2	588/53/54	>> 667275/2
25	4000	4050	B		asymmetric left	SA-L R2	R2	588/53/54	>> 686009/2
25	4000	4050	B	yes	asymmetric left	SA-L R2	R2	588/53/54	>> 686160/2
25	4000	4050	B		asymmetric right	SA-R R2	R2	588/53/54	>> 666254/2
25	4000	4050	B	yes	asymmetric right	SA-R R2	R2	588/53/54	>> 667312/2
25	4000	4200	B		35/67	CN		588/53/54	>> 666162
25	4000	4200	B	yes	35/67	CN		588/53/54	>> 667220
25	4000	4200	B		90	MW		588/53/54	>> 666063
25	4000	4200	B	yes	90	MW		588/53/54	>> 667145
25	4000	4200	B		105	VW		588/53/54	>> 666100
25	4000	4200	B	yes	105	VW		588/53/54	>> 667183
25	4000	4200	B		90	MW R2	R2	588/53/54	>> 666063/2
25	4000	4200	B	yes	90	MW R2	R2	588/53/54	>> 667145/2
25	4000	4200	B		105	VW R2	R2	588/53/54	>> 666100/2
25	4000	4200	B	yes	105	VW R2	R2	588/53/54	>> 667183/2
25	4000	4250	B		120	symmetric		588/53/54	>> 594007
25	4000	4250	B	yes	120	symmetric		588/53/54	>> 594014

Linea S LED Eco 2

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
13	4000	1900	C		105	symmetric		1176/53/54	>> 594144
13	4000	1900	C	yes	105	symmetric		1176/53/54	>> 594151

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
13	4000	2100	B		120	symmetric		1176/53/54	>> 594106
13	4000	2100	B	yes	120	symmetric		1176/53/54	>> 594113
17	4000	2450	C		butterfly	DAN		1176/53/54	>> 666995
17	4000	2450	C	yes	butterfly	DAN		1176/53/54	>> 671692
17	4000	2450	C		asymmetric left	SA-L		1176/53/54	>> 686122
17	4000	2450	C	yes	asymmetric left	SA-L		1176/53/54	>> 686283
17	4000	2450	C		asymmetric right	SA-R		1176/53/54	>> 667039
17	4000	2450	C	yes	asymmetric right	SA-R		1176/53/54	>> 671739
17	4000	2450	C		butterfly	DAN R2	R2	1176/53/54	>> 666995/2
17	4000	2450	C	yes	butterfly	DAN R2	R2	1176/53/54	>> 671692/2
17	4000	2450	C		asymmetric left	SA-L R2	R2	1176/53/54	>> 686122/2
17	4000	2450	C	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686283/2
17	4000	2450	C		asymmetric right	SA-R R2	R2	1176/53/54	>> 667039/2
17	4000	2450	C	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 671739/2
17	4000	2550	C		35/67	CN		1176/53/54	>> 666957
17	4000	2550	C	yes	35/67	CN		1176/53/54	>> 671654
17	4000	2550	C		90	MW		1176/53/54	>> 666872
17	4000	2550	C	yes	90	MW		1176/53/54	>> 667930
17	4000	2550	C		105	VW		1176/53/54	>> 666919
17	4000	2550	C	yes	105	VW		1176/53/54	>> 667978
17	4000	2550	C		90	MW R2	R2	1176/53/54	>> 666872/2
17	4000	2550	C	yes	90	MW R2	R2	1176/53/54	>> 667930/2
17	4000	2550	C		105	VW R2	R2	1176/53/54	>> 666919/2
17	4000	2550	C	yes	105	VW R2	R2	1176/53/54	>> 667978/2
19	4000	2800	C		105	symmetric		1176/53/54	>> 666841
19	4000	2800	C	yes	105	symmetric		1176/53/54	>> 667909
19	4000	3050	B		120	symmetric		1176/53/54	>> 666810
19	4000	3050	B	yes	120	symmetric		1176/53/54	>> 667879
21	4000	3050	C		butterfly	DAN		1176/53/54	>> 667008
21	4000	3050	C	yes	butterfly	DAN		1176/53/54	>> 671708
21	4000	3050	C		asymmetric left	SA-L		1176/53/54	>> 686139
21	4000	3050	C	yes	asymmetric left	SA-L		1176/53/54	>> 686290

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
21	4000	3050	C		asymmetric right	SA-R		1176/53/54	>> 667046
21	4000	3050	C	yes	asymmetric right	SA-R		1176/53/54	>> 671746
21	4000	3050	C		butterfly	DAN R2	R2	1176/53/54	>> 667008/2
21	4000	3050	C	yes	butterfly	DAN R2	R2	1176/53/54	>> 671708/2
21	4000	3050	C		asymmetric left	SA-L R2	R2	1176/53/54	>> 686139/2
21	4000	3050	C	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686290/2
21	4000	3050	C		asymmetric right	SA-R R2	R2	1176/53/54	>> 667046/2
21	4000	3050	C	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 671746/2
21	4000	3150	C		35/67	CN		1176/53/54	>> 666964
21	4000	3150	C	yes	35/67	CN		1176/53/54	>> 671661
21	4000	3200	C		90	MW		1176/53/54	>> 666889
21	4000	3200	C	yes	90	MW		1176/53/54	>> 667947
21	4000	3200	C		105	VW		1176/53/54	>> 666926
21	4000	3200	C	yes	105	VW		1176/53/54	>> 667985
21	4000	3200	C		90	MW R2	R2	1176/53/54	>> 666889/2
21	4000	3200	C	yes	90	MW R2	R2	1176/53/54	>> 667947/2
21	4000	3200	C		105	VW R2	R2	1176/53/54	>> 666926/2
21	4000	3200	C	yes	105	VW R2	R2	1176/53/54	>> 667985/2
23	4000	3350	C		105	symmetric		1176/53/54	>> 666858
23	4000	3350	C	yes	105	symmetric		1176/53/54	>> 667916
23	4000	3700	B		120	symmetric		1176/53/54	>> 666827
23	4000	3700	B	yes	120	symmetric		1176/53/54	>> 667886
25	4000	3650	C		butterfly	DAN		1176/53/54	>> 667015
25	4000	3650	C	yes	butterfly	DAN		1176/53/54	>> 671715
25	4000	3650	C		asymmetric left	SA-L		1176/53/54	>> 686146
25	4000	3650	C	yes	asymmetric left	SA-L		1176/53/54	>> 686306
25	4000	3650	C		asymmetric right	SA-R		1176/53/54	>> 667053
25	4000	3650	C	yes	asymmetric right	SA-R		1176/53/54	>> 671753
25	4000	3650	C		butterfly	DAN R2	R2	1176/53/54	>> 667015/2
25	4000	3650	C	yes	butterfly	DAN R2	R2	1176/53/54	>> 671715/2
25	4000	3650	C		asymmetric left	SA-L R2	R2	1176/53/54	>> 686146/2
25	4000	3650	C	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686306/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
25	4000	3650	C		asymmetric right	SA-R R2	R2	1176/53/54	>> 667053/2
25	4000	3650	C	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 671753/2
25	4000	3800	C		35/67	CN		1176/53/54	>> 666971
25	4000	3800	C	yes	35/67	CN		1176/53/54	>> 671678
25	4000	3800	C		90	MW		1176/53/54	>> 666896
25	4000	3800	C	yes	90	MW		1176/53/54	>> 667954
25	4000	3800	C		105	VW		1176/53/54	>> 666933
25	4000	3800	C	yes	105	VW		1176/53/54	>> 667992
25	4000	3800	C		90	MW R2	R2	1176/53/54	>> 666896/2
25	4000	3800	C	yes	90	MW R2	R2	1176/53/54	>> 667954/2
25	4000	3800	C		105	VW R2	R2	1176/53/54	>> 666933/2
25	4000	3800	C	yes	105	VW R2	R2	1176/53/54	>> 667992/2
26	4000	3850	C		105	symmetric		1176/53/54	>> 666865
26	4000	3850	C	yes	105	symmetric		1176/53/54	>> 667923
26	4000	4250	B		120	symmetric		1176/53/54	>> 666834
26	4000	4250	B	yes	120	symmetric		1176/53/54	>> 667893
29	4000	4200	C		butterfly	DAN		1176/53/54	>> 667022
29	4000	4200	C	yes	butterfly	DAN		1176/53/54	>> 671722
29	4000	4200	C		asymmetric left	SA-L		1176/53/54	>> 686153
29	4000	4200	C	yes	asymmetric left	SA-L		1176/53/54	>> 686313
29	4000	4200	C		asymmetric right	SA-R		1176/53/54	>> 667060
29	4000	4200	C	yes	asymmetric right	SA-R		1176/53/54	>> 671760
29	4000	4200	C		butterfly	DAN R2	R2	1176/53/54	>> 667022/2
29	4000	4200	C	yes	butterfly	DAN R2	R2	1176/53/54	>> 671722/2
29	4000	4200	C		asymmetric left	SA-L R2	R2	1176/53/54	>> 686153/2
29	4000	4200	C	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686313/2
29	4000	4200	C		asymmetric right	SA-R R2	R2	1176/53/54	>> 667060/2
29	4000	4200	C	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 671760/2
29	4000	4350	C		35/67	CN		1176/53/54	>> 666988
29	4000	4350	C	yes	35/67	CN		1176/53/54	>> 671685
29	4000	4400	C		90	MW		1176/53/54	>> 666902
29	4000	4400	C	yes	90	MW		1176/53/54	>> 667961
29	4000	4400	C		105	VW		1176/53/54	>> 666940

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
29	4000	4400	C	yes	105	VW		1176/53/54	>> 671647
29	4000	4400	C		90	MW R2	R2	1176/53/54	>> 666902/2
29	4000	4400	C	yes	90	MW R2	R2	1176/53/54	>> 667961/2
29	4000	4400	C		105	VW R2	R2	1176/53/54	>> 666940/2
29	4000	4400	C	yes	105	VW R2	R2	1176/53/54	>> 671647/2
29	4000	4700	B		butterfly	DAN		1176/53/54	>> 666766
29	4000	4700	B	yes	butterfly	DAN		1176/53/54	>> 667824
29	4000	4700	B		butterfly	DAN R2	R2	1176/53/54	>> 666766/2
29	4000	4700	B	yes	butterfly	DAN R2	R2	1176/53/54	>> 667824/2
29	4000	4750	B		asymmetric left	SA-L		1176/53/54	>> 686115
29	4000	4750	B	yes	asymmetric left	SA-L		1176/53/54	>> 686276
29	4000	4750	B		asymmetric right	SA-R		1176/53/54	>> 666803
29	4000	4750	B	yes	asymmetric right	SA-R		1176/53/54	>> 667862
29	4000	4750	B		asymmetric left	SA-L R2	R2	1176/53/54	>> 686115/2
29	4000	4750	B	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686276/2
29	4000	4750	B		asymmetric right	SA-R R2	R2	1176/53/54	>> 666803/2
29	4000	4750	B	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 667862/2
29	4000	4900	B		35/67	CN		1176/53/54	>> 666728
29	4000	4900	B	yes	35/67	CN		1176/53/54	>> 667787
29	4000	4900	B		90	MW		1176/53/54	>> 666643
29	4000	4900	B	yes	90	MW		1176/53/54	>> 667701
29	4000	4900	B		105	VW		1176/53/54	>> 666681
29	4000	4900	B	yes	105	VW		1176/53/54	>> 667749
29	4000	4900	B		90	MW R2	R2	1176/53/54	>> 666643/2
29	4000	4900	B	yes	90	MW R2	R2	1176/53/54	>> 667701/2
29	4000	4900	B		105	VW R2	R2	1176/53/54	>> 666681/2
29	4000	4900	B	yes	105	VW R2	R2	1176/53/54	>> 667749/2
30	4000	4350	C		105	symmetric		1176/53/54	>> 666605
30	4000	4350	C	yes	105	symmetric		1176/53/54	>> 667664
30	4000	4750	B		120	symmetric		1176/53/54	>> 666575
30	4000	4750	B	yes	120	symmetric		1176/53/54	>> 667633
36	4000	5900	B		butterfly	DAN		1176/53/54	>> 666759
36	4000	5900	B	yes	butterfly	DAN		1176/53/54	>> 667817
36	4000	5900	B		butterfly	DAN R2	R2	1176/53/54	>> 666759/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
36	4000	5900	B	yes	butterfly	DAN R2	R2	1176/53/54	>> 667817/2
36	4000	5950	B		asymmetric left	SA-L		1176/53/54	>> 686108
36	4000	5950	B	yes	asymmetric left	SA-L		1176/53/54	>> 686269
36	4000	5950	B		asymmetric right	SA-R		1176/53/54	>> 666797
36	4000	5950	B	yes	asymmetric right	SA-R		1176/53/54	>> 667855
36	4000	5950	B		asymmetric left	SA-L R2	R2	1176/53/54	>> 686108/2
36	4000	5950	B	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686269/2
36	4000	5950	B		asymmetric right	SA-R R2	R2	1176/53/54	>> 666797/2
36	4000	5950	B	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 667855/2
36	4000	6150	B		35/67	CN		1176/53/54	>> 666711
36	4000	6150	B	yes	35/67	CN		1176/53/54	>> 667770
36	4000	6150	B		90	MW		1176/53/54	>> 666636
36	4000	6150	B	yes	90	MW		1176/53/54	>> 667695
36	4000	6150	B		105	VW		1176/53/54	>> 666674
36	4000	6150	B	yes	105	VW		1176/53/54	>> 667732
36	4000	6150	B		90	MW R2	R2	1176/53/54	>> 666636/2
36	4000	6150	B	yes	90	MW R2	R2	1176/53/54	>> 667695/2
36	4000	6150	B		105	VW R2	R2	1176/53/54	>> 666674/2
36	4000	6150	B	yes	105	VW R2	R2	1176/53/54	>> 667732/2
38	4000	5450	C		105	symmetric		1176/53/54	>> 666599
38	4000	5450	C	yes	105	symmetric		1176/53/54	>> 667657
38	4000	5950	C		120	symmetric		1176/53/54	>> 666568
38	4000	5950	C	yes	120	symmetric		1176/53/54	>> 667626
41	4000	6600	B		butterfly	DAN		1176/53/54	>> 666742
41	4000	6600	B	yes	butterfly	DAN		1176/53/54	>> 667800
41	4000	6600	B		butterfly	DAN R2	R2	1176/53/54	>> 666742/2
41	4000	6600	B	yes	butterfly	DAN R2	R2	1176/53/54	>> 667800/2
41	4000	6650	B		asymmetric left	SA-L		1176/53/54	>> 686092
41	4000	6650	B	yes	asymmetric left	SA-L		1176/53/54	>> 686252
41	4000	6650	B		asymmetric right	SA-R		1176/53/54	>> 666780
41	4000	6650	B	yes	asymmetric right	SA-R		1176/53/54	>> 667848

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
41	4000	6650	B		asymmetric left	SA-L R2	R2	1176/53/54	>> 686092/2
41	4000	6650	B	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686252/2
41	4000	6650	B		asymmetric right	SA-R R2	R2	1176/53/54	>> 666780/2
41	4000	6650	B	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 667848/2
41	4000	6850	B		35/67	CN		1176/53/54	>> 666704
41	4000	6850	B	yes	35/67	CN		1176/53/54	>> 667763
41	4000	6900	B		90	MW		1176/53/54	>> 666629
41	4000	6900	B	yes	90	MW		1176/53/54	>> 667688
41	4000	6900	B		105	VW		1176/53/54	>> 666667
41	4000	6900	B	yes	105	VW		1176/53/54	>> 667725
41	4000	6900	B		90	MW R2	R2	1176/53/54	>> 666629/2
41	4000	6900	B	yes	90	MW R2	R2	1176/53/54	>> 667688/2
41	4000	6900	B		105	VW R2	R2	1176/53/54	>> 666667/2
41	4000	6900	B	yes	105	VW R2	R2	1176/53/54	>> 667725/2
46	4000	6400	C		105	symmetric		1176/53/54	>> 666582
46	4000	6400	C	yes	105	symmetric		1176/53/54	>> 667640
46	4000	7000	C		120	symmetric		1176/53/54	>> 666551
46	4000	7000	C	yes	120	symmetric		1176/53/54	>> 667619
49	4000	7700	C		butterfly	DAN		1176/53/54	>> 666735
49	4000	7700	C	yes	butterfly	DAN		1176/53/54	>> 667794
49	4000	7700	C		butterfly	DAN R2	R2	1176/53/54	>> 666735/2
49	4000	7700	C	yes	butterfly	DAN R2	R2	1176/53/54	>> 667794/2
49	4000	7750	B		asymmetric left	SA-L		1176/53/54	>> 686085
49	4000	7750	B	yes	asymmetric left	SA-L		1176/53/54	>> 686245
49	4000	7750	B		asymmetric right	SA-R		1176/53/54	>> 666773
49	4000	7750	B	yes	asymmetric right	SA-R		1176/53/54	>> 667831
49	4000	7750	B		asymmetric left	SA-L R2	R2	1176/53/54	>> 686085/2
49	4000	7750	B	yes	asymmetric left	SA-L R2	R2	1176/53/54	>> 686245/2
49	4000	7750	B		asymmetric right	SA-R R2	R2	1176/53/54	>> 666773/2
49	4000	7750	B	yes	asymmetric right	SA-R R2	R2	1176/53/54	>> 667831/2
49	4000	8000	B		35/67	CN		1176/53/54	>> 666698
49	4000	8000	B	yes	35/67	CN		1176/53/54	>> 667756

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
49	4000	8050	B		90	MW		1176/53/54	>> 666612
49	4000	8050	B	yes	90	MW		1176/53/54	>> 667671
49	4000	8050	B		105	VW		1176/53/54	>> 666650
49	4000	8050	B	yes	105	VW		1176/53/54	>> 667718
49	4000	8050	B		90	MW R2	R2	1176/53/54	>> 666612/2
49	4000	8050	B	yes	90	MW R2	R2	1176/53/54	>> 667671/2
49	4000	8050	B		105	VW R2	R2	1176/53/54	>> 666650/2
49	4000	8050	B	yes	105	VW R2	R2	1176/53/54	>> 667718/2
50	4000	7450	C		105	symmetric		1176/53/54	>> 594120
50	4000	7450	C	yes	105	symmetric		1176/53/54	>> 594137
50	4000	8150	B		120	symmetric		1176/53/54	>> 594083
50	4000	8150	B	yes	120	symmetric		1176/53/54	>> 594090

Linea S LED Eco 3

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
21	4000	3350	B		105	symmetric		1764/53/54	>> 594229
21	4000	3350	B	yes	105	symmetric		1764/53/54	>> 594236
21	4000	3650	B		120	symmetric		1764/53/54	>> 594182
21	4000	3650	B	yes	120	symmetric		1764/53/54	>> 594199
23	4000	3750	B		butterfly	DAN		1764/53/54	>> 686597
23	4000	3750	B	yes	butterfly	DAN		1764/53/54	>> 686986
23	4000	3750	B		butterfly	DAN R2	R2	1764/53/54	>> 686597/2
23	4000	3750	B	yes	butterfly	DAN R2	R2	1764/53/54	>> 686986/2
23	4000	3800	B		asymmetric left	SA-L		1764/53/54	>> 686672
23	4000	3800	B	yes	asymmetric left	SA-L		1764/53/54	>> 687068
23	4000	3800	B		asymmetric right	SA-R		1764/53/54	>> 686634
23	4000	3800	B	yes	asymmetric right	SA-R		1764/53/54	>> 687020
23	4000	3800	B		asymmetric left	SA-L R2	R2	1764/53/54	>> 686672/2
23	4000	3800	B	yes	asymmetric left	SA-L R2	R2	1764/53/54	>> 687068/2
23	4000	3800	B		asymmetric right	SA-R R2	R2	1764/53/54	>> 686634/2
23	4000	3800	B	yes	asymmetric right	SA-R R2	R2	1764/53/54	>> 687020/2
23	4000	3900	B		35/67	CN		1764/53/54	>> 686559
23	4000	3900	B	yes	35/67	CN		1764/53/54	>> 686948
23	4000	3950	B		90	MW		1764/53/54	>> 686474

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
23	4000	3950	B	yes	90	MW		1764/53/54	>> 686863
23	4000	3950	B		105	VW		1764/53/54	>> 686511
23	4000	3950	B	yes	105	VW		1764/53/54	>> 686900
23	4000	3950	B		90	MW R2	R2	1764/53/54	>> 686474/2
23	4000	3950	B	yes	90	MW R2	R2	1764/53/54	>> 686863/2
23	4000	3950	B		105	VW R2	R2	1764/53/54	>> 686511/2
23	4000	3950	B	yes	105	VW R2	R2	1764/53/54	>> 686900/2
26	4000	4200	B		105	symmetric		1764/53/54	>> 686443
26	4000	4200	B	yes	105	symmetric		1764/53/54	>> 686832
26	4000	4600	B		120	symmetric		1764/53/54	>> 686412
26	4000	4600	B	yes	120	symmetric		1764/53/54	>> 686801
28	4000	4700	B		butterfly	DAN		1764/53/54	>> 686603
28	4000	4700	B	yes	butterfly	DAN		1764/53/54	>> 686993
28	4000	4700	B		butterfly	DAN R2	R2	1764/53/54	>> 686603/2
28	4000	4700	B	yes	butterfly	DAN R2	R2	1764/53/54	>> 686993/2
28	4000	4750	B		asymmetric left	SA-L		1764/53/54	>> 686689
28	4000	4750	B	yes	asymmetric left	SA-L		1764/53/54	>> 687075
28	4000	4750	B		asymmetric right	SA-R		1764/53/54	>> 686641
28	4000	4750	B	yes	asymmetric right	SA-R		1764/53/54	>> 687037
28	4000	4750	B		asymmetric left	SA-L R2	R2	1764/53/54	>> 686689/2
28	4000	4750	B	yes	asymmetric left	SA-L R2	R2	1764/53/54	>> 687075/2
28	4000	4750	B		asymmetric right	SA-R R2	R2	1764/53/54	>> 686641/2
28	4000	4750	B	yes	asymmetric right	SA-R R2	R2	1764/53/54	>> 687037/2
28	4000	4850	B		35/67	CN		1764/53/54	>> 686566
28	4000	4850	B	yes	35/67	CN		1764/53/54	>> 686955
28	4000	4900	B		90	MW		1764/53/54	>> 686481
28	4000	4900	B	yes	90	MW		1764/53/54	>> 686870
28	4000	4900	B		105	VW		1764/53/54	>> 686528
28	4000	4900	B	yes	105	VW		1764/53/54	>> 686917
28	4000	4900	B		90	MW R2	R2	1764/53/54	>> 686481/2
28	4000	4900	B	yes	90	MW R2	R2	1764/53/54	>> 686870/2
28	4000	4900	B		105	VW R2	R2	1764/53/54	>> 686528/2
28	4000	4900	B	yes	105	VW R2	R2	1764/53/54	>> 686917/2
31	4000	5050	B		105	symmetric		1764/53/54	>> 686450

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
31	4000	5050	B	yes	105	symmetric		1764/53/54	>> 686849
31	4000	5550	A		120	symmetric		1764/53/54	>> 686429
31	4000	5550	A	yes	120	symmetric		1764/53/54	>> 686818
34	4000	5650	B		butterfly	DAN		1764/53/54	>> 686610
34	4000	5650	B	yes	butterfly	DAN		1764/53/54	>> 687006
34	4000	5650	B		asymmetric left	SA-L		1764/53/54	>> 686696
34	4000	5650	B	yes	asymmetric left	SA-L		1764/53/54	>> 687082
34	4000	5650	B		asymmetric right	SA-R		1764/53/54	>> 686658
34	4000	5650	B	yes	asymmetric right	SA-R		1764/53/54	>> 687044
34	4000	5650	B		butterfly	DAN R2	R2	1764/53/54	>> 686610/2
34	4000	5650	B	yes	butterfly	DAN R2	R2	1764/53/54	>> 687006/2
34	4000	5650	B		asymmetric left	SA-L R2	R2	1764/53/54	>> 686696/2
34	4000	5650	B	yes	asymmetric left	SA-L R2	R2	1764/53/54	>> 687082/2
34	4000	5650	B		asymmetric right	SA-R R2	R2	1764/53/54	>> 686658/2
34	4000	5650	B	yes	asymmetric right	SA-R R2	R2	1764/53/54	>> 687044/2
34	4000	5850	B		35/67	CN		1764/53/54	>> 686573
34	4000	5850	B	yes	35/67	CN		1764/53/54	>> 686962
34	4000	5900	B		90	MW		1764/53/54	>> 686498
34	4000	5900	B	yes	90	MW		1764/53/54	>> 686887
34	4000	5900	B		105	VW		1764/53/54	>> 686535
34	4000	5900	B	yes	105	VW		1764/53/54	>> 686924
34	4000	5900	B		90	MW R2	R2	1764/53/54	>> 686498/2
34	4000	5900	B	yes	90	MW R2	R2	1764/53/54	>> 686887/2
34	4000	5900	B		105	VW R2	R2	1764/53/54	>> 686535/2
34	4000	5900	B	yes	105	VW R2	R2	1764/53/54	>> 686924/2
36	4000	5950	B		105	symmetric		1764/53/54	>> 686467
36	4000	5950	B	yes	105	symmetric		1764/53/54	>> 686856
36	4000	6500	A		120	symmetric		1764/53/54	>> 686436
36	4000	6500	A	yes	120	symmetric		1764/53/54	>> 686825
39	4000	6600	B		butterfly	DAN		1764/53/54	>> 686627
39	4000	6600	B	yes	butterfly	DAN		1764/53/54	>> 687013
39	4000	6600	B		asymmetric left	SA-L		1764/53/54	>> 686702
39	4000	6600	B	yes	asymmetric left	SA-L		1764/53/54	>> 687099

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
39	4000	6600	B		asymmetric right	SA-R		1764/53/54	>> 686665
39	4000	6600	B	yes	asymmetric right	SA-R		1764/53/54	>> 687051
39	4000	6600	B		butterfly	DAN R2	R2	1764/53/54	>> 686627/2
39	4000	6600	B	yes	butterfly	DAN R2	R2	1764/53/54	>> 687013/2
39	4000	6600	B		asymmetric left	SA-L R2	R2	1764/53/54	>> 686702/2
39	4000	6600	B	yes	asymmetric left	SA-L R2	R2	1764/53/54	>> 687099/2
39	4000	6600	B		asymmetric right	SA-R R2	R2	1764/53/54	>> 686665/2
39	4000	6600	B	yes	asymmetric right	SA-R R2	R2	1764/53/54	>> 687051/2
39	4000	6850	B		35/67	CN		1764/53/54	>> 686580
39	4000	6850	B	yes	35/67	CN		1764/53/54	>> 686979
39	4000	6850	B		90	MW		1764/53/54	>> 686504
39	4000	6850	B	yes	90	MW		1764/53/54	>> 686894
39	4000	6850	B		105	VW		1764/53/54	>> 686542
39	4000	6850	B	yes	105	VW		1764/53/54	>> 686931
39	4000	6850	B		90	MW R2	R2	1764/53/54	>> 686504/2
39	4000	6850	B	yes	90	MW R2	R2	1764/53/54	>> 686894/2
39	4000	6850	B		105	VW R2	R2	1764/53/54	>> 686542/2
39	4000	6850	B	yes	105	VW R2	R2	1764/53/54	>> 686931/2
41	4000	6700	B		105	symmetric		1764/53/54	>> 594564
41	4000	6700	B	yes	105	symmetric		1764/53/54	>> 686764
41	4000	7300	B		120	symmetric		1764/53/54	>> 686344
41	4000	7300	B	yes	120	symmetric		1764/53/54	>> 686733
45	4000	7550	B		butterfly	DAN		1764/53/54	>> 594724
45	4000	7550	B	yes	butterfly	DAN		1764/53/54	>> 687211
45	4000	7550	B		asymmetric left	SA-L		1764/53/54	>> 686405
45	4000	7550	B	yes	asymmetric left	SA-L		1764/53/54	>> 686795
45	4000	7550	B		asymmetric right	SA-R		1764/53/54	>> 594786
45	4000	7550	B	yes	asymmetric right	SA-R		1764/53/54	>> 687242
45	4000	7550	B		butterfly	DAN R2	R2	1764/53/54	>> 594724/2
45	4000	7550	B	yes	butterfly	DAN R2	R2	1764/53/54	>> 687211/2
45	4000	7550	B		asymmetric left	SA-L R2	R2	1764/53/54	>> 686405/2
45	4000	7550	B	yes	asymmetric left	SA-L R2	R2	1764/53/54	>> 686795/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
45	4000	7550	B		asymmetric right	SA-R R2	R2	1764/53/54	>> 594786/2
45	4000	7550	B	yes	asymmetric right	SA-R R2	R2	1764/53/54	>> 687242/2
45	4000	7850	B		35/67	CN		1764/53/54	>> 594960
45	4000	7850	B	yes	35/67	CN		1764/53/54	>> 687181
45	4000	7900	B		90	MW		1764/53/54	>> 594847
45	4000	7900	B	yes	90	MW		1764/53/54	>> 687129
45	4000	7900	B		105	VW		1764/53/54	>> 594908
45	4000	7900	B	yes	105	VW		1764/53/54	>> 687150
45	4000	7900	B		90	MW R2	R2	1764/53/54	>> 594847/2
45	4000	7900	B	yes	90	MW R2	R2	1764/53/54	>> 687129/2
45	4000	7900	B		105	VW R2	R2	1764/53/54	>> 594908/2
45	4000	7900	B	yes	105	VW R2	R2	1764/53/54	>> 687150/2
52	4000	8450	B		105	symmetric		1764/53/54	>> 686368
52	4000	8450	B	yes	105	symmetric		1764/53/54	>> 686757
52	4000	9200	B		120	symmetric		1764/53/54	>> 686337
52	4000	9200	B	yes	120	symmetric		1764/53/54	>> 686726
62	4000	10000	B		105	symmetric		1764/53/54	>> 594557
62	4000	10000	B	yes	105	symmetric		1764/53/54	>> 686740
62	4000	10300	B		butterfly	DAN		1764/53/54	>> 594717
62	4000	10300	B	yes	butterfly	DAN		1764/53/54	>> 687204
62	4000	10300	B		butterfly	DAN R2	R2	1764/53/54	>> 594717/2
62	4000	10300	B	yes	butterfly	DAN R2	R2	1764/53/54	>> 687204/2
62	4000	10350	B		asymmetric left	SA-L		1764/53/54	>> 686399
62	4000	10350	B	yes	asymmetric left	SA-L		1764/53/54	>> 686788
62	4000	10350	B		asymmetric right	SA-R		1764/53/54	>> 594779
62	4000	10350	B	yes	asymmetric right	SA-R		1764/53/54	>> 687235
62	4000	10350	B		asymmetric left	SA-L R2	R2	1764/53/54	>> 686399/2
62	4000	10350	B	yes	asymmetric left	SA-L R2	R2	1764/53/54	>> 686788/2
62	4000	10350	B		asymmetric right	SA-R R2	R2	1764/53/54	>> 594779/2
62	4000	10350	B	yes	asymmetric right	SA-R R2	R2	1764/53/54	>> 687235/2
62	4000	10700	B		35/67	CN		1764/53/54	>> 594953
62	4000	10700	B	yes	35/67	CN		1764/53/54	>> 687174
62	4000	10750	B		90	MW		1764/53/54	>> 594830

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
62	4000	10750	B	yes	90	MW		1764/53/54	>> 687112
62	4000	10750	B		105	VW		1764/53/54	>> 594892
62	4000	10750	B	yes	105	VW		1764/53/54	>> 687143
62	4000	10750	B		90	MW R2	R2	1764/53/54	>> 594830/2
62	4000	10750	B	yes	90	MW R2	R2	1764/53/54	>> 687112/2
62	4000	10750	B		105	VW R2	R2	1764/53/54	>> 594892/2
62	4000	10750	B	yes	105	VW R2	R2	1764/53/54	>> 687143/2
62	4000	10900	B		120	symmetric		1764/53/54	>> 686320
62	4000	10900	B	yes	120	symmetric		1764/53/54	>> 686719
75	4000	11950	B		105	symmetric		1764/53/54	>> 594205
75	4000	11950	B	yes	105	symmetric		1764/53/54	>> 594212
75	4000	12350	B		butterfly	DAN		1764/53/54	>> 594700
75	4000	12350	B	yes	butterfly	DAN		1764/53/54	>> 687198
75	4000	12350	B		butterfly	DAN R2	R2	1764/53/54	>> 594700/2
75	4000	12350	B	yes	butterfly	DAN R2	R2	1764/53/54	>> 687198/2
75	4000	12450	B		asymmetric left	SA-L		1764/53/54	>> 686382
75	4000	12450	B	yes	asymmetric left	SA-L		1764/53/54	>> 686771
75	4000	12450	B		asymmetric right	SA-R		1764/53/54	>> 594762
75	4000	12450	B	yes	asymmetric right	SA-R		1764/53/54	>> 687228
75	4000	12450	B		asymmetric left	SA-L R2	R2	1764/53/54	>> 686382/2
75	4000	12450	B	yes	asymmetric left	SA-L R2	R2	1764/53/54	>> 686771/2
75	4000	12450	B		asymmetric right	SA-R R2	R2	1764/53/54	>> 594762/2
75	4000	12450	B	yes	asymmetric right	SA-R R2	R2	1764/53/54	>> 687228/2
75	4000	12850	B		35/67	CN		1764/53/54	>> 594946
75	4000	12850	B	yes	35/67	CN		1764/53/54	>> 687167
75	4000	12900	B		90	MW		1764/53/54	>> 594823
75	4000	12900	B	yes	90	MW		1764/53/54	>> 687105
75	4000	12900	B		105	VW		1764/53/54	>> 594885
75	4000	12900	B	yes	105	VW		1764/53/54	>> 687136
75	4000	12900	B		90	MW R2	R2	1764/53/54	>> 594823/2
75	4000	12900	B	yes	90	MW R2	R2	1764/53/54	>> 687105/2
75	4000	12900	B		105	VW R2	R2	1764/53/54	>> 594885/2
75	4000	12900	B	yes	105	VW R2	R2	1764/53/54	>> 687136/2
75	4000	13100	B		120	symmetric		1764/53/54	>> 594168

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
75	4000	13100	B	yes	120	symmetric		1764/53/54	>> 594175

Linea S LED Eco 4

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
31	4000	5200	B		105	symmetric		2940/53/54	>> 594304
31	4000	5200	B	yes	105	symmetric		2940/53/54	>> 594311
31	4000	5700	A		120	symmetric		2940/53/54	>> 594267
31	4000	5700	A	yes	120	symmetric		2940/53/54	>> 594274
33	4000	5750	B		butterfly	DAN		2940/53/54	>> 687730
33	4000	5750	B	yes	butterfly	DAN		2940/53/54	>> 688331
33	4000	5750	B		asymmetric left	SA-L		2940/53/54	>> 687815
33	4000	5750	B	yes	asymmetric left	SA-L		2940/53/54	>> 688416
33	4000	5750	B		asymmetric right	SA-R		2940/53/54	>> 687778
33	4000	5750	B	yes	asymmetric right	SA-R		2940/53/54	>> 688379
33	4000	5750	B		butterfly	DAN R2	R2	2940/53/54	>> 687730/2
33	4000	5750	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688331/2
33	4000	5750	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687815/2
33	4000	5750	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688416/2
33	4000	5750	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687778/2
33	4000	5750	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688379/2
33	4000	5950	A		35/67	CN		2940/53/54	>> 687693
33	4000	5950	A	yes	35/67	CN		2940/53/54	>> 688294
33	4000	6000	A		90	MW		2940/53/54	>> 687617
33	4000	6000	A	yes	90	MW		2940/53/54	>> 688218
33	4000	6000	A		105	VW		2940/53/54	>> 687655
33	4000	6000	A	yes	105	VW		2940/53/54	>> 688256
33	4000	6000	A		90	MW R2	R2	2940/53/54	>> 687617/2
33	4000	6000	A	yes	90	MW R2	R2	2940/53/54	>> 688218/2
33	4000	6000	A		105	VW R2	R2	2940/53/54	>> 687655/2
33	4000	6000	A	yes	105	VW R2	R2	2940/53/54	>> 688256/2
39	4000	6450	B		105	symmetric		2940/53/54	>> 687587
39	4000	6450	B	yes	105	symmetric		2940/53/54	>> 688188
39	4000	7050	A		120	symmetric		2940/53/54	>> 687556
39	4000	7050	A	yes	120	symmetric		2940/53/54	>> 688157

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
42	4000	7150	B		butterfly	DAN		2940/53/54	>> 687747
42	4000	7150	B	yes	butterfly	DAN		2940/53/54	>> 688348
42	4000	7150	B		asymmetric left	SA-L		2940/53/54	>> 687822
42	4000	7150	B	yes	asymmetric left	SA-L		2940/53/54	>> 688423
42	4000	7150	B		asymmetric right	SA-R		2940/53/54	>> 687785
42	4000	7150	B	yes	asymmetric right	SA-R		2940/53/54	>> 688386
42	4000	7150	B		butterfly	DAN R2	R2	2940/53/54	>> 687747/2
42	4000	7150	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688348/2
42	4000	7150	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687822/2
42	4000	7150	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688423/2
42	4000	7150	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687785/2
42	4000	7150	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688386/2
42	4000	7400	B		35/67	CN		2940/53/54	>> 687709
42	4000	7400	B	yes	35/67	CN		2940/53/54	>> 688300
42	4000	7450	B		90	MW		2940/53/54	>> 687624
42	4000	7450	B	yes	90	MW		2940/53/54	>> 688225
42	4000	7450	B		105	VW		2940/53/54	>> 687662
42	4000	7450	B	yes	105	VW		2940/53/54	>> 688263
42	4000	7450	B		90	MW R2	R2	2940/53/54	>> 687624/2
42	4000	7450	B	yes	90	MW R2	R2	2940/53/54	>> 688225/2
42	4000	7450	B		105	VW R2	R2	2940/53/54	>> 687662/2
42	4000	7450	B	yes	105	VW R2	R2	2940/53/54	>> 688263/2
47	4000	7700	B		105	symmetric		2940/53/54	>> 687594
47	4000	7700	B	yes	105	symmetric		2940/53/54	>> 688195
47	4000	8500	A		120	symmetric		2940/53/54	>> 687563
47	4000	8500	A	yes	120	symmetric		2940/53/54	>> 688164
50	4000	8500	B		butterfly	DAN		2940/53/54	>> 687754
50	4000	8500	B	yes	butterfly	DAN		2940/53/54	>> 688355
50	4000	8500	B		butterfly	DAN R2	R2	2940/53/54	>> 687754/2
50	4000	8500	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688355/2
50	4000	8550	B		asymmetric left	SA-L		2940/53/54	>> 687839
50	4000	8550	B	yes	asymmetric left	SA-L		2940/53/54	>> 688430

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
50	4000	8550	B		asymmetric right	SA-R		2940/53/54	>> 687792
50	4000	8550	B	yes	asymmetric right	SA-R		2940/53/54	>> 688393
50	4000	8550	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687839/2
50	4000	8550	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688430/2
50	4000	8550	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687792/2
50	4000	8550	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688393/2
50	4000	8850	B		35/67	CN		2940/53/54	>> 687716
50	4000	8850	B	yes	35/67	CN		2940/53/54	>> 688317
50	4000	8900	B		90	MW		2940/53/54	>> 687631
50	4000	8900	B	yes	90	MW		2940/53/54	>> 688232
50	4000	8900	B		105	VW		2940/53/54	>> 687679
50	4000	8900	B	yes	105	VW		2940/53/54	>> 688270
50	4000	8900	B		90	MW R2	R2	2940/53/54	>> 687631/2
50	4000	8900	B	yes	90	MW R2	R2	2940/53/54	>> 688232/2
50	4000	8900	B		105	VW R2	R2	2940/53/54	>> 687679/2
50	4000	8900	B	yes	105	VW R2	R2	2940/53/54	>> 688270/2
54	4000	9000	B		105	symmetric		2940/53/54	>> 687600
54	4000	9000	B	yes	105	symmetric		2940/53/54	>> 688201
54	4000	9900	A		120	symmetric		2940/53/54	>> 687570
54	4000	9900	A	yes	120	symmetric		2940/53/54	>> 688171
58	4000	9800	B		butterfly	DAN		2940/53/54	>> 687761
58	4000	9800	B	yes	butterfly	DAN		2940/53/54	>> 688362
58	4000	9800	B		butterfly	DAN R2	R2	2940/53/54	>> 687761/2
58	4000	9800	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688362/2
58	4000	9850	B		asymmetric left	SA-L		2940/53/54	>> 687846
58	4000	9850	B	yes	asymmetric left	SA-L		2940/53/54	>> 688447
58	4000	9850	B		asymmetric right	SA-R		2940/53/54	>> 687808
58	4000	9850	B	yes	asymmetric right	SA-R		2940/53/54	>> 688409
58	4000	9850	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687846/2
58	4000	9850	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688447/2
58	4000	9850	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687808/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
58	4000	9850	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688409/2
58	4000	10200	B		35/67	CN		2940/53/54	>> 687723
58	4000	10200	B	yes	35/67	CN		2940/53/54	>> 688324
58	4000	10250	B		90	MW		2940/53/54	>> 687648
58	4000	10250	B	yes	90	MW		2940/53/54	>> 688249
58	4000	10250	B		105	VW		2940/53/54	>> 687686
58	4000	10250	B	yes	105	VW		2940/53/54	>> 688287
58	4000	10250	B		90	MW R2	R2	2940/53/54	>> 687648/2
58	4000	10250	B	yes	90	MW R2	R2	2940/53/54	>> 688249/2
58	4000	10250	B		105	VW R2	R2	2940/53/54	>> 687686/2
58	4000	10250	B	yes	105	VW R2	R2	2940/53/54	>> 688287/2
63	4000	10500	B		105	symmetric		2940/53/54	>> 687303
63	4000	10500	B	yes	105	symmetric		2940/53/54	>> 687907
63	4000	10850	B		butterfly	DAN		2940/53/54	>> 687464
63	4000	10850	B	yes	butterfly	DAN		2940/53/54	>> 688065
63	4000	10850	B		butterfly	DAN R2	R2	2940/53/54	>> 687464/2
63	4000	10850	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688065/2
63	4000	10950	B		asymmetric left	SA-L		2940/53/54	>> 687549
63	4000	10950	B	yes	asymmetric left	SA-L		2940/53/54	>> 688140
63	4000	10950	B		asymmetric right	SA-R		2940/53/54	>> 687501
63	4000	10950	B	yes	asymmetric right	SA-R		2940/53/54	>> 688102
63	4000	10950	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687549/2
63	4000	10950	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688140/2
63	4000	10950	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687501/2
63	4000	10950	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688102/2
63	4000	11300	A		35/67	CN		2940/53/54	>> 687426
63	4000	11300	A	yes	35/67	CN		2940/53/54	>> 688027
63	4000	11350	A		90	MW		2940/53/54	>> 687341
63	4000	11350	A	yes	90	MW		2940/53/54	>> 687945
63	4000	11350	A		105	VW		2940/53/54	>> 687389
63	4000	11350	A	yes	105	VW		2940/53/54	>> 687983
63	4000	11350	A		90	MW R2	R2	2940/53/54	>> 687341/2
63	4000	11350	A	yes	90	MW R2	R2	2940/53/54	>> 687945/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
63	4000	11350	A		105	VW R2	R2	2940/53/54	>> 687389/2
63	4000	11350	A	yes	105	VW R2	R2	2940/53/54	>> 687983/2
63	4000	11500	A		120	symmetric		2940/53/54	>> 687273
63	4000	11500	A	yes	120	symmetric		2940/53/54	>> 687877
79	4000	13100	B		105	symmetric		2940/53/54	>> 687297
79	4000	13100	B	yes	105	symmetric		2940/53/54	>> 687891
79	4000	13550	B		butterfly	DAN		2940/53/54	>> 687457
79	4000	13550	B	yes	butterfly	DAN		2940/53/54	>> 688058
79	4000	13550	B		butterfly	DAN R2	R2	2940/53/54	>> 687457/2
79	4000	13550	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688058/2
79	4000	13600	B		asymmetric left	SA-L		2940/53/54	>> 687532
79	4000	13600	B	yes	asymmetric left	SA-L		2940/53/54	>> 688133
79	4000	13600	B		asymmetric right	SA-R		2940/53/54	>> 687495
79	4000	13600	B	yes	asymmetric right	SA-R		2940/53/54	>> 688096
79	4000	13600	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687532/2
79	4000	13600	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688133/2
79	4000	13600	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687495/2
79	4000	13600	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688096/2
79	4000	14050	B		35/67	CN		2940/53/54	>> 687419
79	4000	14050	B	yes	35/67	CN		2940/53/54	>> 688010
79	4000	14150	A		90	MW		2940/53/54	>> 687334
79	4000	14150	A	yes	90	MW		2940/53/54	>> 687938
79	4000	14150	A		105	VW		2940/53/54	>> 687372
79	4000	14150	A	yes	105	VW		2940/53/54	>> 687976
79	4000	14150	A		90	MW R2	R2	2940/53/54	>> 687334/2
79	4000	14150	A	yes	90	MW R2	R2	2940/53/54	>> 687938/2
79	4000	14150	A		105	VW R2	R2	2940/53/54	>> 687372/2
79	4000	14150	A	yes	105	VW R2	R2	2940/53/54	>> 687976/2
79	4000	14250	A		120	symmetric		2940/53/54	>> 687266
79	4000	14250	A	yes	120	symmetric		2940/53/54	>> 687860
95	4000	15600	B		105	symmetric		2940/53/54	>> 687280
95	4000	15600	B	yes	105	symmetric		2940/53/54	>> 687884
95	4000	16150	B		butterfly	DAN		2940/53/54	>> 687440
95	4000	16150	B	yes	butterfly	DAN		2940/53/54	>> 688041

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
95	4000	16150	B		butterfly	DAN R2	R2	2940/53/54	>> 687440/2
95	4000	16150	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688041/2
95	4000	16200	B		asymmetric left	SA-L		2940/53/54	>> 687525
95	4000	16200	B	yes	asymmetric left	SA-L		2940/53/54	>> 688126
95	4000	16200	B		asymmetric right	SA-R		2940/53/54	>> 687488
95	4000	16200	B	yes	asymmetric right	SA-R		2940/53/54	>> 688089
95	4000	16200	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687525/2
95	4000	16200	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688126/2
95	4000	16200	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687488/2
95	4000	16200	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688089/2
95	4000	16750	B		35/67	CN		2940/53/54	>> 687402
95	4000	16750	B	yes	35/67	CN		2940/53/54	>> 688003
95	4000	16850	B		90	MW		2940/53/54	>> 687327
95	4000	16850	B	yes	90	MW		2940/53/54	>> 687921
95	4000	16850	B		105	VW		2940/53/54	>> 687365
95	4000	16850	B	yes	105	VW		2940/53/54	>> 687969
95	4000	16850	B		90	MW R2	R2	2940/53/54	>> 687327/2
95	4000	16850	B	yes	90	MW R2	R2	2940/53/54	>> 687921/2
95	4000	16850	B		105	VW R2	R2	2940/53/54	>> 687365/2
95	4000	16850	B	yes	105	VW R2	R2	2940/53/54	>> 687969/2
95	4000	17000	A		120	symmetric		2940/53/54	>> 687259
95	4000	17000	A	yes	120	symmetric		2940/53/54	>> 687853
111	4000	18250	B		105	symmetric		2940/53/54	>> 594281
111	4000	18250	B	yes	105	symmetric		2940/53/54	>> 594298
111	4000	18900	B		butterfly	DAN		2940/53/54	>> 687433
111	4000	18900	B	yes	butterfly	DAN		2940/53/54	>> 688034
111	4000	18900	B		butterfly	DAN R2	R2	2940/53/54	>> 687433/2
111	4000	18900	B	yes	butterfly	DAN R2	R2	2940/53/54	>> 688034/2
111	4000	19000	B		asymmetric left	SA-L		2940/53/54	>> 687518
111	4000	19000	B	yes	asymmetric left	SA-L		2940/53/54	>> 688119
111	4000	19000	B		asymmetric right	SA-R		2940/53/54	>> 687471
111	4000	19000	B	yes	asymmetric right	SA-R		2940/53/54	>> 688072

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
111	4000	19000	B		asymmetric left	SA-L R2	R2	2940/53/54	>> 687518/2
111	4000	19000	B	yes	asymmetric left	SA-L R2	R2	2940/53/54	>> 688119/2
111	4000	19000	B		asymmetric right	SA-R R2	R2	2940/53/54	>> 687471/2
111	4000	19000	B	yes	asymmetric right	SA-R R2	R2	2940/53/54	>> 688072/2
111	4000	19650	B		35/67	CN		2940/53/54	>> 687396
111	4000	19650	B	yes	35/67	CN		2940/53/54	>> 687990
111	4000	19750	B		90	MW		2940/53/54	>> 687310
111	4000	19750	B	yes	90	MW		2940/53/54	>> 687914
111	4000	19750	B		105	VW		2940/53/54	>> 687358
111	4000	19750	B	yes	105	VW		2940/53/54	>> 687952
111	4000	19750	B		90	MW R2	R2	2940/53/54	>> 687310/2
111	4000	19750	B	yes	90	MW R2	R2	2940/53/54	>> 687914/2
111	4000	19750	B		105	VW R2	R2	2940/53/54	>> 687358/2
111	4000	19750	B	yes	105	VW R2	R2	2940/53/54	>> 687952/2
111	4000	20000	A		120	symmetric		2940/53/54	>> 594243
111	4000	20000	A	yes	120	symmetric		2940/53/54	>> 594250

Linea S LED Eco 5

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
37	4000	6200	B		105	symmetric		3528/53/54	>> 594380
37	4000	6200	B	yes	105	symmetric		3528/53/54	>> 594397
37	4000	6800	A		120	symmetric		3528/53/54	>> 594342
37	4000	6800	A	yes	120	symmetric		3528/53/54	>> 594359
40	4000	6950	B		butterfly	DAN		3528/53/54	>> 689185
40	4000	6950	B	yes	butterfly	DAN		3528/53/54	>> 689482
40	4000	6950	B		asymmetric left	SA-L		3528/53/54	>> 689260
40	4000	6950	B	yes	asymmetric left	SA-L		3528/53/54	>> 689567
40	4000	6950	B		asymmetric right	SA-R		3528/53/54	>> 689222
40	4000	6950	B	yes	asymmetric right	SA-R		3528/53/54	>> 689529
40	4000	6950	B		butterfly	DAN R2	R2	3528/53/54	>> 689185/2
40	4000	6950	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 689482/2
40	4000	6950	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 689260/2
40	4000	6950	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 689567/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
40	4000	6950	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 689222/2
40	4000	6950	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 689529/2
40	4000	7200	A		35/67	CN		3528/53/54	>> 689147
40	4000	7200	A	yes	35/67	CN		3528/53/54	>> 689444
40	4000	7250	A		90	MW		3528/53/54	>> 689062
40	4000	7250	A	yes	90	MW		3528/53/54	>> 689369
40	4000	7250	A		105	VW		3528/53/54	>> 689109
40	4000	7250	A	yes	105	VW		3528/53/54	>> 689406
40	4000	7250	A		90	MW R2	R2	3528/53/54	>> 689062/2
40	4000	7250	A	yes	90	MW R2	R2	3528/53/54	>> 689369/2
40	4000	7250	A		105	VW R2	R2	3528/53/54	>> 689109/2
40	4000	7250	A	yes	105	VW R2	R2	3528/53/54	>> 689406/2
47	4000	7700	B		105	symmetric		3528/53/54	>> 689031
47	4000	7700	B	yes	105	symmetric		3528/53/54	>> 689338
47	4000	8500	A		120	symmetric		3528/53/54	>> 689000
47	4000	8500	A	yes	120	symmetric		3528/53/54	>> 689307
50	4000	8600	B		butterfly	DAN		3528/53/54	>> 689192
50	4000	8600	B	yes	butterfly	DAN		3528/53/54	>> 689499
50	4000	8600	B		butterfly	DAN R2	R2	3528/53/54	>> 689192/2
50	4000	8600	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 689499/2
50	4000	8650	B		asymmetric left	SA-L		3528/53/54	>> 689277
50	4000	8650	B	yes	asymmetric left	SA-L		3528/53/54	>> 689574
50	4000	8650	B		asymmetric right	SA-R		3528/53/54	>> 689239
50	4000	8650	B	yes	asymmetric right	SA-R		3528/53/54	>> 689536
50	4000	8650	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 689277/2
50	4000	8650	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 689574/2
50	4000	8650	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 689239/2
50	4000	8650	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 689536/2
50	4000	8950	A		35/67	CN		3528/53/54	>> 689154
50	4000	8950	A	yes	35/67	CN		3528/53/54	>> 689451
50	4000	9000	A		90	MW		3528/53/54	>> 689079
50	4000	9000	A	yes	90	MW		3528/53/54	>> 689376
50	4000	9000	A		105	VW		3528/53/54	>> 689116

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
50	4000	9000	A	yes	105	VW		3528/53/54	>> 689413
50	4000	9000	A		90	MW R2	R2	3528/53/54	>> 689079/2
50	4000	9000	A	yes	90	MW R2	R2	3528/53/54	>> 689376/2
50	4000	9000	A		105	VW R2	R2	3528/53/54	>> 689116/2
50	4000	9000	A	yes	105	VW R2	R2	3528/53/54	>> 689413/2
56	4000	9250	B		105	symmetric		3528/53/54	>> 689048
56	4000	9250	B	yes	105	symmetric		3528/53/54	>> 689345
56	4000	10200	A		120	symmetric		3528/53/54	>> 689017
56	4000	10200	A	yes	120	symmetric		3528/53/54	>> 689314
61	4000	10350	B		butterfly	DAN		3528/53/54	>> 689208
61	4000	10350	B	yes	butterfly	DAN		3528/53/54	>> 689505
61	4000	10350	B		butterfly	DAN R2	R2	3528/53/54	>> 689208/2
61	4000	10350	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 689505/2
61	4000	10400	B		asymmetric left	SA-L		3528/53/54	>> 689284
61	4000	10400	B	yes	asymmetric left	SA-L		3528/53/54	>> 689581
61	4000	10400	B		asymmetric right	SA-R		3528/53/54	>> 689246
61	4000	10400	B	yes	asymmetric right	SA-R		3528/53/54	>> 689543
61	4000	10400	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 689284/2
61	4000	10400	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 689581/2
61	4000	10400	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 689246/2
61	4000	10400	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 689543/2
61	4000	10750	B		35/67	CN		3528/53/54	>> 689161
61	4000	10750	B	yes	35/67	CN		3528/53/54	>> 689468
61	4000	10800	B		90	MW		3528/53/54	>> 689086
61	4000	10800	B	yes	90	MW		3528/53/54	>> 689383
61	4000	10800	B		105	VW		3528/53/54	>> 689123
61	4000	10800	B	yes	105	VW		3528/53/54	>> 689420
61	4000	10800	B		90	MW R2	R2	3528/53/54	>> 689086/2
61	4000	10800	B	yes	90	MW R2	R2	3528/53/54	>> 689383/2
61	4000	10800	B		105	VW R2	R2	3528/53/54	>> 689123/2
61	4000	10800	B	yes	105	VW R2	R2	3528/53/54	>> 689420/2
66	4000	10800	B		105	symmetric		3528/53/54	>> 594601
66	4000	10800	B	yes	105	symmetric		3528/53/54	>> 689352
66	4000	11900	A		120	symmetric		3528/53/54	>> 689024

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
66	4000	11900	A	yes	120	symmetric		3528/53/54	>> 689321
71	4000	12000	B		butterfly	DAN		3528/53/54	>> 689215
71	4000	12000	B	yes	butterfly	DAN		3528/53/54	>> 689512
71	4000	12000	B		butterfly	DAN R2	R2	3528/53/54	>> 689215/2
71	4000	12000	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 689512/2
71	4000	12050	B		asymmetric left	SA-L		3528/53/54	>> 689291
71	4000	12050	B	yes	asymmetric left	SA-L		3528/53/54	>> 689598
71	4000	12050	B		asymmetric right	SA-R		3528/53/54	>> 689253
71	4000	12050	B	yes	asymmetric right	SA-R		3528/53/54	>> 689550
71	4000	12050	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 689291/2
71	4000	12050	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 689598/2
71	4000	12050	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 689253/2
71	4000	12050	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 689550/2
71	4000	12450	B		35/67	CN		3528/53/54	>> 689178
71	4000	12450	B	yes	35/67	CN		3528/53/54	>> 689475
71	4000	12500	B		90	MW		3528/53/54	>> 689093
71	4000	12500	B	yes	90	MW		3528/53/54	>> 689390
71	4000	12500	B		105	VW		3528/53/54	>> 689130
71	4000	12500	B	yes	105	VW		3528/53/54	>> 689437
71	4000	12500	B		90	MW R2	R2	3528/53/54	>> 689093/2
71	4000	12500	B	yes	90	MW R2	R2	3528/53/54	>> 689390/2
71	4000	12500	B		105	VW R2	R2	3528/53/54	>> 689130/2
71	4000	12500	B	yes	105	VW R2	R2	3528/53/54	>> 689437/2
82	4000	13300	B		105	symmetric		3528/53/54	>> 594588
82	4000	13300	B	yes	105	symmetric		3528/53/54	>> 688676
82	4000	13750	B		butterfly	DAN		3528/53/54	>> 594755
82	4000	13750	B	yes	butterfly	DAN		3528/53/54	>> 688836
82	4000	13750	B		butterfly	DAN R2	R2	3528/53/54	>> 594755/2
82	4000	13750	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 688836/2
82	4000	13850	B		asymmetric left	SA-L		3528/53/54	>> 688614
82	4000	13850	B	yes	asymmetric left	SA-L		3528/53/54	>> 688911
82	4000	13850	B		asymmetric right	SA-R		3528/53/54	>> 594816

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
82	4000	13850	B	yes	asymmetric right	SA-R		3528/53/54	>> 688874
82	4000	13850	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 688614/2
82	4000	13850	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 688911/2
82	4000	13850	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 594816/2
82	4000	13850	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 688874/2
82	4000	14300	B		35/67	CN		3528/53/54	>> 594991
82	4000	14300	B	yes	35/67	CN		3528/53/54	>> 688799
82	4000	14350	B		90	MW		3528/53/54	>> 594878
82	4000	14350	B	yes	90	MW		3528/53/54	>> 688713
82	4000	14350	B		105	VW		3528/53/54	>> 594939
82	4000	14350	B	yes	105	VW		3528/53/54	>> 688751
82	4000	14350	B		90	MW R2	R2	3528/53/54	>> 594878/2
82	4000	14350	B	yes	90	MW R2	R2	3528/53/54	>> 688713/2
82	4000	14350	B		105	VW R2	R2	3528/53/54	>> 594939/2
82	4000	14350	B	yes	105	VW R2	R2	3528/53/54	>> 688751/2
82	4000	14600	B		120	symmetric		3528/53/54	>> 688515
82	4000	14600	B	yes	120	symmetric		3528/53/54	>> 688645
103	4000	16650	B		105	symmetric		3528/53/54	>> 688522
103	4000	16650	B	yes	105	symmetric		3528/53/54	>> 688669
103	4000	17250	B		butterfly	DAN		3528/53/54	>> 688560
103	4000	17250	B	yes	butterfly	DAN		3528/53/54	>> 688829
103	4000	17250	B		butterfly	DAN R2	R2	3528/53/54	>> 688560/2
103	4000	17250	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 688829/2
103	4000	17300	B		asymmetric left	SA-L		3528/53/54	>> 688607
103	4000	17300	B	yes	asymmetric left	SA-L		3528/53/54	>> 688904
103	4000	17300	B		asymmetric right	SA-R		3528/53/54	>> 688577
103	4000	17300	B	yes	asymmetric right	SA-R		3528/53/54	>> 688867
103	4000	17300	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 688607/2
103	4000	17300	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 688904/2
103	4000	17300	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 688577/2
103	4000	17300	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 688867/2

LINEA S LED ECO

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
103	4000	17900	B		35/67	CN		3528/53/54	>> 688553
103	4000	17900	B	yes	35/67	CN		3528/53/54	>> 688782
103	4000	18000	B		90	MW		3528/53/54	>> 688539
103	4000	18000	B	yes	90	MW		3528/53/54	>> 688706
103	4000	18000	B		105	VW		3528/53/54	>> 688546
103	4000	18000	B	yes	105	VW		3528/53/54	>> 688744
103	4000	18000	B		90	MW R2	R2	3528/53/54	>> 688539/2
103	4000	18000	B	yes	90	MW R2	R2	3528/53/54	>> 688706/2
103	4000	18000	B		105	VW R2	R2	3528/53/54	>> 688546/2
103	4000	18000	B	yes	105	VW R2	R2	3528/53/54	>> 688744/2
103	4000	18250	B		120	symmetric		3528/53/54	>> 688508
103	4000	18250	B	yes	120	symmetric		3528/53/54	>> 688638
123	4000	19950	B		105	symmetric		3528/53/54	>> 594571
123	4000	19950	B	yes	105	symmetric		3528/53/54	>> 688652
123	4000	20650	B		butterfly	DAN		3528/53/54	>> 594748
123	4000	20650	B	yes	butterfly	DAN		3528/53/54	>> 688812
123	4000	20650	B		butterfly	DAN R2	R2	3528/53/54	>> 594748/2
123	4000	20650	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 688812/2
123	4000	20750	B		asymmetric left	SA-L		3528/53/54	>> 688591
123	4000	20750	B	yes	asymmetric left	SA-L		3528/53/54	>> 688898
123	4000	20750	B		asymmetric right	SA-R		3528/53/54	>> 594809
123	4000	20750	B	yes	asymmetric right	SA-R		3528/53/54	>> 688850
123	4000	20750	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 688591/2
123	4000	20750	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 688898/2
123	4000	20750	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 594809/2
123	4000	20750	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 688850/2
123	4000	21450	B		35/67	CN		3528/53/54	>> 594984
123	4000	21450	B	yes	35/67	CN		3528/53/54	>> 688775
123	4000	21550	B		90	MW		3528/53/54	>> 594861
123	4000	21550	B	yes	90	MW		3528/53/54	>> 688690
123	4000	21550	B		105	VW		3528/53/54	>> 594922
123	4000	21550	B	yes	105	VW		3528/53/54	>> 688737
123	4000	21550	B		90	MW R2	R2	3528/53/54	>> 594861/2
123	4000	21550	B	yes	90	MW R2	R2	3528/53/54	>> 688690/2

LINEA S LED ECO


GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	DIMM DALI	Beam angle [°]	Light distribution type	Version	Dimensions (H/W/T/S) [mm]	Index
123	4000	21550	B		105	VW R2	R2	3528/53/54	>> 594922/2
123	4000	21550	B	yes	105	VW R2	R2	3528/53/54	>> 688737/2
123	4000	21900	B		120	symmetric		3528/53/54	>> 688492
123	4000	21900	B	yes	120	symmetric		3528/53/54	>> 688621
143	4000	23350	B		105	symmetric		3528/53/54	>> 594366
143	4000	23350	B	yes	105	symmetric		3528/53/54	>> 594373
143	4000	24150	B		butterfly	DAN		3528/53/54	>> 594731
143	4000	24150	B	yes	butterfly	DAN		3528/53/54	>> 688805
143	4000	24150	B		butterfly	DAN R2	R2	3528/53/54	>> 594731/2
143	4000	24150	B	yes	butterfly	DAN R2	R2	3528/53/54	>> 688805/2
143	4000	24250	B		asymmetric left	SA-L		3528/53/54	>> 688584
143	4000	24250	B	yes	asymmetric left	SA-L		3528/53/54	>> 688881
143	4000	24250	B		asymmetric right	SA-R		3528/53/54	>> 594793
143	4000	24250	B	yes	asymmetric right	SA-R		3528/53/54	>> 688843
143	4000	24250	B		asymmetric left	SA-L R2	R2	3528/53/54	>> 688584/2
143	4000	24250	B	yes	asymmetric left	SA-L R2	R2	3528/53/54	>> 688881/2
143	4000	24250	B		asymmetric right	SA-R R2	R2	3528/53/54	>> 594793/2
143	4000	24250	B	yes	asymmetric right	SA-R R2	R2	3528/53/54	>> 688843/2
143	4000	25050	B		35/67	CN		3528/53/54	>> 594977
143	4000	25050	B	yes	35/67	CN		3528/53/54	>> 688768
143	4000	25200	B		90	MW		3528/53/54	>> 594854
143	4000	25200	B	yes	90	MW		3528/53/54	>> 688683
143	4000	25200	B		105	VW		3528/53/54	>> 594915
143	4000	25200	B	yes	105	VW		3528/53/54	>> 688720
143	4000	25200	B		90	MW R2	R2	3528/53/54	>> 594854/2
143	4000	25200	B	yes	90	MW R2	R2	3528/53/54	>> 688683/2
143	4000	25200	B		105	VW R2	R2	3528/53/54	>> 594915/2
143	4000	25200	B	yes	105	VW R2	R2	3528/53/54	>> 688720/2
143	4000	25600	A		120	symmetric		3528/53/54	>> 594328
143	4000	25600	A	yes	120	symmetric		3528/53/54	>> 594335


LINEA S LED ECO

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



105D



120D

LINEA S LED ECO


GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
594465	LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm DALI zoom 22-55st. White 840 20W
981173	LINEA S LED hang 1.5m
	LINEA S LED hang 3m
594472	LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm zoom 22-55st. White 840 20W
981425	LINEA S LED chain pendant
594458	LINEA S LED ECO 588mm 260lm AW DOT CS 2W 1h NM AT
981418	LINEA S LED pendant sm 1.5
980961	LINEA S LED pendant sm 3m
980954	Linea S LED surface mount bracket
594403	LINEA S LED ECO - metal cover 588mm
594410	LINEA S LED ECO - metal cover 1176mm
594427	LINEA S LED ECO - metal cover 1764mm
594434	LINEA S LED ECO - metal cover 2940mm
594441	LINEA S LED ECO - metal cover 3528mm
594496	LINEA S LED ECO - metal cover 588mm DALI
594502	LINEA S LED ECO - metal cover 1176mm DALI
594519	LINEA S LED ECO - metal cover 1764mm DALI
594526	LINEA S LED ECO - metal cover 2940mm DALI
594533	LINEA S LED ECO - metal cover 3528mm DALI
594489	LINEA S LED ECO - termination set

LINEA S LED ECO


GENERAL CARD



LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm DALI zoom 22-55st. White 840 20W (594465)




LINEA S LED hang 1.5m (981173)




LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm zoom 22-55st. White 840 20W (594472)



LINEA S LED chain pendant (981425)



LINEA S LED ECO 588mm 260lm AW DOT CS 2W 1h NM AT (594458)



Linea S LED surface mount bracket (980954)

Linea S LED has been equipped with new light distributions:

SW – standard wide lens (conventional angle 80D) with wide application in commercial facilities, industrial halls and even - due to the low UGR glare index.
MW – medium wide lens (conventional angle 90D) with wide application in commercial facilities, industrial halls and even - due to the low UGR glare index.
VW – very wide lens (conventional angle 105D) with wide application in open spaces and low warehouses. It provides high lighting efficiency and helps to meet the most stringent requirements of the EN 12464-1 standard in terms of the glare index (UGR<22, UGR<25), lighting intensity and high uniformity when installing the system in low rooms. Particularly recommended for rooms where lighting fixtures are mounted at a height of 2.5-5 m.
CN - corridor narrow lens (35/67D conventional angle) for lighting communication in industrial halls and rack alleys in high-storage warehouses. Particularly recommended for rooms where lighting fixtures are mounted at a height of 7-12 m.
DAN - butterfly lens, double asymmetric narrow (double asymmetric narrow) for lighting shelves in commercial facilities, where directing light to the displayed goods is key. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-4.5 m.
SA-L - single asymmetric lens (single asymmetric, left - view from the power supply side) for one-sided lighting of shelf surfaces in commercial spaces, boards, advertising surfaces located on the walls of the building, lighting of work surfaces in conditions where it is not possible to place fixtures directly above them. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-4.5 m.
SA-R – single asymmetric lens (single asymmetric, right – view from the power supply side) for one-sided lighting of shelf surfaces in retail spaces, boards, advertising surfaces located on the walls of the building, lighting of work surfaces in conditions where it is not possible to place the luminaires directly above them. Particularly recommended for rooms where the luminaires are mounted at a height of 3-4.5 m.