

LINEA S LED ECO

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|---|---|
| Ingress protection: | IP40 |
| Impact resistance: | IK03 |
| Rated power of the luminaire [W]*: | 7.00 - 143.00 |
| Luminous flux [lm]*: | 1000 - 25600 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | A; B; C |
| Material of the body: | coated steel |
| Colour of the body: | RAL9010 |
| Diffuser material: | PC |
| Diffuser type: | matrix led |
| Mounting version: | surface, suspended |
| Dimensions (H/W/T/S) [mm]: | 588/53/54; 1176/53/54; 1764/53/54; 2940/53/54; 3528/53/54 |
| HACCP: | 852/2004 |

CHARACTERISTICS

Linea S LED Eco is a surface-mounted and pendant light-line system, representing a new generation of luminaires dedicated to LED technology. The design used allows for easy installation and power connection. The steel body, designed from the ground up, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. The ECO version is dedicated to investments where the length of individual light lines supplied from a single cable (not including modules with bezels and not including current protection) does not exceed 40m. The light modules are permanently connected to the carrier modules using dedicated cubes. The optics used in the other luminaires of the LINEA S family are possible.

APPLICATION

A versatile led lamp for indoor use, particularly suitable for lighting large-scale commercial buildings, possibly on production and storage halls.

LINEA S LED ECO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Linea S LED Eco 1

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 7 | 4000 | 1000 | C | | 105 | symmetric | 588/53/54 | >> 594069 |
| 7 | 4000 | 1000 | C | yes | 105 | symmetric | 588/53/54 | >> 594076 |
| 7 | 4000 | 1100 | C | | 120 | symmetric | 588/53/54 | >> 594021 |
| 7 | 4000 | 1100 | C | yes | 120 | symmetric | 588/53/54 | >> 594038 |
| 8 | 4000 | 1150 | C | | butterfly | DAN | 588/53/54 | >> 666476 |
| 8 | 4000 | 1150 | C | yes | butterfly | DAN | 588/53/54 | >> 667534 |
| 8 | 4000 | 1150 | C | | asymmetric left | SA-L | 588/53/54 | >> 686047 |
| 8 | 4000 | 1150 | C | yes | asymmetric left | SA-L | 588/53/54 | >> 686207 |
| 8 | 4000 | 1150 | C | | asymmetric right | SA-R | 588/53/54 | >> 666513 |
| 8 | 4000 | 1150 | C | yes | asymmetric right | SA-R | 588/53/54 | >> 667572 |
| 8 | 4000 | 1200 | C | | 35/67 | CN | 588/53/54 | >> 666438 |
| 8 | 4000 | 1200 | C | yes | 35/67 | CN | 588/53/54 | >> 667497 |
| 8 | 4000 | 1200 | C | | 90 | MW | 588/53/54 | >> 666353 |
| 8 | 4000 | 1200 | C | yes | 90 | MW | 588/53/54 | >> 667411 |
| 8 | 4000 | 1200 | C | | 105 | VW | 588/53/54 | >> 666391 |
| 8 | 4000 | 1200 | C | yes | 105 | VW | 588/53/54 | >> 667459 |
| 9 | 4000 | 1350 | C | | 105 | symmetric | 588/53/54 | >> 666322 |
| 9 | 4000 | 1350 | C | yes | 105 | symmetric | 588/53/54 | >> 667381 |
| 9 | 4000 | 1450 | B | | 120 | symmetric | 588/53/54 | >> 666292 |
| 9 | 4000 | 1450 | B | yes | 120 | symmetric | 588/53/54 | >> 667350 |
| 10 | 4000 | 1450 | C | | butterfly | DAN | 588/53/54 | >> 666483 |
| 10 | 4000 | 1450 | C | yes | butterfly | DAN | 588/53/54 | >> 667541 |
| 10 | 4000 | 1450 | C | | asymmetric left | SA-L | 588/53/54 | >> 686054 |
| 10 | 4000 | 1450 | C | yes | asymmetric left | SA-L | 588/53/54 | >> 686214 |
| 10 | 4000 | 1450 | C | | asymmetric right | SA-R | 588/53/54 | >> 666520 |
| 10 | 4000 | 1450 | C | yes | asymmetric right | SA-R | 588/53/54 | >> 667589 |
| 10 | 4000 | 1500 | C | | 35/67 | CN | 588/53/54 | >> 666445 |
| 10 | 4000 | 1500 | C | yes | 35/67 | CN | 588/53/54 | >> 667503 |
| 10 | 4000 | 1500 | C | | 90 | MW | 588/53/54 | >> 666360 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 10 | 4000 | 1500 | C | yes | 90 | MW | 588/53/54 | >> 667428 |
| 10 | 4000 | 1500 | C | | 105 | VW | 588/53/54 | >> 666407 |
| 10 | 4000 | 1500 | C | yes | 105 | VW | 588/53/54 | >> 667466 |
| 11 | 4000 | 1600 | C | | 105 | symmetric | 588/53/54 | >> 666339 |
| 11 | 4000 | 1600 | C | yes | 105 | symmetric | 588/53/54 | >> 667398 |
| 11 | 4000 | 1700 | C | | 120 | symmetric | 588/53/54 | >> 666308 |
| 11 | 4000 | 1700 | C | yes | 120 | symmetric | 588/53/54 | >> 667367 |
| 12 | 4000 | 1700 | C | | butterfly | DAN | 588/53/54 | >> 666490 |
| 12 | 4000 | 1700 | C | yes | butterfly | DAN | 588/53/54 | >> 667558 |
| 12 | 4000 | 1700 | C | | asymmetric left | SA-L | 588/53/54 | >> 686061 |
| 12 | 4000 | 1700 | C | yes | asymmetric left | SA-L | 588/53/54 | >> 686221 |
| 12 | 4000 | 1700 | C | | asymmetric right | SA-R | 588/53/54 | >> 666537 |
| 12 | 4000 | 1700 | C | yes | asymmetric right | SA-R | 588/53/54 | >> 667596 |
| 12 | 4000 | 1800 | C | | 105 | symmetric | 588/53/54 | >> 666346 |
| 12 | 4000 | 1800 | C | yes | 105 | symmetric | 588/53/54 | >> 667404 |
| 12 | 4000 | 1800 | C | | 35/67 | CN | 588/53/54 | >> 666452 |
| 12 | 4000 | 1800 | C | yes | 35/67 | CN | 588/53/54 | >> 667510 |
| 12 | 4000 | 1800 | C | | 90 | MW | 588/53/54 | >> 666377 |
| 12 | 4000 | 1800 | C | yes | 90 | MW | 588/53/54 | >> 667435 |
| 12 | 4000 | 1800 | C | | 105 | VW | 588/53/54 | >> 666414 |
| 12 | 4000 | 1800 | C | yes | 105 | VW | 588/53/54 | >> 667473 |
| 12 | 4000 | 1950 | B | | 120 | symmetric | 588/53/54 | >> 666315 |
| 12 | 4000 | 1950 | B | yes | 120 | symmetric | 588/53/54 | >> 667374 |
| 13 | 4000 | 1950 | C | | butterfly | DAN | 588/53/54 | >> 666506 |
| 13 | 4000 | 1950 | C | yes | butterfly | DAN | 588/53/54 | >> 667565 |
| 13 | 4000 | 1950 | C | | asymmetric left | SA-L | 588/53/54 | >> 686078 |
| 13 | 4000 | 1950 | C | yes | asymmetric left | SA-L | 588/53/54 | >> 686238 |
| 13 | 4000 | 1950 | C | | asymmetric right | SA-R | 588/53/54 | >> 666544 |
| 13 | 4000 | 1950 | C | yes | asymmetric right | SA-R | 588/53/54 | >> 667602 |
| 13 | 4000 | 2050 | B | | 35/67 | CN | 588/53/54 | >> 666469 |
| 13 | 4000 | 2050 | B | yes | 35/67 | CN | 588/53/54 | >> 667527 |
| 13 | 4000 | 2050 | B | | 90 | MW | 588/53/54 | >> 666384 |
| 13 | 4000 | 2050 | B | yes | 90 | MW | 588/53/54 | >> 667442 |
| 13 | 4000 | 2050 | B | | 105 | VW | 588/53/54 | >> 666421 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 13 | 4000 | 2050 | B | yes | 105 | VW | 588/53/54 | >> 667480 |
| 16 | 4000 | 2400 | C | | 105 | symmetric | 588/53/54 | >> 666056 |
| 16 | 4000 | 2400 | C | yes | 105 | symmetric | 588/53/54 | >> 667138 |
| 16 | 4000 | 2450 | C | | butterfly | DAN | 588/53/54 | >> 666247 |
| 16 | 4000 | 2450 | C | yes | butterfly | DAN | 588/53/54 | >> 667305 |
| 16 | 4000 | 2450 | C | | asymmetric left | SA-L | 588/53/54 | >> 686030 |
| 16 | 4000 | 2450 | C | yes | asymmetric left | SA-L | 588/53/54 | >> 686191 |
| 16 | 4000 | 2450 | C | | asymmetric right | SA-R | 588/53/54 | >> 666285 |
| 16 | 4000 | 2450 | C | yes | asymmetric right | SA-R | 588/53/54 | >> 667343 |
| 16 | 4000 | 2550 | B | | 35/67 | CN | 588/53/54 | >> 666193 |
| 16 | 4000 | 2550 | B | yes | 35/67 | CN | 588/53/54 | >> 667268 |
| 16 | 4000 | 2550 | B | | 90 | MW | 588/53/54 | >> 666094 |
| 16 | 4000 | 2550 | B | yes | 90 | MW | 588/53/54 | >> 667176 |
| 16 | 4000 | 2550 | B | | 105 | VW | 588/53/54 | >> 666155 |
| 16 | 4000 | 2550 | B | yes | 105 | VW | 588/53/54 | >> 667213 |
| 16 | 4000 | 2600 | B | | 120 | symmetric | 588/53/54 | >> 666025 |
| 16 | 4000 | 2600 | B | yes | 120 | symmetric | 588/53/54 | >> 667091 |
| 20 | 4000 | 2950 | C | | 105 | symmetric | 588/53/54 | >> 666049 |
| 20 | 4000 | 2950 | C | yes | 105 | symmetric | 588/53/54 | >> 667114 |
| 20 | 4000 | 3050 | C | | butterfly | DAN | 588/53/54 | >> 666223 |
| 20 | 4000 | 3050 | C | yes | butterfly | DAN | 588/53/54 | >> 667299 |
| 20 | 4000 | 3050 | C | | asymmetric left | SA-L | 588/53/54 | >> 686023 |
| 20 | 4000 | 3050 | C | yes | asymmetric left | SA-L | 588/53/54 | >> 686184 |
| 20 | 4000 | 3050 | C | | asymmetric right | SA-R | 588/53/54 | >> 666278 |
| 20 | 4000 | 3050 | C | yes | asymmetric right | SA-R | 588/53/54 | >> 667336 |
| 20 | 4000 | 3150 | B | | 35/67 | CN | 588/53/54 | >> 666186 |
| 20 | 4000 | 3150 | B | yes | 35/67 | CN | 588/53/54 | >> 667251 |
| 20 | 4000 | 3150 | B | | 90 | MW | 588/53/54 | >> 666087 |
| 20 | 4000 | 3150 | B | yes | 90 | MW | 588/53/54 | >> 667169 |
| 20 | 4000 | 3150 | B | | 105 | VW | 588/53/54 | >> 666148 |
| 20 | 4000 | 3150 | B | yes | 105 | VW | 588/53/54 | >> 667206 |
| 20 | 4000 | 3200 | B | | 120 | symmetric | 588/53/54 | >> 666018 |
| 20 | 4000 | 3200 | B | yes | 120 | symmetric | 588/53/54 | >> 667084 |
| 23 | 4000 | 3400 | C | | 105 | symmetric | 588/53/54 | >> 666032 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 23 | 4000 | 3400 | C | yes | 105 | symmetric | 588/53/54 | >> 667107 |
| 23 | 4000 | 3500 | C | | butterfly | DAN | 588/53/54 | >> 666216 |
| 23 | 4000 | 3500 | C | yes | butterfly | DAN | 588/53/54 | >> 667282 |
| 23 | 4000 | 3500 | C | | asymmetric left | SA-L | 588/53/54 | >> 686016 |
| 23 | 4000 | 3500 | C | yes | asymmetric left | SA-L | 588/53/54 | >> 686177 |
| 23 | 4000 | 3500 | C | | asymmetric right | SA-R | 588/53/54 | >> 666261 |
| 23 | 4000 | 3500 | C | yes | asymmetric right | SA-R | 588/53/54 | >> 667329 |
| 23 | 4000 | 3650 | B | | 35/67 | CN | 588/53/54 | >> 666179 |
| 23 | 4000 | 3650 | B | yes | 35/67 | CN | 588/53/54 | >> 667244 |
| 23 | 4000 | 3650 | B | | 90 | MW | 588/53/54 | >> 666070 |
| 23 | 4000 | 3650 | B | yes | 90 | MW | 588/53/54 | >> 667152 |
| 23 | 4000 | 3650 | B | | 105 | VW | 588/53/54 | >> 666117 |
| 23 | 4000 | 3650 | B | yes | 105 | VW | 588/53/54 | >> 667190 |
| 23 | 4000 | 3700 | B | | 120 | symmetric | 588/53/54 | >> 666001 |
| 23 | 4000 | 3700 | B | yes | 120 | symmetric | 588/53/54 | >> 667077 |
| 25 | 4000 | 3850 | C | | 105 | symmetric | 588/53/54 | >> 594045 |
| 25 | 4000 | 3850 | C | yes | 105 | symmetric | 588/53/54 | >> 594052 |
| 25 | 4000 | 4050 | B | | butterfly | DAN | 588/53/54 | >> 666209 |
| 25 | 4000 | 4050 | B | yes | butterfly | DAN | 588/53/54 | >> 667275 |
| 25 | 4000 | 4050 | B | | asymmetric left | SA-L | 588/53/54 | >> 686009 |
| 25 | 4000 | 4050 | B | yes | asymmetric left | SA-L | 588/53/54 | >> 686160 |
| 25 | 4000 | 4050 | B | | asymmetric right | SA-R | 588/53/54 | >> 666254 |
| 25 | 4000 | 4050 | B | yes | asymmetric right | SA-R | 588/53/54 | >> 667312 |
| 25 | 4000 | 4200 | B | | 35/67 | CN | 588/53/54 | >> 666162 |
| 25 | 4000 | 4200 | B | yes | 35/67 | CN | 588/53/54 | >> 667220 |
| 25 | 4000 | 4200 | B | | 90 | MW | 588/53/54 | >> 666063 |
| 25 | 4000 | 4200 | B | yes | 90 | MW | 588/53/54 | >> 667145 |
| 25 | 4000 | 4200 | B | | 105 | VW | 588/53/54 | >> 666100 |
| 25 | 4000 | 4200 | B | yes | 105 | VW | 588/53/54 | >> 667183 |
| 25 | 4000 | 4250 | B | | 120 | symmetric | 588/53/54 | >> 594007 |
| 25 | 4000 | 4250 | B | yes | 120 | symmetric | 588/53/54 | >> 594014 |

LINEA S LED ECO

GENERAL CARD

Linea S LED Eco 2

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 13 | 4000 | 1900 | C | | 105 | symmetric | 1176/53/54 | >> 594144 |
| 13 | 4000 | 1900 | C | yes | 105 | symmetric | 1176/53/54 | >> 594151 |
| 13 | 4000 | 2100 | B | | 120 | symmetric | 1176/53/54 | >> 594106 |
| 13 | 4000 | 2100 | B | yes | 120 | symmetric | 1176/53/54 | >> 594113 |
| 17 | 4000 | 2450 | C | | butterfly | DAN | 1176/53/54 | >> 666995 |
| 17 | 4000 | 2450 | C | yes | butterfly | DAN | 1176/53/54 | >> 671692 |
| 17 | 4000 | 2450 | C | | asymmetric left | SA-L | 1176/53/54 | >> 686122 |
| 17 | 4000 | 2450 | C | yes | asymmetric left | SA-L | 1176/53/54 | >> 686283 |
| 17 | 4000 | 2450 | C | | asymmetric right | SA-R | 1176/53/54 | >> 667039 |
| 17 | 4000 | 2450 | C | yes | asymmetric right | SA-R | 1176/53/54 | >> 671739 |
| 17 | 4000 | 2550 | C | | 35/67 | CN | 1176/53/54 | >> 666957 |
| 17 | 4000 | 2550 | C | yes | 35/67 | CN | 1176/53/54 | >> 671654 |
| 17 | 4000 | 2550 | C | | 90 | MW | 1176/53/54 | >> 666872 |
| 17 | 4000 | 2550 | C | yes | 90 | MW | 1176/53/54 | >> 667930 |
| 17 | 4000 | 2550 | C | | 105 | VW | 1176/53/54 | >> 666919 |
| 17 | 4000 | 2550 | C | yes | 105 | VW | 1176/53/54 | >> 667978 |
| 19 | 4000 | 2800 | C | | 105 | symmetric | 1176/53/54 | >> 666841 |
| 19 | 4000 | 2800 | C | yes | 105 | symmetric | 1176/53/54 | >> 667909 |
| 19 | 4000 | 3050 | B | | 120 | symmetric | 1176/53/54 | >> 666810 |
| 19 | 4000 | 3050 | B | yes | 120 | symmetric | 1176/53/54 | >> 667879 |
| 21 | 4000 | 3050 | C | | butterfly | DAN | 1176/53/54 | >> 667008 |
| 21 | 4000 | 3050 | C | yes | butterfly | DAN | 1176/53/54 | >> 671708 |
| 21 | 4000 | 3050 | C | | asymmetric left | SA-L | 1176/53/54 | >> 686139 |
| 21 | 4000 | 3050 | C | yes | asymmetric left | SA-L | 1176/53/54 | >> 686290 |
| 21 | 4000 | 3050 | C | | asymmetric right | SA-R | 1176/53/54 | >> 667046 |
| 21 | 4000 | 3050 | C | yes | asymmetric right | SA-R | 1176/53/54 | >> 671746 |
| 21 | 4000 | 3150 | C | | 35/67 | CN | 1176/53/54 | >> 666964 |
| 21 | 4000 | 3150 | C | yes | 35/67 | CN | 1176/53/54 | >> 671661 |
| 21 | 4000 | 3200 | C | | 90 | MW | 1176/53/54 | >> 666889 |
| 21 | 4000 | 3200 | C | yes | 90 | MW | 1176/53/54 | >> 667947 |
| 21 | 4000 | 3200 | C | | 105 | VW | 1176/53/54 | >> 666926 |
| 21 | 4000 | 3200 | C | yes | 105 | VW | 1176/53/54 | >> 667985 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 23 | 4000 | 3350 | C | | 105 | symmetric | 1176/53/54 | >> 666858 |
| 23 | 4000 | 3350 | C | yes | 105 | symmetric | 1176/53/54 | >> 667916 |
| 23 | 4000 | 3700 | B | | 120 | symmetric | 1176/53/54 | >> 666827 |
| 23 | 4000 | 3700 | B | yes | 120 | symmetric | 1176/53/54 | >> 667886 |
| 25 | 4000 | 3650 | C | | butterfly | DAN | 1176/53/54 | >> 667015 |
| 25 | 4000 | 3650 | C | yes | butterfly | DAN | 1176/53/54 | >> 671715 |
| 25 | 4000 | 3650 | C | | asymmetric left | SA-L | 1176/53/54 | >> 686146 |
| 25 | 4000 | 3650 | C | yes | asymmetric left | SA-L | 1176/53/54 | >> 686306 |
| 25 | 4000 | 3650 | C | | asymmetric right | SA-R | 1176/53/54 | >> 667053 |
| 25 | 4000 | 3650 | C | yes | asymmetric right | SA-R | 1176/53/54 | >> 671753 |
| 25 | 4000 | 3800 | C | | 35/67 | CN | 1176/53/54 | >> 666971 |
| 25 | 4000 | 3800 | C | yes | 35/67 | CN | 1176/53/54 | >> 671678 |
| 25 | 4000 | 3800 | C | | 90 | MW | 1176/53/54 | >> 666896 |
| 25 | 4000 | 3800 | C | yes | 90 | MW | 1176/53/54 | >> 667954 |
| 25 | 4000 | 3800 | C | | 105 | VW | 1176/53/54 | >> 666933 |
| 25 | 4000 | 3800 | C | yes | 105 | VW | 1176/53/54 | >> 667992 |
| 26 | 4000 | 3850 | C | | 105 | symmetric | 1176/53/54 | >> 666865 |
| 26 | 4000 | 3850 | C | yes | 105 | symmetric | 1176/53/54 | >> 667923 |
| 26 | 4000 | 4250 | B | | 120 | symmetric | 1176/53/54 | >> 666834 |
| 26 | 4000 | 4250 | B | yes | 120 | symmetric | 1176/53/54 | >> 667893 |
| 29 | 4000 | 4200 | C | | butterfly | DAN | 1176/53/54 | >> 667022 |
| 29 | 4000 | 4200 | C | yes | butterfly | DAN | 1176/53/54 | >> 671722 |
| 29 | 4000 | 4200 | C | | asymmetric left | SA-L | 1176/53/54 | >> 686153 |
| 29 | 4000 | 4200 | C | yes | asymmetric left | SA-L | 1176/53/54 | >> 686313 |
| 29 | 4000 | 4200 | C | | asymmetric right | SA-R | 1176/53/54 | >> 667060 |
| 29 | 4000 | 4200 | C | yes | asymmetric right | SA-R | 1176/53/54 | >> 671760 |
| 29 | 4000 | 4350 | C | | 35/67 | CN | 1176/53/54 | >> 666988 |
| 29 | 4000 | 4350 | C | yes | 35/67 | CN | 1176/53/54 | >> 671685 |
| 29 | 4000 | 4400 | C | | 90 | MW | 1176/53/54 | >> 666902 |
| 29 | 4000 | 4400 | C | yes | 90 | MW | 1176/53/54 | >> 667961 |
| 29 | 4000 | 4400 | C | | 105 | VW | 1176/53/54 | >> 666940 |
| 29 | 4000 | 4400 | C | yes | 105 | VW | 1176/53/54 | >> 671647 |
| 29 | 4000 | 4700 | B | | butterfly | DAN | 1176/53/54 | >> 666766 |
| 29 | 4000 | 4700 | B | yes | butterfly | DAN | 1176/53/54 | >> 667824 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 29 | 4000 | 4750 | B | | asymmetric left | SA-L | 1176/53/54 | >> 686115 |
| 29 | 4000 | 4750 | B | yes | asymmetric left | SA-L | 1176/53/54 | >> 686276 |
| 29 | 4000 | 4750 | B | | asymmetric right | SA-R | 1176/53/54 | >> 666803 |
| 29 | 4000 | 4750 | B | yes | asymmetric right | SA-R | 1176/53/54 | >> 667862 |
| 29 | 4000 | 4900 | B | | 35/67 | CN | 1176/53/54 | >> 666728 |
| 29 | 4000 | 4900 | B | yes | 35/67 | CN | 1176/53/54 | >> 667787 |
| 29 | 4000 | 4900 | B | | 90 | MW | 1176/53/54 | >> 666643 |
| 29 | 4000 | 4900 | B | yes | 90 | MW | 1176/53/54 | >> 667701 |
| 29 | 4000 | 4900 | B | | 105 | VW | 1176/53/54 | >> 666681 |
| 29 | 4000 | 4900 | B | yes | 105 | VW | 1176/53/54 | >> 667749 |
| 30 | 4000 | 4350 | C | | 105 | symmetric | 1176/53/54 | >> 666605 |
| 30 | 4000 | 4350 | C | yes | 105 | symmetric | 1176/53/54 | >> 667664 |
| 30 | 4000 | 4750 | B | | 120 | symmetric | 1176/53/54 | >> 666575 |
| 30 | 4000 | 4750 | B | yes | 120 | symmetric | 1176/53/54 | >> 667633 |
| 36 | 4000 | 5900 | B | | butterfly | DAN | 1176/53/54 | >> 666759 |
| 36 | 4000 | 5900 | B | yes | butterfly | DAN | 1176/53/54 | >> 667817 |
| 36 | 4000 | 5950 | B | | asymmetric left | SA-L | 1176/53/54 | >> 686108 |
| 36 | 4000 | 5950 | B | yes | asymmetric left | SA-L | 1176/53/54 | >> 686269 |
| 36 | 4000 | 5950 | B | | asymmetric right | SA-R | 1176/53/54 | >> 666797 |
| 36 | 4000 | 5950 | B | yes | asymmetric right | SA-R | 1176/53/54 | >> 667855 |
| 36 | 4000 | 6150 | B | | 35/67 | CN | 1176/53/54 | >> 666711 |
| 36 | 4000 | 6150 | B | yes | 35/67 | CN | 1176/53/54 | >> 667770 |
| 36 | 4000 | 6150 | B | | 90 | MW | 1176/53/54 | >> 666636 |
| 36 | 4000 | 6150 | B | yes | 90 | MW | 1176/53/54 | >> 667695 |
| 36 | 4000 | 6150 | B | | 105 | VW | 1176/53/54 | >> 666674 |
| 36 | 4000 | 6150 | B | yes | 105 | VW | 1176/53/54 | >> 667732 |
| 38 | 4000 | 5450 | C | | 105 | symmetric | 1176/53/54 | >> 666599 |
| 38 | 4000 | 5450 | C | yes | 105 | symmetric | 1176/53/54 | >> 667657 |
| 38 | 4000 | 5950 | C | | 120 | symmetric | 1176/53/54 | >> 666568 |
| 38 | 4000 | 5950 | C | yes | 120 | symmetric | 1176/53/54 | >> 667626 |
| 41 | 4000 | 6600 | B | | butterfly | DAN | 1176/53/54 | >> 666742 |
| 41 | 4000 | 6600 | B | yes | butterfly | DAN | 1176/53/54 | >> 667800 |
| 41 | 4000 | 6650 | B | | asymmetric left | SA-L | 1176/53/54 | >> 686092 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 41 | 4000 | 6650 | B | yes | asymmetric left | SA-L | 1176/53/54 | >> 686252 |
| 41 | 4000 | 6650 | B | | asymmetric right | SA-R | 1176/53/54 | >> 666780 |
| 41 | 4000 | 6650 | B | yes | asymmetric right | SA-R | 1176/53/54 | >> 667848 |
| 41 | 4000 | 6850 | B | | 35/67 | CN | 1176/53/54 | >> 666704 |
| 41 | 4000 | 6850 | B | yes | 35/67 | CN | 1176/53/54 | >> 667763 |
| 41 | 4000 | 6900 | B | | 90 | MW | 1176/53/54 | >> 666629 |
| 41 | 4000 | 6900 | B | yes | 90 | MW | 1176/53/54 | >> 667688 |
| 41 | 4000 | 6900 | B | | 105 | VW | 1176/53/54 | >> 666667 |
| 41 | 4000 | 6900 | B | yes | 105 | VW | 1176/53/54 | >> 667725 |
| 46 | 4000 | 6400 | C | | 105 | symmetric | 1176/53/54 | >> 666582 |
| 46 | 4000 | 6400 | C | yes | 105 | symmetric | 1176/53/54 | >> 667640 |
| 46 | 4000 | 7000 | C | | 120 | symmetric | 1176/53/54 | >> 666551 |
| 46 | 4000 | 7000 | C | yes | 120 | symmetric | 1176/53/54 | >> 667619 |
| 49 | 4000 | 7700 | C | | butterfly | DAN | 1176/53/54 | >> 666735 |
| 49 | 4000 | 7700 | C | yes | butterfly | DAN | 1176/53/54 | >> 667794 |
| 49 | 4000 | 7750 | B | | asymmetric left | SA-L | 1176/53/54 | >> 686085 |
| 49 | 4000 | 7750 | B | yes | asymmetric left | SA-L | 1176/53/54 | >> 686245 |
| 49 | 4000 | 7750 | B | | asymmetric right | SA-R | 1176/53/54 | >> 666773 |
| 49 | 4000 | 7750 | B | yes | asymmetric right | SA-R | 1176/53/54 | >> 667831 |
| 49 | 4000 | 8000 | B | | 35/67 | CN | 1176/53/54 | >> 666698 |
| 49 | 4000 | 8000 | B | yes | 35/67 | CN | 1176/53/54 | >> 667756 |
| 49 | 4000 | 8050 | B | | 90 | MW | 1176/53/54 | >> 666612 |
| 49 | 4000 | 8050 | B | yes | 90 | MW | 1176/53/54 | >> 667671 |
| 49 | 4000 | 8050 | B | | 105 | VW | 1176/53/54 | >> 666650 |
| 49 | 4000 | 8050 | B | yes | 105 | VW | 1176/53/54 | >> 667718 |
| 50 | 4000 | 7450 | C | | 105 | symmetric | 1176/53/54 | >> 594120 |
| 50 | 4000 | 7450 | C | yes | 105 | symmetric | 1176/53/54 | >> 594137 |
| 50 | 4000 | 8150 | B | | 120 | symmetric | 1176/53/54 | >> 594083 |
| 50 | 4000 | 8150 | B | yes | 120 | symmetric | 1176/53/54 | >> 594090 |

Linea S LED Eco 3

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|----------------|-------------------------|---------------------------|---------------------------------|
| 21 | 4000 | 3350 | B | | 105 | symmetric | 1764/53/54 | >> 594229 |
| 21 | 4000 | 3350 | B | yes | 105 | symmetric | 1764/53/54 | >> 594236 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 21 | 4000 | 3650 | B | | 120 | symmetric | 1764/53/54 | >> 594182 |
| 21 | 4000 | 3650 | B | yes | 120 | symmetric | 1764/53/54 | >> 594199 |
| 23 | 4000 | 3750 | B | | butterfly | DAN | 1764/53/54 | >> 686597 |
| 23 | 4000 | 3750 | B | yes | butterfly | DAN | 1764/53/54 | >> 686986 |
| 23 | 4000 | 3800 | B | | asymmetric left | SA-L | 1764/53/54 | >> 686672 |
| 23 | 4000 | 3800 | B | yes | asymmetric left | SA-L | 1764/53/54 | >> 687068 |
| 23 | 4000 | 3800 | B | | asymmetric right | SA-R | 1764/53/54 | >> 686634 |
| 23 | 4000 | 3800 | B | yes | asymmetric right | SA-R | 1764/53/54 | >> 687020 |
| 23 | 4000 | 3900 | B | | 35/67 | CN | 1764/53/54 | >> 686559 |
| 23 | 4000 | 3900 | B | yes | 35/67 | CN | 1764/53/54 | >> 686948 |
| 23 | 4000 | 3950 | B | | 90 | MW | 1764/53/54 | >> 686474 |
| 23 | 4000 | 3950 | B | yes | 90 | MW | 1764/53/54 | >> 686863 |
| 23 | 4000 | 3950 | B | | 105 | VW | 1764/53/54 | >> 686511 |
| 23 | 4000 | 3950 | B | yes | 105 | VW | 1764/53/54 | >> 686900 |
| 26 | 4000 | 4200 | B | | 105 | symmetric | 1764/53/54 | >> 686443 |
| 26 | 4000 | 4200 | B | yes | 105 | symmetric | 1764/53/54 | >> 686832 |
| 26 | 4000 | 4600 | B | | 120 | symmetric | 1764/53/54 | >> 686412 |
| 26 | 4000 | 4600 | B | yes | 120 | symmetric | 1764/53/54 | >> 686801 |
| 28 | 4000 | 4700 | B | | butterfly | DAN | 1764/53/54 | >> 686603 |
| 28 | 4000 | 4700 | B | yes | butterfly | DAN | 1764/53/54 | >> 686993 |
| 28 | 4000 | 4750 | B | | asymmetric left | SA-L | 1764/53/54 | >> 686689 |
| 28 | 4000 | 4750 | B | yes | asymmetric left | SA-L | 1764/53/54 | >> 687075 |
| 28 | 4000 | 4750 | B | | asymmetric right | SA-R | 1764/53/54 | >> 686641 |
| 28 | 4000 | 4750 | B | yes | asymmetric right | SA-R | 1764/53/54 | >> 687037 |
| 28 | 4000 | 4850 | B | | 35/67 | CN | 1764/53/54 | >> 686566 |
| 28 | 4000 | 4850 | B | yes | 35/67 | CN | 1764/53/54 | >> 686955 |
| 28 | 4000 | 4900 | B | | 90 | MW | 1764/53/54 | >> 686481 |
| 28 | 4000 | 4900 | B | yes | 90 | MW | 1764/53/54 | >> 686870 |
| 28 | 4000 | 4900 | B | | 105 | VW | 1764/53/54 | >> 686528 |
| 28 | 4000 | 4900 | B | yes | 105 | VW | 1764/53/54 | >> 686917 |
| 31 | 4000 | 5050 | B | | 105 | symmetric | 1764/53/54 | >> 686450 |
| 31 | 4000 | 5050 | B | yes | 105 | symmetric | 1764/53/54 | >> 686849 |
| 31 | 4000 | 5550 | A | | 120 | symmetric | 1764/53/54 | >> 686429 |
| 31 | 4000 | 5550 | A | yes | 120 | symmetric | 1764/53/54 | >> 686818 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 34 | 4000 | 5650 | B | | butterfly | DAN | 1764/53/54 | >> 686610 |
| 34 | 4000 | 5650 | B | yes | butterfly | DAN | 1764/53/54 | >> 687006 |
| 34 | 4000 | 5650 | B | | asymmetric left | SA-L | 1764/53/54 | >> 686696 |
| 34 | 4000 | 5650 | B | yes | asymmetric left | SA-L | 1764/53/54 | >> 687082 |
| 34 | 4000 | 5650 | B | | asymmetric right | SA-R | 1764/53/54 | >> 686658 |
| 34 | 4000 | 5650 | B | yes | asymmetric right | SA-R | 1764/53/54 | >> 687044 |
| 34 | 4000 | 5850 | B | | 35/67 | CN | 1764/53/54 | >> 686573 |
| 34 | 4000 | 5850 | B | yes | 35/67 | CN | 1764/53/54 | >> 686962 |
| 34 | 4000 | 5900 | B | | 90 | MW | 1764/53/54 | >> 686498 |
| 34 | 4000 | 5900 | B | yes | 90 | MW | 1764/53/54 | >> 686887 |
| 34 | 4000 | 5900 | B | | 105 | VW | 1764/53/54 | >> 686535 |
| 34 | 4000 | 5900 | B | yes | 105 | VW | 1764/53/54 | >> 686924 |
| 36 | 4000 | 5950 | B | | 105 | symmetric | 1764/53/54 | >> 686467 |
| 36 | 4000 | 5950 | B | yes | 105 | symmetric | 1764/53/54 | >> 686856 |
| 36 | 4000 | 6500 | A | | 120 | symmetric | 1764/53/54 | >> 686436 |
| 36 | 4000 | 6500 | A | yes | 120 | symmetric | 1764/53/54 | >> 686825 |
| 39 | 4000 | 6600 | B | | butterfly | DAN | 1764/53/54 | >> 686627 |
| 39 | 4000 | 6600 | B | yes | butterfly | DAN | 1764/53/54 | >> 687013 |
| 39 | 4000 | 6600 | B | | asymmetric left | SA-L | 1764/53/54 | >> 686702 |
| 39 | 4000 | 6600 | B | yes | asymmetric left | SA-L | 1764/53/54 | >> 687099 |
| 39 | 4000 | 6600 | B | | asymmetric right | SA-R | 1764/53/54 | >> 686665 |
| 39 | 4000 | 6600 | B | yes | asymmetric right | SA-R | 1764/53/54 | >> 687051 |
| 39 | 4000 | 6850 | B | | 35/67 | CN | 1764/53/54 | >> 686580 |
| 39 | 4000 | 6850 | B | yes | 35/67 | CN | 1764/53/54 | >> 686979 |
| 39 | 4000 | 6850 | B | | 90 | MW | 1764/53/54 | >> 686504 |
| 39 | 4000 | 6850 | B | yes | 90 | MW | 1764/53/54 | >> 686894 |
| 39 | 4000 | 6850 | B | | 105 | VW | 1764/53/54 | >> 686542 |
| 39 | 4000 | 6850 | B | yes | 105 | VW | 1764/53/54 | >> 686931 |
| 41 | 4000 | 6700 | B | | 105 | symmetric | 1764/53/54 | >> 594564 |
| 41 | 4000 | 6700 | B | yes | 105 | symmetric | 1764/53/54 | >> 686764 |
| 41 | 4000 | 7300 | B | | 120 | symmetric | 1764/53/54 | >> 686344 |
| 41 | 4000 | 7300 | B | yes | 120 | symmetric | 1764/53/54 | >> 686733 |
| 45 | 4000 | 7550 | B | | butterfly | DAN | 1764/53/54 | >> 594724 |
| 45 | 4000 | 7550 | B | yes | butterfly | DAN | 1764/53/54 | >> 687211 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 45 | 4000 | 7550 | B | | asymmetric left | SA-L | 1764/53/54 | >> 686405 |
| 45 | 4000 | 7550 | B | yes | asymmetric left | SA-L | 1764/53/54 | >> 686795 |
| 45 | 4000 | 7550 | B | | asymmetric right | SA-R | 1764/53/54 | >> 594786 |
| 45 | 4000 | 7550 | B | yes | asymmetric right | SA-R | 1764/53/54 | >> 687242 |
| 45 | 4000 | 7850 | B | | 35/67 | CN | 1764/53/54 | >> 594960 |
| 45 | 4000 | 7850 | B | yes | 35/67 | CN | 1764/53/54 | >> 687181 |
| 45 | 4000 | 7900 | B | | 90 | MW | 1764/53/54 | >> 594847 |
| 45 | 4000 | 7900 | B | yes | 90 | MW | 1764/53/54 | >> 687129 |
| 45 | 4000 | 7900 | B | | 105 | VW | 1764/53/54 | >> 594908 |
| 45 | 4000 | 7900 | B | yes | 105 | VW | 1764/53/54 | >> 687150 |
| 52 | 4000 | 8450 | B | | 105 | symmetric | 1764/53/54 | >> 686368 |
| 52 | 4000 | 8450 | B | yes | 105 | symmetric | 1764/53/54 | >> 686757 |
| 52 | 4000 | 9200 | B | | 120 | symmetric | 1764/53/54 | >> 686337 |
| 52 | 4000 | 9200 | B | yes | 120 | symmetric | 1764/53/54 | >> 686726 |
| 62 | 4000 | 10000 | B | | 105 | symmetric | 1764/53/54 | >> 594557 |
| 62 | 4000 | 10000 | B | yes | 105 | symmetric | 1764/53/54 | >> 686740 |
| 62 | 4000 | 10300 | B | | butterfly | DAN | 1764/53/54 | >> 594717 |
| 62 | 4000 | 10300 | B | yes | butterfly | DAN | 1764/53/54 | >> 687204 |
| 62 | 4000 | 10350 | B | | asymmetric left | SA-L | 1764/53/54 | >> 686399 |
| 62 | 4000 | 10350 | B | yes | asymmetric left | SA-L | 1764/53/54 | >> 686788 |
| 62 | 4000 | 10350 | B | | asymmetric right | SA-R | 1764/53/54 | >> 594779 |
| 62 | 4000 | 10350 | B | yes | asymmetric right | SA-R | 1764/53/54 | >> 687235 |
| 62 | 4000 | 10700 | B | | 35/67 | CN | 1764/53/54 | >> 594953 |
| 62 | 4000 | 10700 | B | yes | 35/67 | CN | 1764/53/54 | >> 687174 |
| 62 | 4000 | 10750 | B | | 90 | MW | 1764/53/54 | >> 594830 |
| 62 | 4000 | 10750 | B | yes | 90 | MW | 1764/53/54 | >> 687112 |
| 62 | 4000 | 10750 | B | | 105 | VW | 1764/53/54 | >> 594892 |
| 62 | 4000 | 10750 | B | yes | 105 | VW | 1764/53/54 | >> 687143 |
| 62 | 4000 | 10900 | B | | 120 | symmetric | 1764/53/54 | >> 686320 |
| 62 | 4000 | 10900 | B | yes | 120 | symmetric | 1764/53/54 | >> 686719 |
| 75 | 4000 | 11950 | B | | 105 | symmetric | 1764/53/54 | >> 594205 |
| 75 | 4000 | 11950 | B | yes | 105 | symmetric | 1764/53/54 | >> 594212 |
| 75 | 4000 | 12350 | B | | butterfly | DAN | 1764/53/54 | >> 594700 |
| 75 | 4000 | 12350 | B | yes | butterfly | DAN | 1764/53/54 | >> 687198 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 75 | 4000 | 12450 | B | | asymmetric left | SA-L | 1764/53/54 | >> 686382 |
| 75 | 4000 | 12450 | B | yes | asymmetric left | SA-L | 1764/53/54 | >> 686771 |
| 75 | 4000 | 12450 | B | | asymmetric right | SA-R | 1764/53/54 | >> 594762 |
| 75 | 4000 | 12450 | B | yes | asymmetric right | SA-R | 1764/53/54 | >> 687228 |
| 75 | 4000 | 12850 | B | | 35/67 | CN | 1764/53/54 | >> 594946 |
| 75 | 4000 | 12850 | B | yes | 35/67 | CN | 1764/53/54 | >> 687167 |
| 75 | 4000 | 12900 | B | | 90 | MW | 1764/53/54 | >> 594823 |
| 75 | 4000 | 12900 | B | yes | 90 | MW | 1764/53/54 | >> 687105 |
| 75 | 4000 | 12900 | B | | 105 | VW | 1764/53/54 | >> 594885 |
| 75 | 4000 | 12900 | B | yes | 105 | VW | 1764/53/54 | >> 687136 |
| 75 | 4000 | 13100 | B | | 120 | symmetric | 1764/53/54 | >> 594168 |
| 75 | 4000 | 13100 | B | yes | 120 | symmetric | 1764/53/54 | >> 594175 |

Linea S LED Eco 4

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 31 | 4000 | 5200 | B | | 105 | symmetric | 2940/53/54 | >> 594304 |
| 31 | 4000 | 5200 | B | yes | 105 | symmetric | 2940/53/54 | >> 594311 |
| 31 | 4000 | 5700 | A | | 120 | symmetric | 2940/53/54 | >> 594267 |
| 31 | 4000 | 5700 | A | yes | 120 | symmetric | 2940/53/54 | >> 594274 |
| 33 | 4000 | 5750 | B | | butterfly | DAN | 2940/53/54 | >> 687730 |
| 33 | 4000 | 5750 | B | yes | butterfly | DAN | 2940/53/54 | >> 688331 |
| 33 | 4000 | 5750 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687815 |
| 33 | 4000 | 5750 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688416 |
| 33 | 4000 | 5750 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687778 |
| 33 | 4000 | 5750 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688379 |
| 33 | 4000 | 5950 | A | | 35/67 | CN | 2940/53/54 | >> 687693 |
| 33 | 4000 | 5950 | A | yes | 35/67 | CN | 2940/53/54 | >> 688294 |
| 33 | 4000 | 6000 | A | | 90 | MW | 2940/53/54 | >> 687617 |
| 33 | 4000 | 6000 | A | yes | 90 | MW | 2940/53/54 | >> 688218 |
| 33 | 4000 | 6000 | A | | 105 | VW | 2940/53/54 | >> 687655 |
| 33 | 4000 | 6000 | A | yes | 105 | VW | 2940/53/54 | >> 688256 |
| 39 | 4000 | 6450 | B | | 105 | symmetric | 2940/53/54 | >> 687587 |
| 39 | 4000 | 6450 | B | yes | 105 | symmetric | 2940/53/54 | >> 688188 |
| 39 | 4000 | 7050 | A | | 120 | symmetric | 2940/53/54 | >> 687556 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 39 | 4000 | 7050 | A | yes | 120 | symmetric | 2940/53/54 | >> 688157 |
| 42 | 4000 | 7150 | B | | butterfly | DAN | 2940/53/54 | >> 687747 |
| 42 | 4000 | 7150 | B | yes | butterfly | DAN | 2940/53/54 | >> 688348 |
| 42 | 4000 | 7150 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687822 |
| 42 | 4000 | 7150 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688423 |
| 42 | 4000 | 7150 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687785 |
| 42 | 4000 | 7150 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688386 |
| 42 | 4000 | 7400 | B | | 35/67 | CN | 2940/53/54 | >> 687709 |
| 42 | 4000 | 7400 | B | yes | 35/67 | CN | 2940/53/54 | >> 688300 |
| 42 | 4000 | 7450 | B | | 90 | MW | 2940/53/54 | >> 687624 |
| 42 | 4000 | 7450 | B | yes | 90 | MW | 2940/53/54 | >> 688225 |
| 42 | 4000 | 7450 | B | | 105 | VW | 2940/53/54 | >> 687662 |
| 42 | 4000 | 7450 | B | yes | 105 | VW | 2940/53/54 | >> 688263 |
| 47 | 4000 | 7700 | B | | 105 | symmetric | 2940/53/54 | >> 687594 |
| 47 | 4000 | 7700 | B | yes | 105 | symmetric | 2940/53/54 | >> 688195 |
| 47 | 4000 | 8500 | A | | 120 | symmetric | 2940/53/54 | >> 687563 |
| 47 | 4000 | 8500 | A | yes | 120 | symmetric | 2940/53/54 | >> 688164 |
| 50 | 4000 | 8500 | B | | butterfly | DAN | 2940/53/54 | >> 687754 |
| 50 | 4000 | 8500 | B | yes | butterfly | DAN | 2940/53/54 | >> 688355 |
| 50 | 4000 | 8550 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687839 |
| 50 | 4000 | 8550 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688430 |
| 50 | 4000 | 8550 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687792 |
| 50 | 4000 | 8550 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688393 |
| 50 | 4000 | 8850 | B | | 35/67 | CN | 2940/53/54 | >> 687716 |
| 50 | 4000 | 8850 | B | yes | 35/67 | CN | 2940/53/54 | >> 688317 |
| 50 | 4000 | 8900 | B | | 90 | MW | 2940/53/54 | >> 687631 |
| 50 | 4000 | 8900 | B | yes | 90 | MW | 2940/53/54 | >> 688232 |
| 50 | 4000 | 8900 | B | | 105 | VW | 2940/53/54 | >> 687679 |
| 50 | 4000 | 8900 | B | yes | 105 | VW | 2940/53/54 | >> 688270 |
| 54 | 4000 | 9000 | B | | 105 | symmetric | 2940/53/54 | >> 687600 |
| 54 | 4000 | 9000 | B | yes | 105 | symmetric | 2940/53/54 | >> 688201 |
| 54 | 4000 | 9900 | A | | 120 | symmetric | 2940/53/54 | >> 687570 |
| 54 | 4000 | 9900 | A | yes | 120 | symmetric | 2940/53/54 | >> 688171 |
| 58 | 4000 | 9800 | B | | butterfly | DAN | 2940/53/54 | >> 687761 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 58 | 4000 | 9800 | B | yes | butterfly | DAN | 2940/53/54 | >> 688362 |
| 58 | 4000 | 9850 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687846 |
| 58 | 4000 | 9850 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688447 |
| 58 | 4000 | 9850 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687808 |
| 58 | 4000 | 9850 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688409 |
| 58 | 4000 | 10200 | B | | 35/67 | CN | 2940/53/54 | >> 687723 |
| 58 | 4000 | 10200 | B | yes | 35/67 | CN | 2940/53/54 | >> 688324 |
| 58 | 4000 | 10250 | B | | 90 | MW | 2940/53/54 | >> 687648 |
| 58 | 4000 | 10250 | B | yes | 90 | MW | 2940/53/54 | >> 688249 |
| 58 | 4000 | 10250 | B | | 105 | VW | 2940/53/54 | >> 687686 |
| 58 | 4000 | 10250 | B | yes | 105 | VW | 2940/53/54 | >> 688287 |
| 63 | 4000 | 10500 | B | | 105 | symmetric | 2940/53/54 | >> 687303 |
| 63 | 4000 | 10500 | B | yes | 105 | symmetric | 2940/53/54 | >> 687907 |
| 63 | 4000 | 10850 | B | | butterfly | DAN | 2940/53/54 | >> 687464 |
| 63 | 4000 | 10850 | B | yes | butterfly | DAN | 2940/53/54 | >> 688065 |
| 63 | 4000 | 10950 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687549 |
| 63 | 4000 | 10950 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688140 |
| 63 | 4000 | 10950 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687501 |
| 63 | 4000 | 10950 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688102 |
| 63 | 4000 | 11300 | A | | 35/67 | CN | 2940/53/54 | >> 687426 |
| 63 | 4000 | 11300 | A | yes | 35/67 | CN | 2940/53/54 | >> 688027 |
| 63 | 4000 | 11350 | A | | 90 | MW | 2940/53/54 | >> 687341 |
| 63 | 4000 | 11350 | A | yes | 90 | MW | 2940/53/54 | >> 687945 |
| 63 | 4000 | 11350 | A | | 105 | VW | 2940/53/54 | >> 687389 |
| 63 | 4000 | 11350 | A | yes | 105 | VW | 2940/53/54 | >> 687983 |
| 63 | 4000 | 11500 | A | | 120 | symmetric | 2940/53/54 | >> 687273 |
| 63 | 4000 | 11500 | A | yes | 120 | symmetric | 2940/53/54 | >> 687877 |
| 79 | 4000 | 13100 | B | | 105 | symmetric | 2940/53/54 | >> 687297 |
| 79 | 4000 | 13100 | B | yes | 105 | symmetric | 2940/53/54 | >> 687891 |
| 79 | 4000 | 13550 | B | | butterfly | DAN | 2940/53/54 | >> 687457 |
| 79 | 4000 | 13550 | B | yes | butterfly | DAN | 2940/53/54 | >> 688058 |
| 79 | 4000 | 13600 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687532 |
| 79 | 4000 | 13600 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688133 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 79 | 4000 | 13600 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687495 |
| 79 | 4000 | 13600 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688096 |
| 79 | 4000 | 14050 | B | | 35/67 | CN | 2940/53/54 | >> 687419 |
| 79 | 4000 | 14050 | B | yes | 35/67 | CN | 2940/53/54 | >> 688010 |
| 79 | 4000 | 14150 | A | | 90 | MW | 2940/53/54 | >> 687334 |
| 79 | 4000 | 14150 | A | yes | 90 | MW | 2940/53/54 | >> 687938 |
| 79 | 4000 | 14150 | A | | 105 | VW | 2940/53/54 | >> 687372 |
| 79 | 4000 | 14150 | A | yes | 105 | VW | 2940/53/54 | >> 687976 |
| 79 | 4000 | 14250 | A | | 120 | symmetric | 2940/53/54 | >> 687266 |
| 79 | 4000 | 14250 | A | yes | 120 | symmetric | 2940/53/54 | >> 687860 |
| 95 | 4000 | 15600 | B | | 105 | symmetric | 2940/53/54 | >> 687280 |
| 95 | 4000 | 15600 | B | yes | 105 | symmetric | 2940/53/54 | >> 687884 |
| 95 | 4000 | 16150 | B | | butterfly | DAN | 2940/53/54 | >> 687440 |
| 95 | 4000 | 16150 | B | yes | butterfly | DAN | 2940/53/54 | >> 688041 |
| 95 | 4000 | 16200 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687525 |
| 95 | 4000 | 16200 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688126 |
| 95 | 4000 | 16200 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687488 |
| 95 | 4000 | 16200 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688089 |
| 95 | 4000 | 16750 | B | | 35/67 | CN | 2940/53/54 | >> 687402 |
| 95 | 4000 | 16750 | B | yes | 35/67 | CN | 2940/53/54 | >> 688003 |
| 95 | 4000 | 16850 | B | | 90 | MW | 2940/53/54 | >> 687327 |
| 95 | 4000 | 16850 | B | yes | 90 | MW | 2940/53/54 | >> 687921 |
| 95 | 4000 | 16850 | B | | 105 | VW | 2940/53/54 | >> 687365 |
| 95 | 4000 | 16850 | B | yes | 105 | VW | 2940/53/54 | >> 687969 |
| 95 | 4000 | 17000 | A | | 120 | symmetric | 2940/53/54 | >> 687259 |
| 95 | 4000 | 17000 | A | yes | 120 | symmetric | 2940/53/54 | >> 687853 |
| 111 | 4000 | 18250 | B | | 105 | symmetric | 2940/53/54 | >> 594281 |
| 111 | 4000 | 18250 | B | yes | 105 | symmetric | 2940/53/54 | >> 594298 |
| 111 | 4000 | 18900 | B | | butterfly | DAN | 2940/53/54 | >> 687433 |
| 111 | 4000 | 18900 | B | yes | butterfly | DAN | 2940/53/54 | >> 688034 |
| 111 | 4000 | 19000 | B | | asymmetric left | SA-L | 2940/53/54 | >> 687518 |
| 111 | 4000 | 19000 | B | yes | asymmetric left | SA-L | 2940/53/54 | >> 688119 |
| 111 | 4000 | 19000 | B | | asymmetric right | SA-R | 2940/53/54 | >> 687471 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 111 | 4000 | 19000 | B | yes | asymmetric right | SA-R | 2940/53/54 | >> 688072 |
| 111 | 4000 | 19650 | B | | 35/67 | CN | 2940/53/54 | >> 687396 |
| 111 | 4000 | 19650 | B | yes | 35/67 | CN | 2940/53/54 | >> 687990 |
| 111 | 4000 | 19750 | B | | 90 | MW | 2940/53/54 | >> 687310 |
| 111 | 4000 | 19750 | B | yes | 90 | MW | 2940/53/54 | >> 687914 |
| 111 | 4000 | 19750 | B | | 105 | VW | 2940/53/54 | >> 687358 |
| 111 | 4000 | 19750 | B | yes | 105 | VW | 2940/53/54 | >> 687952 |
| 111 | 4000 | 20000 | A | | 120 | symmetric | 2940/53/54 | >> 594243 |
| 111 | 4000 | 20000 | A | yes | 120 | symmetric | 2940/53/54 | >> 594250 |

Linea S LED Eco 5

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 37 | 4000 | 6200 | B | | 105 | symmetric | 3528/53/54 | >> 594380 |
| 37 | 4000 | 6200 | B | yes | 105 | symmetric | 3528/53/54 | >> 594397 |
| 37 | 4000 | 6800 | A | | 120 | symmetric | 3528/53/54 | >> 594342 |
| 37 | 4000 | 6800 | A | yes | 120 | symmetric | 3528/53/54 | >> 594359 |
| 40 | 4000 | 6950 | B | | butterfly | DAN | 3528/53/54 | >> 689185 |
| 40 | 4000 | 6950 | B | yes | butterfly | DAN | 3528/53/54 | >> 689482 |
| 40 | 4000 | 6950 | B | | asymmetric left | SA-L | 3528/53/54 | >> 689260 |
| 40 | 4000 | 6950 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 689567 |
| 40 | 4000 | 6950 | B | | asymmetric right | SA-R | 3528/53/54 | >> 689222 |
| 40 | 4000 | 6950 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 689529 |
| 40 | 4000 | 7200 | A | | 35/67 | CN | 3528/53/54 | >> 689147 |
| 40 | 4000 | 7200 | A | yes | 35/67 | CN | 3528/53/54 | >> 689444 |
| 40 | 4000 | 7250 | A | | 90 | MW | 3528/53/54 | >> 689062 |
| 40 | 4000 | 7250 | A | yes | 90 | MW | 3528/53/54 | >> 689369 |
| 40 | 4000 | 7250 | A | | 105 | VW | 3528/53/54 | >> 689109 |
| 40 | 4000 | 7250 | A | yes | 105 | VW | 3528/53/54 | >> 689406 |
| 47 | 4000 | 7700 | B | | 105 | symmetric | 3528/53/54 | >> 689031 |
| 47 | 4000 | 7700 | B | yes | 105 | symmetric | 3528/53/54 | >> 689338 |
| 47 | 4000 | 8500 | A | | 120 | symmetric | 3528/53/54 | >> 689000 |
| 47 | 4000 | 8500 | A | yes | 120 | symmetric | 3528/53/54 | >> 689307 |
| 50 | 4000 | 8600 | B | | butterfly | DAN | 3528/53/54 | >> 689192 |
| 50 | 4000 | 8600 | B | yes | butterfly | DAN | 3528/53/54 | >> 689499 |
| 50 | 4000 | 8650 | B | | asymmetric left | SA-L | 3528/53/54 | >> 689277 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 50 | 4000 | 8650 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 689574 |
| 50 | 4000 | 8650 | B | | asymmetric right | SA-R | 3528/53/54 | >> 689239 |
| 50 | 4000 | 8650 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 689536 |
| 50 | 4000 | 8950 | A | | 35/67 | CN | 3528/53/54 | >> 689154 |
| 50 | 4000 | 8950 | A | yes | 35/67 | CN | 3528/53/54 | >> 689451 |
| 50 | 4000 | 9000 | A | | 90 | MW | 3528/53/54 | >> 689079 |
| 50 | 4000 | 9000 | A | yes | 90 | MW | 3528/53/54 | >> 689376 |
| 50 | 4000 | 9000 | A | | 105 | VW | 3528/53/54 | >> 689116 |
| 50 | 4000 | 9000 | A | yes | 105 | VW | 3528/53/54 | >> 689413 |
| 56 | 4000 | 9250 | B | | 105 | symmetric | 3528/53/54 | >> 689048 |
| 56 | 4000 | 9250 | B | yes | 105 | symmetric | 3528/53/54 | >> 689345 |
| 56 | 4000 | 10200 | A | | 120 | symmetric | 3528/53/54 | >> 689017 |
| 56 | 4000 | 10200 | A | yes | 120 | symmetric | 3528/53/54 | >> 689314 |
| 61 | 4000 | 10350 | B | | butterfly | DAN | 3528/53/54 | >> 689208 |
| 61 | 4000 | 10350 | B | yes | butterfly | DAN | 3528/53/54 | >> 689505 |
| 61 | 4000 | 10400 | B | | asymmetric left | SA-L | 3528/53/54 | >> 689284 |
| 61 | 4000 | 10400 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 689581 |
| 61 | 4000 | 10400 | B | | asymmetric right | SA-R | 3528/53/54 | >> 689246 |
| 61 | 4000 | 10400 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 689543 |
| 61 | 4000 | 10750 | B | | 35/67 | CN | 3528/53/54 | >> 689161 |
| 61 | 4000 | 10750 | B | yes | 35/67 | CN | 3528/53/54 | >> 689468 |
| 61 | 4000 | 10800 | B | | 90 | MW | 3528/53/54 | >> 689086 |
| 61 | 4000 | 10800 | B | yes | 90 | MW | 3528/53/54 | >> 689383 |
| 61 | 4000 | 10800 | B | | 105 | VW | 3528/53/54 | >> 689123 |
| 61 | 4000 | 10800 | B | yes | 105 | VW | 3528/53/54 | >> 689420 |
| 66 | 4000 | 10800 | B | | 105 | symmetric | 3528/53/54 | >> 594601 |
| 66 | 4000 | 10800 | B | yes | 105 | symmetric | 3528/53/54 | >> 689352 |
| 66 | 4000 | 11900 | A | | 120 | symmetric | 3528/53/54 | >> 689024 |
| 66 | 4000 | 11900 | A | yes | 120 | symmetric | 3528/53/54 | >> 689321 |
| 71 | 4000 | 12000 | B | | butterfly | DAN | 3528/53/54 | >> 689215 |
| 71 | 4000 | 12000 | B | yes | butterfly | DAN | 3528/53/54 | >> 689512 |
| 71 | 4000 | 12050 | B | | asymmetric left | SA-L | 3528/53/54 | >> 689291 |
| 71 | 4000 | 12050 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 689598 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 71 | 4000 | 12050 | B | | asymmetric right | SA-R | 3528/53/54 | >> 689253 |
| 71 | 4000 | 12050 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 689550 |
| 71 | 4000 | 12450 | B | | 35/67 | CN | 3528/53/54 | >> 689178 |
| 71 | 4000 | 12450 | B | yes | 35/67 | CN | 3528/53/54 | >> 689475 |
| 71 | 4000 | 12500 | B | | 90 | MW | 3528/53/54 | >> 689093 |
| 71 | 4000 | 12500 | B | yes | 90 | MW | 3528/53/54 | >> 689390 |
| 71 | 4000 | 12500 | B | | 105 | VW | 3528/53/54 | >> 689130 |
| 71 | 4000 | 12500 | B | yes | 105 | VW | 3528/53/54 | >> 689437 |
| 82 | 4000 | 13300 | B | | 105 | symmetric | 3528/53/54 | >> 594588 |
| 82 | 4000 | 13300 | B | yes | 105 | symmetric | 3528/53/54 | >> 688676 |
| 82 | 4000 | 13750 | B | | butterfly | DAN | 3528/53/54 | >> 594755 |
| 82 | 4000 | 13750 | B | yes | butterfly | DAN | 3528/53/54 | >> 688836 |
| 82 | 4000 | 13850 | B | | asymmetric left | SA-L | 3528/53/54 | >> 688614 |
| 82 | 4000 | 13850 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 688911 |
| 82 | 4000 | 13850 | B | | asymmetric right | SA-R | 3528/53/54 | >> 594816 |
| 82 | 4000 | 13850 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 688874 |
| 82 | 4000 | 14300 | B | | 35/67 | CN | 3528/53/54 | >> 594991 |
| 82 | 4000 | 14300 | B | yes | 35/67 | CN | 3528/53/54 | >> 688799 |
| 82 | 4000 | 14350 | B | | 90 | MW | 3528/53/54 | >> 594878 |
| 82 | 4000 | 14350 | B | yes | 90 | MW | 3528/53/54 | >> 688713 |
| 82 | 4000 | 14350 | B | | 105 | VW | 3528/53/54 | >> 594939 |
| 82 | 4000 | 14350 | B | yes | 105 | VW | 3528/53/54 | >> 688751 |
| 82 | 4000 | 14600 | B | | 120 | symmetric | 3528/53/54 | >> 688515 |
| 82 | 4000 | 14600 | B | yes | 120 | symmetric | 3528/53/54 | >> 688645 |
| 103 | 4000 | 16650 | B | | 105 | symmetric | 3528/53/54 | >> 688522 |
| 103 | 4000 | 16650 | B | yes | 105 | symmetric | 3528/53/54 | >> 688669 |
| 103 | 4000 | 17250 | B | | butterfly | DAN | 3528/53/54 | >> 688560 |
| 103 | 4000 | 17250 | B | yes | butterfly | DAN | 3528/53/54 | >> 688829 |
| 103 | 4000 | 17300 | B | | asymmetric left | SA-L | 3528/53/54 | >> 688607 |
| 103 | 4000 | 17300 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 688904 |
| 103 | 4000 | 17300 | B | | asymmetric right | SA-R | 3528/53/54 | >> 688577 |
| 103 | 4000 | 17300 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 688867 |
| 103 | 4000 | 17900 | B | | 35/67 | CN | 3528/53/54 | >> 688553 |

LINEA S LED ECO

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|------------------|-------------------------|---------------------------|---------------------------------|
| 103 | 4000 | 17900 | B | yes | 35/67 | CN | 3528/53/54 | >> 688782 |
| 103 | 4000 | 18000 | B | | 90 | MW | 3528/53/54 | >> 688539 |
| 103 | 4000 | 18000 | B | yes | 90 | MW | 3528/53/54 | >> 688706 |
| 103 | 4000 | 18000 | B | | 105 | VW | 3528/53/54 | >> 688546 |
| 103 | 4000 | 18000 | B | yes | 105 | VW | 3528/53/54 | >> 688744 |
| 103 | 4000 | 18250 | B | | 120 | symmetric | 3528/53/54 | >> 688508 |
| 103 | 4000 | 18250 | B | yes | 120 | symmetric | 3528/53/54 | >> 688638 |
| 123 | 4000 | 19950 | B | | 105 | symmetric | 3528/53/54 | >> 594571 |
| 123 | 4000 | 19950 | B | yes | 105 | symmetric | 3528/53/54 | >> 688652 |
| 123 | 4000 | 20650 | B | | butterfly | DAN | 3528/53/54 | >> 594748 |
| 123 | 4000 | 20650 | B | yes | butterfly | DAN | 3528/53/54 | >> 688812 |
| 123 | 4000 | 20750 | B | | asymmetric left | SA-L | 3528/53/54 | >> 688591 |
| 123 | 4000 | 20750 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 688898 |
| 123 | 4000 | 20750 | B | | asymmetric right | SA-R | 3528/53/54 | >> 594809 |
| 123 | 4000 | 20750 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 688850 |
| 123 | 4000 | 21450 | B | | 35/67 | CN | 3528/53/54 | >> 594984 |
| 123 | 4000 | 21450 | B | yes | 35/67 | CN | 3528/53/54 | >> 688775 |
| 123 | 4000 | 21550 | B | | 90 | MW | 3528/53/54 | >> 594861 |
| 123 | 4000 | 21550 | B | yes | 90 | MW | 3528/53/54 | >> 688690 |
| 123 | 4000 | 21550 | B | | 105 | VW | 3528/53/54 | >> 594922 |
| 123 | 4000 | 21550 | B | yes | 105 | VW | 3528/53/54 | >> 688737 |
| 123 | 4000 | 21900 | B | | 120 | symmetric | 3528/53/54 | >> 688492 |
| 123 | 4000 | 21900 | B | yes | 120 | symmetric | 3528/53/54 | >> 688621 |
| 143 | 4000 | 23350 | B | | 105 | symmetric | 3528/53/54 | >> 594366 |
| 143 | 4000 | 23350 | B | yes | 105 | symmetric | 3528/53/54 | >> 594373 |
| 143 | 4000 | 24150 | B | | butterfly | DAN | 3528/53/54 | >> 594731 |
| 143 | 4000 | 24150 | B | yes | butterfly | DAN | 3528/53/54 | >> 688805 |
| 143 | 4000 | 24250 | B | | asymmetric left | SA-L | 3528/53/54 | >> 688584 |
| 143 | 4000 | 24250 | B | yes | asymmetric left | SA-L | 3528/53/54 | >> 688881 |
| 143 | 4000 | 24250 | B | | asymmetric right | SA-R | 3528/53/54 | >> 594793 |
| 143 | 4000 | 24250 | B | yes | asymmetric right | SA-R | 3528/53/54 | >> 688843 |
| 143 | 4000 | 25050 | B | | 35/67 | CN | 3528/53/54 | >> 594977 |
| 143 | 4000 | 25050 | B | yes | 35/67 | CN | 3528/53/54 | >> 688768 |
| 143 | 4000 | 25200 | B | | 90 | MW | 3528/53/54 | >> 594854 |

LINEA S LED ECO


GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Energy efficiency class | DIMM DALI | Beam angle [°] | Light distribution type | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|------------------------|---------------------|-------------------------|-----------|----------------|-------------------------|---------------------------|---------------------------------|
| 143 | 4000 | 25200 | B | yes | 90 | MW | 3528/53/54 | >> 688683 |
| 143 | 4000 | 25200 | B | | 105 | VW | 3528/53/54 | >> 594915 |
| 143 | 4000 | 25200 | B | yes | 105 | VW | 3528/53/54 | >> 688720 |
| 143 | 4000 | 25600 | A | | 120 | symmetric | 3528/53/54 | >> 594328 |
| 143 | 4000 | 25600 | A | yes | 120 | symmetric | 3528/53/54 | >> 594335 |


LINEA S LED ECO

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



105D



120D

LINEA S LED ECO

GENERAL CARD

ACCESSORIES AVAILABLE


| index | Name |
|------------------------|---|
| 981173 | LINEA S LED hang 1.5m |
| 594465 | LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm DALI zoom 22-55st. White 840 20W |
| 980077 | LINEA S LED hang 3m |
| 981425 | LINEA S LED chain pendant |
| 594472 | LINEA S LED ECO 588mm - 1xEXPO ADJUST 2050lm zoom 22-55st. White 840 20W |
| 981418 | LINEA S LED pendant sm 1.5 |
| 594458 | LINEA S LED ECO 588mm 260lm AW DOT CS 2W 1h NM AT |
| 980961 | LINEA S LED pendant sm 3m |
| 980954 | Linea S LED surface mount bracket |
| 594403 | LINEA S LED ECO - metal cover 588mm |
| 594410 | LINEA S LED ECO - metal cover 1176mm |
| 594427 | LINEA S LED ECO - metal cover 1764mm |
| 594434 | LINEA S LED ECO - metal cover 2940mm |
| 594441 | LINEA S LED ECO - metal cover 3528mm |
| 594496 | LINEA S LED ECO - metal cover 588mm DALI |
| 594502 | LINEA S LED ECO - metal cover 1176mm DALI |
| 594519 | LINEA S LED ECO - metal cover 1764mm DALI |
| 594526 | LINEA S LED ECO - metal cover 2940mm DALI |
| 594533 | LINEA S LED ECO - metal cover 3528mm DALI |
| 594489 | LINEA S LED ECO - termination set |

LINEA S LED ECO

GENERAL CARD




LINEA S LED hang 1.5m (981173)




LINEA S LED ECO 588mm - 1xEXPO
ADJUST 2050lm DALI zoom 22-55st.
White 840 20W (594465)



LINEA S LED chain pendant (981425)



LINEA S LED ECO 588mm - 1xEXPO
ADJUST 2050lm zoom 22-55st. White
840 20W (594472)



LINEA S LED ECO 588mm 260lm AW
DOT CS 2W 1h NM AT (594458)



Linea S LED surface mount
bracket (980954)

Card creation date: 04 December 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 106/2024

Linea S LED has been equipped with new light distributions:

SW – standard wide lens (conventional angle 80D) with wide application in commercial facilities, industrial halls and even - due to the low UGR glare index.

MW – medium wide lens (conventional angle 90D) with wide application in commercial facilities, industrial halls and even - due to the low UGR glare index.

VW – very wide lens (conventional angle 105D) with wide application in open spaces and low warehouses. It provides high lighting efficiency and helps to meet the most stringent requirements of the EN 12464-1 standard in terms of the glare index (UGR<22, UGR<25), lighting intensity and high uniformity when installing the system in low rooms. Particularly recommended for rooms where lighting fixtures are mounted at a height of 2.5-5 m.

CN - corridor narrow lens (35/67D conventional angle) for lighting communication in industrial halls and rack alleys in high-storage warehouses. Particularly recommended for rooms where lighting fixtures are mounted at a height of 7-12 m.

DAN - butterfly lens, double asymmetric narrow (double asymmetric narrow) for lighting shelves in commercial facilities, where directing light to the displayed goods is key. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-4.5 m.

SA-L - single asymmetric lens (single asymmetric, left - view from the power supply side) for one-sided lighting of shelf surfaces in commercial spaces, boards, advertising surfaces located on the walls of the building, lighting of work surfaces in conditions where it is not possible to place fixtures directly above them. Particularly recommended for rooms where lighting fixtures are mounted at a height of 3-4.5 m.

SA-R – single asymmetric lens (single asymmetric, right – view from the power supply side) for one-sided lighting of shelf surfaces in retail spaces, boards, advertising surfaces located on the walls of the building, lighting of work surfaces in conditions where it is not possible to place the luminaires directly above them. Particularly recommended for rooms where the luminaires are mounted at a height of 3-4.5 m.