TAURUS MULTIBATTERY LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection: IP65

Impact resistance: IK08

Colour temperature [K] - range: 2700 - 6500

Luminous flux [lm]*: 5000

Supply voltage [V]: 18

Electrical protection class:

Material of the body: PP

Colour of the body: green

Diffuser type: milky

Dimensions (H/W/T/S) [mm]: 280/280/148;

CHARACTERISTICS

Compact LED floodlight for professional use. Provides even and stable directional illumination. Made from impact-resistant polypropylene (PP). Smaller size and compact design make it more convenient to transport. Equipped with an on/off switch with 4-stage luminous flux adjustment. An additional button allows adjustment of the light colour in the range: 2700K to 6500K. The lamp is compatible with 18V batteries from manufacturers such as Bosch (18V Professional), Milwaukee, DeWalt, Metabo. The unit has a display showing the battery charge level.

Operating modes for battery operation:

for 5Ah Battery:

- 500 lm - operating time: 20h

- 1500 lm - operating time: 7h 15min

- 2500 lm - operating time: 4h 30min

- 5000 lm - operating time: 2h 15min

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.



TAURUS MULTIBATTERY LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Light source	Colour temperature [K] - range	Luminous flux [lm]*	Additional accessories	Dimensions (H/W/T/S) [mm]	Index
LED module	2700 - 6500	5000	Adapter for Bosch 18V. Milwaukee 18V, DeWalt 18V, Makita 18V and Metabo 18V batteries.	280/280/148	>> 256882

Card creation date: 30 July 2025





Certificate CE - Nr: 77/2024

This product is a subject to electric and electronic waste equipment regulations (WEEE).