

# ILUMI BOLLARD

## GENERAL CARD



### TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	24.00
Ingress protection:	IP65
Impact resistance:	IK10
Luminous flux [lm]*:	1100
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	antracyt
Beam angle [°]:	360
Dimensions (H/W/T/S) [mm]:	600/fi170; 1000/fi170;

### CHARACTERISTICS

The Bollard series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of aluminium. Power supply 220-240V AC. 5-year warranty. Power: 24W.

### APPLICATION

Bollard outdoor luminaires can be used to light and illuminate a wide range of locations and objects, including but not limited to:

- \* parks,
- \* gardens,
- \* monuments,
- \* squares,
- \* fountains.

# ILUMI BOLLARD

GENERAL CARD

## AVAILABLE VERSIONS




Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Control	Colour of the body	Cable length [m]	Working temperature [°C]	Dimensions (H/W/T/S) [mm]	Index
24	3000	1100	ON/OFF	antracyt	0.50	from -20 to +55	600/fi170	<a href="#">&gt;&gt; 377303</a>
24	3000	1100	ON/OFF	antracyt	0.50	from -20 to +55	1000/fi170	<a href="#">&gt;&gt; 377310</a>

# ILUMI BOLLARD

## GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



360

Card creation date: 09 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 78/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl