INDO LED

GENERAL CARD

TECHNICAL PARAMETERS

Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	30.00
Luminous flux [lm]*:	2400 - 2600
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	A; F
Material of the body:	powder coated steel
Diffuser material:	powder coated steel
Diffuser type:	perforated
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	595/595/105;

CHARACTERISTICS

Recessed mounted square luminaire with an integrated energy-saving LED light source. Powder-coated steel body. The lens diffuser is made of perforated metal sheet. It provides comfortable and soft light. UGR < 19.

APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. Suitable as a general light source for all sorts of work that require optical focus. Dedicated for new applications and as a replacement of traditional T8 and T5 tube luminaires with energy-saving LED lamps.

INDO LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

INDO LED 595/595/105mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
30	4000	2600		595/595/105	F	>> 380099
30	3000	2400		595/595/105	A	>> 380181
30	3000	2400	yes	595/595/105	F	>> 380242
30	4000	2600	yes	595/595/105	A	>> 380150

INDO LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



INDO LED P1 30W 4000K

INDO LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
374845	Frame adapter KG 635x635 WHITE



Frame adapter KG 635x635
WHITE (374845)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 29/2015

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl