

# OCULUS LED S ECO

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK08
<b>Rated power of the luminaire [W]*:</b>	150.00
<b>Luminous flux [lm]*:</b>	23000 - 24700
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>70; >80
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	B; C
<b>Material of the body:</b>	aluminium
<b>Diffuser material:</b>	glass
<b>Diffuser type:</b>	transparent
<b>Beam angle [°]:</b>	120
<b>Dimensions (H/W/T/S) [mm]:</b>	143/245/245;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

The Oculus LED S ECO is a HIGH-BAY luminaire made using LED technology. After the Oculus LED XS ECO, it is the smallest representative of the renowned OCULUS LED series, with dimensions optimised for maximum power obtained from a body made of die-cast aluminium, powder-coated in black or grey. The passive cooling system and the isolated power supply (black) have a positive effect on the thermal management of the lamp, its service life and the maintenance of the highest performance. LED modules with high luminous efficacy (up to 165 lm/W) ensure that the required lighting levels are achieved while saving energy and reducing purchasing costs. The diffuser is made of tempered glass, which does not alter the optics of the light source - providing a general distribution of 120 degrees. The lamp is terminated with electrical cables (which require an airtight connector if the connection is to be IP65 tight). The design of the lamp is suitable for pendant mounting using the threaded, eyebolt hook supplied. The lamp should be suspended using a cord or chain dedicated to such solutions (not supplied).

## APPLICATION

The luminaire is designed for suspended mounting (using chains, cables, etc.) indoors, even in high humidity (IP65). It is ideal for factories and production halls as well as large warehouses and logistics centres.

# OCULUS LED S ECO

GENERAL CARD

## AVAILABLE VERSIONS




Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Colour of the body	Working temperature [°C]	Index
150	4000	23000	>80	black	from -20 to +35	<a href="#">&gt;&gt; 744716</a>
150	4000	23000	>80	grey	from -20 to +35	<a href="#">&gt;&gt; 744730</a>
150	4000	24700	>70	black	from -25 to +35	<a href="#">&gt;&gt; 744709</a>
150	4000	24700	>70	grey	from -20 to +35	<a href="#">&gt;&gt; 744723</a>

# OCULUS LED S ECO

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



120D

Card creation date: 14 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 82/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl