

TYTAN STEEL LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK06
Rated power of the luminaire [W]*:	14.00 - 73.00
Luminous flux [lm]*:	2150 - 12000
Colour temperature [K]:	4000
Colour rendering index:	>80
Electrical protection class:	I
Material of the body:	coated steel
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matrix led
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	600/57/45; 1188/57/45;

CHARACTERISTICS

The Tytan Steel LED reflects an innovative approach to the classic hermetic luminaire that combines functionality with aesthetics. All the technical advantages of a traditional hermetic luminaire are encapsulated in a sleek, low profile, giving the lamp a modern design. Thanks to its advanced optics, the Tytan Steel LED will be suitable for both the simplest applications and demanding industrial solutions. The product is characterised by exceptional ease of installation, low purchase and operating costs (169 lm/W). The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED is made of steel for exceptional durability and, thanks to its U-shaped profile design, retains the lightness typical of plastic luminaires, making it easy to install and not weighing down load-bearing structures. The Tytan Steel LED is the optimum combination of functionality and economy, ideal for a wide range of applications.

APPLICATION

The multi-purpose LED luminaire is designed for use in areas with high dust- and water-tightness requirements. It is particularly recommended for the illumination of industrial and warehouse halls, garages, car parks (underground and multi-storey), public facilities including hospitals, educational and educational facilities, retail and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.

TYTAN STEEL LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

TYTAN STEEL LED 1188/57/45mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	Colour of the body	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
27	4000	4150	105	symmetric	white			1188/57/45	>> 596506
27	4000	4150	105	symmetric	white		LS2	1188/57/45	>> 598647
27	4000	4550	120	symmetric	white			1188/57/45	>> 596483
27	4000	4550	120	symmetric	white		LS2	1188/57/45	>> 598623
40	4000	5950	105	symmetric	white			1188/57/45	>> 596513
40	4000	5950	105	symmetric	white	yes		1188/57/45	>> 596612
40	4000	5950	105	symmetric	white		LS2	1188/57/45	>> 598654
40	4000	5950	105	symmetric	white	yes	LS2	1188/57/45	>> 598753
40	4000	6500	120	symmetric	white			1188/57/45	>> 596490
40	4000	6500	120	symmetric	white	yes		1188/57/45	>> 596605
40	4000	6500	120	symmetric	white		LS2	1188/57/45	>> 598630
40	4000	6500	120	symmetric	white	yes	LS2	1188/57/45	>> 598746
50	4000	7550	105	symmetric	white			1188/57/45	>> 596537
50	4000	7550	105	symmetric	white		LS2	1188/57/45	>> 598678
50	4000	8300	120	symmetric	white			1188/57/45	>> 596520
50	4000	8300	120	symmetric	white		LS2	1188/57/45	>> 598661
73	4000	10900	105	symmetric	white			1188/57/45	>> 596551
73	4000	10900	105	symmetric	white	yes		1188/57/45	>> 596636
73	4000	10900	105	symmetric	white		LS2	1188/57/45	>> 598692
73	4000	10900	105	symmetric	white	yes	LS2	1188/57/45	>> 598777
73	4000	12000	120	symmetric	white			1188/57/45	>> 596544
73	4000	12000	120	symmetric	white	yes		1188/57/45	>> 596629
73	4000	12000	120	symmetric	white		LS2	1188/57/45	>> 598685
73	4000	12000	120	symmetric	white	yes	LS2	1188/57/45	>> 598760

TYTAN STEEL LED 600/57/45mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	Colour of the body	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
14	4000	2150	105	symmetric	white			600/57/45	>> 596438
14	4000	2150	105	symmetric	white		LS2	600/57/45	>> 598579
14	4000	2300	120	symmetric	white			600/57/45	>> 596414
14	4000	2300	120	symmetric	white		LS2	600/57/45	>> 598555
20	4000	2950	105	symmetric	white			600/57/45	>> 596421
20	4000	2950	105	symmetric	white	yes		600/57/45	>> 596575

TYTAN STEEL LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	Colour of the body	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
20	4000	2950	105	symmetric	white		LS2	600/57/45	>> 598562
20	4000	2950	105	symmetric	white	yes	LS2	600/57/45	>> 598715
20	4000	3250	120	symmetric	white			600/57/45	>> 596407
20	4000	3250	120	symmetric	white	yes		600/57/45	>> 596568
20	4000	3250	120	symmetric	white		LS2	600/57/45	>> 598548
20	4000	3250	120	symmetric	white	yes	LS2	600/57/45	>> 598708
30	4000	4400	105	symmetric	white			600/57/45	>> 596476
30	4000	4400	105	symmetric	white		LS2	600/57/45	>> 598616
30	4000	4800	120	symmetric	white			600/57/45	>> 596452
30	4000	4800	120	symmetric	white		LS2	600/57/45	>> 598593
34	4000	4900	105	symmetric	white			600/57/45	>> 596469
34	4000	4900	105	symmetric	white	yes		600/57/45	>> 596599
34	4000	4900	105	symmetric	white		LS2	600/57/45	>> 598609
34	4000	4900	105	symmetric	white	yes	LS2	600/57/45	>> 598739
34	4000	5500	120	symmetric	white			600/57/45	>> 596445
34	4000	5500	120	symmetric	white	yes		600/57/45	>> 596582
34	4000	5500	120	symmetric	white		LS2	600/57/45	>> 598586
34	4000	5500	120	symmetric	white	yes	LS2	600/57/45	>> 598722

Card creation date: 17 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 86/2024