

# MERCURY LED EVO

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	10.00
<b>Luminous flux [lm]*:</b>	900; 1000
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	ø255/85;

## CHARACTERISTICS

Mercury LED Evo surface-mounted, round LED light fixture with a high luminous flux (94 lm/W), high ingress protection class IP54 and an integrated energy-saving light source LED. Base and ring made of UV-resistant plastic. A specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10). Available in white; optional equipment: radio motion sensor (RCR). Color temperature 3000K/4000K, CRI>80, lifespan of LED 50 000h (L70B50) ta= 25 °C.

## APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

# MERCURY LED EVO

GENERAL CARD

## AVAILABLE VERSIONS




Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Motion sensor	Dimensions (H/W/T/S) [mm]	Index
10	4000	1000		ø255/85	<a href="#">&gt;&gt; 187308</a>
10	3000	900		ø255/85	<a href="#">&gt;&gt; 187315</a>
10	4000	1000	yes	ø255/85	<a href="#">&gt;&gt; 187322</a>
10	3000	900	yes	ø255/85	<a href="#">&gt;&gt; 187339</a>

# MERCURY LED EVO

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



MERCURY LED EVO

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 91/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl