

INDUSTRY 2 LED IOT

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP23
Impact resistance:	IK07
Nominal power [W]:	147.00
Luminous flux [lm]*:	23600
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	silver satin
Diffuser material:	glass
Diffuser type:	transparent
Optics material:	PMMA
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	1490/190/70;

CHARACTERISTICS

Galvanized steel sheet Industrial luminaire with IP23, with in-built energy-saving LED modules. Thanks to line lenses, following light distribution angles are available: 90°, 60°, 45°.

IoT characteristics

IoT RC PIR HYT DALI has: **PIR** motion and light sensor programmed by **RC** remote control and **DALI** driver enabling dimming of the light source.

APPLICATION

Luminaire intended for warehouses, large stores, production halls and sports facilities. Meant for new installations and replacement of traditional T8 & T5 luminaires with energy saving LED sources.

INDUSTRY 2 LED IOT

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Through wiring	Beam angle [°]	Ingress protection	Impact resistance	DIMM DALI	Control	Version	Dimensions (H/W/T/S) [mm]	Index
147	4000	23600	LS1	90	IP23	IK07	yes	DALI	RC PIR HYT DALI	1490/190/70	>> 973574

Card creation date:10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric andelectronic waste equipment regulations (WEEE).



Certificate CE - Nr: 145/2023; 446/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl