

BARIS 40 LED UGR PLUS

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20; IP44
Impact resistance:	IK03
Rated power of the luminaire [W]*:	19.00 - 45.00
Luminous flux [lm]*:	1875 - 5875
Colour temperature [K]:	3000; 4000
Material of the body:	aluminium
Colour of the body:	black; grey; white
Diffuser material:	PC
Diffuser type:	transparent
Optics material:	PC
Mounting version:	surface; suspended
Dimensions (H/W/T/S) [mm]:	53/40/1140; 53/40/1421;

CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver.

The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED UGR PLUS

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

BARIS 40 LED UGR PLUS surface

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
19	3000	2050	70	IP20	black		surface	53/40/1140	>> 770128
19	3000	2050	70	IP20	black	yes	surface	53/40/1140	>> 770180
19	3000	2075	70	IP20	grey		surface	53/40/1140	>> 770104
19	3000	2075	70	IP20	grey	yes	surface	53/40/1140	>> 770166
19	4000	2175	70	IP20	black		surface	53/40/1140	>> 770005
19	4000	2175	70	IP20	black	yes	surface	53/40/1140	>> 770067
19	4000	2200	70	IP20	grey		surface	53/40/1140	>> 769986
19	4000	2200	70	IP20	grey	yes	surface	53/40/1140	>> 770043
19	3000	2250	60	IP20	black		surface	53/40/1140	>> 769160
19	3000	2250	60	IP20	black	yes	surface	53/40/1140	>> 769221
19	3000	2275	60	IP20	grey		surface	53/40/1140	>> 769146
19	3000	2275	60	IP20	grey	yes	surface	53/40/1140	>> 769207
19	4000	2375	60	IP20	black		surface	53/40/1140	>> 769047
19	4000	2375	60	IP20	black	yes	surface	53/40/1140	>> 769108
19	3000	2375	70	IP20	white		surface	53/40/1140	>> 770081
19	3000	2375	70	IP20	white	yes	surface	53/40/1140	>> 770142
19	4000	2400	60	IP20	grey		surface	53/40/1140	>> 769023
19	4000	2400	60	IP20	grey	yes	surface	53/40/1140	>> 769085
19	3000	2500	60	IP20	white		surface	53/40/1140	>> 769122
19	3000	2500	60	IP20	white	yes	surface	53/40/1140	>> 769184
19	4000	2500	70	IP20	white		surface	53/40/1140	>> 769962
19	4000	2500	70	IP20	white	yes	surface	53/40/1140	>> 770029
19	4000	2625	60	IP20	white		surface	53/40/1140	>> 769009
19	4000	2625	60	IP20	white	yes	surface	53/40/1140	>> 769061
27	3000	2850	70	IP20	black		surface	53/40/1140	>> 770135
27	3000	2850	70	IP20	black	yes	surface	53/40/1140	>> 770197
27	3000	2900	70	IP20	grey		surface	53/40/1140	>> 770111
27	3000	2900	70	IP20	grey	yes	surface	53/40/1140	>> 770173
27	4000	2975	70	IP20	black		surface	53/40/1140	>> 770012
27	4000	2975	70	IP20	black	yes	surface	53/40/1140	>> 770074
27	4000	3025	70	IP20	grey		surface	53/40/1140	>> 769993
27	4000	3025	70	IP20	grey	yes	surface	53/40/1140	>> 770050
27	3000	3125	60	IP20	black		surface	53/40/1140	>> 769177

BARIS 40 LED UGR PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
27	3000	3125	60	IP20	black	yes	surface	53/40/1140	>> 769238
27	3000	3175	60	IP20	grey		surface	53/40/1140	>> 769153
27	3000	3175	60	IP20	grey	yes	surface	53/40/1140	>> 769214
27	4000	3275	60	IP20	black		surface	53/40/1140	>> 769054
27	4000	3275	60	IP20	black	yes	surface	53/40/1140	>> 769115
27	3000	3300	70	IP20	white		surface	53/40/1140	>> 770098
27	3000	3300	70	IP20	white	yes	surface	53/40/1140	>> 770159
27	4000	3325	60	IP20	grey		surface	53/40/1140	>> 769030
27	4000	3325	60	IP20	grey	yes	surface	53/40/1140	>> 769092
27	3000	3475	60	IP20	white		surface	53/40/1140	>> 769139
27	3000	3475	60	IP20	white	yes	surface	53/40/1140	>> 769191
27	4000	3475	70	IP20	white		surface	53/40/1140	>> 769979
27	4000	3475	70	IP20	white	yes	surface	53/40/1140	>> 770036
27	4000	3650	60	IP20	white		surface	53/40/1140	>> 769016
27	4000	3650	60	IP20	white	yes	surface	53/40/1140	>> 769078
29	3000	3175	70	IP20	black		surface	53/40/1421	>> 770371
29	3000	3175	70	IP20	black	yes	surface	53/40/1421	>> 770432
29	3000	3225	70	IP20	grey		surface	53/40/1421	>> 770357
29	3000	3225	70	IP20	grey	yes	surface	53/40/1421	>> 770418
29	4000	3325	70	IP20	black		surface	53/40/1421	>> 770258
29	4000	3325	70	IP20	black	yes	surface	53/40/1421	>> 770319
29	4000	3350	70	IP20	grey		surface	53/40/1421	>> 770234
29	4000	3350	70	IP20	grey	yes	surface	53/40/1421	>> 770296
29	3000	3700	70	IP20	white		surface	53/40/1421	>> 770333
29	3000	3700	70	IP20	white	yes	surface	53/40/1421	>> 770395
29	4000	3850	70	IP20	white		surface	53/40/1421	>> 770210
29	4000	3850	70	IP20	white	yes	surface	53/40/1421	>> 770272
35	3000	3725	70	IP20	black		surface	53/40/1421	>> 770364
35	3000	3725	70	IP20	black	yes	surface	53/40/1421	>> 770425
35	3000	3775	70	IP20	grey		surface	53/40/1421	>> 770340
35	3000	3775	70	IP20	grey	yes	surface	53/40/1421	>> 770401
35	4000	3925	70	IP20	black		surface	53/40/1421	>> 770241
35	4000	3925	70	IP20	black	yes	surface	53/40/1421	>> 770302
35	4000	3950	70	IP20	grey		surface	53/40/1421	>> 770227
35	4000	3950	70	IP20	grey	yes	surface	53/40/1421	>> 770289
35	3000	4100	60	IP20	black		surface	53/40/1421	>> 769405
35	3000	4100	60	IP20	black	yes	surface	53/40/1421	>> 769467
35	3000	4150	60	IP20	grey		surface	53/40/1421	>> 769382

BARIS 40 LED UGR PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
35	3000	4150	60	IP20	grey	yes	surface	53/40/1421	>> 769443
35	4000	4300	60	IP20	black		surface	53/40/1421	>> 769283
35	4000	4300	60	IP20	black	yes	surface	53/40/1421	>> 769344
35	3000	4325	70	IP20	white		surface	53/40/1421	>> 770326
35	3000	4325	70	IP20	white	yes	surface	53/40/1421	>> 770388
35	4000	4350	60	IP20	grey		surface	53/40/1421	>> 769269
35	4000	4350	60	IP20	grey	yes	surface	53/40/1421	>> 769320
35	3000	4550	60	IP20	white		surface	53/40/1421	>> 769368
35	3000	4550	60	IP20	white	yes	surface	53/40/1421	>> 769429
35	4000	4550	70	IP20	white		surface	53/40/1421	>> 770203
35	4000	4550	70	IP20	white	yes	surface	53/40/1421	>> 770265
35	4000	4775	60	IP20	white		surface	53/40/1421	>> 769245
35	4000	4775	60	IP20	white	yes	surface	53/40/1421	>> 769306
45	3000	5050	60	IP20	black		surface	53/40/1421	>> 769412
45	3000	5050	60	IP20	black	yes	surface	53/40/1421	>> 769474
45	3000	5100	60	IP20	grey		surface	53/40/1421	>> 769399
45	3000	5100	60	IP20	grey	yes	surface	53/40/1421	>> 769450
45	4000	5300	60	IP20	black		surface	53/40/1421	>> 769290
45	4000	5300	60	IP20	black	yes	surface	53/40/1421	>> 769351
45	4000	5350	60	IP20	grey		surface	53/40/1421	>> 769276
45	4000	5350	60	IP20	grey	yes	surface	53/40/1421	>> 769337
45	3000	5625	60	IP20	white		surface	53/40/1421	>> 769375
45	3000	5625	60	IP20	white	yes	surface	53/40/1421	>> 769436
45	4000	5875	60	IP20	white		surface	53/40/1421	>> 769252
45	4000	5875	60	IP20	white	yes	surface	53/40/1421	>> 769313

BARIS 40 LED UGR PLUS suspended

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
19	3000	1875	70	IP44	black		suspended	53/40/1140	>> 771569
19	3000	1875	70	IP44	black	yes	suspended	53/40/1140	>> 771620
19	3000	1900	70	IP44	grey		suspended	53/40/1140	>> 771545
19	3000	1900	70	IP44	grey	yes	suspended	53/40/1140	>> 771606
19	4000	1975	70	IP44	black		suspended	53/40/1140	>> 771446
19	4000	1975	70	IP44	black	yes	suspended	53/40/1140	>> 771507
19	4000	2000	70	IP44	grey		suspended	53/40/1140	>> 771422
19	4000	2000	70	IP44	grey	yes	suspended	53/40/1140	>> 771484
19	3000	2050	70	IP20	black		suspended	53/40/1140	>> 770609
19	3000	2050	70	IP20	black	yes	suspended	53/40/1140	>> 770661

BARIS 40 LED UGR PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
19	3000	2075	70	IP20	grey		suspended	53/40/1140	>> 770586
19	3000	2075	70	IP20	grey	yes	suspended	53/40/1140	>> 770647
19	3000	2075	60	IP44	black		suspended	53/40/1140	>> 771088
19	3000	2075	60	IP44	black	yes	suspended	53/40/1140	>> 771149
19	3000	2100	60	IP44	grey		suspended	53/40/1140	>> 771064
19	3000	2100	60	IP44	grey	yes	suspended	53/40/1140	>> 771125
19	4000	2175	70	IP20	black		suspended	53/40/1140	>> 770487
19	4000	2175	70	IP20	black	yes	suspended	53/40/1140	>> 770548
19	3000	2175	70	IP44	white		suspended	53/40/1140	>> 771521
19	3000	2175	70	IP44	white	yes	suspended	53/40/1140	>> 771583
19	4000	2200	70	IP20	grey		suspended	53/40/1140	>> 770463
19	4000	2200	70	IP20	grey	yes	suspended	53/40/1140	>> 770524
19	4000	2200	60	IP44	black		suspended	53/40/1140	>> 770968
19	4000	2200	60	IP44	black	yes	suspended	53/40/1140	>> 771026
19	4000	2225	60	IP44	grey		suspended	53/40/1140	>> 770944
19	4000	2225	60	IP44	grey	yes	suspended	53/40/1140	>> 771002
19	3000	2250	60	IP20	black		suspended	53/40/1140	>> 769641
19	3000	2250	60	IP20	black	yes	suspended	53/40/1140	>> 769702
19	3000	2275	60	IP20	grey		suspended	53/40/1140	>> 769627
19	3000	2275	60	IP20	grey	yes	suspended	53/40/1140	>> 769689
19	4000	2275	70	IP44	white		suspended	53/40/1140	>> 771408
19	4000	2275	70	IP44	white	yes	suspended	53/40/1140	>> 771460
19	3000	2300	60	IP44	white		suspended	53/40/1140	>> 771040
19	3000	2300	60	IP44	white	yes	suspended	53/40/1140	>> 771101
19	4000	2375	60	IP20	black		suspended	53/40/1140	>> 769528
19	4000	2375	60	IP20	black	yes	suspended	53/40/1140	>> 769580
19	3000	2375	70	IP20	white		suspended	53/40/1140	>> 770562
19	3000	2375	70	IP20	white	yes	suspended	53/40/1140	>> 770623
19	4000	2400	60	IP20	grey		suspended	53/40/1140	>> 769504
19	4000	2400	60	IP20	grey	yes	suspended	53/40/1140	>> 769566
19	4000	2425	60	IP44	white		suspended	53/40/1140	>> 770920
19	4000	2425	60	IP44	white	yes	suspended	53/40/1140	>> 770982
19	3000	2500	60	IP20	white		suspended	53/40/1140	>> 769603
19	3000	2500	60	IP20	white	yes	suspended	53/40/1140	>> 769665
19	4000	2500	70	IP20	white		suspended	53/40/1140	>> 770449
19	4000	2500	70	IP20	white	yes	suspended	53/40/1140	>> 770500
19	4000	2625	60	IP20	white		suspended	53/40/1140	>> 769481
19	4000	2625	60	IP20	white	yes	suspended	53/40/1140	>> 769542

BARIS 40 LED UGR PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
27	3000	2600	70	IP44	black		suspended	53/40/1140	>> 771576
27	3000	2600	70	IP44	black	yes	suspended	53/40/1140	>> 771637
27	3000	2650	70	IP44	grey		suspended	53/40/1140	>> 771552
27	3000	2650	70	IP44	grey	yes	suspended	53/40/1140	>> 771613
27	4000	2725	70	IP44	black		suspended	53/40/1140	>> 771453
27	4000	2725	70	IP44	black	yes	suspended	53/40/1140	>> 771514
27	4000	2775	70	IP44	grey		suspended	53/40/1140	>> 771439
27	4000	2775	70	IP44	grey	yes	suspended	53/40/1140	>> 771491
27	3000	2850	70	IP20	black		suspended	53/40/1140	>> 770616
27	3000	2850	70	IP20	black	yes	suspended	53/40/1140	>> 770678
27	3000	2875	60	IP44	black		suspended	53/40/1140	>> 771095
27	3000	2875	60	IP44	black	yes	suspended	53/40/1140	>> 771156
27	3000	2900	70	IP20	grey		suspended	53/40/1140	>> 770593
27	3000	2900	70	IP20	grey	yes	suspended	53/40/1140	>> 770654
27	3000	2925	60	IP44	grey		suspended	53/40/1140	>> 771071
27	3000	2925	60	IP44	grey	yes	suspended	53/40/1140	>> 771132
27	4000	2975	70	IP20	black		suspended	53/40/1140	>> 770494
27	4000	2975	70	IP20	black	yes	suspended	53/40/1140	>> 770555
27	4000	3025	70	IP20	grey		suspended	53/40/1140	>> 770470
27	4000	3025	70	IP20	grey	yes	suspended	53/40/1140	>> 770531
27	4000	3025	60	IP44	black		suspended	53/40/1140	>> 770975
27	4000	3025	60	IP44	black	yes	suspended	53/40/1140	>> 771033
27	3000	3025	70	IP44	white		suspended	53/40/1140	>> 771538
27	3000	3025	70	IP44	white	yes	suspended	53/40/1140	>> 771590
27	4000	3075	60	IP44	grey		suspended	53/40/1140	>> 770951
27	4000	3075	60	IP44	grey	yes	suspended	53/40/1140	>> 771019
27	3000	3125	60	IP20	black		suspended	53/40/1140	>> 769658
27	3000	3125	60	IP20	black	yes	suspended	53/40/1140	>> 769719
27	3000	3175	60	IP20	grey		suspended	53/40/1140	>> 769634
27	3000	3175	60	IP20	grey	yes	suspended	53/40/1140	>> 769696
27	4000	3175	70	IP44	white		suspended	53/40/1140	>> 771415
27	4000	3175	70	IP44	white	yes	suspended	53/40/1140	>> 771477
27	3000	3200	60	IP44	white		suspended	53/40/1140	>> 771057
27	3000	3200	60	IP44	white	yes	suspended	53/40/1140	>> 771118
27	4000	3275	60	IP20	black		suspended	53/40/1140	>> 769535
27	4000	3275	60	IP20	black	yes	suspended	53/40/1140	>> 769597
27	3000	3300	70	IP20	white		suspended	53/40/1140	>> 770579
27	3000	3300	70	IP20	white	yes	suspended	53/40/1140	>> 770630

BARIS 40 LED UGR PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
27	4000	3325	60	IP20	grey		suspended	53/40/1140	>> 769511
27	4000	3325	60	IP20	grey	yes	suspended	53/40/1140	>> 769573
27	4000	3375	60	IP44	white		suspended	53/40/1140	>> 770937
27	4000	3375	60	IP44	white	yes	suspended	53/40/1140	>> 770999
27	3000	3475	60	IP20	white		suspended	53/40/1140	>> 769610
27	3000	3475	60	IP20	white	yes	suspended	53/40/1140	>> 769672
27	4000	3475	70	IP20	white		suspended	53/40/1140	>> 770456
27	4000	3475	70	IP20	white	yes	suspended	53/40/1140	>> 770517
27	4000	3650	60	IP20	white		suspended	53/40/1140	>> 769498
27	4000	3650	60	IP20	white	yes	suspended	53/40/1140	>> 769559
29	3000	2900	70	IP44	black		suspended	53/40/1421	>> 771811
29	3000	2900	70	IP44	black	yes	suspended	53/40/1421	>> 771873
29	3000	2925	70	IP44	grey		suspended	53/40/1421	>> 771798
29	3000	2925	70	IP44	grey	yes	suspended	53/40/1421	>> 771859
29	4000	3050	70	IP44	grey		suspended	53/40/1421	>> 771675
29	4000	3050	70	IP44	black		suspended	53/40/1421	>> 771699
29	4000	3050	70	IP44	grey	yes	suspended	53/40/1421	>> 771736
29	4000	3050	70	IP44	black	yes	suspended	53/40/1421	>> 771750
29	3000	3175	70	IP20	black		suspended	53/40/1421	>> 770852
29	3000	3175	70	IP20	black	yes	suspended	53/40/1421	>> 770913
29	3000	3225	70	IP20	grey		suspended	53/40/1421	>> 770838
29	3000	3225	70	IP20	grey	yes	suspended	53/40/1421	>> 770890
29	4000	3325	70	IP20	black		suspended	53/40/1421	>> 770739
29	4000	3325	70	IP20	black	yes	suspended	53/40/1421	>> 770791
29	4000	3350	70	IP20	grey		suspended	53/40/1421	>> 770715
29	4000	3350	70	IP20	grey	yes	suspended	53/40/1421	>> 770777
29	3000	3375	70	IP44	white		suspended	53/40/1421	>> 771774
29	3000	3375	70	IP44	white	yes	suspended	53/40/1421	>> 771835
29	4000	3525	70	IP44	white		suspended	53/40/1421	>> 771651
29	4000	3525	70	IP44	white	yes	suspended	53/40/1421	>> 771712
29	3000	3700	70	IP20	white		suspended	53/40/1421	>> 770814
29	3000	3700	70	IP20	white	yes	suspended	53/40/1421	>> 770876
29	4000	3850	70	IP20	white		suspended	53/40/1421	>> 770692
29	4000	3850	70	IP20	white	yes	suspended	53/40/1421	>> 770753
35	3000	3400	70	IP44	black		suspended	53/40/1421	>> 771804
35	3000	3400	70	IP44	black	yes	suspended	53/40/1421	>> 771866
35	3000	3450	70	IP44	grey		suspended	53/40/1421	>> 771781
35	3000	3450	70	IP44	grey	yes	suspended	53/40/1421	>> 771842

BARIS 40 LED UGR PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
35	4000	3575	70	IP44	black		suspended	53/40/1421	>> 771682
35	4000	3575	70	IP44	black	yes	suspended	53/40/1421	>> 771743
35	4000	3625	70	IP44	grey		suspended	53/40/1421	>> 771668
35	4000	3625	70	IP44	grey	yes	suspended	53/40/1421	>> 771729
35	3000	3725	70	IP20	black		suspended	53/40/1421	>> 770845
35	3000	3725	70	IP20	black	yes	suspended	53/40/1421	>> 770906
35	3000	3775	70	IP20	grey		suspended	53/40/1421	>> 770821
35	3000	3775	70	IP20	grey	yes	suspended	53/40/1421	>> 770883
35	3000	3775	60	IP44	black		suspended	53/40/1421	>> 771323
35	3000	3775	60	IP44	black	yes	suspended	53/40/1421	>> 771385
35	3000	3825	60	IP44	grey		suspended	53/40/1421	>> 771309
35	3000	3825	60	IP44	grey	yes	suspended	53/40/1421	>> 771361
35	4000	3925	70	IP20	black		suspended	53/40/1421	>> 770722
35	4000	3925	70	IP20	black	yes	suspended	53/40/1421	>> 770784
35	4000	3950	70	IP20	grey		suspended	53/40/1421	>> 770708
35	4000	3950	70	IP20	grey	yes	suspended	53/40/1421	>> 770760
35	3000	3950	70	IP44	white		suspended	53/40/1421	>> 771767
35	3000	3950	70	IP44	white	yes	suspended	53/40/1421	>> 771828
35	4000	3975	60	IP44	black		suspended	53/40/1421	>> 771200
35	4000	3975	60	IP44	black	yes	suspended	53/40/1421	>> 771262
35	4000	4025	60	IP44	grey		suspended	53/40/1421	>> 771187
35	4000	4025	60	IP44	grey	yes	suspended	53/40/1421	>> 771248
35	3000	4100	60	IP20	black		suspended	53/40/1421	>> 769887
35	3000	4100	60	IP20	black	yes	suspended	53/40/1421	>> 769948
35	3000	4150	60	IP20	grey		suspended	53/40/1421	>> 769863
35	3000	4150	60	IP20	grey	yes	suspended	53/40/1421	>> 769924
35	4000	4150	70	IP44	white		suspended	53/40/1421	>> 771644
35	4000	4150	70	IP44	white	yes	suspended	53/40/1421	>> 771705
35	3000	4200	60	IP44	white		suspended	53/40/1421	>> 771286
35	3000	4200	60	IP44	white	yes	suspended	53/40/1421	>> 771347
35	4000	4300	60	IP20	black		suspended	53/40/1421	>> 769764
35	4000	4300	60	IP20	black	yes	suspended	53/40/1421	>> 769825
35	3000	4325	70	IP20	white		suspended	53/40/1421	>> 770807
35	3000	4325	70	IP20	white	yes	suspended	53/40/1421	>> 770869
35	4000	4350	60	IP20	grey		suspended	53/40/1421	>> 769740
35	4000	4350	60	IP20	grey	yes	suspended	53/40/1421	>> 769801
35	4000	4400	60	IP44	white		suspended	53/40/1421	>> 771163
35	4000	4400	60	IP44	white	yes	suspended	53/40/1421	>> 771224

BARIS 40 LED UGR PLUS

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
35	3000	4550	60	IP20	white		suspended	53/40/1421	>> 769849
35	3000	4550	60	IP20	white	yes	suspended	53/40/1421	>> 769900
35	4000	4550	70	IP20	white		suspended	53/40/1421	>> 770685
35	4000	4550	70	IP20	white	yes	suspended	53/40/1421	>> 770746
35	4000	4775	60	IP20	white		suspended	53/40/1421	>> 769726
35	4000	4775	60	IP20	white	yes	suspended	53/40/1421	>> 769788
45	3000	4650	60	IP44	black		suspended	53/40/1421	>> 771330
45	3000	4650	60	IP44	black	yes	suspended	53/40/1421	>> 771392
45	3000	4700	60	IP44	grey		suspended	53/40/1421	>> 771316
45	3000	4700	60	IP44	grey	yes	suspended	53/40/1421	>> 771378
45	4000	4900	60	IP44	black		suspended	53/40/1421	>> 771217
45	4000	4900	60	IP44	black	yes	suspended	53/40/1421	>> 771279
45	4000	4925	60	IP44	grey		suspended	53/40/1421	>> 771194
45	4000	4925	60	IP44	grey	yes	suspended	53/40/1421	>> 771255
45	3000	5050	60	IP20	black		suspended	53/40/1421	>> 769894
45	3000	5050	60	IP20	black	yes	suspended	53/40/1421	>> 769955
45	3000	5100	60	IP20	grey		suspended	53/40/1421	>> 769870
45	3000	5100	60	IP20	grey	yes	suspended	53/40/1421	>> 769931
45	3000	5175	60	IP44	white		suspended	53/40/1421	>> 771293
45	3000	5175	60	IP44	white	yes	suspended	53/40/1421	>> 771354
45	4000	5300	60	IP20	black		suspended	53/40/1421	>> 769771
45	4000	5300	60	IP20	black	yes	suspended	53/40/1421	>> 769832
45	4000	5350	60	IP20	grey		suspended	53/40/1421	>> 769757
45	4000	5350	60	IP20	grey	yes	suspended	53/40/1421	>> 769818
45	4000	5425	60	IP44	white		suspended	53/40/1421	>> 771170
45	4000	5425	60	IP44	white	yes	suspended	53/40/1421	>> 771231
45	3000	5625	60	IP20	white		suspended	53/40/1421	>> 769856
45	3000	5625	60	IP20	white	yes	suspended	53/40/1421	>> 769917
45	4000	5875	60	IP20	white		suspended	53/40/1421	>> 769733
45	4000	5875	60	IP20	white	yes	suspended	53/40/1421	>> 769795

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2024