

# BARIS 40 LED UGR PLUS

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20; IP44
<b>Impact resistance:</b>	IK03
<b>Rated power of the luminaire [W]*:</b>	17.00 - 40.00
<b>Luminous flux [lm]*:</b>	1875 - 5875
<b>Colour temperature [K]:</b>	3000; 4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black; grey; white
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	transparent
<b>Optics material:</b>	PC
<b>Mounting version:</b>	surface; suspended
<b>Dimensions (H/W/T/S) [mm]:</b>	53/40/1140; 53/40/1421;

## CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver.

The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

# BARIS 40 LED UGR PLUS

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### BARIS 40 LED UGR PLUS surface

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
17	3000	2050	121	70	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 770128</a>
17	3000	2050	121	70	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770180</a>
17	3000	2075	122	70	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 770104</a>
17	3000	2075	122	70	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770166</a>
17	4000	2175	128	70	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 770005</a>
17	4000	2175	128	70	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770067</a>
17	4000	2200	129	70	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 769986</a>
17	4000	2200	129	70	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770043</a>
17	3000	2250	132	60	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 769160</a>
17	3000	2250	132	60	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769221</a>
17	3000	2275	134	60	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 769146</a>
17	3000	2275	134	60	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769207</a>
17	4000	2375	140	60	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 769047</a>
17	4000	2375	140	60	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769108</a>
17	3000	2375	140	70	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 770081</a>
17	3000	2375	140	70	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770142</a>
17	4000	2400	141	60	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 769023</a>
17	4000	2400	141	60	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769085</a>
17	3000	2500	147	60	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 769122</a>
17	3000	2500	147	60	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769184</a>
17	4000	2500	147	70	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 769962</a>
17	4000	2500	147	70	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770029</a>
17	4000	2625	154	60	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 769009</a>
17	4000	2625	154	60	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769061</a>
24	3000	2850	119	70	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 770135</a>
24	3000	2850	119	70	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770197</a>
24	3000	2900	121	70	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 770111</a>
24	3000	2900	121	70	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770173</a>
24	4000	2975	124	70	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 770012</a>
24	4000	2975	124	70	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770074</a>
24	4000	3025	126	70	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 769993</a>
24	4000	3025	126	70	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770050</a>
24	3000	3125	130	60	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 769177</a>

# BARIS 40 LED UGR PLUS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
24	3000	3125	130	60	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769238</a>
24	3000	3175	132	60	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 769153</a>
24	3000	3175	132	60	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769214</a>
24	4000	3275	136	60	IP20	black		surface	53/40/1140	<a href="#">&gt;&gt; 769054</a>
24	4000	3275	136	60	IP20	black	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769115</a>
24	3000	3300	138	70	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 770098</a>
24	3000	3300	138	70	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770159</a>
24	4000	3325	139	60	IP20	grey		surface	53/40/1140	<a href="#">&gt;&gt; 769030</a>
24	4000	3325	139	60	IP20	grey	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769092</a>
24	3000	3475	145	60	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 769139</a>
24	3000	3475	145	60	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769191</a>
24	4000	3475	145	70	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 769979</a>
24	4000	3475	145	70	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 770036</a>
24	4000	3650	152	60	IP20	white		surface	53/40/1140	<a href="#">&gt;&gt; 769016</a>
24	4000	3650	152	60	IP20	white	yes	surface	53/40/1140	<a href="#">&gt;&gt; 769078</a>
26	3000	3175	122	70	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 770371</a>
26	3000	3175	122	70	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770432</a>
26	3000	3225	124	70	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 770357</a>
26	3000	3225	124	70	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770418</a>
26	4000	3325	128	70	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 770258</a>
26	4000	3325	128	70	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770319</a>
26	4000	3350	129	70	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 770234</a>
26	4000	3350	129	70	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770296</a>
26	3000	3700	142	70	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 770333</a>
26	3000	3700	142	70	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770395</a>
26	4000	3850	148	70	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 770210</a>
26	4000	3850	148	70	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770272</a>
31	3000	3725	120	70	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 770364</a>
31	3000	3725	120	70	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770425</a>
31	3000	3775	122	70	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 770340</a>
31	3000	3775	122	70	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770401</a>
31	4000	3925	127	70	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 770241</a>
31	4000	3925	127	70	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770302</a>
31	4000	3950	127	70	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 770227</a>
31	4000	3950	127	70	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770289</a>
31	3000	4100	132	60	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 769405</a>
31	3000	4100	132	60	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769467</a>
31	3000	4150	134	60	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 769382</a>

# BARIS 40 LED UGR PLUS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
31	3000	4150	134	60	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769443</a>
31	4000	4300	139	60	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 769283</a>
31	4000	4300	139	60	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769344</a>
31	3000	4325	140	70	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 770326</a>
31	3000	4325	140	70	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770388</a>
31	4000	4350	140	60	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 769269</a>
31	4000	4350	140	60	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769320</a>
31	3000	4550	147	60	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 769368</a>
31	3000	4550	147	60	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769429</a>
31	4000	4550	147	70	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 770203</a>
31	4000	4550	147	70	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 770265</a>
31	4000	4775	154	60	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 769245</a>
31	4000	4775	154	60	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769306</a>
40	3000	5050	126	60	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 769412</a>
40	3000	5050	126	60	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769474</a>
40	3000	5100	128	60	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 769399</a>
40	3000	5100	128	60	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769450</a>
40	4000	5300	133	60	IP20	black		surface	53/40/1421	<a href="#">&gt;&gt; 769290</a>
40	4000	5300	133	60	IP20	black	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769351</a>
40	4000	5350	134	60	IP20	grey		surface	53/40/1421	<a href="#">&gt;&gt; 769276</a>
40	4000	5350	134	60	IP20	grey	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769337</a>
40	3000	5625	141	60	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 769375</a>
40	3000	5625	141	60	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769436</a>
40	4000	5875	147	60	IP20	white		surface	53/40/1421	<a href="#">&gt;&gt; 769252</a>
40	4000	5875	147	60	IP20	white	yes	surface	53/40/1421	<a href="#">&gt;&gt; 769313</a>

## BARIS 40 LED UGR PLUS suspended

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
17	3000	1875	110	70	IP44	black		suspended	53/40/1140	<a href="#">&gt;&gt; 771569</a>
17	3000	1875	110	70	IP44	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771620</a>
17	3000	1900	112	70	IP44	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 771545</a>
17	3000	1900	112	70	IP44	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771606</a>
17	4000	1975	116	70	IP44	black		suspended	53/40/1140	<a href="#">&gt;&gt; 771446</a>
17	4000	1975	116	70	IP44	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771507</a>
17	4000	2000	118	70	IP44	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 771422</a>
17	4000	2000	118	70	IP44	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771484</a>
17	3000	2050	121	70	IP20	black		suspended	53/40/1140	<a href="#">&gt;&gt; 770609</a>

# BARIS 40 LED UGR PLUS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
17	3000	2050	121	70	IP20	black	yes	suspended	53/40/1140	<a href="#">» 770661</a>
17	3000	2075	122	70	IP20	grey		suspended	53/40/1140	<a href="#">» 770586</a>
17	3000	2075	122	70	IP20	grey	yes	suspended	53/40/1140	<a href="#">» 770647</a>
17	3000	2075	122	60	IP44	black		suspended	53/40/1140	<a href="#">» 771088</a>
17	3000	2075	122	60	IP44	black	yes	suspended	53/40/1140	<a href="#">» 771149</a>
17	3000	2100	124	60	IP44	grey		suspended	53/40/1140	<a href="#">» 771064</a>
17	3000	2100	124	60	IP44	grey	yes	suspended	53/40/1140	<a href="#">» 771125</a>
17	4000	2175	128	70	IP20	black		suspended	53/40/1140	<a href="#">» 770487</a>
17	4000	2175	128	70	IP20	black	yes	suspended	53/40/1140	<a href="#">» 770548</a>
17	3000	2175	128	70	IP44	white		suspended	53/40/1140	<a href="#">» 771521</a>
17	3000	2175	128	70	IP44	white	yes	suspended	53/40/1140	<a href="#">» 771583</a>
17	4000	2200	129	70	IP20	grey		suspended	53/40/1140	<a href="#">» 770463</a>
17	4000	2200	129	70	IP20	grey	yes	suspended	53/40/1140	<a href="#">» 770524</a>
17	4000	2200	129	60	IP44	black		suspended	53/40/1140	<a href="#">» 770968</a>
17	4000	2200	129	60	IP44	black	yes	suspended	53/40/1140	<a href="#">» 771026</a>
17	4000	2225	131	60	IP44	grey		suspended	53/40/1140	<a href="#">» 770944</a>
17	4000	2225	131	60	IP44	grey	yes	suspended	53/40/1140	<a href="#">» 771002</a>
17	3000	2250	132	60	IP20	black		suspended	53/40/1140	<a href="#">» 769641</a>
17	3000	2250	132	60	IP20	black	yes	suspended	53/40/1140	<a href="#">» 769702</a>
17	3000	2275	134	60	IP20	grey		suspended	53/40/1140	<a href="#">» 769627</a>
17	3000	2275	134	60	IP20	grey	yes	suspended	53/40/1140	<a href="#">» 769689</a>
17	4000	2275	134	70	IP44	white		suspended	53/40/1140	<a href="#">» 771408</a>
17	4000	2275	134	70	IP44	white	yes	suspended	53/40/1140	<a href="#">» 771460</a>
17	3000	2300	135	60	IP44	white		suspended	53/40/1140	<a href="#">» 771040</a>
17	3000	2300	135	60	IP44	white	yes	suspended	53/40/1140	<a href="#">» 771101</a>
17	4000	2375	140	60	IP20	black		suspended	53/40/1140	<a href="#">» 769528</a>
17	4000	2375	140	60	IP20	black	yes	suspended	53/40/1140	<a href="#">» 769580</a>
17	3000	2375	140	70	IP20	white		suspended	53/40/1140	<a href="#">» 770562</a>
17	3000	2375	140	70	IP20	white	yes	suspended	53/40/1140	<a href="#">» 770623</a>
17	4000	2400	141	60	IP20	grey		suspended	53/40/1140	<a href="#">» 769504</a>
17	4000	2400	141	60	IP20	grey	yes	suspended	53/40/1140	<a href="#">» 769566</a>
17	4000	2425	143	60	IP44	white		suspended	53/40/1140	<a href="#">» 770920</a>
17	4000	2425	143	60	IP44	white	yes	suspended	53/40/1140	<a href="#">» 770982</a>
17	3000	2500	147	60	IP20	white		suspended	53/40/1140	<a href="#">» 769603</a>
17	3000	2500	147	60	IP20	white	yes	suspended	53/40/1140	<a href="#">» 769665</a>
17	4000	2500	147	70	IP20	white		suspended	53/40/1140	<a href="#">» 770449</a>
17	4000	2500	147	70	IP20	white	yes	suspended	53/40/1140	<a href="#">» 770500</a>
17	4000	2625	154	60	IP20	white		suspended	53/40/1140	<a href="#">» 769481</a>

# BARIS 40 LED UGR PLUS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
17	4000	2625	154	60	IP20	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 769542</a>
24	3000	2600	108	70	IP44	black		suspended	53/40/1140	<a href="#">&gt;&gt; 771576</a>
24	3000	2600	108	70	IP44	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771637</a>
24	3000	2650	110	70	IP44	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 771552</a>
24	3000	2650	110	70	IP44	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771613</a>
24	4000	2725	114	70	IP44	black		suspended	53/40/1140	<a href="#">&gt;&gt; 771453</a>
24	4000	2725	114	70	IP44	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771514</a>
24	4000	2775	116	70	IP44	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 771439</a>
24	4000	2775	116	70	IP44	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771491</a>
24	3000	2850	119	70	IP20	black		suspended	53/40/1140	<a href="#">&gt;&gt; 770616</a>
24	3000	2850	119	70	IP20	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 770678</a>
24	3000	2875	120	60	IP44	black		suspended	53/40/1140	<a href="#">&gt;&gt; 771095</a>
24	3000	2875	120	60	IP44	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771156</a>
24	3000	2900	121	70	IP20	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 770593</a>
24	3000	2900	121	70	IP20	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 770654</a>
24	3000	2925	122	60	IP44	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 771071</a>
24	3000	2925	122	60	IP44	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771132</a>
24	4000	2975	124	70	IP20	black		suspended	53/40/1140	<a href="#">&gt;&gt; 770494</a>
24	4000	2975	124	70	IP20	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 770555</a>
24	4000	3025	126	70	IP20	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 770470</a>
24	4000	3025	126	70	IP20	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 770531</a>
24	4000	3025	126	60	IP44	black		suspended	53/40/1140	<a href="#">&gt;&gt; 770975</a>
24	4000	3025	126	60	IP44	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771033</a>
24	3000	3025	126	70	IP44	white		suspended	53/40/1140	<a href="#">&gt;&gt; 771538</a>
24	3000	3025	126	70	IP44	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771590</a>
24	4000	3075	128	60	IP44	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 770951</a>
24	4000	3075	128	60	IP44	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771019</a>
24	3000	3125	130	60	IP20	black		suspended	53/40/1140	<a href="#">&gt;&gt; 769658</a>
24	3000	3125	130	60	IP20	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 769719</a>
24	3000	3175	132	60	IP20	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 769634</a>
24	3000	3175	132	60	IP20	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 769696</a>
24	4000	3175	132	70	IP44	white		suspended	53/40/1140	<a href="#">&gt;&gt; 771415</a>
24	4000	3175	132	70	IP44	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771477</a>
24	3000	3200	133	60	IP44	white		suspended	53/40/1140	<a href="#">&gt;&gt; 771057</a>
24	3000	3200	133	60	IP44	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 771118</a>
24	4000	3275	136	60	IP20	black		suspended	53/40/1140	<a href="#">&gt;&gt; 769535</a>
24	4000	3275	136	60	IP20	black	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 769597</a>
24	3000	3300	138	70	IP20	white		suspended	53/40/1140	<a href="#">&gt;&gt; 770579</a>

# BARIS 40 LED UGR PLUS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
24	3000	3300	138	70	IP20	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 770630</a>
24	4000	3325	139	60	IP20	grey		suspended	53/40/1140	<a href="#">&gt;&gt; 769511</a>
24	4000	3325	139	60	IP20	grey	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 769573</a>
24	4000	3375	141	60	IP44	white		suspended	53/40/1140	<a href="#">&gt;&gt; 770937</a>
24	4000	3375	141	60	IP44	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 770999</a>
24	3000	3475	145	60	IP20	white		suspended	53/40/1140	<a href="#">&gt;&gt; 769610</a>
24	3000	3475	145	60	IP20	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 769672</a>
24	4000	3475	145	70	IP20	white		suspended	53/40/1140	<a href="#">&gt;&gt; 770456</a>
24	4000	3475	145	70	IP20	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 770517</a>
24	4000	3650	152	60	IP20	white		suspended	53/40/1140	<a href="#">&gt;&gt; 769498</a>
24	4000	3650	152	60	IP20	white	yes	suspended	53/40/1140	<a href="#">&gt;&gt; 769559</a>
26	3000	2900	112	70	IP44	black		suspended	53/40/1421	<a href="#">&gt;&gt; 771811</a>
26	3000	2900	112	70	IP44	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771873</a>
26	3000	2925	113	70	IP44	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 771798</a>
26	3000	2925	113	70	IP44	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771859</a>
26	4000	3050	117	70	IP44	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 771675</a>
26	4000	3050	117	70	IP44	black		suspended	53/40/1421	<a href="#">&gt;&gt; 771699</a>
26	4000	3050	117	70	IP44	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771736</a>
26	4000	3050	117	70	IP44	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771750</a>
26	3000	3175	122	70	IP20	black		suspended	53/40/1421	<a href="#">&gt;&gt; 770852</a>
26	3000	3175	122	70	IP20	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 770913</a>
26	3000	3225	124	70	IP20	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 770838</a>
26	3000	3225	124	70	IP20	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 770890</a>
26	4000	3325	128	70	IP20	black		suspended	53/40/1421	<a href="#">&gt;&gt; 770739</a>
26	4000	3325	128	70	IP20	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 770791</a>
26	4000	3350	129	70	IP20	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 770715</a>
26	4000	3350	129	70	IP20	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 770777</a>
26	3000	3375	130	70	IP44	white		suspended	53/40/1421	<a href="#">&gt;&gt; 771774</a>
26	3000	3375	130	70	IP44	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771835</a>
26	4000	3525	136	70	IP44	white		suspended	53/40/1421	<a href="#">&gt;&gt; 771651</a>
26	4000	3525	136	70	IP44	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771712</a>
26	3000	3700	142	70	IP20	white		suspended	53/40/1421	<a href="#">&gt;&gt; 770814</a>
26	3000	3700	142	70	IP20	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 770876</a>
26	4000	3850	148	70	IP20	white		suspended	53/40/1421	<a href="#">&gt;&gt; 770692</a>
26	4000	3850	148	70	IP20	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 770753</a>
31	3000	3400	110	70	IP44	black		suspended	53/40/1421	<a href="#">&gt;&gt; 771804</a>
31	3000	3400	110	70	IP44	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771866</a>
31	3000	3450	111	70	IP44	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 771781</a>

# BARIS 40 LED UGR PLUS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
31	3000	3450	111	70	IP44	grey	yes	suspended	53/40/1421	<a href="#">» 771842</a>
31	4000	3575	115	70	IP44	black		suspended	53/40/1421	<a href="#">» 771682</a>
31	4000	3575	115	70	IP44	black	yes	suspended	53/40/1421	<a href="#">» 771743</a>
31	4000	3625	117	70	IP44	grey		suspended	53/40/1421	<a href="#">» 771668</a>
31	4000	3625	117	70	IP44	grey	yes	suspended	53/40/1421	<a href="#">» 771729</a>
31	3000	3725	120	70	IP20	black		suspended	53/40/1421	<a href="#">» 770845</a>
31	3000	3725	120	70	IP20	black	yes	suspended	53/40/1421	<a href="#">» 770906</a>
31	3000	3775	122	70	IP20	grey		suspended	53/40/1421	<a href="#">» 770821</a>
31	3000	3775	122	70	IP20	grey	yes	suspended	53/40/1421	<a href="#">» 770883</a>
31	3000	3775	122	60	IP44	black		suspended	53/40/1421	<a href="#">» 771323</a>
31	3000	3775	122	60	IP44	black	yes	suspended	53/40/1421	<a href="#">» 771385</a>
31	3000	3825	123	60	IP44	grey		suspended	53/40/1421	<a href="#">» 771309</a>
31	3000	3825	123	60	IP44	grey	yes	suspended	53/40/1421	<a href="#">» 771361</a>
31	4000	3925	127	70	IP20	black		suspended	53/40/1421	<a href="#">» 770722</a>
31	4000	3925	127	70	IP20	black	yes	suspended	53/40/1421	<a href="#">» 770784</a>
31	4000	3950	127	70	IP20	grey		suspended	53/40/1421	<a href="#">» 770708</a>
31	4000	3950	127	70	IP20	grey	yes	suspended	53/40/1421	<a href="#">» 770760</a>
31	3000	3950	127	70	IP44	white		suspended	53/40/1421	<a href="#">» 771767</a>
31	3000	3950	127	70	IP44	white	yes	suspended	53/40/1421	<a href="#">» 771828</a>
31	4000	3975	128	60	IP44	black		suspended	53/40/1421	<a href="#">» 771200</a>
31	4000	3975	128	60	IP44	black	yes	suspended	53/40/1421	<a href="#">» 771262</a>
31	4000	4025	130	60	IP44	grey		suspended	53/40/1421	<a href="#">» 771187</a>
31	4000	4025	130	60	IP44	grey	yes	suspended	53/40/1421	<a href="#">» 771248</a>
31	3000	4100	132	60	IP20	black		suspended	53/40/1421	<a href="#">» 769887</a>
31	3000	4100	132	60	IP20	black	yes	suspended	53/40/1421	<a href="#">» 769948</a>
31	3000	4150	134	60	IP20	grey		suspended	53/40/1421	<a href="#">» 769863</a>
31	3000	4150	134	60	IP20	grey	yes	suspended	53/40/1421	<a href="#">» 769924</a>
31	4000	4150	134	70	IP44	white		suspended	53/40/1421	<a href="#">» 771644</a>
31	4000	4150	134	70	IP44	white	yes	suspended	53/40/1421	<a href="#">» 771705</a>
31	3000	4200	135	60	IP44	white		suspended	53/40/1421	<a href="#">» 771286</a>
31	3000	4200	135	60	IP44	white	yes	suspended	53/40/1421	<a href="#">» 771347</a>
31	4000	4300	139	60	IP20	black		suspended	53/40/1421	<a href="#">» 769764</a>
31	4000	4300	139	60	IP20	black	yes	suspended	53/40/1421	<a href="#">» 769825</a>
31	3000	4325	140	70	IP20	white		suspended	53/40/1421	<a href="#">» 770807</a>
31	3000	4325	140	70	IP20	white	yes	suspended	53/40/1421	<a href="#">» 770869</a>
31	4000	4350	140	60	IP20	grey		suspended	53/40/1421	<a href="#">» 769740</a>
31	4000	4350	140	60	IP20	grey	yes	suspended	53/40/1421	<a href="#">» 769801</a>
31	4000	4400	142	60	IP44	white	yes	suspended	53/40/1421	<a href="#">» 771224</a>

# BARIS 40 LED UGR PLUS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Beam angle [°]	Ingress protection	Colour of the body	DIMM DALI	Mounting version	Dimensions (H/W/T/S) [mm]	Index
31	3000	4550	147	60	IP20	white		suspended	53/40/1421	<a href="#">&gt;&gt; 769849</a>
31	3000	4550	147	60	IP20	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769900</a>
31	4000	4550	147	70	IP20	white		suspended	53/40/1421	<a href="#">&gt;&gt; 770685</a>
31	4000	4550	147	70	IP20	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 770746</a>
31	4000	4775	154	60	IP20	white		suspended	53/40/1421	<a href="#">&gt;&gt; 769726</a>
31	4000	4775	154	60	IP20	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769788</a>
33	4000	4400	133	60	IP44	white		suspended	53/40/1421	<a href="#">&gt;&gt; 771163</a>
40	3000	4650	116	60	IP44	black		suspended	53/40/1421	<a href="#">&gt;&gt; 771330</a>
40	3000	4650	116	60	IP44	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771392</a>
40	3000	4700	118	60	IP44	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 771316</a>
40	3000	4700	118	60	IP44	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771378</a>
40	4000	4900	123	60	IP44	black		suspended	53/40/1421	<a href="#">&gt;&gt; 771217</a>
40	4000	4900	123	60	IP44	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771279</a>
40	4000	4925	123	60	IP44	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 771194</a>
40	4000	4925	123	60	IP44	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771255</a>
40	3000	5050	126	60	IP20	black		suspended	53/40/1421	<a href="#">&gt;&gt; 769894</a>
40	3000	5050	126	60	IP20	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769955</a>
40	3000	5100	128	60	IP20	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 769870</a>
40	3000	5100	128	60	IP20	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769931</a>
40	3000	5175	129	60	IP44	white		suspended	53/40/1421	<a href="#">&gt;&gt; 771293</a>
40	3000	5175	129	60	IP44	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771354</a>
40	4000	5300	133	60	IP20	black		suspended	53/40/1421	<a href="#">&gt;&gt; 769771</a>
40	4000	5300	133	60	IP20	black	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769832</a>
40	4000	5350	134	60	IP20	grey		suspended	53/40/1421	<a href="#">&gt;&gt; 769757</a>
40	4000	5350	134	60	IP20	grey	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769818</a>
40	4000	5425	136	60	IP44	white		suspended	53/40/1421	<a href="#">&gt;&gt; 771170</a>
40	4000	5425	136	60	IP44	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 771231</a>
40	3000	5625	141	60	IP20	white		suspended	53/40/1421	<a href="#">&gt;&gt; 769856</a>
40	3000	5625	141	60	IP20	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769917</a>
40	4000	5875	147	60	IP20	white		suspended	53/40/1421	<a href="#">&gt;&gt; 769733</a>
40	4000	5875	147	60	IP20	white	yes	suspended	53/40/1421	<a href="#">&gt;&gt; 769795</a>

Card creation date: 30 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 122/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl