# **BARIS STAND**

**GENERAL CARD** 





#### **TECHNICAL PARAMETERS**

Rated power of the luminaire [W]\*: 81.00

Colour temperature [K] - range: 2700-6500

**Luminous flux [lm]\*:** 10150; 10650

Colour of the body: black; white

Color rendering index (Ra) >: 90

**UGR (4H8H):** <10

**Beam angle** [°]: 70/120

**Light distribution type:** symmetric

Material of the body: aluminium

**Dimensions (H/W/T/S) [mm]:** 2108/51/1325;

Mounting version: standing

Version: H; T

### **CHARACTERISTICS**

A freestanding LED office luminaire that provides the ideal solution for modern office spaces. This advanced lamp combines elegant design with outstanding functionality, offering a complete lighting solution for demanding users. The luminaire is distinguished by its slim, minimalist design that blends perfectly with any interior design. Available in elegant, neutral colours - white, grey and black - it adapts to a variety of settings, from spacious open spaces to intimate offices. At the heart of the luminaire is an advanced LED module using Tunable White technology, which allows the colour temperature to be adjusted between 2700-6500K. This innovative solution makes it possible to adapt the light characteristics to the time of day and individual user preferences. The dual-zone lighting system provides both direct illumination of the work surface and pleasant, diffuse ambient light, creating a comfortable atmosphere throughout the room. The luminaire is equipped with an advanced control system that allows stepless adjustment of light intensity. The advanced models feature intelligent motion and light sensors that automatically adjust the lighting parameters to the ambient conditions, maximising comfort while optimising energy consumption. A unique advantage of the luminaire is its mobility - no ceiling mounting and ease of movement make it ideal for dynamic office spaces that require frequent reorganisation. The stable base guarantees safety of use and the clever design makes it easy to adjust the light direction to suit current needs.

### **APPLICATION**

The luminaire is widely used in a variety of office spaces - from individual workstations to conference rooms and coworking spaces. It is particularly recommended for areas with long periods of computer work, as its advanced features effectively reduce visual fatigue. It is also ideal for meetings and presentations, where flexible lighting settings are crucial. The technical solutions used not only increase work comfort and efficiency, but also contribute to significant energy savings. Intelligent sensors combined with energy-saving LED technology optimise energy consumption, making the luminaire environmentally friendly and economical to operate. This state-of-the-art luminaire is the ideal combination of innovative technology, ergonomics and aesthetics, providing a complete solution for today's office spaces where work comfort and energy efficiency play a key role.



# **BARIS STAND**

**GENERAL CARD** 

## **AVAILABLE VERSIONS**



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K] - range	Luminous flux [lm]*	Colour of the body	UGR (4H8H)	PIR	Dusk sensor	Switch	Version	Dimensions (H/W/T/S) [mm]	Index
81	2700-6500	10150	black	<10	yes	yes	yes	Н	2108/51/1325	>> 744808
81	2700-6500	10650	white	<10	yes	yes	yes	Н	2108/51/1325	>> 744815
81	2700-6500	10650	white	<10	yes	yes	yes	Т	2108/51/1325	>> 744891
81	2700-6500	10150	black	<10	yes	yes	yes	Т	2108/51/1325	>> 744884



# **BARIS STAND**

**GENERAL CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
744822	Grille -PET Baris Stand GRAYL
744839	Grille -PET Baris Stand GRAYD
744846	Grille -PET Baris Stand BLUE02
744853	Grille -PET Baris Stand GRAYM
744860	Grille -PET Baris Stand MTCH
744877	Grille -PET Baris Stand BRN01
807015	Terra Balance - PET panel colour chart





GRAYL (744822)

Terra Balance - PET panel colour chart (807015)

Card creation date: 16 December 2025

 $The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10$ 





