

# QUEST LED EVO XS

## GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP67
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	20.00 - 56.00
<b>Luminous flux [lm]*:</b>	2800 - 9000
<b>Colour temperature [K]:</b>	2700 - 6500
<b>Colour rendering index:</b>	>70; >80; >90
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	B; C; D; E
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	RAL7016
<b>Diffuser material:</b>	glass
<b>Diffuser type:</b>	transparent
<b>Beam angle [°]:</b>	120
<b>Mounting version:</b>	surface
<b>Working temperature [°C]:</b>	from -20 to +35
<b>Dimensions (H/W/T/S) [mm]:</b>	280/240/55 (390/310/325)**; 280/240/55 (355/222/380)**;

## CHARACTERISTICS

Quest LED Evo XS floodlights and their surface-mounted versions Quest LED Evo XS HB NT are compact, yet extremely efficient premium floodlights and HBs, manufactured in Poland. Their body is made of die-cast aluminium in corrosivity class C5, powder-coated, with no external heat sink or fins to make maintenance difficult. The diffuser is tempered glass, underneath which are LEDs with the highest efficiency. The different types of optics, particularly asymmetrical optics, provide great freedom of choice for a specific solution. Thanks to the highest level of protection on the market (IP67) and maximum impact resistance (IK10), the floodlights will prove their worth in all conditions - regardless of the weather and location. The new version of the well-established and proven QUEST model offers even better luminous performance, achieving an efficiency of more than 170 lm/W. The Quest LED Evo XS meets the requirements of the PN-EN 60598-2 part 5 standard, which allows it to be classified as an illuminating projector, enabling it to be installed in any position, with 360° rotation and resistance to strong wind. An additional advantage for contractors is the sealed quick-connect - an innovative solution that eliminates traditional, time-consuming connection methods. Thanks to an intuitive colour-coded ratchet system, fitting the connector becomes simple, fast and tool-free. The HB NT version is designed for surface mounting as a highbay using dedicated brackets. The accessory kit includes pole mounting brackets, a frame for flush-mounting (e.g. sheds), light pollution reduction shades and protective grids in two colours with varying degrees of light reduction (white RAL7016: 4%, body colour RAL7016: 8%). Models are also available with an integrated motion and twilight sensor (RCR on remote control) and in the ENDURA version, resistant to elevated ambient temperatures of up to 50°C. In addition, a version is available for RGB+W illumination and for suspended mounting as a highbay.

## APPLICATION

Quest LED Evo XS floodlights and their surface-mounted versions Quest LED Evo XS HB NT are widely used in the illumination of educational and administrative buildings, halls, garages, passageways, warehouses, shops, as well as in the food industry and food-related retail and service facilities. They are ideal for illuminating buildings, small sports fields, open spaces and car parks. They can be mounted as a floodlight on poles and masts, on the facade of buildings, or as a surface-mounted highbay (HB NT version). Thanks to the flush-mount option, they are ideal for shelters. The HB version allows surface-mounted installation directly into a partition. Quest LED Evo XS and HB NT are the perfect choice for factories and production halls as well as large-scale warehouses.

# QUEST LED EVO XS

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### QUEST LED EVO XS HB surface

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
20	4000	2800	>70	ASM			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839306</a>
20	4000	2800	>70	ASM	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839313</a>
20	4000	2800	>70	ASM		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839320</a>
20	4000	2800	>70	ASW			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839665</a>
20	4000	2800	>70	ASW	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839672</a>
20	4000	2800	>70	ASW		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839689</a>
20	4000	3000	>70	ASN			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839481</a>
20	4000	3000	>70	ASN	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839498</a>
20	4000	3000	>70	ASN		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839504</a>
20	4000	3000	>70	RM20			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839849</a>
20	4000	3000	>70	RM20	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839856</a>
20	4000	3000	>70	RM20		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839863</a>
20	4000	3000	>70	RW10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840128</a>
20	4000	3000	>70	RW10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840135</a>
20	4000	3000	>70	RW10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840142</a>
20	4000	3000	>70	RM10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840302</a>
20	4000	3000	>70	RM10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840319</a>
20	4000	3000	>70	RM10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840326</a>
20	4000	3400	>70	symmetric			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839122</a>
20	4000	3400	>70	symmetric	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839139</a>
34	4000	5800	>70	symmetric			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839092</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
34	4000	5800	>70	symmetric	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839108</a>
35	4000	4800	>70	ASM			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839276</a>
35	4000	4800	>70	ASM	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839283</a>
35	4000	4800	>70	ASM		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839290</a>
35	4000	4800	>70	ASW			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839634</a>
35	4000	4800	>70	ASW	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839641</a>
35	4000	4800	>70	ASW		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839658</a>
35	4000	5000	>70	RM20			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839818</a>
35	4000	5000	>70	RM20	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839825</a>
35	4000	5000	>70	RM20		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839832</a>
35	4000	5100	>70	ASN			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839450</a>
35	4000	5100	>70	ASN	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839467</a>
35	4000	5100	>70	ASN		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839474</a>
35	4000	5100	>70	RW10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839993</a>
35	4000	5100	>70	RW10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840104</a>
35	4000	5100	>70	RW10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840111</a>
35	4000	5100	>70	RM10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840272</a>
35	4000	5100	>70	RM10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840289</a>
35	4000	5100	>70	RM10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840296</a>
40	4000	6800	>70	symmetric			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839061</a>
40	4000	6800	>70	symmetric	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839078</a>
41	4000	5600	>70	ASM			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839245</a>
41	4000	5600	>70	ASM	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839252</a>
41	4000	5600	>70	ASM		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839269</a>
41	4000	5600	>70	ASW			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839603</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
41	4000	5600	>70	ASW	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839610</a>
41	4000	5600	>70	ASW		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839627</a>
41	4000	5900	>70	RM20			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839788</a>
41	4000	5900	>70	RM20	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839795</a>
41	4000	5900	>70	RM20		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839801</a>
41	4000	5900	>70	RW10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839962</a>
41	4000	5900	>70	RW10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839979</a>
41	4000	5900	>70	RW10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839986</a>
41	4000	5900	>70	RM10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840241</a>
41	4000	5900	>70	RM10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840258</a>
41	4000	5900	>70	RM10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840265</a>
41	4000	6000	>70	ASN			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839429</a>
41	4000	6000	>70	ASN	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839436</a>
41	4000	6000	>70	ASN		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839443</a>
50	4000	8500	>70	symmetric			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839030</a>
50	4000	8500	>70	symmetric	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839047</a>
50	4000	8500	>70	symmetric		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839054</a>
52	4000	6800	>70	ASW			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839573</a>
52	4000	6800	>70	ASW	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839580</a>
52	4000	6800	>70	ASW		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839597</a>
52	4000	6900	>70	ASM			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839214</a>
52	4000	6900	>70	ASM	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839221</a>
52	4000	6900	>70	ASM		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839238</a>
52	4000	7200	>70	RM20			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839757</a>
52	4000	7200	>70	RM20	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839764</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
52	4000	7200	>70	RM20		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839771</a>
52	4000	7200	>70	RW10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839931</a>
52	4000	7200	>70	RW10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839948</a>
52	4000	7200	>70	RW10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839955</a>
52	4000	7200	>70	RM10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840210</a>
52	4000	7200	>70	RM10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840227</a>
52	4000	7200	>70	RM10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840234</a>
52	4000	7300	>70	ASN			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839399</a>
52	4000	7300	>70	ASN	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839405</a>
52	4000	7300	>70	ASN		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839412</a>
54	4000	9000	>70	symmetric			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839009</a>
54	4000	9000	>70	symmetric	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839016</a>
54	4000	9000	>70	symmetric		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839023</a>
56	4000	7200	>70	ASW			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839542</a>
56	4000	7200	>70	ASW	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839559</a>
56	4000	7200	>70	ASW		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839566</a>
56	4000	7300	>70	ASM			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839184</a>
56	4000	7300	>70	ASM	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839191</a>
56	4000	7300	>70	ASM		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839207</a>
56	4000	7500	>70	RP			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840364</a>
56	4000	7600	>70	ASN			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839368</a>
56	4000	7600	>70	ASN	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839375</a>
56	4000	7600	>70	ASN		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839382</a>
56	4000	7600	>70	RM20			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839726</a>
56	4000	7600	>70	RM20	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839733</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
56	4000	7600	>70	RM20		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839740</a>
56	4000	7600	>70	RW10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839900</a>
56	4000	7600	>70	RW10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839917</a>
56	4000	7600	>70	RW10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 839924</a>
56	4000	7600	>70	RM10			HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840180</a>
56	4000	7600	>70	RM10	yes		HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840197</a>
56	4000	7600	>70	RM10		yes	HB surface	280/240/55 (390/310/325)**	<a href="#">&gt;&gt; 840203</a>

## QUEST LED EVO XS floodlight

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
20	4000	2800	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865305</a>
20	4000	2800	>70	ASM	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865312</a>
20	4000	2800	>70	ASM		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865329</a>
20	4000	2800	>70	ASW			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865664</a>
20	4000	2800	>70	ASW	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865671</a>
20	4000	2800	>70	ASW		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865688</a>
20	4000	3000	>70	ASN			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865480</a>
20	4000	3000	>70	ASN	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865497</a>
20	4000	3000	>70	ASN		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865503</a>
20	4000	3000	>70	RM20			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865848</a>
20	4000	3000	>70	RM20	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865855</a>
20	4000	3000	>70	RM20		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865862</a>
20	4000	3000	>70	RW10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881480</a>
20	4000	3000	>70	RW10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881497</a>
20	4000	3000	>70	RW10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881503</a>
20	4000	3000	>70	RM10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881664</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
20	4000	3000	>70	RM10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881671</a>
20	4000	3000	>70	RM10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881688</a>
20	4000	3400	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865121</a>
20	4000	3400	>70	symmetric	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865138</a>
34	4000	5800	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865091</a>
34	4000	5800	>70	symmetric	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865107</a>
35	4000	4800	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865275</a>
35	4000	4800	>70	ASM	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865282</a>
35	4000	4800	>70	ASM		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865299</a>
35	4000	4800	>70	ASW			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865633</a>
35	4000	4800	>70	ASW	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865640</a>
35	4000	4800	>70	ASW		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865657</a>
35	4000	5000	>70	RM20			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865817</a>
35	4000	5000	>70	RM20	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865824</a>
35	4000	5000	>70	RM20		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865831</a>
35	4000	5100	>70	ASN			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865459</a>
35	4000	5100	>70	ASN	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865466</a>
35	4000	5100	>70	ASN		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865473</a>
35	4000	5100	>70	RW10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865992</a>
35	4000	5100	>70	RW10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881466</a>
35	4000	5100	>70	RW10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881473</a>
35	4000	5100	>70	RM10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881633</a>
35	4000	5100	>70	RM10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881640</a>
35	4000	5100	>70	RM10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881657</a>
40	4000	6800	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865060</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
40	4000	6800	>70	symmetric	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865077</a>
41	4000	5600	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865244</a>
41	4000	5600	>70	ASM	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865251</a>
41	4000	5600	>70	ASM		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865268</a>
41	4000	5600	>70	ASW			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865602</a>
41	4000	5600	>70	ASW	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865619</a>
41	4000	5600	>70	ASW		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865626</a>
41	4000	5900	>70	RM20			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865787</a>
41	4000	5900	>70	RM20	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865794</a>
41	4000	5900	>70	RM20		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865800</a>
41	4000	5900	>70	RW10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865961</a>
41	4000	5900	>70	RW10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865978</a>
41	4000	5900	>70	RW10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865985</a>
41	4000	5900	>70	RM10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881602</a>
41	4000	5900	>70	RM10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881619</a>
41	4000	5900	>70	RM10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881626</a>
41	4000	6000	>70	ASN			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865428</a>
41	4000	6000	>70	ASN	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865435</a>
41	4000	6000	>70	ASN		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865442</a>
50	4000	8500	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865039</a>
50	4000	8500	>70	symmetric	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865046</a>
50	4000	8500	>70	symmetric		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865053</a>
52	4000	6800	>70	ASW			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865572</a>
52	4000	6800	>70	ASW	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865589</a>
52	4000	6800	>70	ASW		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865596</a>



# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
52	4000	6900	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865213</a>
52	4000	6900	>70	ASM	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865220</a>
52	4000	6900	>70	ASM		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865237</a>
52	4000	7200	>70	RM20			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865756</a>
52	4000	7200	>70	RM20	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865763</a>
52	4000	7200	>70	RM20		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865770</a>
52	4000	7200	>70	RW10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865930</a>
52	4000	7200	>70	RW10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865947</a>
52	4000	7200	>70	RW10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865954</a>
52	4000	7200	>70	RM10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881572</a>
52	4000	7200	>70	RM10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881589</a>
52	4000	7200	>70	RM10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881596</a>
52	4000	7300	>70	ASN			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865398</a>
52	4000	7300	>70	ASN	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865404</a>
52	4000	7300	>70	ASN		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865411</a>
54	4000	6600	>90	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840609</a>
54	5700	6700	>90	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840616</a>
54	5000	7400	>80	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840579</a>
54	2700	7600	>80	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840548</a>
54	5000	7900	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840524</a>
54	3000	7900	>80	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840555</a>
54	5700	8000	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840531</a>
54	6500	8100	>80	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840593</a>
54	5700	8200	>80	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840586</a>
54	4000	8300	>80	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840562</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
54	3000	8600	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840517</a>
54	4000	9000	>70	symmetric			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865008</a>
54	4000	9000	>70	symmetric	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865015</a>
54	4000	9000	>70	symmetric		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865022</a>
56	5700	5400	>90	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840722</a>
56	4000	5500	>90	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840715</a>
56	5000	6100	>80	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840685</a>
56	2700	6300	>80	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840654</a>
56	5000	6500	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840630</a>
56	3000	6500	>80	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840661</a>
56	5700	6600	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840647</a>
56	6500	6700	>80	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840708</a>
56	4000	6800	>80	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840678</a>
56	5700	6800	>80	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840692</a>
56	3000	7100	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 840623</a>
56	4000	7200	>70	ASW			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865541</a>
56	4000	7200	>70	ASW	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865558</a>
56	4000	7200	>70	ASW		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865565</a>
56	4000	7300	>70	ASM			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865183</a>
56	4000	7300	>70	ASM	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865190</a>
56	4000	7300	>70	ASM		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865206</a>
56	4000	7500	>70	RP			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881725</a>
56	4000	7600	>70	ASN			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865367</a>
56	4000	7600	>70	ASN	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865374</a>
56	4000	7600	>70	ASN		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865381</a>

# QUEST LED EVO XS

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Colour rendering index	Light distribution type	Motion sensor	DIMM DALI	Version	Dimensions (H/W/T/S) [mm]	Index
56	4000	7600	>70	RM20			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865725</a>
56	4000	7600	>70	RM20	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865732</a>
56	4000	7600	>70	RM20		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865749</a>
56	4000	7600	>70	RW10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865909</a>
56	4000	7600	>70	RW10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865916</a>
56	4000	7600	>70	RW10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 865923</a>
56	4000	7600	>70	RM10			floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881541</a>
56	4000	7600	>70	RM10	yes		floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881558</a>
56	4000	7600	>70	RM10		yes	floodlight	280/240/55 (355/222/380)**	<a href="#">&gt;&gt; 881565</a>

# QUEST LED EVO XS

GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
WSEL438	Remote control for motion sensor HD01R
840395	QUEST LED EVO XS pole holder
840425	QUEST LED EVO XS protective grid RAL7016
840456	QUEST LED EVO XS recessed frame RAL7016
840487	QUEST LED EVO XS cover RAL7016
881732	QUEST LED EVO XS protective grid RAL9003



Remote control for motion sensor HD01R (WSEL438)

Card creation date: 28 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 02/2025