TUBA IP69K

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP69K
Impact resistance:	IK05; IK06; IK10
Rated power of the luminaire [W]*:	10.00 - 59.00
Luminous flux [lm]*:	1350 - 11150
Colour temperature [K]:	4000
Material of the body:	stainless steel
Diffuser material:	PC; PMMA; glass
Colour of the body:	white
Beam angle [°]:	30; 105; 120; 35/67; 65; 80; 90; asymetric; butterfly
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	1250/64.5; 660/64.5; 697/64.5; 1281/64.5; 600/64.5;

CHARACTERISTICS

Tuba IP69K is a cylindrical luminaire for special tasks - where other solutions fail. Designed for extreme conditions, it combines superior sealing, chemical resistance and mechanical durability. Meeting the standard for IP69K means full protection against dust (IP6X) and complete resistance to water at extremely high pressure (100 bar) at 80°C (IPX9K). This makes the luminaire ideal for areas requiring intensive cleaning, including with powerful water jets and detergents. The IP69K tube is designed to operate in the most demanding conditions. Made from chemically resistant materials: PMMA and extremely resistant borosilicate glass - ensuring exceptional durability even in aggressive industrial environments. The turned acid-resistant steel endcap eliminates the risk of corrosion, and its resistance to ammonia and zoonotic gases makes it ideal for livestock and processing facilities. Thanks to the decompression valve, the luminaire easily withstands rapid temperature changes, and the highest IK10 impact resistance rating (for the PC version) guarantees reliability in the harshest operating conditions. The IP69K tube achieves up to 194 lm/W, meeting the requirements of the highest energy class A. Through-beam versions, different lens distributions and two lengths (630 and 1220 mm) are available. In addition, versions with UGR<19, UGR<22, UGR<25 provide visual comfort even in demanding applications. Minimalist design, ease of installation and cleanliness make the Tuba IP69K a reliable and timeless solution.

APPLICATION

Ideal for areas requiring regular high-pressure cleaning, such as car washes, sewage treatment plants, food processing plants or slaughterhouses. It excels in environments with high humidity, sub-zero temperatures and aggressive fumes - from cold stores and freezers to mushroom, animal and plant farms. Thanks to its superior chemical and mechanical resistance, it is a reliable solution for workshops and service channels. It is also ideal for industrial halls, traffic routes and even as minimalist, decorative general lighting in commercial buildings.

TUBA IP69K

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

TUBA IP69K 10W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
10	1350	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773723
10	1350	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773754
10	1400	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211621
10	1400	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217142
10	1400	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215261
10	1400	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212505
10	1400	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214387
10	1400	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211591
10	1400	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217111
10	1400	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215230
10	1400	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212475
10	1400	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214356
10	1400	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211621/2
10	1400	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217142/2
10	1400	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212505/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
10	1400	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214387/2
10	1400	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211591/2
10	1400	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217111/2
10	1400	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212475/2
10	1400	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214356/2
10	1450	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773631
10	1450	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773662
10	1450	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773815
10	1450	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773846
10	1450	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775260
10	1450	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775291
10	1450	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775802
10	1450	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775833
10	1450	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776342
10	1450	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776373
10	1450	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219078
10	1450	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219108
10	1450	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 219078/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
10	1450	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 219108/2
10	1450	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775833/2
10	1450	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775291/2
10	1450	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775802/2
10	1450	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775260/2
10	1500	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211683
10	1500	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217203
10	1500	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215322
10	1500	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212567
10	1500	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214448
10	1500	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211652
10	1500	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217173
10	1500	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215292
10	1500	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212536
10	1500	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214417
10	1500	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211560
10	1500	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217081
10	1500	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215209

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
10	1500	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212444
10	1500	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214325
10	1500	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211539
10	1500	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217050
10	1500	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215179
10	1500	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212413
10	1500	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214295
10	1500	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211683/2
10	1500	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217203/2
10	1500	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212567/2
10	1500	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214448/2
10	1500	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211652/2
10	1500	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217173/2
10	1500	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212536/2
10	1500	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214417/2
10	1500	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211560/2
10	1500	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217081/2
10	1500	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212444/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
10	1500	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214325/2
10	1500	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211539/2
10	1500	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217050/2
10	1500	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212413/2
10	1500	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214295/2
10	1550	IK10	PC	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773181
10	1550	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773211
10	1550	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775178
10	1550	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775208
10	1550	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775352
10	1550	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775383
10	1550	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775710
10	1550	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775741
10	1550	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775895
10	1550	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775925
10	1550	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776250
10	1550	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776281
10	1550	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776434

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
10	1550	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776465
10	1550	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219139
10	1550	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219160
10	1550	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219016
10	1550	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219047
10	1550	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 219139/2
10	1550	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 219160/2
10	1550	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775925/2
10	1550	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775383/2
10	1550	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775895/2
10	1550	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775352/2
10	1550	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 219016/2
10	1550	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 219047/2
10	1550	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775741/2
10	1550	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775208/2
10	1550	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775710/2
10	1550	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775178/2
10	1650	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773099

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
10	1650	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773129
10	1650	IK06	glass	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773273
10	1650	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773303

TUBA IP69K 13W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
13	1850	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773716
13	1850	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773747
13	1900	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211614
13	1900	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212499
13	1900	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214370
13	1900	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211584
13	1900	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212468
13	1900	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214349
13	1900	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211614/2
13	1900	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212499/2
13	1900	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214370/2
13	1900	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211584/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
13	1900	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212468/2
13	1900	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214349/2
13	1950	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776335
13	1950	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776366
13	1950	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219061
13	1950	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219092
13	1950	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217135
13	1950	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215254
13	1950	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217104
13	1950	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215223
13	1950	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 219061/2
13	1950	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 219092/2
13	1950	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217135/2
13	1950	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217104/2
13	2000	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773624
13	2000	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773655
13	2000	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773808
13	2000	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773839

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
13	2000	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775253
13	2000	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775284
13	2000	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775796
13	2000	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775826
13	2000	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775826/2
13	2000	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775284/2
13	2000	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775796/2
13	2000	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775253/2
13	2050	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211676
13	2050	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217197
13	2050	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215315
13	2050	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212550
13	2050	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214431
13	2050	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211645
13	2050	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217166
13	2050	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215285
13	2050	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212529
13	2050	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214400

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
13	2050	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211553
13	2050	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217074
13	2050	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215193
13	2050	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212437
13	2050	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214318
13	2050	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211522
13	2050	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217043
13	2050	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215162
13	2050	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212406
13	2050	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214288
13	2050	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211676/2
13	2050	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217197/2
13	2050	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212550/2
13	2050	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214431/2
13	2050	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211645/2
13	2050	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217166/2
13	2050	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212529/2
13	2050	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214400/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
13	2050	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211553/2
13	2050	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217074/2
13	2050	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212437/2
13	2050	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214318/2
13	2050	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211522/2
13	2050	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217043/2
13	2050	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212406/2
13	2050	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214288/2
13	2100	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776243
13	2100	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776274
13	2100	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776427
13	2100	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776458
13	2100	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219122
13	2100	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219153
13	2100	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217999
13	2100	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219030
13	2100	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 219122/2
13	2100	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 219153/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
13	2100	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217999/2
13	2100	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 219030/2
13	2150	IK10	PC	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773174
13	2150	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773204
13	2150	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775161
13	2150	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775192
13	2150	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775345
13	2150	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775376
13	2150	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775703
13	2150	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775734
13	2150	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775888
13	2150	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775918
13	2150	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775918/2
13	2150	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775376/2
13	2150	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775888/2
13	2150	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775345/2
13	2150	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775734/2
13	2150	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775192/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
13	2150	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775703/2
13	2150	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775161/2
13	2300	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773082
13	2300	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773112
13	2300	IK06	glass	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773266
13	2300	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773297

TUBA IP69K 16W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
16	2250	IK06	glass	105	symmetric	matrix lens				3	380	660/64.5	>> 778537
16	2250	IK10	PC	105	symmetric	matrix lens				3	380	660/64.5	>> 778513
16	2250	IK05	PMMA	105	symmetric	matrix lens				3	380	660/64.5	>> 778520
16	2300	IK10	PC	butterfly	DAN	matrix lens				3	380	660/64.5	>> 778483
16	2300	IK10	PC	90	MW MAT	matrix lens				3	380	660/64.5	>> 212017
16	2300	IK10	PC	90	SA MAT	matrix lens				3	380	660/64.5	>> 217555
16	2300	IK10	PC	90	SN MAT	matrix lens				3	380	660/64.5	>> 215643
16	2300	IK10	PC	90	SW MAT	matrix lens				3	380	660/64.5	>> 212888
16	2300	IK10	PC	90	VW MAT	matrix lens				3	380	660/64.5	>> 214769
16	2300	IK10	PC	butterfly	DAN	2 rows				3	380	660/64.5	>> 778483/2
16	2300	IK10	PC	90	MW MAT	2 rows				3	380	660/64.5	>> 212017/2
16	2300	IK10	PC	90	SA MAT	2 rows				3	380	660/64.5	>> 217555/2
16	2300	IK10	PC	90	SW MAT	2 rows				3	380	660/64.5	>> 212888/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
16	2300	IK10	PC	90	VW MAT	2 rows				3	380	660/64.5	>> 214769/2
16	2350	IK10	PC	asymetric	SA	matrix lens				3	380	660/64.5	>> 778452
16	2350	IK10	PC	90	DAN MAT	matrix lens				3	380	660/64.5	>> 219498
16	2350	IK10	PC	90	DAN MAT	2 rows				3	380	660/64.5	>> 219498/2
16	2350	IK10	PC	asymetric	SA	2 rows				3	380	660/64.5	>> 778452/2
16	2400	IK10	PC	35/67	CN	matrix lens				3	380	660/64.5	>> 778391
16	2400	IK10	PC	65	SN	matrix lens				3	380	660/64.5	>> 778360
16	2400	IK10	PC	80	SW	matrix lens				3	380	660/64.5	>> 778339
16	2400	IK10	PC	30	VN	matrix lens				3	380	660/64.5	>> 778421
16	2400	IK10	PC	105	VW	matrix lens				3	380	660/64.5	>> 778308
16	2400	IK10	PC	80	SW	2 rows				3	380	660/64.5	>> 778339/2
16	2400	IK10	PC	105	VW	2 rows				3	380	660/64.5	>> 778308/2
16	2500	IK06	glass	butterfly	DAN	matrix lens				3	380	660/64.5	>> 778506
16	2500	IK06	glass	asymetric	SA	matrix lens				3	380	660/64.5	>> 778476
16	2500	IK05	PMMA	butterfly	DAN	matrix lens				3	380	660/64.5	>> 778490
16	2500	IK05	PMMA	asymetric	SA	matrix lens				3	380	660/64.5	>> 778469
16	2500	IK06	glass	90	MW MAT	matrix lens				3	380	660/64.5	>> 212031
16	2500	IK06	glass	90	SA MAT	matrix lens				3	380	660/64.5	>> 217579
16	2500	IK06	glass	90	SN MAT	matrix lens				3	380	660/64.5	>> 215667
16	2500	IK06	glass	90	SW MAT	matrix lens				3	380	660/64.5	>> 212901
16	2500	IK06	glass	90	VW MAT	matrix lens				3	380	660/64.5	>> 214783
16	2500	IK05	PMMA	90	MW MAT	matrix lens				3	380	660/64.5	>> 212024
16	2500	IK05	PMMA	90	SA MAT	matrix lens				3	380	660/64.5	>> 217562
16	2500	IK05	PMMA	90	SN MAT	matrix lens				3	380	660/64.5	>> 215650

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
16	2500	IK05	PMMA	90	SW MAT	matrix lens				3	380	660/64.5	>> 212895
16	2500	IK05	PMMA	90	VW MAT	matrix lens				3	380	660/64.5	>> 214776
16	2500	IK06	glass	butterfly	DAN	2 rows				3	380	660/64.5	>> 778506/2
16	2500	IK06	glass	90	MW MAT	2 rows				3	380	660/64.5	>> 212031/2
16	2500	IK06	glass	90	SA MAT	2 rows				3	380	660/64.5	>> 217579/2
16	2500	IK06	glass	asymetric	SA	2 rows				3	380	660/64.5	>> 778476/2
16	2500	IK06	glass	90	SW MAT	2 rows				3	380	660/64.5	>> 212901/2
16	2500	IK06	glass	90	VW MAT	2 rows				3	380	660/64.5	>> 214783/2
16	2500	IK05	PMMA	butterfly	DAN	2 rows				3	380	660/64.5	>> 778490/2
16	2500	IK05	PMMA	90	MW MAT	2 rows				3	380	660/64.5	>> 212024/2
16	2500	IK05	PMMA	90	SA MAT	2 rows				3	380	660/64.5	>> 217562/2
16	2500	IK05	PMMA	asymetric	SA	2 rows				3	380	660/64.5	>> 778469/2
16	2500	IK05	PMMA	90	SW MAT	2 rows				3	380	660/64.5	>> 212895/2
16	2500	IK05	PMMA	90	VW MAT	2 rows				3	380	660/64.5	>> 214776/2
16	2550	IK06	glass	90	DAN MAT	matrix lens				3	380	660/64.5	>> 219511
16	2550	IK05	PMMA	90	DAN MAT	matrix lens				3	380	660/64.5	>> 219504
16	2550	IK06	glass	90	DAN MAT	2 rows				3	380	660/64.5	>> 219511/2
16	2550	IK05	PMMA	90	DAN MAT	2 rows				3	380	660/64.5	>> 219504/2
16	2600	IK06	glass	35/67	CN	matrix lens				3	380	660/64.5	>> 778414
16	2600	IK06	glass	90	MW	matrix lens				3	380	660/64.5	>> 778292
16	2600	IK06	glass	65	SN	matrix lens				3	380	660/64.5	>> 778384
16	2600	IK06	glass	80	SW	matrix lens				3	380	660/64.5	>> 778353
16	2600	IK06	glass	30	VN	matrix lens				3	380	660/64.5	>> 778445
16	2600	IK06	glass	105	VW	matrix lens				3	380	660/64.5	>> 778322

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
16	2600	IK10	PC	120	symmetric					3	380	660/64.5	>> 778544
16	2600	IK05	PMMA	35/67	CN	matrix lens				3	380	660/64.5	>> 778407
16	2600	IK05	PMMA	90	MW	matrix lens				3	380	600/64.5	>> 778285
16	2600	IK05	PMMA	65	SN	matrix lens				3	380	660/64.5	>> 778377
16	2600	IK05	PMMA	80	SW	matrix lens				3	380	660/64.5	>> 778346
16	2600	IK05	PMMA	30	VN	matrix lens				3	380	660/64.5	>> 778438
16	2600	IK05	PMMA	105	VW	matrix lens				3	380	660/64.5	>> 778315
16	2600	IK06	glass	90	MW	2 rows				3	380	660/64.5	>> 778292/2
16	2600	IK06	glass	80	SW	2 rows				3	380	660/64.5	>> 778353/2
16	2600	IK06	glass	105	VW	2 rows				3	380	660/64.5	>> 778322/2
16	2600	IK05	PMMA	90	MW	2 rows				3	380	600/64.5	>> 778285/2
16	2600	IK05	PMMA	80	SW	2 rows				3	380	660/64.5	>> 778346/2
16	2600	IK05	PMMA	105	VW	2 rows				3	380	660/64.5	>> 778315/2
16	2750	IK06	glass	120	symmetric					3	380	660/64.5	>> 778568
16	2750	IK05	PMMA	120	symmetric					3	380	660/64.5	>> 778551

TUBA IP69K 22W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
22	3050	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773440
22	3050	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773471
22	3100	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211430
22	3100	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212314
22	3100	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214196

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
22	3100	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211409
22	3100	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212284
22	3100	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214165
22	3100	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211430/2
22	3100	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212314/2
22	3100	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214196/2
22	3100	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211409/2
22	3100	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212284/2
22	3100	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214165/2
22	3150	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215940
22	3150	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215070
22	3150	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215919
22	3150	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215049
22	3150	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 215940/2
22	3150	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215919/2
22	3200	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217876
22	3200	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217906
22	3200	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217876/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
22	3200	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217906/2
22	3250	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773983
22	3250	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775017
22	3250	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775529
22	3250	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775550
22	3250	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776069
22	3250	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776090
22	3250	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775550/2
22	3250	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775017/2
22	3250	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775529/2
22	3250	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 773983/2
22	3300	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773358
22	3300	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773389
22	3300	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773532
22	3300	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773563
22	3350	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211492
22	3350	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217012
22	3350	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215131

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
22	3350	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212376
22	3350	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214257
22	3350	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211461
22	3350	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215971
22	3350	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215100
22	3350	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212345
22	3350	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214226
22	3350	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211379
22	3350	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215889
22	3350	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215018
22	3350	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212253
22	3350	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214134
22	3350	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211348
22	3350	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215858
22	3350	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214974
22	3350	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212222
22	3350	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214103
22	3350	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211492/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
22	3350	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217012/2
22	3350	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212376/2
22	3350	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214257/2
22	3350	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211461/2
22	3350	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215971/2
22	3350	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212345/2
22	3350	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214226/2
22	3350	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211379/2
22	3350	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 215889/2
22	3350	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212253/2
22	3350	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214134/2
22	3350	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211348/2
22	3350	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215858/2
22	3350	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212222/2
22	3350	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214103/2
22	3450	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217937
22	3450	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217968
22	3450	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217814

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
22	3450	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217845
22	3450	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217937/2
22	3450	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217968/2
22	3450	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217814/2
22	3450	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217845/2
22	3500	IK10	PC	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772368
22	3500	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772481
22	3500	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773891
22	3500	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773921
22	3500	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775079
22	3500	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775109
22	3500	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775437
22	3500	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775468
22	3500	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775611
22	3500	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775642
22	3500	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775970
22	3500	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776007
22	3500	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776151

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
22	3500	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776182
22	3500	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775642/2
22	3500	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775109/2
22	3500	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775611/2
22	3500	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775079/2
22	3500	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775468/2
22	3500	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 773921/2
22	3500	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775437/2
22	3500	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 773891/2
22	3750	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772009
22	3750	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772122
22	3750	IK06	glass	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772726
22	3750	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772849

TUBA IP69K 26W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
26	3700	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773457
26	3700	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773488

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
26	3800	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211447
26	3800	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212321
26	3800	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214202
26	3800	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211416
26	3800	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212291
26	3800	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214172
26	3800	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211447/2
26	3800	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212321/2
26	3800	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214202/2
26	3800	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211416/2
26	3800	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212291/2
26	3800	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214172/2
26	3850	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215957
26	3850	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215087
26	3850	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215926
26	3850	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215056
26	3850	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 215957/2
26	3850	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215926/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
26	3950	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776076
26	3950	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776106
26	3950	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217883
26	3950	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217913
26	3950	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217883/2
26	3950	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217913/2
26	4000	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773365
26	4000	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773396
26	4000	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773549
26	4000	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773570
26	4000	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773990
26	4000	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775024
26	4000	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775536
26	4000	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775567
26	4000	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775567/2
26	4000	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775024/2
26	4000	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775536/2
26	4000	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 773990/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
26	4100	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211508
26	4100	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212383
26	4100	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214264
26	4100	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211478
26	4100	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212352
26	4100	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214233
26	4100	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211386
26	4100	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212260
26	4100	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214141
26	4100	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211355
26	4100	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212239
26	4100	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214110
26	4100	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211508/2
26	4100	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212383/2
26	4100	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214264/2
26	4100	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211478/2
26	4100	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212352/2
26	4100	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214233/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
26	4100	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211386/2
26	4100	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212260/2
26	4100	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214141/2
26	4100	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211355/2
26	4100	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212239/2
26	4100	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214110/2
26	4150	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217029
26	4150	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215148
26	4150	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215988
26	4150	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215117
26	4150	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215896
26	4150	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215025
26	4150	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215865
26	4150	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214981
26	4150	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217029/2
26	4150	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215988/2
26	4150	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 215896/2
26	4150	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215865/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
26	4250	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775987
26	4250	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776014
26	4250	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776168
26	4250	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776199
26	4250	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217944
26	4250	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217975
26	4250	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217821
26	4250	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217852
26	4250	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217944/2
26	4250	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217975/2
26	4250	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217821/2
26	4250	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217852/2
26	4300	IK10	PC	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772375
26	4300	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772498
26	4300	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773907
26	4300	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773938
26	4300	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775086
26	4300	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775116

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
26	4300	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775444
26	4300	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775475
26	4300	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775628
26	4300	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775659
26	4300	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775659/2
26	4300	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775116/2
26	4300	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775628/2
26	4300	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775086/2
26	4300	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775475/2
26	4300	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 773938/2
26	4300	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775444/2
26	4300	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 773907/2
26	4600	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772016
26	4600	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772139
26	4600	IK06	glass	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772733
26	4600	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772856

TUBA IP69K

GENERAL CARD

TUBA IP69K 32W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
32	4500	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773464
32	4500	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773495
32	4550	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211454
32	4550	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212338
32	4550	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214219
32	4550	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211423
32	4550	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212307
32	4550	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214189
32	4550	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211454/2
32	4550	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212338/2
32	4550	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214219/2
32	4550	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211423/2
32	4550	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212307/2
32	4550	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214189/2
32	4600	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215964
32	4600	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215094
32	4600	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215933

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
32	4600	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215063
32	4600	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 215964/2
32	4600	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215933/2
32	4750	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217890
32	4750	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217920
32	4750	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217890/2
32	4750	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217920/2
32	4800	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775000
32	4800	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775031
32	4800	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775543
32	4800	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775574
32	4800	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776083
32	4800	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776113
32	4800	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775574/2
32	4800	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775031/2
32	4800	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775543/2
32	4800	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775000/2
32	4850	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773372

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
32	4850	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773402
32	4850	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773556
32	4850	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773587
32	4950	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211515
32	4950	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212390
32	4950	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214271
32	4950	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211485
32	4950	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212369
32	4950	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214240
32	4950	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211393
32	4950	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212277
32	4950	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214158
32	4950	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211362
32	4950	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212246
32	4950	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214127
32	4950	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211515/2
32	4950	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212390/2
32	4950	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214271/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
32	4950	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211485/2
32	4950	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212369/2
32	4950	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214240/2
32	4950	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 211393/2
32	4950	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 212277/2
32	4950	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 214158/2
32	4950	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 211362/2
32	4950	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 212246/2
32	4950	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 214127/2
32	5000	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217036
32	5000	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215155
32	5000	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215995
32	5000	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215124
32	5000	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215902
32	5000	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215032
32	5000	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215872
32	5000	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214998
32	5000	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217036/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
32	5000	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215995/2
32	5000	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 215902/2
32	5000	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 215872/2
32	5100	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217951
32	5100	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217982
32	5100	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217838
32	5100	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217869
32	5100	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217951/2
32	5100	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217982/2
32	5100	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			660/64.5	>> 217838/2
32	5100	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 217869/2
32	5150	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775994
32	5150	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776021
32	5150	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776175
32	5150	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776205
32	5200	IK10	PC	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772382
32	5200	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772504
32	5200	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773914

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
32	5200	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773945
32	5200	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775093
32	5200	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775123
32	5200	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775451
32	5200	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775482
32	5200	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775635
32	5200	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775666
32	5200	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775666/2
32	5200	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775123/2
32	5200	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775635/2
32	5200	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775093/2
32	5200	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 775482/2
32	5200	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			697/64.5	>> 773945/2
32	5200	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 775451/2
32	5200	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			660/64.5	>> 773914/2
32	5550	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772023
32	5550	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772146
32	5550	IK06	glass	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 772740

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
32	5550	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 772863

TUBA IP69K 36W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5050	IK10	PC	105	symmetric	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 772542
36	5050	IK10	PC	105	symmetric	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772559
36	5050	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773730
36	5050	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773761
36	5150	IK10	PC	90	MW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 211904
36	5150	IK10	PC	90	SW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 212789
36	5150	IK10	PC	90	VW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 214660
36	5150	IK10	PC	90	MW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 211911
36	5150	IK10	PC	90	SW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 212796
36	5150	IK10	PC	90	VW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 214677
36	5150	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211638
36	5150	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212512
36	5150	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214394
36	5150	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211607
36	5150	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212482

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5150	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214363
36	5200	IK10	PC	butterfly	DAN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776649
36	5200	IK10	PC	90	SA MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 217425
36	5200	IK10	PC	90	SN MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 215544
36	5200	IK10	PC	90	SA MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 217432
36	5200	IK10	PC	90	SN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 215551
36	5200	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217159
36	5200	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215278
36	5200	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217128
36	5200	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215247
36	5250	IK10	PC	asymetric	SA	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776618
36	5300	IK10	PC	90	DAN MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 219399
36	5300	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219085
36	5300	IK10	PC	90	DAN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 219405
36	5300	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219115
36	5400	IK10	PC	105	VW	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 772665
36	5400	IK10	PC	105	VW	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772672
36	5400	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775277

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5400	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775307
36	5400	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775819
36	5400	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775840
36	5400	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776359
36	5400	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776380
36	5400	IK10	PC	80	SW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776526
36	5400	IK10	PC	35/67	CN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776557
36	5400	IK10	PC	30	VN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776588
36	5400	IK10	PC	90	MW	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 777929
36	5400	IK10	PC	90	MW	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 777936
36	5400	IK10	PC	65	SN	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 778018
36	5400	IK10	PC	65	SN	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 778025
36	5450	IK05	PMMA	105	symmetric	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 772184
36	5450	IK05	PMMA	105	symmetric	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772191
36	5450	IK06	glass	105	symmetric	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 772900
36	5450	IK06	glass	105	symmetric	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772917
36	5450	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773648
36	5450	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773679

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5450	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 773822
36	5450	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 773853
36	5550	IK06	glass	90	MW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 211928
36	5550	IK06	glass	90	SW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 212802
36	5550	IK06	glass	90	VW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 214684
36	5550	IK06	glass	90	MW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 211935
36	5550	IK06	glass	90	SW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 212819
36	5550	IK06	glass	90	VW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 214691
36	5550	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211690
36	5550	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212574
36	5550	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214455
36	5550	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211669
36	5550	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212543
36	5550	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214424
36	5550	IK05	PMMA	90	MW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 211881
36	5550	IK05	PMMA	90	SW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 212765
36	5550	IK05	PMMA	90	VW MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 214646
36	5550	IK05	PMMA	90	MW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 211898

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5550	IK05	PMMA	90	SW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 212772
36	5550	IK05	PMMA	90	VW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 214653
36	5550	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 211577
36	5550	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 212451
36	5550	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 214332
36	5550	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 211546
36	5550	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 212420
36	5550	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 214301
36	5600	IK06	glass	90	SA MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 217449
36	5600	IK06	glass	90	SN MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 215568
36	5600	IK06	glass	90	SA MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 217456
36	5600	IK06	glass	90	SN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 215575
36	5600	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217210
36	5600	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215339
36	5600	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217180
36	5600	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215308
36	5600	IK05	PMMA	90	SA MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 217401
36	5600	IK05	PMMA	90	SN MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 215520

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5600	IK05	PMMA	90	SA MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 217418
36	5600	IK05	PMMA	90	SN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 215537
36	5600	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 217098
36	5600	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 215216
36	5600	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 217067
36	5600	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 215186
36	5650	IK05	PMMA	asymetric	SA	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776601
36	5650	IK06	glass	asymetric	SA	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776625
36	5650	IK05	PMMA	butterfly	DAN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776632
36	5650	IK06	glass	butterfly	DAN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776656
36	5700	IK06	glass	90	DAN MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 219412
36	5700	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219146
36	5700	IK06	glass	90	DAN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 219429
36	5700	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219177
36	5700	IK05	PMMA	90	DAN MAT	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 219375
36	5700	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 219023
36	5700	IK05	PMMA	90	DAN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 219382
36	5700	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 219054

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5800	IK05	PMMA	105	VW	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 772306
36	5800	IK05	PMMA	105	VW	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772313
36	5800	IK06	glass	105	VW	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 773020
36	5800	IK06	glass	105	VW	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 773037
36	5800	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775185
36	5800	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775215
36	5800	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775369
36	5800	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775390
36	5800	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775727
36	5800	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775758
36	5800	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 775901
36	5800	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 775932
36	5800	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776267
36	5800	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776298
36	5800	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776441
36	5800	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			697/64.5	>> 776472
36	5800	IK05	PMMA	80	SW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776519
36	5800	IK06	glass	80	SW	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776533

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	5800	IK05	PMMA	35/67	CN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776540
36	5800	IK06	glass	35/67	CN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776564
36	5800	IK05	PMMA	30	VN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776571
36	5800	IK06	glass	30	VN	matrix lens		LS1	Cable length 1.4m			660/64.5	>> 776595
36	5800	IK05	PMMA	90	MW	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 777899
36	5800	IK05	PMMA	90	MW	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 777905
36	5800	IK06	glass	90	MW	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 777950
36	5800	IK06	glass	90	MW	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 777967
36	5800	IK05	PMMA	65	SN	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 777981
36	5800	IK05	PMMA	65	SN	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 777998
36	5800	IK06	glass	65	SN	matrix lens	yes	LS1	Cable length 1.4m			660/64.5	>> 778049
36	5800	IK06	glass	65	SN	matrix lens	yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 778056
36	5850	IK10	PC	120	symmetric		yes	LS1	Cable length 1.4m			660/64.5	>> 772429
36	5850	IK10	PC	120	symmetric		yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772436
36	5850	IK10	PC	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773198
36	5850	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773228
36	6250	IK05	PMMA	120	symmetric		yes	LS1	Cable length 1.4m			660/64.5	>> 772061
36	6250	IK05	PMMA	120	symmetric		yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772078

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	6250	IK06	glass	120	symmetric		yes	LS1	Cable length 1.4m			660/64.5	>> 772788
36	6250	IK06	glass	120	symmetric		yes	LS2	Cable length 2 x 1.4m			697/64.5	>> 772795
36	6250	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773105
36	6250	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773136
36	6250	IK06	glass	120	symmetric			LS1	Cable length 1.4m			660/64.5	>> 773280
36	6250	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			697/64.5	>> 773310

TUBA IP69K 40W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
40	6200	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776755
40	6200	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776786
40	6400	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211799
40	6400	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212673
40	6400	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214554
40	6400	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211768
40	6400	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212642
40	6400	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214523
40	6400	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211799/2
40	6400	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212673/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
40	6400	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214554/2
40	6400	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211768/2
40	6400	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212642/2
40	6400	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214523/2
40	6450	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217319
40	6450	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215438
40	6450	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217289
40	6450	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215407
40	6450	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217319/2
40	6450	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217289/2
40	6600	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219252
40	6600	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219283
40	6600	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219252/2
40	6600	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219283/2
40	6650	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777561
40	6650	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777592
40	6700	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777028
40	6700	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777059

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
40	6700	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777295
40	6700	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777325
40	6700	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777325/2
40	6700	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777059/2
40	6700	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777295/2
40	6700	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777028/2
40	6750	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776663
40	6750	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776694
40	6750	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776847
40	6750	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776878
40	6850	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211850
40	6850	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212734
40	6850	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214615
40	6850	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211829
40	6850	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212703
40	6850	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214585
40	6850	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211737
40	6850	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212611

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
40	6850	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214493
40	6850	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211706
40	6850	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212581
40	6850	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214462
40	6850	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211850/2
40	6850	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212734/2
40	6850	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214615/2
40	6850	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211829/2
40	6850	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212703/2
40	6850	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214585/2
40	6850	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211737/2
40	6850	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212611/2
40	6850	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214493/2
40	6850	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211706/2
40	6850	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212581/2
40	6850	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214462/2
40	6950	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217371
40	6950	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215490

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
40	6950	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217340
40	6950	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215469
40	6950	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217258
40	6950	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215377
40	6950	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217227
40	6950	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215346
40	6950	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217371/2
40	6950	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217340/2
40	6950	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217258/2
40	6950	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217227/2
40	7100	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219313
40	7100	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219344
40	7100	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219184
40	7100	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219221
40	7100	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219313/2
40	7100	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219344/2
40	7100	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219184/2
40	7100	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219221/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
40	7150	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777479
40	7150	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777509
40	7150	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777653
40	7150	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777684
40	7200	IK10	PC	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772399
40	7200	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772511
40	7200	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776939
40	7200	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776960
40	7200	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777110
40	7200	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777141
40	7200	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777202
40	7200	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777233
40	7200	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777387
40	7200	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777417
40	7200	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777417/2
40	7200	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777141/2
40	7200	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777387/2
40	7200	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777110/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
40	7200	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777233/2
40	7200	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776960/2
40	7200	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777202/2
40	7200	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 776939/2
40	7750	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772030
40	7750	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772153
40	7750	IK06	glass	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772757
40	7750	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772870

TUBA IP69K 46W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
46	7100	IK10	PC	105	symmetric	matrix lens						1250/64.5	>> 776762
46	7100	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776793
46	7250	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211805
46	7250	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212680
46	7250	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214561
46	7250	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211775
46	7250	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212659
46	7250	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214530

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
46	7250	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211805/2
46	7250	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212680/2
46	7250	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214561/2
46	7250	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211775/2
46	7250	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212659/2
46	7250	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214530/2
46	7300	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217326
46	7300	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215445
46	7300	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217296
46	7300	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215414
46	7300	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217326/2
46	7300	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217296/2
46	7500	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219269
46	7500	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219290
46	7500	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219269/2
46	7500	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219290/2
46	7600	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777035
46	7600	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777066

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
46	7600	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777301
46	7600	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777332
46	7600	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777578
46	7600	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777608
46	7600	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777332/2
46	7600	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777066/2
46	7600	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777301/2
46	7600	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777035/2
46	7650	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776670
46	7650	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776700
46	7650	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776854
46	7650	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776885
46	7800	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211867
46	7800	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212741
46	7800	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214622
46	7800	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211836
46	7800	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212710
46	7800	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214592

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
46	7800	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211744
46	7800	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212628
46	7800	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214509
46	7800	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211713
46	7800	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212598
46	7800	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214479
46	7800	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211867/2
46	7800	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212741/2
46	7800	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214622/2
46	7800	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211836/2
46	7800	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212710/2
46	7800	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214592/2
46	7800	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211744/2
46	7800	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212628/2
46	7800	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214509/2
46	7800	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211713/2
46	7800	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212598/2
46	7800	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214479/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
46	7900	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217388
46	7900	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215506
46	7900	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217357
46	7900	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215476
46	7900	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217265
46	7900	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215384
46	7900	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217234
46	7900	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215353
46	7900	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217388/2
46	7900	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217357/2
46	7900	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217265/2
46	7900	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217234/2
46	8100	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219320
46	8100	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219351
46	8100	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219191
46	8100	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219238
46	8100	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219320/2
46	8100	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219351/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
46	8100	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219191/2
46	8100	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219238/2
46	8150	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777486
46	8150	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777516
46	8150	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777660
46	8150	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777691
46	8200	IK10	PC	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772405
46	8200	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772528
46	8200	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776946
46	8200	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776977
46	8200	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777127
46	8200	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777158
46	8200	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777219
46	8200	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777240
46	8200	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777394
46	8200	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777424
46	8200	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777424/2
46	8200	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777158/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
46	8200	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777394/2
46	8200	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777127/2
46	8200	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777240/2
46	8200	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776977/2
46	8200	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777219/2
46	8200	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 776946/2
46	8800	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772047
46	8800	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772160
46	8800	IK06	glass	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772764
46	8800	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772887

TUBA IP69K 59W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9000	IK10	PC	105	symmetric	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 772573
59	9000	IK10	PC	105	symmetric	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772580
59	9000	IK10	PC	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776779
59	9000	IK10	PC	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776809
59	9200	IK10	PC	90	MW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 211966
59	9200	IK10	PC	90	SW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 212840

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9200	IK10	PC	90	VW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 214721
59	9200	IK10	PC	90	MW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 211973
59	9200	IK10	PC	90	SW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 212857
59	9200	IK10	PC	90	VW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 214738
59	9200	IK10	PC	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211812
59	9200	IK10	PC	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212697
59	9200	IK10	PC	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214578
59	9200	IK10	PC	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211782
59	9200	IK10	PC	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212666
59	9200	IK10	PC	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214547
59	9200	IK10	PC	90	MW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 211966/2
59	9200	IK10	PC	90	SW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 212840/2
59	9200	IK10	PC	90	VW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 214721/2
59	9200	IK10	PC	90	MW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 211973/2
59	9200	IK10	PC	90	SW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 212857/2
59	9200	IK10	PC	90	VW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 214738/2
59	9200	IK10	PC	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211812/2
59	9200	IK10	PC	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212697/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9200	IK10	PC	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214578/2
59	9200	IK10	PC	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211782/2
59	9200	IK10	PC	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212666/2
59	9200	IK10	PC	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214547/2
59	9300	IK10	PC	90	SA MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 217487
59	9300	IK10	PC	90	SN MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 215605
59	9300	IK10	PC	90	SA MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 217494
59	9300	IK10	PC	90	SN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 215612
59	9300	IK10	PC	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217333
59	9300	IK10	PC	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215452
59	9300	IK10	PC	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217302
59	9300	IK10	PC	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215421
59	9300	IK10	PC	90	SA MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 217487/2
59	9300	IK10	PC	90	SA MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 217494/2
59	9300	IK10	PC	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217333/2
59	9300	IK10	PC	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217302/2
59	9350	IK10	PC	butterfly	DAN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777875
59	9350	IK10	PC	butterfly	DAN	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777875/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9400	IK10	PC	asymetric	SA	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777844
59	9400	IK10	PC	asymetric	SA	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777844/2
59	9500	IK10	PC	90	DAN MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 219450
59	9500	IK10	PC	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219276
59	9500	IK10	PC	90	DAN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 219467
59	9500	IK10	PC	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219306
59	9500	IK10	PC	90	DAN MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 219450/2
59	9500	IK10	PC	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219276/2
59	9500	IK10	PC	90	DAN MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 219467/2
59	9500	IK10	PC	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219306/2
59	9600	IK10	PC	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777585
59	9600	IK10	PC	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777615
59	9600	IK10	PC	35/67	CN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777783
59	9600	IK10	PC	30	VN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777813
59	9600	IK10	PC	65	SN	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 778193
59	9600	IK10	PC	65	SN	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778209
59	9650	IK10	PC	105	VW	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 772696
59	9650	IK10	PC	105	VW	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772702

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9650	IK10	PC	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777042
59	9650	IK10	PC	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777073
59	9650	IK10	PC	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777318
59	9650	IK10	PC	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777349
59	9650	IK10	PC	80	SW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777752
59	9650	IK10	PC	90	MW	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 778100
59	9650	IK10	PC	90	MW	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778117
59	9650	IK10	PC	90	MW	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 778100/2
59	9650	IK10	PC	105	VW	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 772696/2
59	9650	IK10	PC	90	MW	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778117/2
59	9650	IK10	PC	105	VW	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772702/2
59	9650	IK10	PC	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777349/2
59	9650	IK10	PC	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777073/2
59	9650	IK10	PC	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777318/2
59	9650	IK10	PC	80	SW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777752/2
59	9650	IK10	PC	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777042/2
59	9700	IK05	PMMA	105	symmetric	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 772214
59	9700	IK05	PMMA	105	symmetric	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772221

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9700	IK06	glass	105	symmetric	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 772931
59	9700	IK06	glass	105	symmetric	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772948
59	9700	IK05	PMMA	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776687
59	9700	IK05	PMMA	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776717
59	9700	IK06	glass	105	symmetric	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776861
59	9700	IK06	glass	105	symmetric	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776892
59	9900	IK06	glass	90	MW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 211980
59	9900	IK06	glass	90	SW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 212864
59	9900	IK06	glass	90	VW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 214745
59	9900	IK06	glass	90	MW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 211997
59	9900	IK06	glass	90	SW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 212871
59	9900	IK06	glass	90	VW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 214752
59	9900	IK06	glass	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211874
59	9900	IK06	glass	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212758
59	9900	IK06	glass	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214639
59	9900	IK06	glass	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211843
59	9900	IK06	glass	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212727
59	9900	IK06	glass	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214608

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9900	IK05	PMMA	90	MW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 211942
59	9900	IK05	PMMA	90	SW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 212826
59	9900	IK05	PMMA	90	VW MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 214707
59	9900	IK05	PMMA	90	MW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 211959
59	9900	IK05	PMMA	90	SW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 212833
59	9900	IK05	PMMA	90	VW MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 214714
59	9900	IK05	PMMA	90	MW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211751
59	9900	IK05	PMMA	90	SW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212635
59	9900	IK05	PMMA	90	VW MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214516
59	9900	IK05	PMMA	90	MW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 211720
59	9900	IK05	PMMA	90	SW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 212604
59	9900	IK05	PMMA	90	VW MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 214486
59	9900	IK06	glass	90	MW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 211980/2
59	9900	IK06	glass	90	SW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 212864/2
59	9900	IK06	glass	90	VW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 214745/2
59	9900	IK06	glass	90	MW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 211997/2
59	9900	IK06	glass	90	SW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 212871/2
59	9900	IK06	glass	90	VW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 214752/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	9900	IK06	glass	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211874/2
59	9900	IK06	glass	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212758/2
59	9900	IK06	glass	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214639/2
59	9900	IK06	glass	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211843/2
59	9900	IK06	glass	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212727/2
59	9900	IK06	glass	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214608/2
59	9900	IK05	PMMA	90	MW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 211942/2
59	9900	IK05	PMMA	90	SW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 212826/2
59	9900	IK05	PMMA	90	VW MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 214707/2
59	9900	IK05	PMMA	90	MW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 211959/2
59	9900	IK05	PMMA	90	SW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 212833/2
59	9900	IK05	PMMA	90	VW MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 214714/2
59	9900	IK05	PMMA	90	MW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 211751/2
59	9900	IK05	PMMA	90	SW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 212635/2
59	9900	IK05	PMMA	90	VW MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 214516/2
59	9900	IK05	PMMA	90	MW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 211720/2
59	9900	IK05	PMMA	90	SW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 212604/2
59	9900	IK05	PMMA	90	VW MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 214486/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	10000	IK06	glass	90	SA MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 217500
59	10000	IK06	glass	90	SN MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 215629
59	10000	IK06	glass	90	SA MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 217548
59	10000	IK06	glass	90	SN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 215636
59	10000	IK06	glass	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217395
59	10000	IK06	glass	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215513
59	10000	IK06	glass	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217364
59	10000	IK06	glass	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215483
59	10000	IK05	PMMA	90	SA MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 217463
59	10000	IK05	PMMA	90	SN MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 215582
59	10000	IK05	PMMA	90	SA MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 217470
59	10000	IK05	PMMA	90	SN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 215599
59	10000	IK05	PMMA	90	SA MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217272
59	10000	IK05	PMMA	90	SN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 215391
59	10000	IK05	PMMA	90	SA MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 217241
59	10000	IK05	PMMA	90	SN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 215360
59	10000	IK06	glass	90	SA MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 217500/2
59	10000	IK06	glass	90	SA MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 217548/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	10000	IK06	glass	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217395/2
59	10000	IK06	glass	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217364/2
59	10000	IK05	PMMA	90	SA MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 217463/2
59	10000	IK05	PMMA	90	SA MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 217470/2
59	10000	IK05	PMMA	90	SA MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 217272/2
59	10000	IK05	PMMA	90	SA MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 217241/2
59	10050	IK05	PMMA	butterfly	DAN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777868
59	10050	IK06	glass	butterfly	DAN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777882
59	10050	IK06	glass	butterfly	DAN	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777882/2
59	10050	IK05	PMMA	butterfly	DAN	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777868/2
59	10100	IK05	PMMA	asymetric	SA	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777837
59	10100	IK06	glass	asymetric	SA	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777851
59	10100	IK06	glass	asymetric	SA	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777851/2
59	10100	IK05	PMMA	asymetric	SA	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777837/2
59	10250	IK06	glass	90	DAN MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 219474
59	10250	IK06	glass	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219337
59	10250	IK06	glass	90	DAN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 219481
59	10250	IK06	glass	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219368

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	10250	IK05	PMMA	90	DAN MAT	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 219436
59	10250	IK05	PMMA	90	DAN MAT	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 219214
59	10250	IK05	PMMA	90	DAN MAT	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 219443
59	10250	IK05	PMMA	90	DAN MAT	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219245
59	10250	IK06	glass	90	DAN MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 219474/2
59	10250	IK06	glass	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219337/2
59	10250	IK06	glass	90	DAN MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 219481/2
59	10250	IK06	glass	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219368/2
59	10250	IK05	PMMA	90	DAN MAT	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 219436/2
59	10250	IK05	PMMA	90	DAN MAT	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 219214/2
59	10250	IK05	PMMA	90	DAN MAT	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 219443/2
59	10250	IK05	PMMA	90	DAN MAT	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 219245/2
59	10350	IK05	PMMA	35/67	CN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777776
59	10350	IK05	PMMA	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777493
59	10350	IK05	PMMA	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777523
59	10350	IK06	glass	65	SN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777677
59	10350	IK06	glass	65	SN	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777707
59	10350	IK06	glass	35/67	CN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777790

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	10350	IK05	PMMA	30	VN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777806
59	10350	IK06	glass	30	VN	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777820
59	10350	IK05	PMMA	65	SN	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 778162
59	10350	IK05	PMMA	65	SN	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778179
59	10350	IK06	glass	65	SN	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 778223
59	10350	IK06	glass	65	SN	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778230
59	10400	IK05	PMMA	105	VW	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 772337
59	10400	IK05	PMMA	105	VW	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772344
59	10400	IK06	glass	105	VW	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 773051
59	10400	IK06	glass	105	VW	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 773068
59	10400	IK05	PMMA	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 776953
59	10400	IK05	PMMA	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776984
59	10400	IK06	glass	105	VW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777134
59	10400	IK06	glass	105	VW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777165
59	10400	IK05	PMMA	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777226
59	10400	IK05	PMMA	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777257
59	10400	IK06	glass	90	MW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777400
59	10400	IK06	glass	90	MW	matrix lens		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777431

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	10400	IK05	PMMA	80	SW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777745
59	10400	IK06	glass	80	SW	matrix lens		LS1	Cable length 1.4m			1250/64.5	>> 777769
59	10400	IK05	PMMA	90	MW	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 778070
59	10400	IK05	PMMA	90	MW	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778087
59	10400	IK06	glass	90	MW	matrix lens	yes	LS1	Cable length 1.4m			1250/64.5	>> 778131
59	10400	IK06	glass	90	MW	matrix lens	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778148
59	10400	IK06	glass	90	MW	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 778131/2
59	10400	IK06	glass	105	VW	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 773051/2
59	10400	IK06	glass	90	MW	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778148/2
59	10400	IK06	glass	105	VW	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 773068/2
59	10400	IK06	glass	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777431/2
59	10400	IK06	glass	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777165/2
59	10400	IK06	glass	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777400/2
59	10400	IK06	glass	80	SW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777769/2
59	10400	IK06	glass	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777134/2
59	10400	IK05	PMMA	90	MW	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 778070/2
59	10400	IK05	PMMA	105	VW	2 rows	yes	LS1	Cable length 1.4m			1250/64.5	>> 772337/2
59	10400	IK05	PMMA	90	MW	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 778087/2

TUBA IP69K

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Impact resistance	Diffuser material	Beam angle [°]	Light distribution type	Optics	DIMM DALI	Through wiring	Remarks	Emergency lighting [h]	Emergency luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
59	10400	IK05	PMMA	105	VW	2 rows	yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772344/2
59	10400	IK05	PMMA	90	MW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 777257/2
59	10400	IK05	PMMA	105	VW	2 rows		LS2	Cable length 2 x 1.4m			1281/64.5	>> 776984/2
59	10400	IK05	PMMA	90	MW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777226/2
59	10400	IK05	PMMA	80	SW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 777745/2
59	10400	IK05	PMMA	105	VW	2 rows		LS1	Cable length 1.4m			1250/64.5	>> 776953/2
59	10450	IK10	PC	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772412
59	10450	IK10	PC	120	symmetric		yes	LS1	Cable length 1.4m			1250/64.5	>> 772450
59	10450	IK10	PC	120	symmetric		yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772467
59	10450	IK10	PC	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772535
59	11150	IK05	PMMA	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772054
59	11150	IK05	PMMA	120	symmetric		yes	LS1	Cable length 1.4m			1250/64.5	>> 772092
59	11150	IK05	PMMA	120	symmetric		yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772108
59	11150	IK05	PMMA	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772177
59	11150	IK06	glass	120	symmetric			LS1	Cable length 1.4m			1250/64.5	>> 772771
59	11150	IK06	glass	120	symmetric		yes	LS1	Cable length 1.4m			1250/64.5	>> 772818
59	11150	IK06	glass	120	symmetric		yes	LS2	Cable length 2 x 1.4m			1281/64.5	>> 772825
59	11150	IK06	glass	120	symmetric			LS2	Cable length 2 x 1.4m			1281/64.5	>> 772894

TUBA IP69K

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
778254	Tuba IP69K 3P connector set
778261	Connector set Tuba IP69K 5P DALI



Tuba IP69K 3P connector set (778254)



Connector set Tuba IP69K 5P DALI (778261)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 11/2025; 84/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

New light distributions:

SW - standard wide lens (conventional angle 80D) with wide application in commercial buildings, industrial halls and even - due to its low glare index UGR<19 - in office areas of the building. It provides high luminous efficacy and helps meet the stringent requirements of EN 12464-1 for glare index, illuminance and high uniformity on aisle and shelf surfaces. Particularly recommended for rooms where luminaires are mounted at heights of 3-8m.

MW - medium wide lens (90D conventional angle) with a wide range of applications in commercial buildings, industrial halls and even - due to the low glare UGR<19 - in office areas of the building. It provides high luminous efficacy and helps to meet the stringent requirements of EN 12464-1 for glare index, illuminance and high uniformity on aisle and shelf surfaces. Particularly recommended for rooms where luminaires are mounted at heights of 3-6m.

VW - very wide lens (105D conventional angle) with wide application in open spaces and low warehouses. It provides high luminous efficacy and helps meet the most stringent requirements of EN 12464-1 in terms of glare index (UGR<22, UGR<25), illuminance and high uniformity when the system is installed in low spaces. Particularly recommended for rooms where luminaires are mounted at heights of 2.5-5m.

SN - standard narrow lens (standard narrow, conventional angle 65D) for general lighting in open areas in industrial and storage halls, workshops and even - due to the low glare index UGR<19 - in office areas of the facility. Particularly recommended for rooms where luminaires are mounted at a height of 8-12m.

VN - very narrow lens (very narrow, conventional angle 30D) for illuminating open spaces in facilities where the luminaire mounting height exceeds 13m. Particularly recommended for premises where luminaires are mounted at heights of 13-20m.

CN - corridor narrow lens (corridor narrow, conventional angle 35/67D) for communication lighting in industrial halls and shelf aisles in high storage warehouses. Particularly suitable for rooms where luminaires are mounted at a height of 7-12m.

DAN - butterfly lens, double asymmetric narrow, for shelf lighting in retail facilities where it is essential to direct light onto the goods on display. Particularly recommended for premises where luminaires are mounted at a height of 3-4.5m.

UGR < 19

The Unified Glare Rating is an indicator that characterises glare. The lower the Unified Glare Rating (UGR), the lower the glare.