SOLANTO QUATTRO

GENERAL CARD





TECHNICAL PARAMETERS

Light source: LED module

Rated power [W] - range: 120-212

Luminous flux of the luminaire [lm] - 6906-12190; 8160-14400 range:

Colour temperature [K]: 3000; 4000

Color rendering index (Ra) >: 80

Diffuser type: OPAL

Colour of the body: black; white

Cable length [m]: 1.20

Dimensions (H/W/T/S) [mm]: 2x Ø 900/32.2x Ø 602/32;

002/32,

Mounting version: suspended

CHARACTERISTICS

A suspended LED lamp made up of two rings of 602mm diameter and two rings of 900mm diameter, allowing for an attractive arrangement of representative interiors. The lamp is made of powder-coated steel in white, black or any other colour to match the character of the interior. The thermoformed milk shades emphasise the decorative character of the lamp. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings, increasing the versatility and functionality of the lamp while keeping the number of indexes to a minimum.

APPLICATION

Solanto Quattro is an extremely impressive pendant lamp, dedicated to interiors such as lobbies, receptions, shopping malls and showrooms. It is also perfect for flats and flats, blending in perfectly with stylish surroundings.



SOLANTO QUATTRO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Ring material	Diffuser type	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
120-212	8160-14400	4000	Steel	OPAL	black	2x Ø 900/32.2x Ø 602/32	>> 467462
120-212	6906-12190	3000	Steel	OPAL	white	2x Ø 900/32.2x Ø 602/32	>> 467493

Card creation date: 12 September 2025

 $The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (-10\%) and (-10\%) are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (-10\%) are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Product data sheet does not constitute$





