



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	3.00
Electrical protection class:	II
Diffuser material:	PC
Diffuser type:	PMMA
Battery:	NiCd
Operating mode:	M/NM
Working temperature [°C]:	od +10 do +40
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	255/199;

CHARACTERISTICS

Surface-mounted emergency fitting, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, the battery life in the event of an emergency is 3h. A wide range of optional accessories available - Recessed mounting set, Flag mounting bracket, Suspended mounting set.

APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

DIRECTO S

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Diffuser type	Colour of the body	Emergency lighting [h]	Operating mode	Autotest	Dimensions (H/W/T/S) [mm]	Index
3	PMMA	white	3	M/NM	yes	255/199	>> 897221
3	PMMA	black	3	M/NM	yes	255/199	>> 781667

DIRECTO S


GENERAL CARD

ACCESSORIES AVAILABLE


index	Name
897238	DIRECTO S suspended mounting kit
897245	DIRECTO S Flag Mounting Kit
897252	DIRECTO S Recessed Mounting Kit



DIRECTO S suspended mounting kit (897238)



DIRECTO S Flag Mounting Kit (897245)



DIRECTO S Recessed Mounting Kit (897252)

Card creation date: 29 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 14/2025

Accessories included

