DIRECTO S

GENERAL CARD





TECHNICAL PARAMETERS

Ingress protection: IP20

Nominal power [W]: 3.00

Electrical protection class:

Diffuser material: PC

Diffuser type: PMMA

Battery: NiCd

Operating mode: M/NM

Working temperature [°C]: od +10 do +40

Mounting version: surface

Dimensions (H/W/T/S) [mm]: 255/199;

CHARACTERISTICS

Surface-mounted emergency fitting, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, the battery life in the event of an emergency is 3h. A wide range of optional accessories available - Recessed mounting set, Flag mounting bracket, Suspended mounting set.

APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.



DIRECTO S

GENERAL CARD

AVAILABLE VERSIONS



Nominal power [W]	Diffuser type	Colour of the body	Emergency lighting [h]	Operating mode	Autotest	Dimensions (H/W/T/S) [mm]	Index
3	PMMA	white	3	M/NM	yes	255/199	>> 897221
3	PMMA	black	3	M/NM	yes	255/199	<u>>> 781667</u>




DIRECTO S

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name				
897238	DIRECTO S suspended mounting kit				
897245	DIRECTO S Flag Mounting Kit				
897252	DIRECTO S Recessed Mounting Kit				







DIRECTO S Flag Mounting Kit (897245)



DIRECTO S Recessed Mounting Kit (897252)

Card creation date: 29 July 2025







Accessories included



