ORION

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK08
Nominal power [W]:	3.50; 8.00
Luminous flux [lm]*:	122; 294
Colour temperature [K]:	5000
Electrical protection class:	II
Diffuser material:	PC
Battery:	NiCd
Operating mode:	M/NM
Working temperature [°C]:	od +10 do +55
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	352/110/64;

CHARACTERISTICS

Surface-mounted, universal (maintained or non-maintained system) emergency fitting with a low profile including an integrated, energy-saving LED light source. The base and the lampshade are made of high quality, V0 class polycarbonate PC, optional double-sided set DS(for pictograms illumination) for a version with flat cover – plate made of PMMA, frame made of steel, powder painted. NiCd battery with manual testing function included; battery life in the event of an emergency is 3h. Visibility 20m or 30m (double-sided set / DS version).

APPLICATION

Autonomous emergency fitting, dedicated for illumination of evacuation routes and emergency exits in the event of voltage drop in the power grid, i.e. in emergency mode. Product intended for surface mounting walls. Recommended particularly for areas of technical nature (passageways, staircases, garages, cellars) and for all applications which require the installation of permanent emergency lighting.

ORION

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Emergency lighting [h]	Operating mode	Dimensions (H/W/T/S) [mm]	Index
3.50	5000	122	3	M/NM	352/110/64	>> 897153
8	5000	294	3	M/NM	352/110/64	>> 897160

ORION


GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
897177	Protective net for ORION LED II
897184	Angle assembly kit 0-90 ORION
897191	Protective cover for Orion LED luminaires
897207	Flush mounted bezel for ORION LED II
897214	DS ORION LED II double sided frame




Protective net for ORION LED II (897177)




Angle assembly kit 0-90 ORION (897184)



Protective cover for Orion LED luminaires (897191)



Flush mounted bezel for ORION LED II (897207)



DS ORION LED II double sided frame (897214)

Card creation date: 05 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 15/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

Accessories included



