

# CONTRA LED 400 MULTI

## GENERAL CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	21-32
Luminous flux of the luminaire [lm] - range:	2750-4000; 2900-4200
Colour rendering index:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	400/400/39;

## CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

## APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

# CONTRA LED 400 MULTI

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
21-32	4000	2900-4200	white	400/400/39	<a href="#">&gt;&gt; 375088</a>
21-32	4000	2750-4000	black	400/400/39	<a href="#">&gt;&gt; 375095</a>

Card creation date: 07 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 85/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)