

# CONTRA LED 400 MULTI

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP40
<b>Impact resistance:</b>	IK07
<b>Rated power [W] - range:</b>	21-32; 35
<b>Luminous flux of the luminaire [lm] - range:</b>	2750-4000; 2900-4200; 4450; 4665
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	coated aluminium
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	matt
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	400/400/39;

## CHARACTERISTICS

The Contra LED 400 MULTI is a versatile LED panel featuring a low, slim profile. Designed from the ground up, its construction incorporates innovative solutions that deliver excellent lighting performance. The body is made of aluminium, making it lightweight and highly impact-resistant (IK07). The opal diffuser, made of PS, ensures the luminaire has excellent lighting properties. The integrated LED module ensures low power consumption and all the benefits of modern LED luminaires. The multifunctional LED driver provides 4 brightness levels via a built-in switch. A version with a DALI driver is also available, enabling integration with lighting control systems and smooth dimming.

## APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

# CONTRA LED 400 MULTI

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Index
21-32	4000	2900-4200	white		<a href="#">&gt;&gt; 375088</a>
21-32	4000	2750-4000	black		<a href="#">&gt;&gt; 375095</a>
35	4000	4450	black	yes	<a href="#">&gt;&gt; 978883</a>
35	4000	4665	white	yes	<a href="#">&gt;&gt; 978876</a>

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 68/2026; 69/2026



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl