CONTRA LED 400 MULTI

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	21-32; 35
Luminous flux of the luminaire [lm] - range:	2750-4000; 2900-4200; 4450; 4665
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	400/400/39;

CHARACTERISTICS

The Contra LED 400 MULTI is a versatile LED panel featuring a low, slim profile. Designed from the ground up, its construction incorporates innovative solutions that deliver excellent lighting performance. The body is made of aluminium, making it lightweight and highly impact-resistant (IK07). The opal diffuser, made of PS, ensures the luminaire has excellent lighting properties. The integrated LED module ensures low power consumption and all the benefits of modern LED luminaires. The multifunctional LED driver provides 4 brightness levels via a built-in switch. A version with a DALI driver is also available, enabling integration with lighting control systems and smooth dimming.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400 MULTI

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details


Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Index
21-32	4000	2900-4200	white		>> 375088
21-32	4000	2750-4000	black		>> 375095
35	4000	4450	black	yes	>> 978883
35	4000	4665	white	yes	>> 978876

CONTRA LED 400 MULTI

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
413995	CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish



CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish (413995)

Card creation date: 21 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 68/2026; 69/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl