CONTRA LED 400 MULTI

GENERAL CARD





TECHNICAL PARAMETERS

Ingress protection: IP40

Impact resistance: IK07

Rated power [W] - range: 21-32

Luminous flux of the luminaire [lm] -

range:

2750-4000; 2900-4200

Color rendering index (Ra) >: 80

Energy efficiency class:

Material of the body: coated aluminium

Diffuser material: PS

Diffuser type: matt

Mounting version: surface

Dimensions (H/W/T/S) [mm]: 400/400/39;

CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.



CONTRA LED 400 MULTI

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [Im] - range	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
21-32	4000	2900-4200	white	400/400/39	>> 375088
21-32	4000	2750-4000	black	400/400/39	>> 375095

Card creation date: 19 September 2025





Certificate CE - Nr: 85/2025

This product is a subject to electric and electronic waste equipment regulations (WEEE).