## **SQUARE LED BASIC**

**GENERAL CARD** 





#### **TECHNICAL PARAMETERS**

Ingress protection: IP54 Impact resistance: **IK08** 13.00 - 13.00 Nominal power [W]: 1490 - 1500 Luminous flux [lm]\*: Colour temperature [K]: 4000 SDCM: 3; 5 **Energy efficiency class:** E; F Material of the body: PC PC Diffuser material: Diffuser type: **OPAL Optics material:** PC **Optics:** Lena Mounting version: surface Dimensions (H/W/T/S) [mm]: 260/260/60; **Technical Warranty:** 2; 5

#### **CHARACTERISTICS**

Surface-mounted, square LED light fixture with a luminous flux of 88 lm/W, ingress protection class IP54 and an integrated energy-saving light source LED. White base; diffuser made of impact resistant PC provides even light distribution and ensures a high impact resistance class (IK08). Available version with a radio motion sensor (RCR).

## **APPLICATION**

Surface mounted luminaire for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways, staircases) as well as outdoor use (façade lighting). The version with a radio motion sensor (RCR) is particularly well-suited to be used as a light source for public rooms and buildings (civic buildings, apartment buildings).

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard and for outdoor applications.



# **SQUARE LED BASIC**

GENERAL CARD

### **AVAILABLE VERSIONS**



Click index >>, to see details


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Dimensions (H/W/T/S) [mm]	Index
13	4000	1490	OPAL		260/260/60	<u>&gt;&gt; 226533</u>
13	4000	1490	OPAL	yes	260/260/60	>> 226540/H
13	4000	1500	OPAL	yes	260/260/60	>> 226540/EH
13	4000	1500	OPAL		260/260/60	>> 226533/E



## **SQUARE LED BASIC**

GENERAL CARD

### **LUMINOUS INTENSITY DISTRIB. CURVE**



SQUARE LED 8W 4000K

Card creation date: 12 November 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

