

# LUMEDIC SM R

GENERAL CARD



## TECHNICAL PARAMETERS

|   |   |
|---|---|
| <b>Ingress protection:</b>                | IP65  |
| <b>Impact resistance:</b>                 | IK09  |
| <b>Rated power of the luminaire [W]*:</b> | 47.00; 83.00                                |
| <b>Colour temperature [K]:</b>            | 3000; 4000                                  |
| <b>Luminous flux [lm]*:</b>               | 6050 - 12100                                |
| <b>Color rendering index (Ra) &gt;:</b>   | 80  |
| <b>Material of the body:</b>              | powder coated steel                         |
| <b>Diffuser type:</b>                     | Glass/Opal;<br>Glass/Opal/PRM;<br>Glass/PRM |
| <b>Mounting version:</b>                  | recessed                                    |
| <b>Dimensions (H/W/T/S) [mm]:</b>         | 595/595/65;                                 |

## CHARACTERISTICS

Lumedic SM R this is a specialist cleanroom luminaire designed for cleanrooms with an air cleanliness class of ISO 3–9, in accordance with ISO 14644-1:2015 Cleanroom, and meeting stringent hygiene and sterility requirements. Its design ensures ease of cleaning and high mechanical and environmental resistance. A robust steel housing with IP65 protection on the room side and on the technical side ensures complete tightness in a sterile environment, while allowing free air flow above the suspended ceiling. Service access is provided from the technical side (top inspection), allowing maintenance without interfering with the clean room. The front of the luminaire is made of aluminium and 4 mm thick tempered glass, resistant to impact (IK09 class) and chemicals. The modular shutter system (Glass / Opal / PRM) allows you to select the appropriate optical characteristics depending on the application requirements — from uniform, diffused light to precise directional distribution. The SM R version is designed for installation in modular ceilings.

## APPLICATION

- laboratories (microbiological, pharmaceutical, chemical),
- hospitals (operating theatres, intensive care units, diagnostic laboratories),
- food and pharmaceutical industry,
- cleanrooms in electronics and semiconductor manufacturing.

# LUMEDIC SM R

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### Lumedic SM R Glass/Opal

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | DIMM DALI | Index                           |
|-----------------------------------|------------------------|---------------------|---------------|-----------|---------------------------------|
| 47                                | 3000                   | 7100                | Glass/Opal    | yes       | <a href="#">&gt;&gt; 783364</a> |
| 47                                | 3000                   | 7100                | Glass/Opal    |           | <a href="#">&gt;&gt; 783357</a> |
| 47                                | 3000                   | 7100                | Glass/Opal    |           | <a href="#">&gt;&gt; 520914</a> |
| 47                                | 4000                   | 7350                | Glass/Opal    |           | <a href="#">&gt;&gt; 520907</a> |
| 47                                | 4000                   | 7350                | Glass/Opal    | yes       | <a href="#">&gt;&gt; 783340</a> |
| 47                                | 4000                   | 7350                | Glass/Opal    |           | <a href="#">&gt;&gt; 783333</a> |
| 83                                | 3000                   | 11125               | Glass/Opal    |           | <a href="#">&gt;&gt; 520938</a> |
| 83                                | 3000                   | 11125               | Glass/Opal    | yes       | <a href="#">&gt;&gt; 783401</a> |
| 83                                | 3000                   | 11125               | Glass/Opal    |           | <a href="#">&gt;&gt; 783395</a> |
| 83                                | 4000                   | 11550               | Glass/Opal    |           | <a href="#">&gt;&gt; 783371</a> |
| 83                                | 4000                   | 11550               | Glass/Opal    | yes       | <a href="#">&gt;&gt; 783388</a> |
| 83                                | 4000                   | 11550               | Glass/Opal    |           | <a href="#">&gt;&gt; 520921</a> |

### Lumedic SM R Glass/Opal/PRM

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type  | DIMM DALI | Index                           |
|-----------------------------------|------------------------|---------------------|----------------|-----------|---------------------------------|
| 47                                | 3000                   | 6050                | Glass/Opal/PRM | yes       | <a href="#">&gt;&gt; 783289</a> |
| 47                                | 3000                   | 6050                | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 783272</a> |
| 47                                | 3000                   | 6050                | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 520877</a> |
| 47                                | 4000                   | 6225                | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 520860</a> |
| 47                                | 4000                   | 6225                | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 783258</a> |
| 47                                | 4000                   | 6225                | Glass/Opal/PRM | yes       | <a href="#">&gt;&gt; 783265</a> |
| 83                                | 3000                   | 9925                | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 520891</a> |
| 83                                | 3000                   | 9925                | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 783319</a> |
| 83                                | 3000                   | 9925                | Glass/Opal/PRM | yes       | <a href="#">&gt;&gt; 783326</a> |
| 83                                | 4000                   | 10350               | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 783296</a> |
| 83                                | 4000                   | 10350               | Glass/Opal/PRM | yes       | <a href="#">&gt;&gt; 783302</a> |
| 83                                | 4000                   | 10350               | Glass/Opal/PRM |           | <a href="#">&gt;&gt; 520884</a> |

### Lumedic SM R Glass/PRM

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | DIMM DALI | Index                           |
|-----------------------------------|------------------------|---------------------|---------------|-----------|---------------------------------|
| 47                                | 3000                   | 7425                | Glass/PRM     |           | <a href="#">&gt;&gt; 520952</a> |
| 47                                | 3000                   | 7425                | Glass/PRM     |           | <a href="#">&gt;&gt; 783432</a> |
| 47                                | 3000                   | 7425                | Glass/PRM     | yes       | <a href="#">&gt;&gt; 783449</a> |
| 47                                | 4000                   | 7675                | Glass/PRM     |           | <a href="#">&gt;&gt; 520945</a> |
| 47                                | 4000                   | 7675                | Glass/PRM     | yes       | <a href="#">&gt;&gt; 783425</a> |

# LUMEDIC SM R

## GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | DIMM DALI | Index                           |
|-----------------------------------|------------------------|---------------------|---------------|-----------|---------------------------------|
| 47                                | 4000                   | 7675                | Glass/PRM     |           | <a href="#">&gt;&gt; 783418</a> |
| 83                                | 3000                   | 11675               | Glass/PRM     |           | <a href="#">&gt;&gt; 520976</a> |
| 83                                | 3000                   | 11675               | Glass/PRM     | yes       | <a href="#">&gt;&gt; 783487</a> |
| 83                                | 3000                   | 11675               | Glass/PRM     |           | <a href="#">&gt;&gt; 783470</a> |
| 83                                | 4000                   | 12100               | Glass/PRM     |           | <a href="#">&gt;&gt; 520969</a> |
| 83                                | 4000                   | 12100               | Glass/PRM     | yes       | <a href="#">&gt;&gt; 783463</a> |
| 83                                | 4000                   | 12100               | Glass/PRM     |           | <a href="#">&gt;&gt; 783456</a> |

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 64/2026