LINERO LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Rated power of the luminaire [W]*:	71.00 - 139.00
Luminous flux [lm]*:	10800 - 18650
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	II
Energy efficiency class:	C; D
Material of the body:	aluminium
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	620/61/129;
Warranty [years]:	5
Impact resistance:	IK09
SDCM:	3
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

A range of lightweight, hermetically sealed High-Bay linear luminaires, made from extruded aluminium, featuring a heat sink to dissipate excess heat and an outdoor on/off power supply (an optional 1–10 V dimming function is available for each version). It combines the characteristics of durability and weatherproofing with the highest luminous efficacy. Its uncompromising, modern design represents a breakthrough in the design of efficient yet economical industrial luminaires. Professional optics made from durable polycarbonate (PC) offer great flexibility in selecting the optimal solution, even at significant installation heights.

APPLICATION

Designed for the most demanding production and warehouse environments, where the highest quality and quantity of light at the lowest possible investment cost are the priority.

LINERO LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Light distribution type	Luminous efficacy [lm/W]	Dimensions (H/W/T/S) [mm]	Index
71	4000	10800	CW	152	620/61/129	>> 278990
71	4000	11000	SN	155	620/61/129	>> 488313
71	4000	11000	VN	155	620/61/129	>> 488252
71	4000	11000	MW	155	620/61/129	>> 488054
71	4000	11000	CN	155	620/61/129	>> 488375
71	4000	11000	VW	155	620/61/129	>> 488191
71	4000	11000	SW	155	620/61/129	>> 488139
86	4000	12700	CW	148	620/61/129	>> 278983
86	4000	12950	SN	151	620/61/129	>> 488306
86	4000	12950	VN	151	620/61/129	>> 488245
86	4000	12950	CN	151	620/61/129	>> 488368
86	4000	12950	VW	151	620/61/129	>> 488184
86	4000	12950	MW	151	620/61/129	>> 488047
86	4000	12950	SW	151	620/61/129	>> 488122
99	4000	14200	CW	143	620/61/129	>> 278976
99	4000	14450	SW	146	620/61/129	>> 488115
99	4000	14450	SN	146	620/61/129	>> 488290
99	4000	14450	VW	146	620/61/129	>> 488177
99	4000	14450	VN	146	620/61/129	>> 488238
99	4000	14450	MW	146	620/61/129	>> 488030
99	4000	14450	CN	146	620/61/129	>> 488351
111	4000	15350	CW	138	620/61/129	>> 278969
111	4000	15650	VN	141	620/61/129	>> 488221
111	4000	15650	SN	141	620/61/129	>> 488283
111	4000	15650	CN	141	620/61/129	>> 488344
111	4000	15650	MW	141	620/61/129	>> 488023
111	4000	15650	SW	141	620/61/129	>> 488108
111	4000	15650	VW	141	620/61/129	>> 488160
123	4000	16550	CW	135	620/61/129	>> 278952
123	4000	16850	MW	137	620/61/129	>> 488016
123	4000	16850	CN	137	620/61/129	>> 488337
123	4000	16850	SN	137	620/61/129	>> 488276
123	4000	16850	VN	137	620/61/129	>> 488214
123	4000	16850	VW	137	620/61/129	>> 488153
123	4000	16850	SW	137	620/61/129	>> 488092

LINERO LED

GENERAL CARD

139	4000	18300	CW	132	620/61/129	>> 278945
139	4000	18650	CN	134	620/61/129	>> 488320
139	4000	18650	SN	134	620/61/129	>> 488269
139	4000	18650	VN	134	620/61/129	>> 488207
139	4000	18650	VW	134	620/61/129	>> 488146
139	4000	18650	SW	134	620/61/129	>> 488085
139	4000	18650	MW	134	620/61/129	>> 488009