

LUMEDIC SW R CRI95

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK09
Rated power of the luminaire [W]*:	47.00 - 83.00
Luminous flux [lm]*:	3925 - 7565
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	95
Material of the body:	powder coated steel
Diffuser material:	szyba hartowana
Diffuser type:	Glass/Opal; Glass/Opal/PRM; Glass/PRM
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	595/595/65; 295/1195/65; 595/1195/65;

CHARACTERISTICS

Lumedic SW R CRI95 this is a specialist cleanroom luminaire designed for cleanrooms with an air cleanliness class of ISO 3–9, in accordance with ISO 14644-1:2015 Cleanroom, and meeting stringent hygiene and sterility requirements. Its design ensures ease of cleaning and high mechanical and environmental resistance. A robust steel housing with IP65 protection on the room side and on the technical side ensures complete tightness in a sterile environment, while allowing free air flow above the suspended ceiling. Service access is provided from the technical side (top inspection), allowing maintenance without interfering with the clean room.

The luminaire is characterised by very high colour rendering quality (CRI > 95), with high values for the R9 = 94.7 and R13 = 98.9 components. The R9 parameter, responsible for the reproduction of saturated red colours, is crucial in medical diagnostics, surgery and laboratory analyses, where precise differentiation of shades of blood, tissues and biological materials is critical. A high R9 value indicates the use of light sources with a full, continuous spectrum, which is not available for standard LED luminaires.

The R13 parameter refers to the faithful reproduction of skin tones and materials with light, pastel shades. An R13 value of 98.9 ensures a natural appearance of work surfaces, hands and staff faces, reducing eye strain and the risk of visual misjudgement in high-responsibility environments such as operating theatres, pharmaceutical laboratories and quality control rooms.

The front of the luminaire is made of aluminium and 4 mm thick tempered glass, resistant to impact (IK09 class) and chemicals. The modular shutter system (Glass / Opal / PRM) allows you to select the appropriate optical characteristics depending on the application requirements — from uniform, diffused light to precise directional distribution. The SW R version is designed for installation in reinforced ceilings.

APPLICATION

- laboratories (microbiological, pharmaceutical, chemical),
- hospitals (operating theatres, intensive care units, diagnostic laboratories),
- food and pharmaceutical industry,
- cleanrooms in electronics and semiconductor manufacturing.

LUMEDIC SW R CRI95

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

LUMEDIC SW R CRI95 Glass/Opal

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
47	3000	4765	Glass/Opal			295/1195/65	>> 494710
47	3000	4765	Glass/Opal	yes		295/1195/65	>> 494727
47	3000	4765	Glass/Opal		3	295/1195/65	>> 495694
47	4000	4928	Glass/Opal		3	295/1195/65	>> 495687
47	4000	4928	Glass/Opal	yes		295/1195/65	>> 494703
47	4000	4928	Glass/Opal			295/1195/65	>> 494697
83	3000	6958	Glass/Opal		3	295/1195/65	>> 495717
83	3000	6958	Glass/Opal	yes		295/1195/65	>> 494765
83	3000	6958	Glass/Opal			295/1195/65	>> 494758
83	4000	7228	Glass/Opal		3	295/1195/65	>> 495700
83	4000	7228	Glass/Opal	yes		295/1195/65	>> 494741
83	4000	7228	Glass/Opal			295/1195/65	>> 494734
47	3000	4765	Glass/Opal			595/1195/65	>> 494871
47	3000	4765	Glass/Opal		3	595/1195/65	>> 495779
47	3000	4765	Glass/Opal	yes		595/1195/65	>> 494888
47	4000	4928	Glass/Opal			595/1195/65	>> 494857
47	4000	4928	Glass/Opal	yes		595/1195/65	>> 494864
47	4000	4928	Glass/Opal		3	595/1195/65	>> 495762
83	3000	6958	Glass/Opal		3	595/1195/65	>> 495793
83	3000	6958	Glass/Opal			595/1195/65	>> 494918
83	3000	6958	Glass/Opal	yes		595/1195/65	>> 494925
83	4000	7228	Glass/Opal			595/1195/65	>> 494895
83	4000	7228	Glass/Opal	yes		595/1195/65	>> 494901
83	4000	7228	Glass/Opal		3	595/1195/65	>> 495786
47	3000	4600	Glass/Opal	yes		595/595/65	>> 789632
47	3000	4600	Glass/Opal		3	595/595/65	>> 529351
47	3000	4600	Glass/Opal			595/595/65	>> 789625
47	4000	4775	Glass/Opal		3	595/595/65	>> 529344
47	4000	4775	Glass/Opal	yes		595/595/65	>> 789618
47	4000	4775	Glass/Opal			595/595/65	>> 789601
83	3000	6725	Glass/Opal		3	595/595/65	>> 529375
83	3000	6725	Glass/Opal			595/595/65	>> 789663
83	3000	6725	Glass/Opal	yes		595/595/65	>> 789670

LUMEDIC SW R CRI95

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
83	4000	6975	Glass/Opal			595/595/65	>> 789649
83	4000	6975	Glass/Opal		3	595/595/65	>> 529368
83	4000	6975	Glass/Opal	yes		595/595/65	>> 789656

LUMEDIC SW R CRI95 Glass/Opal/PRM

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
47	3000	3925	Glass/Opal/PRM		3	595/595/65	>> 529313
47	3000	3925	Glass/Opal/PRM	yes		595/595/65	>> 789557
47	3000	3925	Glass/Opal/PRM			595/595/65	>> 789540
47	4000	4075	Glass/Opal/PRM	yes		595/595/65	>> 789533
47	4000	4075	Glass/Opal/PRM			595/595/65	>> 789526
47	4000	4075	Glass/Opal/PRM		3	595/595/65	>> 529306
83	3000	6000	Glass/Opal/PRM	yes		595/595/65	>> 789595
83	3000	6000	Glass/Opal/PRM			595/595/65	>> 789588
83	3000	6000	Glass/Opal/PRM		3	595/595/65	>> 529337
83	4000	6275	Glass/Opal/PRM		3	595/595/65	>> 529320
83	4000	6275	Glass/Opal/PRM			595/595/65	>> 789564
83	4000	6275	Glass/Opal/PRM	yes		595/595/65	>> 789571

LUMEDIC SW R CRI95 Glass/PRM

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
47	3000	4983	Glass/PRM			295/1195/65	>> 494796
47	3000	4983	Glass/PRM	yes		295/1195/65	>> 494802
47	3000	4983	Glass/PRM		3	295/1195/65	>> 495731
47	4000	5146	Glass/PRM		3	295/1195/65	>> 495724
47	4000	5146	Glass/PRM	yes		295/1195/65	>> 494789
47	4000	5146	Glass/PRM			295/1195/65	>> 494772
83	3000	7295	Glass/PRM		3	295/1195/65	>> 495755
83	3000	7295	Glass/PRM	yes		295/1195/65	>> 494840
83	3000	7295	Glass/PRM			295/1195/65	>> 494833
83	4000	7565	Glass/PRM			295/1195/65	>> 494819
83	4000	7565	Glass/PRM	yes		295/1195/65	>> 494826
83	4000	7565	Glass/PRM		3	295/1195/65	>> 495748
47	3000	4983	Glass/PRM		3	595/1195/65	>> 495816
47	3000	4983	Glass/PRM	yes		595/1195/65	>> 494963
47	3000	4983	Glass/PRM			595/1195/65	>> 494956
47	4000	5146	Glass/PRM			595/1195/65	>> 494932
47	4000	5146	Glass/PRM	yes		595/1195/65	>> 494949

LUMEDIC SW R CRI95

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
47	4000	5146	Glass/PRM		3	595/1195/65	>> 495809
83	3000	7295	Glass/PRM			595/1195/65	>> 494994
83	3000	7295	Glass/PRM		3	595/1195/65	>> 495830
83	4000	7565	Glass/PRM			595/1195/65	>> 494970
83	4000	7565	Glass/PRM	yes		595/1195/65	>> 494987
83	4000	7565	Glass/PRM		3	595/1195/65	>> 495823
47	3000	4825	Glass/PRM			595/595/65	>> 789700
47	3000	4825	Glass/PRM	yes		595/595/65	>> 789717
47	3000	4825	Glass/PRM		3	595/595/65	>> 529399
47	4000	4975	Glass/PRM	yes		595/595/65	>> 789694
47	4000	4975	Glass/PRM			595/595/65	>> 789687
47	4000	4975	Glass/PRM		3	595/595/65	>> 529382
83	3000	7050	Glass/PRM		3	595/595/65	>> 529412
83	3000	7050	Glass/PRM			595/595/65	>> 789748
83	3000	7050	Glass/PRM	yes		595/595/65	>> 789755
83	4000	7325	Glass/PRM			595/595/65	>> 789724
83	4000	7325	Glass/PRM	yes		595/595/65	>> 789731
83	4000	7325	Glass/PRM		3	595/595/65	>> 529405

Card creation date: 23 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 89/2026