

# EXPO MODULAR ZOOM

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]*:</b>	12.00 - 35.00
<b>Luminous flux [lm]*:</b>	1500 - 3950
<b>Colour temperature [K]:</b>	2700; 3000; 3500; 4000
<b>Color rendering index (Ra) &gt;:</b>	90
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black matt texture; raw aluminium; white matt texture
<b>Optics material:</b>	PMMA
<b>Optics:</b>	lens
<b>Beam angle [°]:</b>	22-32; 37-57
<b>Mounting version:</b>	surface; track
<b>Dimensions (H/W/T/S) [mm]:</b>	257.9/167/ø83.6; 257.9/240/ø83.6; 235.4/202/ø82;

## CHARACTERISTICS

### Expo Modular ZOOM — lighting that flexibly adapts to changing spaces.

ZOOM is a solution for places that often evolve — boutique spaces, concept stores, seasonal exhibitions, tasting and premium product galleries, product showrooms, and office spaces. The advanced lens allows for smooth adjustment of the beam angle in the ranges of 22–32° and 37–57°, which makes it possible to use the luminaire both as an accent and as display and fill lighting. Thanks to ZOOM, the light 'follows' the arrangement — no need to replace the luminaires, just fine-tune them. It allows you to maintain architectural consistency even with very frequent changes in the display.

ZOOM 22–32° TIR zoom provides focused light with variable distribution, allowing smooth adjustment of the angle from narrow to medium wide while maintaining the same beam characteristics. It allows for dynamic lighting adjustment, so that accent lighting can follow the changing arrangement, creating multiple display scenes from a single spotlight while maintaining the visual consistency of the space. This solution is ideal for showrooms, seasonal spaces and exhibitions with variable scale and layout, as well as boutiques, offices, exhibitions and museums.

The ZOOM 37–57° TIR zoom offers selective light with variable distribution, allowing for a smooth change in angle from medium to wide while maintaining uniform beam characteristics. It enables dynamic lighting adjustment, acting as a fill light that responds flexibly to the layout and allows you to create multiple display scenes from a single spotlight, while maintaining the visual consistency of the space. It is particularly useful in showrooms, seasonal spaces and displays of varying scale and layout, as well as in boutiques, offices, exhibitions and museums.

## APPLICATION

Expo Modular ZOOM is a solution designed for spaces that require maximum flexibility and frequent rearrangements. The system allows for precise adjustment of lighting to the current needs of the exhibition, making it ideal for boutiques, concept stores, showrooms, seasonal spaces, tasting areas, premium product galleries, showrooms and modern offices.

# EXPO MODULAR ZOOM

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Expo Modular Zoom 235.4/202/ø82mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
12	2700	1500	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 230974</a>
12	2700	1500	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231025</a>
12	2700	1500	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231056</a>
12	2700	1500	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231117</a>
12	2700	1500	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231148</a>
12	2700	1500	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231179</a>
22	2700	2600	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 230981</a>
22	2700	2600	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231032</a>
22	2700	2600	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231063</a>
22	2700	2600	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231124</a>
22	2700	2600	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231155</a>
22	2700	2600	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231186</a>
35	2700	3900	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 230998</a>
35	2700	3900	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231049</a>
35	2700	3900	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231070</a>
35	2700	3900	22-32	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231087</a>
35	2700	3900	22-32	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231094</a>
35	2700	3900	22-32	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231100</a>
35	2700	3900	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231131</a>
35	2700	3900	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231162</a>
35	2700	3900	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231193</a>
35	2700	3900	37-57	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231209</a>
35	2700	3900	37-57	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231216</a>
35	2700	3900	37-57	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231223</a>

# EXPO MODULAR ZOOM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
12	3000	1550	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231247</a>
12	3000	1550	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231278</a>
12	3000	1550	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231308</a>
12	3000	1550	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231360</a>
12	3000	1550	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231391</a>
12	3000	1550	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231421</a>
22	3000	2650	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231254</a>
22	3000	2650	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231285</a>
22	3000	2650	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231315</a>
22	3000	2650	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231377</a>
22	3000	2650	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231407</a>
22	3000	2650	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231438</a>
35	3000	3950	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231261</a>
35	3000	3950	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231292</a>
35	3000	3950	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231322</a>
35	3000	3950	22-32	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231339</a>
35	3000	3950	22-32	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231346</a>
35	3000	3950	22-32	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231353</a>
35	3000	3950	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231384</a>
35	3000	3950	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231414</a>
35	3000	3950	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231445</a>
35	3000	3950	37-57	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231452</a>
35	3000	3950	37-57	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231469</a>
35	3000	3950	37-57	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231476</a>
12	3500	1550	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231483</a>
12	3500	1550	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231513</a>
12	3500	1550	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231544</a>
12	3500	1550	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231605</a>

# EXPO MODULAR ZOOM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
12	3500	1550	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231636</a>
12	3500	1550	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231667</a>
22	3500	2650	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231490</a>
22	3500	2650	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231520</a>
22	3500	2650	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231551</a>
22	3500	2650	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231612</a>
22	3500	2650	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231643</a>
22	3500	2650	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231674</a>
35	3500	3950	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231506</a>
35	3500	3950	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231537</a>
35	3500	3950	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231568</a>
35	3500	3950	22-32	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231575</a>
35	3500	3950	22-32	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231582</a>
35	3500	3950	22-32	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231599</a>
35	3500	3950	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231629</a>
35	3500	3950	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231650</a>
35	3500	3950	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231681</a>
35	3500	3950	37-57	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231698</a>
35	3500	3950	37-57	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231704</a>
35	3500	3950	37-57	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231711</a>
12	4000	1550	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231728</a>
12	4000	1550	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231759</a>
12	4000	1550	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231780</a>
12	4000	1550	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231841</a>
12	4000	1550	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231872</a>
12	4000	1550	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231902</a>
22	4000	2650	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231735</a>
22	4000	2650	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231766</a>

# EXPO MODULAR ZOOM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
22	4000	2650	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231797</a>
22	4000	2650	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231858</a>
22	4000	2650	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231889</a>
22	4000	2650	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231919</a>
35	4000	3950	22-32	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231742</a>
35	4000	3950	22-32	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231773</a>
35	4000	3950	22-32	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231803</a>
35	4000	3950	22-32	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231810</a>
35	4000	3950	22-32	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231827</a>
35	4000	3950	22-32	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231834</a>
35	4000	3950	37-57	black matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231865</a>
35	4000	3950	37-57	white matt texture		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231896</a>
35	4000	3950	37-57	raw aluminium		235.4/202/ø82	surface	<a href="#">&gt;&gt; 231926</a>
35	4000	3950	37-57	black matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231933</a>
35	4000	3950	37-57	white matt texture	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231940</a>
35	4000	3950	37-57	raw aluminium	yes	235.4/202/ø82	surface	<a href="#">&gt;&gt; 231957</a>

## Expo Modular Zoom 257.9/167/ø83.6mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
12	2700	1500	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230011</a>
12	2700	1500	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230042</a>
12	2700	1500	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230073</a>
12	2700	1500	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230134</a>
12	2700	1500	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230165</a>
12	2700	1500	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230196</a>
22	2700	2600	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230028</a>
22	2700	2600	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230059</a>
22	2700	2600	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230080</a>
22	2700	2600	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230141</a>

# EXPO MODULAR ZOOM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
22	2700	2600	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230172</a>
22	2700	2600	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230202</a>
35	2700	3900	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230035</a>
35	2700	3900	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230066</a>
35	2700	3900	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230097</a>
35	2700	3900	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230158</a>
35	2700	3900	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230189</a>
35	2700	3900	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230219</a>
12	3000	1550	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230257</a>
12	3000	1550	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230288</a>
12	3000	1550	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230318</a>
12	3000	1550	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230370</a>
12	3000	1550	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230400</a>
12	3000	1550	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230431</a>
22	3000	2650	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230264</a>
22	3000	2650	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230295</a>
22	3000	2650	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230325</a>
22	3000	2650	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230387</a>
22	3000	2650	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230417</a>
22	3000	2650	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230448</a>
35	3000	3950	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230271</a>
35	3000	3950	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230301</a>
35	3000	3950	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230332</a>
35	3000	3950	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230394</a>
35	3000	3950	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230424</a>
35	3000	3950	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230455</a>
12	3500	1550	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230493</a>
12	3500	1550	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230523</a>

# EXPO MODULAR ZOOM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
12	3500	1550	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230554</a>
12	3500	1550	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230615</a>
12	3500	1550	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230646</a>
12	3500	1550	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230677</a>
22	3500	2650	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230509</a>
22	3500	2650	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230530</a>
22	3500	2650	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230561</a>
22	3500	2650	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230622</a>
22	3500	2650	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230653</a>
22	3500	2650	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230684</a>
35	3500	3950	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230516</a>
35	3500	3950	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230547</a>
35	3500	3950	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230578</a>
35	3500	3950	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230639</a>
35	3500	3950	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230660</a>
35	3500	3950	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230691</a>
12	4000	1550	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230738</a>
12	4000	1550	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230769</a>
12	4000	1550	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230790</a>
12	4000	1550	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230851</a>
12	4000	1550	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230882</a>
12	4000	1550	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230912</a>
22	4000	2650	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230745</a>
22	4000	2650	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230776</a>
22	4000	2650	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230806</a>
22	4000	2650	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230868</a>
22	4000	2650	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230899</a>
22	4000	2650	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230929</a>

# EXPO MODULAR ZOOM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
35	4000	3950	22-32	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230752</a>
35	4000	3950	22-32	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230783</a>
35	4000	3950	22-32	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230813</a>
35	4000	3950	37-57	black matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230875</a>
35	4000	3950	37-57	white matt texture		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230905</a>
35	4000	3950	37-57	raw aluminium		257.9/167/ø83.6	track	<a href="#">&gt;&gt; 230936</a>

### Expo Modular Zoom 257.9/240/ø83.6mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
35	2700	3900	22-32	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230103</a>
35	2700	3900	22-32	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230110</a>
35	2700	3900	22-32	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230127</a>
35	2700	3900	37-57	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230226</a>
35	2700	3900	37-57	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230233</a>
35	2700	3900	37-57	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230240</a>
35	3000	3950	22-32	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230349</a>
35	3000	3950	22-32	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230356</a>
35	3000	3950	22-32	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230363</a>
35	3000	3950	37-57	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230462</a>
35	3000	3950	37-57	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230479</a>
35	3000	3950	37-57	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230486</a>
35	3500	3950	22-32	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230585</a>
35	3500	3950	22-32	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230592</a>
35	3500	3950	22-32	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230608</a>
35	3500	3950	37-57	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230707</a>
35	3500	3950	37-57	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230714</a>
35	3500	3950	37-57	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230721</a>
35	4000	3950	22-32	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230820</a>

# EXPO MODULAR ZOOM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
35	4000	3950	22-32	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230837</a>
35	4000	3950	22-32	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230844</a>
35	4000	3950	37-57	black matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230943</a>
35	4000	3950	37-57	white matt texture	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230950</a>
35	4000	3950	37-57	raw aluminium	yes	257.9/240/ø83.6	track	<a href="#">&gt;&gt; 230967</a>

Card creation date: 31 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 156/2025