

TERRACO IN LED

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	2.50; 5.00; 8.00
Luminous flux [lm]*:	160; 300; 400
Colour temperature [K]:	4000
Ingress protection:	IP65
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC
Dimensions (H/W/T/S) [mm]:	130/180/103;

CHARACTERISTICS

The Terraco IN is an architectural luminaire with a modern construction, distinguished by its striking minimalist design. The body is made of weather-resistant, powder-coated aluminium. It is designed for illuminating building façades. It features a high IP65 protection rating and IK08 impact resistance. It is designed for flush-mounted installation. The set includes a mounting box.

APPLICATION

The Terraco IN luminaire is ideal for external lighting of building façades, terraces, balconies and walkways. It can also be successfully used indoors, where it emphasises the modern character of the space. It is the perfect solution for striking illumination of contemporary architecture.

TERRACO IN LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
2.50	4000	160	130/180/103	>> 995996
5	4000	300	130/180/103	>> 995989
8	4000	400	130/180/103	>> 995972

Card creation date: 01 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 65/2026



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl