TERRACO AS LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	18.00
Luminous flux [lm]*:	1100 - 1450
Colour temperature [K]:	4000
Ingress protection:	IP54
Impact resistance:	IK04
Material of the body:	aluminium
Colour of the body:	black; graphite; grey; white
Diffuser material:	PMMA
Diffuser type:	OPAL; PRM
Optics:	general
Mounting version:	surface
CE certificate:	71/2026

CHARACTERISTICS

Terraco AS LED is a luminaire with a modernist structure, distinguished by its striking minimalist design. The powder-coated aluminium body is available in four colours: grey, graphite, white and black. It features a high IP54 protection rating. It is designed for surface mounting.

APPLICATION

The Terraco AS LED luminaire is particularly well-suited for external façade lighting, as well as for illuminating terraces and balconies. Its compact dimensions broaden its range of applications – it can illuminate recesses or hard-to-reach areas. Terraco luminaires can also be used indoors and arranged in various ways on walls to create interesting lighting schemes.

TERRACO AS LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

TERRACO AS LED OPAL

Nominal power [W]	Luminous flux [lm]*	Diffuser type	Colour of the body	PIR	Index
18	1300	OPAL	white		>> 995651
18	1300	OPAL	white	yes	>> 995736
18	1100	OPAL	black		>> 995668
18	1100	OPAL	black	yes	>> 995743
18	1100	OPAL	graphite		>> 995675
18	1100	OPAL	graphite	yes	>> 995750
18	1200	OPAL	grey		>> 995682
18	1200	OPAL	grey	yes	>> 995767

TERRACO AS LED PRM


Nominal power [W]	Luminous flux [lm]*	Diffuser type	Colour of the body	PIR	Index
18	1450	PRM	white		>> 995699
18	1450	PRM	white	yes	>> 995804
18	1300	PRM	black		>> 995705
18	1300	PRM	black	yes	>> 995781
18	1300	PRM	graphite		>> 995712
18	1300	PRM	graphite	yes	>> 995798
18	1300	PRM	grey		>> 995729
18	1300	PRM	grey	yes	>> 995774

TERRACO AS LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
WSE0005	RC MOS MR004 IoT programming remote control



RC MOS MR004 IoT programming remote control (WSE0005)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 71/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl