

CALLISTO LED EVO

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK03
Nominal power [W]:	9.00; 15.00
Luminous flux [lm]*:	960 - 1850
Colour temperature [K]:	3000; 4000
SDCM:	≤ 4
Energy efficiency class:	D; E
Material of the body:	Galvanized steel
Diffuser material:	glass
Diffuser type:	OPAL; OPAL MAT
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	260/103; 305/103; 305/114; 365/103; 365/114; 420/103; 420/114;

CHARACTERISTICS

Surface-mounted, round LED luminaire with a very high luminous flux; includes an integrated energy-saving light source LED. Galvanized steel base, powder-coated white; glass diffuser hand-made of multilayer triplex glass which ensures even light distribution. Decorative fitting with an easy-to-clean, simple system mounting the diffuser to the base. Available in four diameters and two finishes: opal and opal mat.

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.

CALLISTO LED EVO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

CALLISTO LED EVO 260

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
9	3000	1020	OPAL	260/103	E	>> 065729
9	4000	1080	OPAL	260/103	E	>> 065743
9	4000	1040	OPAL MAT	260/103	E	>> 065750
9	3000	960	OPAL MAT	260/103	E	>> 065736

CALLISTO LED EVO 305

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
9	3000	1020	OPAL	305/103	E	>> 065767
9	4000	1080	OPAL	305/103	E	>> 065781
9	4000	1040	OPAL MAT	305/103	E	>> 065798
9	3000	960	OPAL MAT	305/103	E	>> 065774
15	3000	1750	OPAL	305/114	E	>> 065804
15	4000	1850	OPAL	305/114	D	>> 065828
15	3000	1650	OPAL MAT	305/114	E	>> 065811
15	4000	1800	OPAL MAT	305/114	E	>> 065835

CALLISTO LED EVO 365

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
9	3000	1020	OPAL	365/103	E	>> 065842
9	4000	1080	OPAL	365/103	E	>> 065866
9	4000	1040	OPAL MAT	365/103	E	>> 065873
9	3000	960	OPAL MAT	365/103	E	>> 065859
15	3000	1750	OPAL	365/114	E	>> 065880
15	4000	1850	OPAL	365/114	D	>> 065903
15	3000	1650	OPAL MAT	365/114	E	>> 065897
15	4000	1800	OPAL MAT	365/114	E	>> 065910

CALLISTO LED EVO 420

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
9	3000	1020	OPAL	420/103	E	>> 065927
9	4000	1080	OPAL	420/103	E	>> 065941
9	4000	1040	OPAL MAT	420/103	E	>> 065958
9	3000	960	OPAL MAT	420/103	E	>> 065934
15	3000	1750	OPAL	420/114	E	>> 065965
15	4000	1850	OPAL	420/114	D	>> 065989

CALLISTO LED EVO


GENERAL CARD

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
15	3000	1650	OPAL MAT	420/114	E	>> 065972
15	4000	1800	OPAL MAT	420/114	E	>> 065996

CALLISTO LED EVO

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



CALLISTO LED

Card creation date: 01 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 395/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl