


# CONTRA II LED IOT

GENERAL CARD



## TECHNICAL PARAMETERS

|   |                                     |
|---|-------------------------------------|
| <b>Ingress protection:</b>                | IP40/IP20                           |
| <b>Impact resistance:</b>                 | IK06                                |
| <b>Rated power of the luminaire [W]*:</b> | 24.00; 31.00; 36.00                 |
| <b>Luminous flux [lm]*:</b>               | 3200; 4300; 5000                    |
| <b>Colour temperature [K]:</b>            | 4000                                |
| <b>Color rendering index (Ra) &gt;:</b>   | 80                                  |
| <b>SDCM:</b>                              | 2                                   |
| <b>Material of the body:</b>              | coated aluminium                    |
| <b>Diffuser material:</b>                 | PS                                  |
| <b>Diffuser type:</b>                     | matt                                |
| <b>Mounting version:</b>                  | podtynkowy, natynkowy,<br>zwieszany |
| <b>Version:</b>                           | DS HYT DALI                         |
| <b>Dimensions (H/W/T/S) [mm]:</b>         | 595/595/60;<br>1195/295/60;         |

## CHARACTERISTICS

Contra II LED versatile LED panel characterised by its low, slim profile and elegant design. Adapted for flush-mounted installation in modular ceilings, surface-mounted or suspended using an additional frame (available as an accessory). Luminaire with integrated energy-saving LED module, made of white painted aluminium profile, equipped with structured multi-layer PS MAT or PRM shade for perfect light diffusion. Contra II LED is a new version of the proven series of LED cassette panels, designed for maximum energy efficiency, user comfort and modern commercial and office spaces. The use of a new, high-efficiency LED module with a luminous efficacy of 145–163 lm/W significantly reduces energy consumption while maintaining high light quality. Contra II LED is ideally suited to the requirements of modern investments where energy efficiency, durability and compliance with current lighting standards are of key importance.

### IoT characteristics

The IoT RC DS HYT DALI version features: a built-in DS daylight sensor programmable via an RC remote control (HRC-11) and a DALI driver enabling dimming of the light source.

## APPLICATION

The luminaire is intended for indoor use in office (offices, conference rooms) or representative use (hotels, restaurants); illumination of public facilities, including hospitals, educational facilities, offices, halls, garages, passageways, warehouses, shops, as well as in the food industry and food-related retail and service facilities. The unique design and excellent light performance enable CONTRA LED to be used as the main source of light, also for work that requires visual focus. The lamp is suitable for both new applications and the replacement of traditional T8 and T5 luminaires with energy-efficient LED solutions.

# CONTRA II LED IOT

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Control | DALI-2 | Version     | Dimensions (H/W/T/S) [mm] | Index                           |
|-----------------------------------|------------------------|---------------------|---------|--------|-------------|---------------------------|---------------------------------|
| 24                                | 4000                   | 3200                | DS.     | yes    | DS HYT DALI | 595/595/60                | <a href="#">&gt;&gt; 761324</a> |
| 24                                | 4000                   | 3200                | DS.     | yes    | DS HYT DALI | 1195/295/60               | <a href="#">&gt;&gt; 761348</a> |
| 31                                | 4000                   | 4300                | DS.     | yes    | DS HYT DALI | 595/595/60                | <a href="#">&gt;&gt; 761317</a> |
| 31                                | 4000                   | 4300                | DS.     | yes    | DS HYT DALI | 1195/295/60               | <a href="#">&gt;&gt; 761331</a> |
| 36                                | 4000                   | 5000                | DS.     | yes    | DS HYT DALI | 595/595/60                | <a href="#">&gt;&gt; 761300</a> |

Card creation date: 25 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 06/2026



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl