

# CONTRA II LED ZK

## GENERAL CARD



### TECHNICAL PARAMETERS

|                                    |                 |
|------------------------------------|-----------------|
| Ingress protection:                | IP40/IP20       |
| Rated power of the luminaire [W]*: | 24.00 - 36.00   |
| Luminous flux [lm]*:               | 3500 - 5850     |
| Luminous efficacy [lm/W]:          | 145.00 - 163.00 |
| Colour temperature [K]:            | 4000            |
| Color rendering index (Ra) >:      | 80              |
| SDCM:                              | 3               |
| Energy efficiency class:           | B; C            |
| Material of the body:              | coated steel    |
| Diffuser material:                 | PS              |
| Diffuser type:                     | PRM; matt       |
| Mounting version:                  | recessed        |
| Dimensions (H/W/T/S) [mm]:         | 595/595/87;     |

### CHARACTERISTICS

CONTRA II LED versatile LED panel characterised by its low, slim profile and elegant design. Adapted for flush-mounted installation in modular ceilings, surface-mounted or suspended using an additional frame (available as an accessory). Luminaire with integrated energy-saving LED module, made of white painted aluminium profile, equipped with structured multi-layer PS MAT or PRM shade for perfect light diffusion. Contra II LED is a new version of the proven series of LED cassette panels, designed for maximum energy efficiency, user comfort and modern commercial and office spaces. The use of a new, high-efficiency LED module with a luminous efficacy of 145–163 lm/W significantly reduces energy consumption while maintaining high light quality. Contra II LED is ideally suited to the requirements of modern investments where energy efficiency, durability and compliance with current lighting standards are of key importance. ZK – a version designed for installation in modular ceilings with a concealed supporting structure (e.g. ROCKFON T24 X), ensuring that the luminaire sits flush with the ceiling surface.

### APPLICATION

The luminaire is intended for indoor use in office (offices, conference rooms) or representative use (hotels, restaurants); illumination of public facilities, including hospitals, educational facilities, offices, halls, garages, passageways, warehouses, shops, as well as in the food industry and food-related retail and service facilities. The unique design and excellent light performance enable CONTRA LED to be used as the main source of light, also for work that requires visual focus. The lamp is suitable for both new applications and the replacement of traditional T8 and T5 luminaires with energy-efficient LED solutions.

# CONTRA II LED ZK

GENERAL CARD

## AVAILABLE VERSIONS

 Click index >>, to see details

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Luminous efficacy [lm/W] | Diffuser type | Index                           |
|-----------------------------------|------------------------|---------------------|--------------------------|---------------|---------------------------------|
| 24                                | 4000                   | 3500                | 146                      | matt          | <a href="#">&gt;&gt; 379789</a> |
| 24                                | 4000                   | 3900                | 163                      | PRM           | <a href="#">&gt;&gt; 379819</a> |
| 31                                | 4000                   | 4500                | 145                      | matt          | <a href="#">&gt;&gt; 379796</a> |
| 31                                | 4000                   | 5050                | 163                      | PRM           | <a href="#">&gt;&gt; 379802</a> |
| 36                                | 4000                   | 5250                | 146                      | matt          | <a href="#">&gt;&gt; 379857</a> |
| 36                                | 4000                   | 5850                | 163                      | PRM           | <a href="#">&gt;&gt; 379826</a> |

Card creation date: 19 August 2026  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: /2026; 105/2026