

SQ 300 LED EVO PLUS

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK08
Rated power of the luminaire [W]*:	13.00 - 31.00
Mounting version:	surface
Luminous flux [lm]*:	1350 - 3100
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E; F
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL
Dimensions (H/W/T/S) [mm]:	300/300/58;

CHARACTERISTICS

Is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.

SQ 300 LED EVO PLUS

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

SQ 300 LED EVO PLUS 3000K

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Motion sensor	Index
13	3000	1350	104	yes	>> 742484
13	3000	1350	104		>> 729744
17	3000	1750	103		>> 729737
17	3000	1750	103	yes	>> 742477
23	3000	2300	100		>> 729713
23	3000	2300	100	yes	>> 742460
27	3000	2650	99		>> 729706
27	3000	2650	99	yes	>> 742453
31	3000	3000	97		>> 729690
31	3000	3000	97	yes	>> 742446

SQ 300 LED EVO PLUS 4000K

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Luminous efficacy [lm/W]	Motion sensor	Index
13	4000	1450	112		>> 729683
13	4000	1450	112	yes	>> 742439
17	4000	1850	109		>> 729676
17	4000	1850	109	yes	>> 742422
23	4000	2400	105		>> 729652
23	4000	2400	105	yes	>> 742415
27	4000	2800	104		>> 729645
27	4000	2800	104	yes	>> 742408
31	4000	3100	100	yes	>> 742392
31	4000	3100	100		>> 729638

Card creation date: 24 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 97/2026



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl